

MICHELIN® X-STRADDLE® 2
480/95 R 25

MOVING CONTAINERS
FURTHER AND FASTER⁽¹⁾



RUN FURTHER⁽⁷⁾

EXTENDED TIRE LIFE MEANS LESS STOPS
FOR MORE PRODUCTIVITY


+8% TREAD VOLUME⁽¹⁾



NARROWER LONGITUDINAL GROVES MEANS LESS EXPOSED PLYS
AND GREATER RESISTANCE TO CROWN AGGRESSION



MICHELIN® X-STRADDLE®




MICHELIN® X-STRADDLE® 2

EXTENDED BEAD AREA DURABILITY⁽¹⁾

30% larger⁽¹⁾ bead wire

Thicker bead and sidewall profile⁽¹⁾



UP TO
+15%
TIRE LIFE⁽⁷⁾

MICHELIN® X-STRADDLE® 2 480/95 R 25 TL 206 A7 CAI 653072

(1) Compared to MICHELIN® X-STRADDLE® 480/95 R 25

(7) Compared to MICHELIN® X-STRADDLE® 480/95 R 25, average performance by port site. Projected improvement in tire life based on field performance in customer port sites of the MICHELIN® X-STRADDLE® 2 450/95R25 size compared to the MICHELIN® X-STRADDLE® 16.00R25 (the 450/95R25 is an equivalent size of the 16.00R25), that included individual design improvements incorporated into the MICHELIN® X-STRADDLE® 2 480/95R25.



More information: www.michelinearthmover.com
Michelin Earthmover Youtube

MICHELIN® X-STRADDLE® 2
MOVING CONTAINERS
FURTHER AND FASTER⁽¹⁾



Get more productivity
for your twin lift operations:
further, faster with
no compromise
on safety⁽¹⁾.



(1) Compared to MICHELIN® X-STRADDLE® 480/95 R 25





YOUR STAKES
 "I EXPECT TIRES TO BE SAFE FOR MY DRIVERS, TO CONTRIBUTE TO MEETING MY PRODUCTIVITY CHALLENGES WHILE KEEPING MY COSTS UNDER CONTROL."

GET MORE PRODUCTIVITY FOR YOUR TWIN LIFT OPERATIONS: FURTHER, FASTER WITH NO COMPROMISE ON SAFETY⁽¹⁾.



HIGH LOAD CAPACITY

MORE AIR INSIDE MEANS MORE LOAD CAPACITY

The MICHELIN® X-STRADDLE® 2 480/95 R 25 tire has **+20%** more air volume than MICHELIN® X-STRADDLE® 2 450/95 R 25



MICHELIN® X-STRADDLE® 2 450/95 R 25
 MICHELIN® X-STRADDLE® 2 480/95 R 25

The highest load capacity of the straddle carrier tire market **between 15 and 22km/h⁽²⁾**

+
Carry up to 17.85 Tons⁽³⁾



RUN FASTER⁽⁴⁾

A faster running tire thanks to improved heat dissipation



MICHELIN® X-STRADDLE® 480/95 R 25

12KM DISTANCE PER HOUR

and 30km/h max speed

MICHELIN® X-STRADDLE® 2 480/95 R 25

15KM DISTANCE PER HOUR

and 35km/h max speed

+25%⁽⁴⁾
OF DISTANCE PER HOUR



SIMPLICITY

The MICHELIN® X-STRADDLE® 2 480/95 R 25 should be mounted on **13.00/2.5** recommended rim⁽⁵⁾ and can also be fitted on **11.25/2.0** rim⁽⁶⁾



(1) Compared to MICHELIN® X-STRADDLE® 480/95 R 25

(2) At the nominal pressure of 10 bars, vs 15.75 Tons for MICHELIN X-STRADDLE® 2 450/95 R 25. And carry 17 Tons from 22km/h to 25km/h

(3) Data gathered from Bridgestone "off-the-road tires for industrial use" e-brochure (July2016), Goodyear "container handling tyres and industrial use" e-brochure (July2016)

(4) MICHELIN® X-STRADDLE® 2 480/95R25 max distance of 15 kilometers in one hour and 35 km/h max speed vs MICHELIN® X-STRADDLE® 480/95R25 : max distance of 12 kilometers in one hour and 30 km/h max speed

(5) 13.00/2.5 measuring rim - Rim width : 13.00" Flange height : 2,5"

(6) 11.25/2.0 approved rim - Rim width : 11.25" Flange height : 2,0"