

MICHELIN ***MEGAXBIB 2***



***THE GREAT VALUE TYRE
FOR HARVESTING
AND SPREADING***



MEGAXBIB 2 BENEFITS

- ✓ Excellent road handling
- ✓ High load capacity
- ✓ High speed capability

MORE ROBUST & MORE RESISTANT TO STUBBLE*

- ✓ Reinforced carcass
- ✓ Long tyre life
- ✓ More resistant to stubble
- ✓ New STUBBLE SHIELD marking



*VS MEGAXBIB



agricultural.michelin.co.uk



www.youtube.com/user/agmichelin



MICHELIN

MICHELIN MEGAXBIB 2

PRESSURE (BAR/PSI) - LOAD PER TYRE (KG)

Ø inches	Designation	CAI	S mm	D mm	R' mm	RC mm	Recommended rim(s)	Permitted rim(s)	Tube code	Vol. 75%	Tread depth
25	1000/50 R25 172A8/166D TL	852423	1 033	1 654	732	4 907	36.0TH	-	Joint R1438	892	46
	Bar 1 1.3 1.6 1.9 2.2 2.3 2.4 2.5 2.6 2.7 2.8 2.9 3.2										
	Psi 15 19 23 28 32 33 35 36 38 39 41 42 46										
	10 km/h Cyc	8290	9005	9725	9960	10200	10330	10455	10585	10710	
	30 km/h Cyc	6565	7480	8390	8695	9000	9115	9225	9340	9450	
	10 km/h 5815 6940	7740	8385	9025	9235	9450					
	30 km/h 4145 4950	5670	6070	6475	6605	6740					
	40 km/h 3875 4625	5300	5675	6050	6175	6300					
	65 km/h 3255 3885	4450	4765	5080	5185	5290					

Ø inches	Designation			CAI	S mm	D mm	R' mm	RC mm	Recommended rim(s)		Permitted rim(s)		Tube code	Vol. 75%	Tread depth
26	750/50 R26 160A8/154D TL			236906	742	1 406	629	4 171	DW25B (A)		-		-	466	39
	Bar	1	1.3	1.6	1.9	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.2	
	Psi	15	19	23	28	32	33	35	36	38	39	41	42	46	
	10 km/h Cyc			5230	5660	6090	6230	6375	6535	6695	6855	7015	7170	7650	
	30 km/h Cyc			4200	4735	5270	5445	5625	5765	5910	6050	6190	6330	6750	
	10 km/h	3750	4400	5175	5555	5935	6065	6190	6330	6470	6610	6750			
	30 km/h	2675	3135	3690	3960	4235	4325	4415	4515	4615	4715	4815			
	40 km/h	2500	2930	3450	3705	3955	4040	4125	4220	4310	4405	4500			
	65 km/h	2100	2465	2900	3110	3325	3395	3465	3545	3620	3700	3780			

Ø inches	Designation			CAI	S mm	D mm	R' mm	RC mm	Recommended rim(s)	Permitted rim(s)	Tube code	Vol. 75%	Tread depth		
32	1050/50 R32 178A8/172D TL			424273	1 037	1 866	828	5 537	36.00VA	-	Joint OR2052 1 233		42		
	Bar	1	1.3	1.6	1.9	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.2	
	Psi	15	19	23	28	32	33	35	36	38	39	41	42	46	
	10 km/h Cyc			9860	10690	11520	11795	12070	12240	12410	12580	12750			
	30 km/h Cyc			7725	8820	9920	10285	10650	10800	10950	11100	11250			
	10 km/h	6940	8260	9450	10125	10800	11025	11250							
	30 km/h	4950	5890	6740	7220	7705	7865	8025							
	40 km/h	4625	5505	6300	6750	7200	7350	7500							
	65 km/h	3885	4625	5290	5670	6050	6175	6300							

RECOMMENDATIONS

MACHINE #1

Front Pressure (bar/psi)

Rear Pressure (bar/psi)

MACHINE #2

Front Pressure (bar/psi)

Rear Pressure (bar/psi)





PRESSURE (BAR/PSI) - LOAD PER TYRE (KG)

NEW

Ø inches	Designation			CAI		S mm	D mm	R' mm	RC mm	Recommended rim(s)		Permitted rim(s)		Tube code	Vol. 75%	Tread depth
32	800/65 R32 178A8/178B TL			135425		786	1 839	832	5 471	DW27B (A)		DH27(B) - DW25B (A)		831	871	56
	Bar	1	1.3	1.6	1.9	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.2	3.5	3.8
	Psi	15	19	23	28	32	33	35	36	38	39	41	42	46	51	55
	10 km/h Cyc	5865	7080	8290	8880	9470	9665	9860	10075	10285	10500	10710	10915	11525	12140	12750
	30 km/h Cyc	5175	6060	6940	7600	8260	8480	8700	8890	9075	9265	9450	9630	10170	10710	11250
	10 km/h	4440	5165	5885	6300	6720	6855	6995	7160	7330	7495	7660	7825	8325		
	30 km/h	4280	4975	5670	6070	6475	6605	6740	6900	7065	7225	7385	7545	8025		
	40 km/h	4000	4650	5300	5675	6050	6175	6300	6450	6600	6750	6900	7050	7500		
	50 km/h	4000	4650	5300	5675	6050	6175	6300	6450	6600	6750	6900	7050	7500		

NEW

Ø inches	Designation			CAI	S mm	D mm	R' mm	RC mm	Recommended rim(s)		Permitted rim(s)		Tube code	Vol. 75%	Tread depth	
32	900/60 R32 181A8/181B TL			166896	862	1 899	848	5 635	DW27B (A)		DW30B (A)		831	1 033	57	
	Bar	1	1.3	1.6	1.9	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	3.2	3.5	3.8
	Psi	15	19	23	28	32	33	35	36	38	39	41	42	46	51	55
	10 km/h Cyc	6375	7695	9010	9775	10540	10795	11050	11305	11560	11815	12070	12265	12850	13440	14025
	30 km/h Cyc	5625	6675	7725	8485	9245	9495	9750	9975	10200	10425	10650	10825	11340	11860	12375
	10 km/h	4720	5580	6440	6980	7520	7700	7880	8060	8245	8425	8605	8745	9160		
	30 km/h	4550	5380	6205	6725	7250	7420	7595	7770	7945	8120	8295	8430	8830		
	40 km/h	4250	5025	5800	6290	6775	6940	7100	7265	7425	7590	7750	7875	8250		
	50 km/h	4250	5025	5800	6290	6775	6940	7100	7265	7425	7590	7750	7875	8250		

RECOMMENDATIONS

MACHINE #3

Front Pressure (bar/psi)

Rear Pressure (bar/psi)

MACHINE #4

Front Pressure (bar/psi)

Rear Pressure (bar/psi)

