

Ø inches	Tyre size		CAI		S mm	D mm	R' mm	R.C mm	Recommended rim		Acceptable rim	Tube (code)	Interne volume 75% (liters)	Tread depth (mm)	
26.5	650/55 R26.5 169D TL		693431		657	1402	617	4158	AG20.00 (H2)			716	437	18	
Bar	0.80	0.90	1.00	1.20	1.50	1.80	2.10	2.40	2.70	3.00	3.20	3.40	3.60	3.80	4.00
Psi	12	13	15	17	22	26	30	35	39	44	46	49	52	55	58
10 km/h	3330	3985	4635	5220	6100	6875	7600	8325	8780	9235	9540	9765	9990	10215	10440
25 km/h	2925	3500	4070	4585	5355	6035	6675	7310	7710	8110	8375	8575	8770	8970	9165
40 km/h	2515	3010	3500	3945	4610	5195	5745	6290	6635	6980	7210	7380	7550	7720	7890
50 km/h	2240	2680	3115	3510	4100	4620	5110	5595	5905	6210	6415	6565	6720	6870	7020
65 km/h	1850	2215	2575	2900	3390	3820	4220	4625	4880	5130	5300	5425	5550	5675	5800

26.5	VF650/55 R26,5 174D IMP TL		776393	657	1402	607	4131	AG20.00	AG20.00 (H2)		437	18
		NEW										
Bar	0.80	0.90	1.00	1.20	1.50	1.80	2.10	2.40	2.70	3.00	3.20	
Psi	12	13	15	17	22	26	30	35	39	44	46	
10 km/h	4223	4572	4920	5494	6355	7175	8021	8938	9799	10660	10988	
25 km/h	3760	4070	4380	4891	5658	6388	7140	7957	8724	9490	9782	
40 km/h	3322	3596	3870	4322	4999	5644	6309	7031	7708	8385	8643	
50 km/h	3013	3261	3510	3919	4534	5119	5722	6377	6991	7605	7839	
65 km/h	2575	2770	2965	3350	3875	4325	4830	5450	5975	6500	6700	

30.5	650/65 R30.5 176D TL <i>Jante AG profil H2 admis</i>		139310	674	1622	699	4776	AG20.00 (H2)					600	21	
Bar	0.80	0.90	1.00	1.20	1.50	1.80	2.10	2.40	2.70	3.00	3.20	3.40	3.60	3.80	4.00
Psi	12	13	15	17	22	26	30	35	39	44	46	49	52	55	58
10 km/h	4140	4970	5800	6450	7430	8405	9385	10360	10815	11270	11570	11875	12175	12480	12780
25 km/h	3640	4270	4900	5495	6395	7290	8185	9080	9480	9885	10150	10420	10685	10955	11220
40 km/h	3130	3705	4280	4785	5545	6305	7060	7820	8165	8510	8740	8970	9200	9430	9660
50 km/h	2780	3285	3790	4245	4920	5600	6280	6960	7265	7570	7775	7980	8185	8385	8590
65 km/h	2300	2735	3170	3540	4090	4645	5195	5750	6005	6255	6425	6595	6765	6930	7100

30.5	750/60 R30.5 181D TL <i>Jante AG profil H2 admis</i>		101332	786	1675	716	4936	AG24.00 (H2)					750	22	
Bar	0.80	0.90	1.00	1.20	1.50	1.80	2.10	2.40	2.70	3.00	3.20	3.40	3.60	3.80	4.00
Psi	12	13	15	17	22	26	30	35	39	44	46	49	52	55	58
10 km/h	4770	5750	6730	7490	8625	9765	10900	12040	12565	13095	13445	13795	14150	14500	14850
25 km/h	4185	4945	5700	6395	7430	8470	9510	10550	11015	11485	11795	12105	12420	12730	13040
40 km/h	3605	4290	4970	5560	6440	7325	8205	9090	9490	9890	10155	10420	10690	10955	11220
50 km/h	3205	3810	4410	4935	5720	6505	7295	8080	8435	8795	9030	9270	9505	9745	9980
65 km/h	2650	3165	3680	4110	4750	5395	6035	6680	6975	7270	7465	7660	7860	8055	8250

30.5	VF750/60 R30,5 187D IMP TL		139588	760	1680	724	4944	AG20.00 (H2)			650	21
		NEW										
Bar	0.80	0.90	1.00	1.20	1.50	1.80	2.10	2.40	2.70	3.00	3.20	
Psi	12	13	15	17	22	26	30	35	39	44	46	
10 km/h	6150	6560	6970	7790	9184	10266	11496	12710	13940	15170	15990	
25 km/h	5475	5840	6205	6935	8176	9140	10235	11315	12410	13505	14235	
40 km/h	4838	5160	5483	6128	7224	8075	9043	9998	10965	11933	12578	
50 km/h	4388	4680	4973	5558	6552	7324	8202	9068	9945	10823	11408	
65 km/h	3750	4000	4250	4750	5600	6260	6965	7750	8500	9250	9750	

32	800/60 R32 185D IMP TL <i>Jante AG profil H2 admis</i>			322432	810	1800	786	5319	DW27B (A)		DW25B (A)		831	780	23.5
Bar	0.80	0.90	1.00	1.20	1.50	1.80	2.10	2.40	2.70	3.00	3.20	3.40	3.60	3.80	4.00
Psi	12	13	15	17	22	26	30	35	39	44	46	49	52	55	58
10 km/h	5400	6525	7650	8580	9975	11205	12355	13500	14345	15190	15750	15975	16200	16425	16650
25 km/h	4740	5730	6715	7530	8755	9835	10845	11850	12590	13330	13825	14025	14220	14420	14615
40 km/h	4080	4930	5780	6485	7540	8470	9335	10200	10840	11475	11900	12070	12240	12410	12580
50 km/h	3630	4390	5145	5770	6710	7535	8305	9075	9645	10210	10590	10740	10895	11045	11195
65 km/h	3000	3625	4250	4765	5540	6225	6865	7500	7970	8440	8750	8875	9000	9125	9250

IMPORTANT : The inflation pressure must always be appropriate for the load per tyre, the speed of travel and the work to be done.

MICHELIN

CARGOXBIB

HIGH FLOTATION



THE TRAILER TYRE THAT RESPECTS YOUR SOIL

NEW

4 NEW VF DIMENSIONS (Very high Flexion)*

*VF (Very High Flexion) tyres are designed to operate at higher rated load at the same inflation pressure or at lower pressure for the same load.

Example for a given load of 5.8 t at 65 km/h:
- CARGOXBIB HIGH FLOTATION 650/55 R26.5: 4 bars
- CARGOXBIB HIGH FLOTATION 650/55 R26.5 VF : 2.6 bars



agricultural.michelin.co.uk

www.youtube.com/user/agmichelin

MICHELIN CARGOXBIB

HIGH FLOTATION

THE LOW PRESSURE TRAILER TYRE
THAT IS GENTLE ON THE LAND




A RELIABLE AND EFFICIENT TRACTOR / TRAILER RIG

FROM
0.8
BAR

**LESS
PRESSURE**

1ST LOW PRESSURE TRAILER TYRE
designed for use with
Central Tyre Inflation Systems



**MORE
PRODUCTIVITY**

LESS RUTTING and
compaction compared to
tyres inflated to 4 bar⁽²⁾



⁽¹⁾Customer references, April 2014 - ⁽²⁾Internal studies at Michelin's Technology Center April 2012 / June 2013

THE BEST PERFORMANCE FROM ROAD TO FIELD

ROAD

MICHELIN ULTRAFLEX CASING

- Unrivalled casing endurance
- Central Tyre Inflation System compatibility
- Excellent road handling

SOLID ROUNDED SHOULDERS

- Greater wear resistance
- Enables easier turning and less scrub

CONTINUOUS CENTRAL RIB

- Excellent tread wear resistance
- Reduces rolling resistance
- Excellent directional stability

STEEL CROWN BELTS

- Great stability
- Excellent puncture resistance and better load distribution.



FIELD

MICHELIN ULTRAFLEX CASING

- Very low inflation pressure preserves the soil
- Reduces draw bar pull and uses less fuel

SOLID ROUNDED SHOULDERS

- Limits the scrub when turning on grass

CENTRAL RIB AND MULTI-ANGLE BLOCKS

- Excellent grip on side slopes

VF standard: new casing material
to meet the requirements of the VF standard

Ø inches	Tyre size		CAI		S mm	D mm	R' mm	R.C mm	Recommended rim		Acceptable rim	Tube (code)	Interne volume 75% (liters)	Tread depth (mm)	
22.5	710/45 R22.5 16SD TL Jante AG profil H2 admis		723051		723	1208	514	3545	AG24.00 (H2)		AG20.00 (H2)		317	16	
Bar	0.80	0.90	1.00	1.20	1.50	1.80	2.10	2.40	2.70	3.00	3.20	3.40	3.60	3.80	4.00
Psi	12	13	15	17	22	26	30	35	39	44	46	49	52	55	58
10 km/h	2970	3430	3890	4325	4970	5620	6270	6920	7360	7800	8095	8390	8685	8975	9270
25 km/h	2610	2930	3250	3650	4255	4855	5460	6060	6450	6840	7100	7360	7620	7880	8140
40 km/h	2250	2525	2800	3145	3665	4185	4700	5220	5555	5890	6110	6335	6555	6780	7000
50 km/h	2000	2245	2490	2795	3260	3720	4180	4640	4940	5235	5435	5635	5835	6030	6230
65 km/h	1650	1855	2060	2315	2695	3075	3460	3840	4085	4330	4495	4660	4825	4985	5150

26	28 LR 26 175D TL (710/65 R26)		224829		740	1581	705	4685	DW25B (A)		DW23B (A)			577	26
Bar	0.80	0.90	1.00	1.20	1.50	1.80	2.10	2.40	2.70	3.00	3.20	3.40	3.60	3.80	4.00
Psi	12	13	15	17	22	26	30	35	39	44	46	49	52	55	58
15 km/h	3750	3935	4120	4615	5360	5905	6460	7035	7605	7905	8140	8375	8710	8980	9245
25 km/h	3320	3485	3645	4085	4740	5220	5710	6220	6725	6990	7200	7405	7705	7940	8175
40 km/h	3065	3215	3365	3770	4380	4825	5280	5750	6215	6460	6655	6845	7120	7340	7555
50 km/h	2940	3085	3230	3620	4200	4625	5060	5515	5960	6195	6380	6565	6825	7035	7245
65 km/h	2800	2940	3075	3445	4000	4405	4820	5250	5675	5900	6075	6250	6500	6700	6900

26.5	600/55 R26.5 16SD TL														
	Jante AG profil H2 admis		550621	626	1341	581	3954	AG20.00 (H2)			716	312	17		
Bar	0.80	0.90	1.00	1.20	1.50	1.80	2.10	2.40	2.70	3.00	3.20	3.40	3.60	3.80	4.00
Psi	12	13	15	17	22	26	30	35	39	44	46	49	52	55	58
10 km/h	2970	3585	4200	4675	5380	6090	6800	7510	7840	8170	8390	8610	8830	9050	9270
25 km/h	2610	3085	3560	3995	4640	5290	5940	6590	6880	7170	7365	7560	7755	7945	8140
40 km/h	2250	2675	3100	3465	4020	4570	5120	5670	5920	6170	6335	6500	6670	6835	7000
50 km/h	2000	2375	2750	3080	3570	4065	4555	5050	5270	5495	5640	5790	5935	6085	6230
65 km/h	1650	1975	2300	2565	2970	3370	3770	4170	4355	4540	4660	4785	4905	5030	5150

26.5	VF600/55 R26,5 170D IMP TL		377726	626	1341	587	3959	AG20.00 (H2)			312	17
		NEW										
Bar	0.80	0.90	1.00	1.20	1.50	1.80	2.10	2.40	2.70	3.00	3.20	
Psi	12	13	15	17	22	26	30	35	39	44	46	
10 km/h	3772	4025	4264	4756	5658	6322	7081	7790	8549	9184	9840	
25 km/h	3358	3583	3796	4234	5037	5628	6304	6935	7610	8176	8760	
40 km/h	2967	3166	3354	3741	4451	4973	5570	6128	6724	7224	7740	
50 km/h	2691	2871	3042	3393	4036	4510	5051	5558	6099	6552	7020	
65 km/h	2300	2450	2600	2900	3450	3855	4280	4750	5275	5600	6000	

26.5	710/50 R26.5 170D TL <i>Jante AG profil H2 admis</i>		892516		729	1380	594	4061	AG24.00 (H2)		AG20.00 (H2)		407		18
Bar	0.80	0.90	1.00	1.20	1.50	1.80	2.10	2.40	2.70	3.00	3.20	3.40	3.60	3.80	4.00
Psi	12	13	15	17	22	26	30	35	39	44	46	49	52	55	58
10 km/h	3510	4205	4900	5450	6275	7100	7925	8750	9135	9520	9775	10030	10290	10545	10800
25 km/h	3080	3610	4140	4645	5400	6155	6915	7670	8010	8350	8575	8800	9030	9255	9480
40 km/h	2650	3130	3610	4040	4680	5325	5965	6610	6900	7190	7385	7580	7775	7965	8160
50 km/h	2360	2780	3200	3585	4155	4730	5305	5880	6140	6400	6570	6745	6915	7090	7260
65 km/h	1950	2315	2680	2990	3460	3925	4395	4860	5075	5290	5430	5575	5715	5860	6000

26.5	VF710/50 R26,5 176D IMP TL		343405	729	1380	600	3934	AG24.00 (H2)	AG20.00 (H2)		407	18
		NEW										
Bar	0.80	0.90	1.00	1.20	1.50	1.80	2.10	2.40	2.70	3.00	3.20	
Psi	12	13	15	17	22	26	30	35	39	44	46	
10 km/h	4469	4768	5150	5822	6765	7503	8400	9184	10081	10988	11644	
25 km/h	3979	4245	4584	5183	6023	6680	7478	8176	8974	9782	10366	
40 km/h	3515	3750	4051	4580	5321	5902	6607	7224	7929	8643	9159	
50 km/h	3188	3402	3674	4154	4826	5353	5993	6552	7192	7839	8307	
65 km/h	2725	2930	3140	3550	4125	4575	5055	5600	6275	6700	7100	



agricultural.michelin.co.uk



www.youtube.com/user/agmichelin



agricultural.michelin.co.uk



www.youtube.com/user/agmichelin

