

MICHELIN **MACHXBIB**



***DELIVERING VALUE
AND VERSATILITY***
FOR HIGH POWERED TRACTORS



MICHELIN

MICHELIN MACHXBIB

Tyre specifications and pressure table. Load per tyre in kg.

DESCRIPTION	CAI	S (mm)	OD (mm)	LR (mm)	RC (mm)	Tube (code)	Tread depth (mm)	75% internal volume (litres)	Recommended rim	Acceptable rims					
MACHXBIB 600/65 R28 154D/150E TL	429970	626	1494		4465	184	54	405	DW20B (A)	DW18L, DW21B(A), W18L					
Bar (Psi)	0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.70 (25)	1.80 (26)	1.90 (28)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h	2250	2530	2810	3090	3445	3805	4160	4340	4520	4695	4875	5065	5250	5440	5625
30 km/h	1725	2040	2360	2675	2990	3310	3625	3710	3800	3885	3970	4145	4315		
40 km/h		1915	2220	2530	2835	3145	3450	3530	3615	3695	3780	3940	4105		
50 km/h		1840	2135	2430	2720	3015	3310	3390	3470	3545	3625	3785	3940		
65 km/h			2060	2335	2605	2880	3150	3225	3300	3375	3450	3600	3750		
40 km/h Dual	1445	1710	1975	2240	2505	2770	3035	3110	3180	3255	3325	3470	3615		
MACHXBIB 600/70 R28 157D/154E TL	211033	629	1571	703	4652	717	54	447.75	DW20B (A)	DW18L, DW21B(A)					
Bar (Psi)	0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.70 (25)	1.80 (26)	1.90 (28)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h	2475	2800	3125	3450	3855	4260	4665	4870	5070	5275	5475	5655	5835	6010	6190
30 km/h	1900	2265	2630	2995	3355	3720	4085	4170	4250	4335	4415	4580	4745		
40 km/h		2135	2485	2835	3185	3535	3885	3965	4045	4120	4200	4360	4515		
50 km/h		2050	2385	2720	3060	3395	3730	3805	3880	3955	4030	4180	4330		
65 km/h			2300	2615	2925	3240	3550	3620	3695	3765	3840	3980	4125		
40 km/h Dual	1590	1895	2200	2505	2810	3115	3420	3490	3560	3630	3700	3835	3975		
MACHXBIB 600/70 R30 158D TL	566557	638	1604	717	4760	737	56	468	DW20B (A)	DW18L, DW21B(A)					
Bar (Psi)	0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.70 (25)	1.80 (26)	1.90 (28)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h	2475	2830	3185	3540	3955	4375	4790	5000	5210	5415	5625	5815	6000	6190	6375
30 km/h	1900	2285	2665	3050	3435	3815	4200	4285	4375	4460	4545	4720	4890		
40 km/h		2190	2550	2910	3275	3635	3995	4080	4160	4245	4325	4490	4655		
50 km/h		2100	2445	2795	3140	3490	3835	3915	3995	4070	4150	4310	4465		
65 km/h			2360	2685	3005	3325	3650	3725	3800	3875	3950	4100	4250		
40 km/h Dual	1590	1910	2230	2555	2875	3195	3515	3590	3660	3735	3805	3950	4095		
MACHXBIB 710/55 R30 153D TL	992342	678	1518	668	4489	-	50	506.25	DW23B (A)						
Bar (Psi)	0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.70 (25)	1.80 (26)	1.90 (28)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h	2475	2960	3370	3775	4185	4590	5000	5160	5320	5480					
30 km/h	1900	2270	2655	3040	3430	3815	4200								
40 km/h		2165	2530	2900	3265	3635	4000								
50 km/h		2075	2425	2775	3130	3480	3830								
65 km/h			2300	2650	2985	3315	3650								
40 km/h Dual	1590	1905	2225	2550	2870	3195	3515								
MACHXBIB 650/60 R34 159D/155E TL	549996	659	1664	752	4950	823	58	499.5	DW21B (A)	DW20B (A), DW23B (A)					
Bar (Psi)	0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.70 (25)	1.80 (26)	1.90 (28)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h	2475	2800	3125	3450	3885	4320	4755	4975	5190	5410	5625	5860	6095	6330	6565
30 km/h	1900	2285	2665	3050	3435	3815	4200	4305	4410	4510	4615	4825	5030		
40 km/h		2190	2550	2910	3275	3635	3995	4095	4195	4295	4395	4590	4790		
50 km/h		2100	2445	2795	3140	3490	3835	3930	4025	4120	4215	4405	4595		
65 km/h			2300	2640	2975	3310	3650	3740	3830	3920	4015	4195	4375		
70 km/h			2095	2400	2710	3015	3320	3390	3460	3530	3600	3735	3875		
40 km/h Dual	1590	1910	2230	2555	2875	3195	3515	3605	3690	3780	3865	4040	4215		
MACHXBIB 650/65 R34 161D/157E TL	817386	666	1726	779	5133	823	58	555	DW21B (A)	DW20B (A), DW23B (A)					
Bar (Psi)	0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.70 (25)	1.80 (26)	1.90 (28)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h	2700	3090	3475	3865	4290	4720	5145	5360	5575	5785	6000	6235	6470	6705	6940
30 km/h	2070	2470	2865	3265	3660	4055	4455	4565	4670	4780	4890	5105	5320		
40 km/h		2385	2755	3130	3500	3875	4245	4350	4450	4555	4655	4860	5065		
50 km/h		2290	2645	3000	3360	3715	4070	4170	4265	4365	4465	4660	4855		
65 km/h			2575	2900	3225	3550	3875	3970	4065	4155	4250	4440	4625		
70 km/h			2345	2640	2935	3230	3525	3600	3675	3750	3825	3975	4125		
40 km/h Dual	1735	2070	2400	2735	3070	3400	3735	3825	3915	4005	4095	4275	4455		
MACHXBIB 650/75 R38 169A8/169B TL	219467	664	1948	880	5761	804	61	730.5	DW23B (A)	MW23B (A)					
Bar (Psi)	0.40 (6)	0.60 (9)	0.80 (12)	1.00 (15)	1.20 (17)	1.40 (20)	1.60 (23)	1.70 (25)	1.80 (26)	1.90 (28)	2.00 (29)	2.20 (32)	2.40 (35)	2.60 (38)	2.80 (41)
10 km/h	3360	4150	4940	5730	6050	6370	6690	6860	7025	7195	7360	7695	8030	8365	8700
30 km/h	2410	3075	3745	4410	4680	4950	5220	5345	5470	5590	5715	5965	6210		
40 km/h		2725	3435	4140	4385	4630	4875	4990	5105	5220	5340	5570	5800		
50 km/h		2725	3435	4140	4385	4630	4875	4990	5105	5220	5340	5570	5800		
40 km/h Dual	1965	2525	3085	3645	3860	4075	4290	4390	4495	4595	4700	4900	5105		

IMPORTANT: The inflation pressure is always determined according to the load per tyre, speed and work to be carried out.

10 km/h Cyc: max. speed 10 km/h with cyclic load. 25, 30, 40, 50, 60 and 70 km/h: use on the road up to 25, 30, 40, 50, 60 and 70 km/h.

MICHELIN MACHXBIB



VERSATILITY


Ideal for road transport and efficient in the field:

- speed of up to 65 km/h
- load capacity in the field
- damage resistance



ROBUSTNESS

Proven casing robustness



TRACTION

Super traction in the field thanks to deep tread pattern, but also **great road handling** thanks to the overlap of the bars in the center of the tyre

SIZES

NEW 600/65 R28 154D/150E	650/65 R34 161D/157E	710/70 R42 173D
NEW 600/70 R28 157D/154E	650/75 R38 169A8/169B	710/75 R42 175D/171E
NEW 600/70 R30 158D	650/85 R38 173A8/173B	900/50 R42 168D
710/55 R30 153D	710/70 R38 171D	NEW 620/70 R46 162D
650/60 R34 159D/155E	800/70 R38 173D	

RECOMMENDATIONS

VEHICLE N° 1

FRONT PRESSURE (bars / psi)
 REAR PRESSURE (bars / psi)

VEHICLE N° 2

FRONT PRESSURE (bars / psi)
 REAR PRESSURE (bars / psi)

