




AXIOBIB®

EXCELLENT TRACTION & SOIL PROTECTION



RETURN ON INVESTMENT

- Improved yields of +4%/Year¹
- Long tire life



COMFORT

- Outstanding sidewall flexibility enhances operator comfort



EXCELLENT TRACTION

- +11% traction with AXIOBIB IF 710/70R42 vs standard 710/70R42



SOIL PROTECTION

- Low pressure up to 20% less versus standard radials



IF Increased Flexion



SIZES

IF 600/70 R30 159D TL

IF 620/75 R30 164D TL

IF 650/75 R30 166D TL

IF 650/60 R34 165D TL

IF 710/60 R34 164D TL

IF 650/65 R34 161D TL

IF 650/65 R38 169D TL

IF 710/60 R38 172D TL

IF 650/85 R38 179D TL

IF 800/70 R38 179D TL

IF 710/85 R38 178D TL

IF 710/70 R42 179D TL

IF 900/60 R42 186D TL

IF 710/75 R42 176D TL

IF 750/75 R46 186D TL

IF 900/65 R46 190D TL

(1) Harper Adams University 2014/2016

AXIOBIB®

Tire specifications and pressure table. Load per tire in lbs.*

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|----|----|----|----------------------------------|----------------------------|------------------------|----|----|
| 30 | | IF 600/70 R30 159D TL | | | | | | | | | | 96393 (280086) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 23.6 | 62.4 | 27.4 | 184.4 | DW21B (A) | DW20B (A) | | | | | | 30.5 | 118.9 | 71 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 7100 | 8180 | 9260 | 10175 | 11090 | | | | | | | | |
| 20mph | | | 6415 | 7395 | 8365 | 9205 | 10030 | | | | | | | | |
| 40 mph | | | 6175 | 7110 | 8045 | 8850 | 9645 | | | | | | | | |
| 40 mph Dual | 3880 | 4650 | 5425 | 6250 | 7075 | 7780 | 8490 | | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|----------------------|-------|-------|----|----|----|----------------------------------|----------------------------|------------------------|----|----|
| 30 | | IF 620/75 R30 164D TL | | | | | | | | | | 96772 (668406) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 25.9 | 65.7 | 28.7 | 194 | DW23B (A) | DW21B (A), MW23B (A) | | | | | | 31.1 | 150.6 | 73 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 7980 | 9060 | 10140 | 11410 | 12675 | | | | | | | | |
| 20mph | | | 7220 | 8200 | 9170 | 10320 | 11465 | | | | | | | | |
| 40 mph | | | 6945 | 7880 | 8820 | 9920 | 11025 | | | | | | | | |
| 40 mph Dual | 4345 | 5225 | 6105 | 6935 | 7760 | 8730 | 9700 | | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|----|----|----|----------------------------------|----------------------------|------------------------|----|----|
| 30 | | IF 650/75 R30 166D TL | | | | | | | | | | 96826 (828322) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 26.7 | 67.8 | 29.3 | 199.6 | DW23B (A) | MW23B(A) | | | | | | 33.0 | 168.5 | 72 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 8740 | 9920 | 11090 | 12270 | 13435 | | | | | | | | |
| 20mph | | | 7915 | 8975 | 10030 | 11090 | 12145 | | | | | | | | |
| 40 mph | | | 7605 | 8630 | 9645 | 10670 | 11685 | | | | | | | | |
| 40 mph Dual | 4720 | 5710 | 6700 | 7595 | 8490 | 9380 | 10275 | | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|----------------------|-------|-------|-------|-------|-------|----------------------------------|----------------------------|------------------------|-------|-------|
| 34 | | IF 650/60 R34 165D TL | | | | | | | | | | 94599 (100511) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 24.9 | 65.4 | 29.3 | 194.2 | DW23B (A) | DW21B (A), DW24B (A) | | | | | | 32.7 | 132.1 | 73 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 7100 | 8100 | 9105 | 10095 | 11090 | 11345 | 11585 | 11840 | 12080 | 12325 | 12565 | 12810 | 13050 |
| 20mph | | | 6415 | 7330 | 8235 | 9140 | 10030 | 10250 | 10485 | 10705 | 10925 | 11145 | 11365 | 11585 | 11805 |
| 40 mph | | | 6175 | 7045 | 7915 | 8785 | 9645 | 9865 | 10075 | 10295 | 10505 | 10715 | 10935 | 11145 | 11355 |
| 40 mph Dual | 3880 | 4665 | 5435 | 6205 | 6965 | 7725 | 8490 | 8675 | 8865 | 9050 | 9235 | 9425 | 9610 | 9800 | 9985 |

* Refer to the notes at the end of the tables of this range

AXIOBIB®

Tire specifications and pressure table. Load per tire in lbs.*

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|----|----|----|----------------------------------|----------------------------|------------------------|----|----|
| 34 | | IF 710/60 R34 164D TL | | | | | | | | | | 67777 (712503) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 27.9 | 66.8 | 29.8 | 198 | DW25B (A) | | | | | | | 35.4 | 162.5 | 73 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 7980 | 9225 | 10460 | 11575 | 12675 | | | | | | | | |
| 20mph | | | 7220 | 8345 | 9460 | 10460 | 11465 | | | | | | | | |
| 40 mph | | | 6945 | 8025 | 9095 | 10065 | 11025 | | | | | | | | |
| 40 mph Dual | 4345 | 5225 | 6105 | 7055 | 8005 | 8850 | 9700 | | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|----|----|----|----------------------------------|----------------------------|------------------------|----|----|
| 34 | | IF 650/65 R34 161D TL | | | | | | | | | | 26241 (711975) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 25.7 | 67.8 | 30.1 | 200.7 | DW23B (A) | | | | | | | 32.7 | 146.6 | 73 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 7795 | 8975 | 10140 | 10935 | 11730 | | | | | | | | |
| 20mph | | | 7055 | 8115 | 9170 | 9890 | 10605 | | | | | | | | |
| 40 mph | | | 6780 | 7805 | 8820 | 9515 | 10195 | | | | | | | | |
| 40 mph Dual | 4235 | 5105 | 5975 | 6865 | 7760 | 8365 | 8975 | | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|-------|-------|-------|----------------------------------|----------------------------|------------------------|-------|-------|
| 38 | | IF 650/65 R38 169D TL | | | | | | | | | | 87017 (508421) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 25.6 | 71.9 | 32.8 | 214.4 | DW23B (A) | MN21B(A) | | | | | | 32.7 | 158.2 | 73 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 8235 | 9350 | 10460 | 11410 | 12355 | 12655 | 12950 | 13240 | 13535 | 13835 | 14120 | 14420 | 14705 |
| 20mph | | | 7450 | 8455 | 9460 | 10320 | 11175 | 11440 | 11720 | 11980 | 12245 | 12510 | 12775 | 13030 | 13295 |
| 40 mph | | | 7165 | 8135 | 9095 | 9920 | 10750 | 11000 | 11265 | 11520 | 11775 | 12025 | 12280 | 12535 | 12785 |
| 40 mph Dual | 4465 | 5390 | 6305 | 7155 | 8005 | 8730 | 9460 | 9680 | 9910 | 10130 | 10350 | 10570 | 10805 | 11025 | 11245 |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|-------|-------|-------|----------------------------------|----------------------------|------------------------|-------|-------|
| 38 | | IF 650/85 R38 179D TL | | | | | | | | | | 97250 (084900) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 27.2 | 80.7 | 35.9 | 239.3 | DW23B (A) | MW23B (A) | | | | | | 32.3 | 237.8 | 79 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 10780 | 12300 | 13810 | 15400 | 16985 | 17370 | 17745 | 18135 | 18510 | 18795 | 19080 | 19370 | 19655 |
| 20mph | | | 9745 | 11120 | 12500 | 13935 | 15365 | 15710 | 16050 | 16390 | 16735 | 17000 | 17250 | 17515 | 17770 |
| 40 mph | | | 9370 | 10690 | 12015 | 13395 | 14770 | 15100 | 15430 | 15765 | 16095 | 16345 | 16590 | 16845 | 17085 |
| 40 mph Dual | 5820 | 7035 | 8245 | 9415 | 10580 | 11795 | 13005 | 13295 | 13580 | 13865 | 14155 | 14375 | 14595 | 14815 | 15035 |

* Refer to the notes at the end of the tables of this range



AXIOBIB®

Tire specifications and pressure table. Load per tire in lbs.*

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|-------|-------|-------|----------------------------------|----------------------------|------------------------|-------|-------|
| 38 | | IF 710/60 R38 172D TL | | | | | | | | | | 69189 (220975) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 28 | 72.6 | 32.8 | 216 | DW25B (A) | | | | | | | 35.4 | 174.6 | 73 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 8490 | 9735 | 10970 | 12205 | 13435 | 13755 | 14075 | 14385 | 14705 | 15025 | 15345 | 15655 | 15970 |
| 20mph | | | 7685 | 8805 | 9920 | 11035 | 12145 | 12435 | 12720 | 13005 | 13295 | 13580 | 13865 | 14155 | 14440 |
| 40 mph | | | 7385 | 8465 | 9535 | 10615 | 11685 | 11960 | 12235 | 12510 | 12785 | 13060 | 13340 | 13615 | 13890 |
| 40 mph Dual | 5205 | 5910 | 6615 | 7520 | 8410 | 9305 | 10195 | 10450 | 10705 | 10955 | 11210 | 11465 | 11720 | 11970 | 12225 |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|----|----|----|----------------------------------|----------------------------|------------------------|----|----|--|
| 38 | | IF 800/70 R38 179D TL | | | | | | | | | | 99142 (528166) | | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | | |
| 31.9 | 81.4 | 35.2 | 239.7 | DW27B (A) | | | | | | | 39.5 | 287.4 | 80 | | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 | |
| 6 mph ** | | | 12355 | 14165 | 15970 | 17815 | 19655 | | | | | | | | | |
| 20mph | | | 11175 | 12810 | 14440 | 16105 | 17770 | | | | | | | | | |
| 40 mph | | | 10750 | 12325 | 13890 | 15485 | 17085 | | | | | | | | | |
| 40 mph Dual | 6700 | 8080 | 9460 | 10835 | 12215 | 13625 | 15035 | | | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|----|----|----|----------------------------------|----------------------------|------------------------|----|----|--|
| 38 | | IF 710/85 R38 178D TL | | | | | | | | | | 99013 (992951) | | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | | |
| 28.9 | 85 | 36.9 | 250.6 | DW25B (A) | MW25B (A) | | | | | | 36.1 | 287.4 | 82 | | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 | |
| 6 mph ** | | | 12355 | 13975 | 15585 | 17305 | 19015 | | | | | | | | | |
| 20mph | | | 11175 | 12645 | 14100 | 15655 | 17195 | | | | | | | | | |
| 40 mph | | | 10750 | 12160 | 13560 | 15045 | 16535 | | | | | | | | | |
| 40 mph Dual | 6700 | 8080 | 9460 | 10690 | 11925 | 13240 | 14550 | | | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|------------------|-------|-------|-------|-------|-------|----------------------------------|----------------------------|------------------------|-------|-------|
| 42 | | IF 710/70 R42 179D TL | | | | | | | | | | 99783 (771752) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 29.2 | 81.2 | 36.2 | 240.7 | DW25B (A) | DW23B, MW25B (A) | | | | | | 35.8 | 229.8 | 79 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 10780 | 12300 | 13810 | 15400 | 16985 | 17370 | 17745 | 18135 | 18510 | 18795 | 19080 | 19370 | 19655 |
| 20mph | | | 9745 | 11120 | 12500 | 13935 | 15365 | 15710 | 16050 | 16390 | 16735 | 17000 | 17250 | 17515 | 17770 |
| 40 mph | | | 9370 | 10690 | 12015 | 13395 | 14770 | 15100 | 15430 | 15765 | 16095 | 16345 | 16590 | 16845 | 17085 |
| 40 mph Dual | 5820 | 7035 | 8245 | 9415 | 10580 | 11795 | 13005 | 13295 | 13580 | 13865 | 14155 | 14375 | 14595 | 14815 | 15035 |

* Refer to the notes at the end of the tables of this range

AXIOBIB®

Tire specifications and pressure table. Load per tire in lbs.*

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|----|----|----|----------------------------------|----------------------------|------------------------|----|----|
| 42 | | IF 710/75 R42 176D TL | | | | | | | | | | 25479 (037489) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 28.1 | 85.1 | 37.6 | 251.8 | DW25B (A) | | | | | | | 35.8 | 251.8 | 83 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 11440 | 13085 | 14725 | 16370 | 18000 | | | | | | | | |
| 20mph | | | 10350 | 11840 | 13315 | 14805 | 16280 | | | | | | | | |
| 40 mph | | | 9955 | 11385 | 12810 | 14230 | 15655 | | | | | | | | |
| 40 mph Dual | 6270 | 7530 | 8775 | 10030 | 11275 | 12535 | 13780 | | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|-------|-------|-------|----------------------------------|----------------------------|------------------------|-------|-------|
| 42 | | IF 900/60 R42 186D TL | | | | | | | | | | 82481 (111950) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 34.7 | 83.6 | 37.5 | 248.2 | DW30B (A) | | | | | | | 45.0 | 324.9 | 82 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 12675 | 14585 | 16480 | 18385 | 20285 | 20755 | 21240 | 21715 | 22190 | 22665 | 23140 | 23610 | 24085 |
| 20mph | | | 11465 | 13185 | 14905 | 16625 | 18340 | 18770 | 19200 | 19630 | 20060 | 20490 | 20920 | 21350 | 21780 |
| 40 mph | | | 11025 | 12675 | 14330 | 15985 | 17635 | 18055 | 18465 | 18885 | 19290 | 19710 | 20115 | 20535 | 20945 |
| 40 mph Dual | 7075 | 8390 | 9700 | 11155 | 12610 | 14065 | 15520 | 15885 | 16250 | 16610 | 16975 | 17340 | 17705 | 18065 | 18430 |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|-------|-------|-------|----------------------------------|----------------------------|------------------------|-------|-------|
| 46 | | IF 750/75 R46 186D TL | | | | | | | | | | 07217 (487001) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 30 | 90 | 41.1 | 268.5 | DW25B (A) | | | | | | | 37.0 | 303 | 89 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 13050 | 14770 | 16480 | 18385 | 20285 | 20755 | 21240 | 21715 | 22190 | 22665 | 23140 | 23610 | 24085 |
| 20mph | | | 11805 | 13360 | 14905 | 16625 | 18340 | 18770 | 19200 | 19630 | 20060 | 20490 | 20920 | 21350 | 21780 |
| 40 mph | | | 11355 | 12840 | 14330 | 15985 | 17635 | 18055 | 18465 | 18885 | 19290 | 19710 | 20115 | 20535 | 20945 |
| 40 mph Dual | 7075 | 8530 | 9985 | 11300 | 12610 | 14065 | 15520 | 15885 | 16250 | 16610 | 16975 | 17340 | 17705 | 18065 | 18430 |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|-----------------------|-----------------------|-----------------|-----------------|-------|-------|-------|-------|-------|----------------------------------|----------------------------|------------------------|-------|-------|
| 46 | | IF 900/65 R46 190D TL | | | | | | | | | | 36973 (162365) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 36 | 91.4 | 40.9 | 271.2 | MW30B (A) | | | | | | | 43.6 | 383 | 89 | | |
| Psi | 6 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 30 | 32 | 33 | 35 |
| 6 mph ** | | | 14705 | 16865 | 19015 | 20600 | 22190 | 22775 | 23360 | 23940 | 24525 | 25110 | 25705 | 26290 | 26875 |
| 20mph | | | 13295 | 15245 | 17195 | 18630 | 20060 | 20590 | 21120 | 21650 | 22180 | 22710 | 23250 | 23775 | 24305 |
| 40 mph | | | 12785 | 14660 | 16535 | 17915 | 19290 | 19800 | 20315 | 20825 | 21330 | 21835 | 22355 | 22860 | 23370 |
| 40 mph Dual | 8005 | 9635 | 11255 | 12910 | 14550 | 15765 | 16975 | 17430 | 17880 | 18320 | 18770 | 19225 | 19675 | 20115 | 20570 |

***IMPORTANT:**

The inflation pressure must always be appropriate for the load per tire, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (June 2018). Technical data is subject to change without prior notice.

- When using single tire configuration:
 - add 6 psi for use on slopes of more than 20%
 - add 6 psi for intense road use exceeding 50%
- **6 mph LT (Low Torque) (max speed 6 mph). For plowing and other field applications subject to high torque use the 20 mph line.

* Refer to the notes at the end of the tables of this range

