





MULTIBIB™

VERSATILE 65 SERIES WIDE TIRE
WITH LONG SERVICE LIFE



VERSATILITY

- Great performance in the field & on the road
- Fuel efficiency and wide contact patch for soil protection



PRODUCTIVITY

- Excellent traction to save time and fuel
- Capable of speeds of up to 40 mph¹
- Larger air chamber & footprint to carry heavier loads at lower pressures vs standard profile radials



LONG SERVICE LIFE

- Deepest tread depth vs. 4 main competitors²



COMFORT

- Excellent road handling and ride comfort



(1) When authorised by the laws in force in the country
(2) For 650/65 R42 size

SIZES

| |
|--------------------------------|
| 320/65 R16 107D TL |
| 320/65 R18 109A8/106B TL XM108 |
| 340/65 R18 113A8/110B TL XM108 |
| 420/65 R20 125A8/125B TL XM108 |
| 440/65 R20 128D TL |
| 420/65 R24 126A8/126B TL XM108 |
| 440/65 R24 128D TL |

| |
|--------------------|
| 480/65 R24 133D TL |
| 540/65 R24 140D TL |
| 420/65 R28 135D TL |
| 440/65 R28 131D TL |
| 480/65 R28 136D TL |
| 540/65 R28 142D TL |
| 540/65 R30 143D TL |

| |
|--------------------|
| 540/65 R34 145D TL |
| 540/65 R34 152D TL |
| 600/65 R34 151D TL |
| 540/65 R38 147D TL |
| 600/65 R38 153D TL |
| 650/65 R38 157D TL |
| 650/65 R42 158D TL |

MULTIBIB™

Tire specifications and pressure table. Load per tire in lbs.*

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-----------------|------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|
| 16 | | 320/65 R16 107D TL | | | | | | | | | | 39517 (494658) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 11.8 | 32.6 | 14.5 | 96.5 | W8 | W10L, W8L, W9 | | | | | | 17.1 | 17.2 | 37 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 1170 | 1280 | 1390 | 1675 | 1950 | 2240 | 2515 | 2800 | 3075 | 3220 | | | | | |
| 20 mph | 1145 | 1255 | 1365 | 1585 | 1810 | 2030 | 2260 | 2480 | | | | | | | |
| 25 mph | | 1170 | 1280 | 1500 | 1710 | 1930 | 2150 | 2360 | | | | | | | |
| 30 mph | | 1125 | 1225 | 1435 | 1640 | 1850 | 2060 | 2260 | | | | | | | |
| 40 mph | | 1080 | 1180 | 1380 | 1565 | 1765 | 1960 | 2150 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|--------------------------------|-----------------------|-----------------|-----------------|------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|
| 18 | | 320/65 R18 109A8/106B TL XM108 | | | | | | | | | | 78520 (123898) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 12.2 | 34.4 | 15.3 | 102.1 | W9 | W10 | | | | | | | 16.9 | 35 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 880 | 1180 | 1475 | 1775 | 2070 | 2370 | 2670 | 2965 | 3265 | 3415 | | | | | |
| 20 mph | 860 | 1100 | 1345 | 1565 | 1775 | 1995 | 2205 | 2425 | | | | | | | |
| 25 mph | | 1015 | 1255 | 1465 | 1665 | 1875 | 2070 | 2270 | | | | | | | |
| 30 mph | | 950 | 1145 | 1335 | 1520 | 1720 | 1905 | 2095 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|--------------------------------|-----------------------|-----------------|-----------------|------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|
| 18 | | 340/65 R18 113A8/110B TL XM108 | | | | | | | | | | 79647 (123888) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 12.6 | 35.9 | 16 | 107 | W9 | W10 | | | | | | | 20.1 | 37 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 990 | 1325 | 1655 | 1985 | 2315 | 2645 | 2985 | 3320 | 3650 | 3815 | | | | | |
| 20 mph | 970 | 1235 | 1500 | 1740 | 1985 | 2225 | 2470 | 2710 | | | | | | | |
| 25 mph | | 1145 | 1390 | 1620 | 1850 | 2085 | 2315 | 2535 | | | | | | | |
| 30 mph | | 1060 | 1280 | 1490 | 1700 | 1920 | 2125 | 2335 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|--------------------------------|-----------------------|-----------------|-----------------|------|------|------|------|----|----------------------------------|----------------------------|------------------------|----|----|
| 20 | | 420/65 R20 125A8/125B TL XM108 | | | | | | | | | | 86582 (122702) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 15.6 | 41.9 | 18.1 | 123.4 | W11 | W10, W12 | | | | | | | 37 | 45 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 2140 | 2515 | 2890 | 3360 | 3825 | 4300 | 4760 | 5235 | | | | | | | |
| 20 mph | 1700 | 2040 | 2380 | 2765 | 3140 | 3525 | 3900 | | | | | | | | |
| 25 mph | | 1830 | 2225 | 2580 | 2930 | 3285 | 3640 | | | | | | | | |
| 30 mph | | 1830 | 2225 | 2460 | 2700 | 2930 | 3165 | 3405 | 3640 | | | | | | |

* Refer to the notes at the end of the tables of this range

MULTIBIB™

Tire specifications and pressure table. Load per tire in lbs.*

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-----------------|------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|
| 20 | | 440/65 R20 128D TL | | | | | | | | | | 15810 (675464) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 17.5 | 42.9 | 18.7 | 128.3 | W14L | W13, W15L | | | | | | 22.8 | 41.5 | 56 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 2645 | 2855 | 3065 | 3460 | 3860 | 4255 | 4685 | 5105 | 5535 | 5745 | 5950 | | | | |
| 20 mph | 2030 | 2250 | 2470 | 2875 | 3275 | 3680 | 4125 | 4565 | | | | | | | |
| 25 mph | | | 2360 | 2745 | 3120 | 3505 | 3925 | | | | | | | | |
| 30 mph | | | 2260 | 2570 | 2890 | 3195 | 3680 | | | | | | | | |
| 40 mph | | | 2150 | 2500 | 2845 | 3195 | 3585 | | | | | | | | |
| 25 mph Dual | 1700 | 1885 | 2070 | 2415 | 2745 | 3085 | 3460 | 3825 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|--------------------------------|-----------------------|-----------------|-----------------|------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|
| 24 | | 420/65 R24 126A8/126B TL XM108 | | | | | | | | | | 77842 (122712) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 15.6 | 45.7 | 20 | 134.8 | W11 | W10, W12 | | | | | | | 39.6 | 47 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 25 | 26 | 28 | 29 | 32 | 35 | 39 |
| 6 mph ** | 2185 | 2580 | 2975 | 3460 | 3935 | 4420 | 4905 | 5380 | | | | | | | |
| 20 mph | 1740 | 2095 | 2445 | 2845 | 3230 | 3625 | 4010 | | | | | | | | |
| 25 mph | | | 1875 | 2295 | 2655 | 3020 | 3385 | | | | | | | | |
| 30 mph | | | 1875 | 2295 | 2535 | 2780 | 3020 | 3265 | 3505 | 3625 | 3750 | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|------------------------------|------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|
| 24 | | 440/65 R24 128D TL | | | | | | | | | | 04039 (426389) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 17.3 | 46.7 | 20.8 | 138.5 | DW14L | DW13, DW15L, W13, W14L, W15L | | | | | | 22.8 | 47 | 56 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 2835 | 3020 | 3195 | 3650 | 4090 | 4540 | 4905 | 5280 | 5645 | 5820 | 6010 | | | | |
| 20 mph | 2160 | 2380 | 2600 | 3040 | 3485 | 3925 | 4245 | | | | | | | | |
| 25 mph | | | 2490 | 2910 | 3330 | 3750 | 4045 | | | | | | | | |
| 30 mph | | | 2380 | 2790 | 3185 | 3595 | 3880 | | | | | | | | |
| 40 mph | | | 2270 | 2655 | 3030 | 3415 | 3695 | | | | | | | | |
| 25 mph Dual | 1810 | 2005 | 2195 | 2555 | 2930 | 3295 | 3560 | 3825 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-------------------|------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|
| 24 | | 480/65 R24 133D TL | | | | | | | | | | 03176 (531721) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 19 | 48.8 | 21.5 | 144.4 | DW15L | DW14L, W14L, W15L | | | | | | 24.6 | 57.6 | 58 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 3195 | 3470 | 3750 | 4235 | 4720 | 5205 | 5645 | 6075 | 6515 | 6725 | 6945 | | | | |
| 20 mph | 2470 | 2735 | 3000 | 3470 | 3955 | 4430 | 4830 | | | | | | | | |
| 25 mph | | | 2845 | 3305 | 3770 | 4235 | 4610 | | | | | | | | |
| 30 mph | | | 2735 | 3175 | 3615 | 4055 | 4410 | | | | | | | | |
| 40 mph | | | 2600 | 3020 | 3440 | 3860 | 4200 | | | | | | | | |
| 25 mph Dual | 2070 | 2295 | 2500 | 2910 | 3320 | 3725 | 4055 | 4385 | | | | | | | |

* Refer to the notes at the end of the tables of this range

MULTIBIB™

Tire specifications and pressure table. Load per tire in lbs.*

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-------------------|------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|
| 24 | | 540/65 R24 140D TL | | | | | | | | | | 08801 (097057) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 20.9 | 51.7 | 22.6 | 152.5 | DW16L | DW18L, W16L, W18L | | | | | | 28.0 | 75.8 | 61 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 3860 | 4135 | 4410 | 4995 | 5590 | 6175 | 6700 | 7220 | 7750 | 8005 | 8265 | | | | |
| 20 mph | 3000 | 3275 | 3550 | 4155 | 4775 | 5380 | 5865 | 6350 | | | | | | | |
| 25 mph | | | 3375 | 3955 | 4530 | 5115 | 5580 | 6040 | | | | | | | |
| 30 mph | | | 3240 | 3805 | 4355 | 4915 | 5355 | 5800 | | | | | | | |
| 40 mph | | | 3085 | 3615 | 4145 | 4675 | 5095 | 5510 | | | | | | | |
| 25 mph Dual | 2515 | 2745 | 2965 | 3470 | 3990 | 4495 | 4905 | 5315 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-----------------|------|------|------|------|------|----------------------------------|----------------------------|------------------------|------|------|
| 28 | | 420/65 R28 135D TL | | | | | | | | | | 62700 (778211) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 15.4 | 48.7 | 22 | 144.9 | W11 | W12 | | | | | | 21.7 | 46.8 | 56 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 2810 | 3110 | 3405 | 3770 | 4135 | 4495 | 4815 | 5125 | 5500 | 5690 | 5875 | 6240 | 6615 | 7065 | 7210 |
| 20 mph | 2160 | 2390 | 2610 | 2985 | 3385 | 3780 | 4165 | 4565 | 4805 | 4925 | 5050 | 5280 | 5525 | | |
| 25 mph | | | 2490 | 2845 | 3220 | 3595 | 3970 | 4345 | 4575 | 4685 | 4805 | 5025 | 5260 | | |
| 30 mph | | | 2270 | 2735 | 3095 | 3450 | 3805 | 4165 | 4385 | 4495 | 4610 | 4830 | 5050 | | |
| 40 mph | | | 2270 | 2600 | 2945 | 3285 | 3625 | 3970 | 4180 | 4290 | 4385 | 4595 | 4805 | | |
| 25 mph Dual | 1810 | 2005 | 2195 | 2555 | 2930 | 3295 | 3560 | 3825 | 4025 | 4125 | 4235 | 4430 | 4630 | 4915 | 5015 |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|------------------------|------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|
| 28 | | 440/65 R28 131D TL | | | | | | | | | | 96372 (386212) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 17.2 | 50.8 | 22.8 | 150.9 | DW14L | DW15L, W13, W14L, W15L | | | | | | 22.8 | 52.3 | 54 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 3000 | 3265 | 3525 | 3955 | 4375 | 4805 | 5205 | 5600 | 5995 | 6195 | 6395 | | | | |
| 20 mph | 2335 | 2545 | 2755 | 3230 | 3715 | 4190 | 4565 | 4940 | | | | | | | |
| 25 mph | | | 2625 | 3075 | 3540 | 3990 | 4355 | 4720 | | | | | | | |
| 30 mph | | | 2515 | 2945 | 3385 | 3815 | 4165 | 4520 | | | | | | | |
| 40 mph | | | 2405 | 2810 | 3230 | 3640 | 3970 | 4300 | | | | | | | |
| 25 mph Dual | 1960 | 2140 | 2305 | 2710 | 3110 | 3515 | 3835 | 4155 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-------------------|------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|
| 28 | | 480/65 R28 136D TL | | | | | | | | | | 14369 (897574) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 18.7 | 52.7 | 23.5 | 156.3 | DW15L | DW14L, W14L, W15L | | | | | | 24.6 | 63.9 | 57 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 3415 | 3695 | 3970 | 4485 | 4995 | 5510 | 5985 | 6450 | 6925 | 7155 | 7385 | | | | |
| 20 mph | 2600 | 2890 | 3175 | 3725 | 4275 | 4830 | 5260 | 5690 | | | | | | | |
| 25 mph | | | 3020 | 3540 | 4070 | 4585 | 4995 | 5400 | | | | | | | |
| 30 mph | | | 2890 | 3395 | 3900 | 4410 | 4795 | 5180 | | | | | | | |
| 40 mph | | | 2755 | 3230 | 3715 | 4190 | 4565 | 4940 | | | | | | | |
| 25 mph Dual | 2185 | 2425 | 2655 | 3120 | 3570 | 4035 | 4400 | 4750 | | | | | | | |

* Refer to the notes at the end of the tables of this range

MULTIBIB™

Tire specifications and pressure table. Load per tire in lbs.*

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-------------------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|----|
| 28 | | 540/65 R28 142D TL | | | | | | | | | | 36062 (792274) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | | |
| 20.8 | 56.2 | 24.8 | 166.3 | DW16L | DW18L, W16L, W18L | | | | | 28.0 | 84 | 61 | | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 4190 | 4495 | 4805 | 5410 | 6010 | 6615 | 7165 | 7715 | 8265 | 8545 | 8820 | | | | |
| 20 mph | 3175 | 3495 | 3815 | 4440 | 5060 | 5690 | 6205 | 6725 | | | | | | | |
| 25 mph | | | 3615 | 4210 | 4805 | 5400 | 5895 | 6395 | | | | | | | |
| 30 mph | | | 3485 | 4045 | 4620 | 5180 | 5655 | 6130 | | | | | | | |
| 40 mph | | | 3305 | 3845 | 4400 | 4940 | 5390 | 5840 | | | | | | | |
| 25 mph Dual | 2655 | 2920 | 3185 | 3705 | 4235 | 4750 | 5190 | 5620 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-------------------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|----|
| 30 | | 540/65 R30 143D TL | | | | | | | | | | 28553 (223153) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | | |
| 20.7 | 58 | 25.5 | 171.4 | DW16L | DW18L, W16L, W18L | | | | | 28.0 | 88 | 61 | | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 4300 | 4620 | 4940 | 5555 | 6160 | 6780 | 7365 | 7935 | 8520 | 8805 | 9095 | | | | |
| 20 mph | 3265 | 3595 | 3925 | 4565 | 5205 | 5840 | 6370 | 6900 | | | | | | | |
| 25 mph | | | 3750 | 4355 | 4950 | 5555 | 6065 | 6570 | | | | | | | |
| 30 mph | | | 3595 | 4180 | 4750 | 5335 | 5820 | 6305 | | | | | | | |
| 40 mph | | | 3415 | 3970 | 4520 | 5070 | 5545 | 6010 | | | | | | | |
| 25 mph Dual | 2735 | 3020 | 3295 | 3825 | 4365 | 4895 | 5335 | 5775 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-------------------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|----|
| 34 | | 540/65 R34 145D TL | | | | | | | | | | 22243 (712064) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | | |
| 20.9 | 62 | 27.3 | 183.3 | DW16L | DW18L, W16L, W18L | | | | | 28.0 | 96.2 | 61 | | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 4540 | 4870 | 5205 | 5855 | 6515 | 7165 | 7780 | 8410 | 9030 | 9335 | 9645 | | | | |
| 20 mph | 3440 | 3815 | 4190 | 4905 | 5635 | 6350 | 6855 | 7365 | | | | | | | |
| 25 mph | | | 3990 | 4675 | 5355 | 6040 | 6525 | 7010 | | | | | | | |
| 30 mph | | | 3815 | 4475 | 5135 | 5800 | 6260 | 6725 | | | | | | | |
| 40 mph | | | 3640 | 4265 | 4885 | 5510 | 5950 | 6395 | | | | | | | |
| 25 mph Dual | 2890 | 3210 | 3515 | 4110 | 4720 | 5315 | 5745 | 6175 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-------------------|------|------|------|------|----------------------------------|----------------------------|------------------------|-------|-------|-------|
| 34 | | 540/65 R34 152D TL | | | | | | | | | | 99445 (214036) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | | |
| 20.9 | 62.6 | 27.9 | 185.7 | DW16L | DW18L, W16L, W18L | | | | | 28.0 | 96.2 | 61 | | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 4540 | 4870 | 5205 | 5855 | 6515 | 7165 | 7780 | 8410 | 9030 | 9335 | 9645 | 10195 | 10750 | 11495 | 11740 |
| 20 mph | 3440 | 3815 | 4190 | 4905 | 5635 | 6350 | 6855 | 7365 | 7770 | 7980 | 8180 | 8585 | 8995 | | |
| 25 mph | | | 3990 | 4675 | 5355 | 6040 | 6525 | 7010 | 7410 | 7595 | 7795 | 8190 | 8575 | | |
| 30 mph | | | 3815 | 4475 | 5135 | 5800 | 6260 | 6725 | 7100 | 7285 | 7475 | 7850 | 8225 | | |
| 40 mph | | | 3640 | 4265 | 4885 | 5510 | 5950 | 6395 | 6755 | 6935 | 7110 | 7475 | 7825 | | |
| 25 mph Dual | 2890 | 3210 | 3515 | 4110 | 4720 | 5315 | 5745 | 6175 | 6515 | 6690 | 6855 | 7200 | 7540 | | |

* Refer to the notes at the end of the tables of this range

MULTIBIB™

Tire specifications and pressure table. Load per tire in lbs.*

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-----------------|------|------|------|-------|-------|----------------------------------|----------------------------|------------------------|----|----|
| 34 | | 600/65 R34 151D TL | | | | | | | | | | 16291 (557189) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 23.4 | 65.1 | 28.8 | 192.8 | DW20B (A) | DW18L, W18L | | | | | | 29.9 | 122.6 | 68 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 5355 | 5765 | 6175 | 6965 | 7750 | 8545 | 9250 | 9955 | 10650 | 11000 | 11355 | | | | |
| 20 mph | 4055 | 4495 | 4940 | 5745 | 6560 | 7365 | 8060 | 8750 | | | | | | | |
| 25 mph | | | 4720 | 5480 | 6250 | 7010 | 7670 | 8335 | | | | | | | |
| 30 mph | | | 4520 | 5260 | 5985 | 6725 | 7350 | 7980 | | | | | | | |
| 40 mph | | | 4300 | 4995 | 5700 | 6395 | 7000 | 7605 | | | | | | | |
| 25 mph Dual | 3395 | 3780 | 4155 | 4830 | 5500 | 6175 | 6755 | 7330 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-------------------|------|------|------|------|------|----------------------------------|----------------------------|------------------------|----|----|
| 38 | | 540/65 R38 147D TL | | | | | | | | | | 28857 (114518) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 20.8 | 65.9 | 29.3 | 195.5 | DW16L | DW18L, W16L, W18L | | | | | | 28.0 | 104.1 | 61 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 4805 | 5160 | 5510 | 6205 | 6910 | 7605 | 8255 | 8905 | 9545 | 9875 | 10195 | | | | |
| 20 mph | 3680 | 4055 | 4430 | 5125 | 5830 | 6525 | 7165 | 7805 | | | | | | | |
| 25 mph | | | 4235 | 4895 | 5555 | 6215 | 6825 | 7430 | | | | | | | |
| 30 mph | | | 4055 | 4685 | 5325 | 5950 | 6535 | 7120 | | | | | | | |
| 40 mph | | | 3860 | 4465 | 5070 | 5675 | 6230 | 6780 | | | | | | | |
| 25 mph Dual | 3085 | 3405 | 3725 | 4310 | 4885 | 5465 | 6010 | 6535 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-----------------|------|------|-------|-------|-------|----------------------------------|----------------------------|------------------------|----|----|
| 38 | | 600/65 R38 153D TL | | | | | | | | | | 29767 (228045) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 23.4 | 69.6 | 30.7 | 205.9 | DW20B (A) | DW18L, W18L | | | | | | 29.9 | 132.1 | 67 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 5675 | 6120 | 6550 | 7395 | 8245 | 9095 | 9820 | 10560 | 11290 | 11650 | 12015 | | | | |
| 20 mph | 4320 | 4775 | 5225 | 6085 | 6945 | 7805 | 8530 | 9260 | | | | | | | |
| 25 mph | | | 4980 | 5800 | 6615 | 7430 | 8125 | 8820 | | | | | | | |
| 30 mph | | | 4760 | 5545 | 6340 | 7120 | 7780 | 8445 | | | | | | | |
| 40 mph | | | 4540 | 5290 | 6030 | 6780 | 7420 | 8045 | | | | | | | |
| 25 mph Dual | 3625 | 4010 | 4385 | 5105 | 5820 | 6535 | 7155 | 7760 | | | | | | | |

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-----------------|-------|-------|-------|-------|-------|----------------------------------|----------------------------|------------------------|----|----|
| 38 | | 650/65 R38 157D TL | | | | | | | | | | 12871 (292904) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 25.4 | 71.6 | 31.5 | 211.8 | DW20B (A) | | | | | | | 32.5 | 159 | 71 | | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 6395 | 6890 | 7385 | 8320 | 9260 | 10195 | 11035 | 11885 | 12720 | 13140 | 13560 | | | | |
| 20 mph | 4830 | 5335 | 5840 | 6810 | 7780 | 8750 | 9600 | 10450 | | | | | | | |
| 25 mph | | | 5555 | 6480 | 7410 | 8335 | 9150 | 9965 | | | | | | | |
| 30 mph | | | 5335 | 6215 | 7100 | 7980 | 8765 | 9545 | | | | | | | |
| 40 mph | | | 5070 | 5920 | 6755 | 7605 | 8355 | 9095 | | | | | | | |
| 25 mph Dual | 4045 | 4475 | 4895 | 5710 | 6515 | 7330 | 8060 | 8775 | | | | | | | |

* Refer to the notes at the end of the tables of this range

MULTIBIB™

Tire specifications and pressure table. Load per tire in lbs.*

| Rim Size (inch) | | Description | | | | | | | | | | MSPN (CAI) | | | |
|-----------------|---------------------|---------------------|-----------------------|-----------------|-----------------|-------|-------|-------|-------|-------|----------------------------------|----------------------------|------------------------|----|----|
| 42 | | 650/65 R42 158D TL | | | | | | | | | | 38881 (167733) | | | |
| Section Width | Overall Diam. (in.) | Loaded Radius (in.) | Rolling Circum. (in.) | Recommended Rim | Acceptable Rims | | | | | | Min. Dual / Triple Spacing (in.) | 75% internal volume (gal.) | Tread depth (32nd in.) | | |
| 25.1 | 76 | 33.8 | 225.3 | DW20B (A) | | | | | | | | 32.5 | 170.9 | 72 | |
| Psi | 6 | 7 | 9 | 12 | 15 | 17 | 20 | 23 | 26 | 28 | 29 | 32 | 35 | 39 | 41 |
| 6 mph ** | 6615 | 7110 | 7605 | 8565 | 9515 | 10470 | 11365 | 12270 | 13160 | 13605 | 14055 | | | | |
| 20 mph | 5070 | 5610 | 6150 | 7185 | 8225 | 9260 | 10020 | 10780 | | | | | | | |
| 25 mph | | | 5865 | 6845 | 7835 | 8820 | 9535 | 10250 | | | | | | | |
| 30 mph | | | 5620 | 6560 | 7505 | 8445 | 9140 | 9835 | | | | | | | |
| 40 mph | | | 5355 | 6250 | 7155 | 8045 | 8710 | 9370 | | | | | | | |
| 25 mph Dual | 4255 | 4705 | 5160 | 6030 | 6890 | 7760 | 8390 | 9015 | | | | | | | |

***IMPORTANT:**

The inflation pressure must always be appropriate for the load per tire, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (June 2018). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque use the 20 mph line.
- When using single tire configuration:
 - add 6 psi for use on slopes of more than 20%
 - add 6 psi for intense road use exceeding 50%
- **6 mph LT (Low Torque) (max speed 6 mph).