

MICHELIN[®] X MINE[®] D2

GET ALL THE BENEFITS OF MICHELIN[®]
RADIAL TIRE TECHNOLOGY!

With the MICHELIN[®] X MINE[®] D2 tire, you will get:

- Excellent productivity and uptime
- Long tire life
- Maximum operator comfort and machine protection
- No chains or foam/poly fill required



MICHELIN® X MINE® D2

This rugged MICHELIN® super L5 traction radial designed to give maximum protection in severe hard rock quarries, underground mines, scrap and solid waste applications.

THE BENEFITS OF MICHELIN® RADIAL TIRES

Exceptional Performance:

- Excellent traction and flotation; outstanding stability; enhanced operator comfort; less vehicle damage

Excellent Productivity:

- Resistance to impacts and cuts means fewer flats

Low Operating Costs:

- Long-lasting, even-wearing tread pattern; durable with low rolling resistance for efficient fuel economy; easy to repair

THE TIRE OF CHOICE FOR:



LOADERS



UNDERGROUND HAULERS



UNDERGROUND LOADERS



Increased Productivity

The ultra-deep L5 rock tread with massive buttressed shoulders and sidewalls provide resistance to damage in severe operating conditions.

Maximum Comfort and Machine Protection

The MICHELIN® radial design helps protect valuable machine components while giving operators a smooth, comfortable ride. It eliminates the need for expensive foam/poly fill or chains.

Long Tire Life

The combination of multiple steel belts, cut-resistant rubber compounds and a heavy-duty casing means fewer flats.

MICHELIN NORTH AMERICA, INC.

One Parkway South, P.O. Box 19001, Greenville, SC 29602-9001
1-877-574-8473

www.michelinearthmover.com

© 1999 MNA, Inc.
MEL41597 (Rev 7/12)

| SIZE | TREAD DEPTH | |
|----------------------|-------------|-----|
| | 32nds | MM |
| 7.50 R 15 TT | 58 | 46 |
| 8.25 R 15 TT | 61 | 48 |
| 10.00 R 15 TT | 61 | 48 |
| 350/65 R 15 TL | 45 | 36 |
| 400/80 R 15 TL | 43 | 34 |
| 14.5 R 15 TL | 61 | 48 |
| 9.00 R 20 TT | 64 | 51 |
| 12.00 R 20 TT | 72 | 57 |
| 14.00 R 20 TL | 61 | 48 |
| 12.00 R 24 TL | 72 | 57 |
| 15.5 R 25 TL | 76 | 60 |
| 17.5 R 25 TL ** | 82 | 65 |
| 18.00 R 25 TL ** | 103 | 82 |
| 20.5 R 25 TL ** | 93 | 74 |
| 23.5 R 25 TL ** | 105 | 83 |
| 26.5 R 25 TL ** | 115 | 91 |
| 29.5 R 25 TL ** | 126 | 100 |
| 29.5 R 29 TL ** | 126 | 100 |
| 35/65 R 33 TL ** | 117 | 93 |
| 45/65 R 39 L5R TL ** | 146 | 116 |
| 45/65 R 45 L5R TL ** | 146 | 116 |
| 55/80 R 57 SR TL | 150 | 119 |
| 55/80 R 57 HR TL | 150 | 119 |
| 55/80 R 57 LC TL | 150 | 119 |
| 60/80 R 57 SR TL | 149 | 118 |
| 60/80 R 57 HR TL | 149 | 118 |
| 50/65 R 51 HR TL ** | 146 | 116 |
| 50/65 R 51 SR TL ** | 146 | 116 |

