

MICHELIN® X-STACKER® 2 LC

STACKS UP IN PERFORMANCE



X-STACKER 2 LC 207A5
18.00 R 25 TUBELESS



REACH STACKERS



MICHELIN® X-STACKER® 2 LC

STACKS UP IN PERFORMANCE



REACH STACKERS



MORE ROBUST¹

Designed to address very severe usages (speed, load combination) on reach stacker's rear axle



MICHELIN® X-STACKER 2 18.00 R 25




MICHELIN® X-STACKER 2 LC 18.00 R 25



+8.6%
INTERNAL AIR
VOLUME ⁽²⁾

-25%
TREAD
THICKNESS ⁽³⁾

- LESS RUBBER FOR A COOLER TIRE
- MORE INTERNAL AIR VOLUME FOR AN IMPROVED RESISTANCE TO LOAD



MICHELIN

(1) Compared to 18.00 R 25 MICHELIN® X-STACKER® 2 tire. Less rubber for a cooler tire and more internal air volume for an improved resistance to load.

(2) 18.00 R 25 MICHELIN® X-STACKER® 2 tire air volume is 465 liters and 18.00 R 25 MICHELIN® X-STACKER® 2 LC tire air volume is 505 liters.


(3) 18.00 R 25 MICHELIN® X-STACKER® 2 tire tread depth is 72 mm and 18.00 R 25 MICHELIN® X-STACKER® 2 LC tire tread depth is 54 mm.



MICHELIN TECHNICAL DATA

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim ⁽⁴⁾	Other Approved Rims ⁽⁴⁾
X-STACKER 2 LC 207A5 18.00 R 25 Tubeless	042180 09186	11 6.8 if load per tire <=17.5 t	501 19.7	1656 65.2	750 29.5	5006 197.1	54 68	612 24.1	465 122.9	13.00/2.5	15.00/2.5
		10 6.2 if load per tire >17.5 t									
Bar		6				8				10	
Psi		87				116				145	
Machine - Use (kg - lb)	MECHANICAL HANDLING, CYCLIC SERVICE: On reachstackers rear axle. Also suitable for AGVs.										
STATIC		18380 40528				22280 49127				26250 57881	
<= 10 KM/H		15930				19180				22750	
<= 6 MPH		35126				42292				50164	
25 KM/H		12250				14750				17500	
15 MPH		27011				32524				38588	
Machine - Use (kg - lb)	MECHANICAL HANDLING, CYCLIC SERVICE: On reachstackers rear axle. Also suitable for AGVs.										
<= 10 KM/H		15930				19180				22750	
<= 6 MPH		35126				42292				50164	
25 KM/H		15930				19180				22750	
15 MPH		35126				42292				50164	
Machine - Use (kg - lb)	AGV PORT										
<= 10 KM/H		15930				19180				22750	
<= 6 MPH		35126				42292				50164	
25 KM/H		15930				19180				22750	
15 MPH		35126				42292				50164	

For non cyclic use, or other vehicles, contact your Michelin representative.



MICHELIN

⁽⁴⁾ More informations in the Michelin Databook 2019.



MICHELIN



OUR WEBSITE
michelinearthmover.com



TESTIMONIALS
YouTube channel



PRESSURE ADVISOR
pressureadvisor.michelinearthmover.com

AUTHORIZED DISTRIBUTOR:

A large, empty white rounded rectangular box intended for the name of the authorized distributor.