

MICHELIN®

XZM™ 2+

**YOUR PRODUCTIVITY
DESERVES MICHELIN**



XZM 2+ 207A5 18.00 R 25 TUBELESS

XZM 2+ 214A5 18.00 R 33 TUBELESS



FORKLIFTS TRUCKS



YOUR PRODUCTIVITY DESERVES MICHELIN



FORKLIFT TRUCKS



■ **PRODUCTIVITY**

REDUCED DOWNTIME

15% longer service life¹



■ **STRENGTH**

REINFORCED-CROWN ARCHITECTURE

Highly resistant to impact and puncture




■ **COMFORT**

Radial technology



Highly resistant to impact and puncture

15% longer service life¹
Massive tread, wear-resistant, low abrasion rubber





MICHELIN TECHNICAL DATA

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (2)	Other Approved Rims (2)
XZM 2+ 207A5 18.00 R 25 Tubeless (14)	230783 98640	10 6.2	503 19.8	1668 65.7	751 29.6	5032 198.1	78 98.3	612 24.1	470 124.2	13.00/2.5	15.00/2.5

Bar	6	8	10
Psi	87	116	145

Machine - Use (kg - lb) MECHANICAL HANDLING, CYCLIC SERVICE: Side loaders and forklift trucks steer axle

STATIC	18380 40528	22280 49127	26250 57881
<= 10 KM/H	15930	19180	22750
<= 6 MP/H	35126	42292	50164
25 KM/H	12250	14750	17500
15 MPH	27011	32524	38588

Machine - Use (kg - lb) MECHANICAL HANDLING, CYCLIC SERVICE: Forklift trucks drive axle

<= 10 KM/H	15930	19180	22750
<= 6 MP/H	35126	42292	50164
25 KM/H	15930	19180	22750
15 MPH	35126	42292	50164

For non cyclic use, or other vehicles, contact your Michelin representative.

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (2)	Other Approved Rims (2)
XZM 2+ 214A5 18.00 R 33 Tubeless (14)	305696 98655	10 6.2	503 19.8	1841 72.5	826 32.5	5547 218.4	78 98.3	604 23.8	520 137.4	13.00/2.5	

Bar	6	8	10
Psi	87	116	145


Machine - Use (kg - lb) MECHANICAL HANDLING, CYCLIC SERVICE: Side loaders and forklift trucks steer axle

STATIC	22500 49613	27000 59535	31800 70119
<= 10 KM/H	19500	23400	27560
<= 6 MP/H	42998	51597	60770
25 KM/H	15000	18000	21200
15 MPH	33075	39690	46746

Machine - Use (kg - lb) MECHANICAL HANDLING, CYCLIC SERVICE: Forklift trucks drive axle

<= 10 KM/H	19500	23400	27560
<= 6 MP/H	35126	42292	60770
25 KM/H	19500	23400	27560
15 MPH	35126	42292	60770

For non cyclic use, or other vehicles, contact your Michelin representative.



MICHELIN

(2) More informations in the Michelin Databook 2019.



MICHELIN



OUR WEBSITE
michelinearthmover.com



TESTIMONIALS
YouTube channel



PRESSURE ADVISOR
pressureadvisor.michelinearthmover.com

AUTHORIZED DISTRIBUTOR:

A large, empty white rounded rectangular box intended for the name of the authorized distributor.