

# **MICHELIN®**

## **X-STRADDLE® 2**

**MOVING CONTAINERS  
FURTHER AND FASTER**



X-STRADDLE 2 202A7 450/95 R 25 TUBELESS

X-STRADDLE 2 206A7 480/95 R 25 TUBELESS




STRADDLE CARRIERS



# MICHELIN® X-STRADDLE® 2

## MOVING CONTAINERS **FURTHER AND FASTER**



STRADDLE CARRIERS

Michelin  
**TPMS**  
Ready



### ■ **HIGH LOAD CAPACITY AT HIGH SPEEDS**

**CARRY UP TO 17.85  
TONS<sup>1</sup> UP TO 22 KM/H  
(13 MPH)**

Due to +20% tire inner air volume<sup>2</sup>



### ■ **RUN LONGER DISTANCES<sup>3</sup>**

**DRIVE UP TO 15 KM  
IN 1 HOUR AND 35 KM/H  
MAX SPEED**

Due to a cooler running tire<sup>4</sup>



### ■ **SIMPLICITY**

**CAN BE FITTED ON BOTH  
11.25 AND 13.00 RIMS<sup>6</sup>**


Due to a new bead area design



### ■ **RUN FURTHER**

**UP TO +15% TIRE LIFE<sup>5</sup>**

Due to a new tread design with 8% more rubber and an improved crown and bead durability<sup>4</sup>



**MICHELIN**

(1) At the nominal pressure of 10 bars and carry 17 Tons from 22km/h to 25km/h.

(2) Compared to MICHELIN® X-STRADDLE® 16.00R25 and MICHELIN® X-STRADDLE® 2 450/95R25 tires.

(3) Compared to MICHELIN® X-STRADDLE® 480/95R25: max distance of 12 kilometers in one hour and 30 mi/h max speed.

(4) Compared to MICHELIN® X-STRADDLE® 480/95R25 tire.

(5) Compared to MICHELIN® X-STRADDLE® 480/95R25 tire, average performance by port site. Projected improvement in tire life based on field performance in customer port sites of the MICHELIN® X-STRADDLE® 2 450/95R25 tire size compared to the MICHELIN® X-STRADDLE® 16.00R25 tire (the 450/95R25 is an equivalent size of the 16.00R25), that included individual design improvements incorporated into the MICHELIN® X-STRADDLE® 2 480/95R25 tire.

(6) Measuring rim: 13.00/2.5 and approved rim: 11.25/2.0





## MICHELIN TECHNICAL DATA

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (7)	Other Approved Rims (7)
X-STRADDLE 2 202A7 450/95 R 25 Tubeless (16-18)	278967 38706	15 9.3	422 16.6	1510 59.4	670 26.4	4530 178.3	50 63		342 90.4	11.25/2.0	13.00/2.0

Bar	6	8	10
Psi	87	116	145

Machine - Use (kg - lb)	STRADDLE CARRIER		
22 KM/H	10630	13150	15750
14 MPH	23439	28996	34729
25 KM/H	10125	12525	15000
15 MPH	22326	27618	33075
35 KM/H	9370	11590	13875
22 MPH	20661	25556	30594

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (7)	Other Approved Rims (7)
X-STRADDLE 2 206A7 480/95 R 25 Tubeless (16)	653072 07011	15 9.3	467 18.4	1553 61.1	687 27	4655 183.3	50 63	580 22.8	410 108.3	13.00/2.5	11.25/2.0 [1.7]

Bar	6	8	10
Psi	87	116	145

Machine - Use (kg - lb)	STRADDLE CARRIER		
22 KM/H	11970	14900	17850
14 MPH	26394	32855	39359
25 KM/H	11400	14200	17000
15 MPH	25137	31311	37485
35 KM/H	10545	13135	15725
22 MPH	23252	28963	34674

(7) More informations in the Michelin Databook 2019.





**OUR WEBSITE**  
[michelinearthmover.com](http://michelinearthmover.com)



**TESTIMONIALS**  
YouTube channel



**PRESSURE ADVISOR**  
[pressureadvisor.michelinearthmover.com](http://pressureadvisor.michelinearthmover.com)

**AUTHORIZED DISTRIBUTOR:**