

# MICHELIN® X-STRADDLE® 2

MOVING CONTAINERS  
FURTHER AND FASTER



X-STRADDLE 2 202A7 450/95 R 25 TUBELESS  
X-STRADDLE 2 206A7 480/95 R 25 TUBELESS




STRADDLE CARRIERS



# MICHELIN® X-STRADDLE® 2

## MOVING CONTAINERS **FURTHER AND FASTER**



STRADDLE CARRIERS

Michelin  
**TPMS**  
Ready



### ■ **HIGH LOAD CAPACITY AT HIGH SPEEDS**

**CARRY UP TO 17.85  
TONS<sup>1</sup> UP TO 22 KM/H  
(13 MPH)**

Due to +20% tire inner air volume<sup>2</sup>



### ■ **RUN LONGER DISTANCES<sup>3</sup>**

**DRIVE UP TO 15 KM  
IN 1 HOUR AND 35 KM/H  
MAX SPEED**

Due to a cooler running tire<sup>4</sup>



### ■ **SIMPLICITY**

**CAN BE FITTED ON BOTH  
11.25 AND 13.00 RIMS<sup>6</sup>**


Due to a new bead area design



### ■ **RUN FURTHER**

**UP TO +15% TIRE LIFE<sup>5</sup>**

Due to a new tread design with 8%  
more rubber and an improved crown  
and bead durability<sup>4</sup>



**MICHELIN**

(1) At the nominal pressure of 10 bars and carry 17 Tons from 22km/h to 25km/h.

(2) Compared to MICHELIN® X-STRADDLE® 16.00R25 and MICHELIN® X-STRADDLE® 2 450/95R25 tires.

(3) Compared to MICHELIN® X-STRADDLE® 480/95R25: max distance of 12 kilometers in one hour and 30 mi/h max speed.

(4) Compared to MICHELIN® X-STRADDLE® 480/95R25 tire.

(5) Compared to MICHELIN® X-STRADDLE® 480/95R25 tire, average performance by port site. Projected improvement in tire life based on field performance in customer port sites of the MICHELIN® X-STRADDLE® 2 450/95R25 tire size compared to the MICHELIN® X-STRADDLE® 16.00R25 tire (the 450/95R25 is an equivalent size of the 16.00R25), that included individual design improvements incorporated into the MICHELIN® X-STRADDLE® 2 480/95R25 tire.

(6) Measuring rim: 13.00/2.5 and approved rim: 11.25/2.0



## MICHELIN TECHNICAL DATA

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (7)	Other Approved Rims (7)
<b>X-STRADDLE 2 202A7</b> 450/95 R 25 Tubeless (16-18)	<b>278967</b> 38706	<b>15</b> 9.3	<b>422</b> 16.6	<b>1510</b> 59.4	<b>670</b> 26.4	<b>4530</b> 178.3	<b>50</b> 63		<b>342</b> 90.4	11.25/2.0	13.00/2.0

<b>Bar</b>	<b>6</b>	<b>8</b>	<b>10</b>
<i>Psi</i>	87	116	145

Machine - Use  
(kg - lb)

### STRADDLE CARRIER

<b>22 KM/H</b>	<b>10630</b>	<b>13150</b>	<b>15750</b>
14 MPH	23439	28996	34729
<b>25 KM/H</b>	<b>10125</b>	<b>12525</b>	<b>15000</b>
15 MPH	22326	27618	33075
<b>35 KM/H</b>	<b>9370</b>	<b>11590</b>	<b>13875</b>
22 MPH	20661	25556	30594

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (7)	Other Approved Rims (7)
<b>X-STRADDLE 2 206A7</b> 480/95 R 25 Tubeless (16)	<b>653072</b> 07011	<b>15</b> 9.3	<b>467</b> 18.4	<b>1553</b> 61.1	<b>687</b> 27	<b>4655</b> 183.3	<b>50</b> 63	<b>580</b> 22.8	<b>410</b> 108.3	13.00/2.5	11.25/2.0 [1.7]

<b>Bar</b>	<b>6</b>	<b>8</b>	<b>10</b>
<i>Psi</i>	87	116	145

Machine - Use  
(kg - lb)

### STRADDLE CARRIER

<b>22 KM/H</b>	<b>11970</b>	<b>14900</b>	<b>17850</b>
14 MPH	26394	32855	39359
<b>25 KM/H</b>	<b>11400</b>	<b>14200</b>	<b>17000</b>
15 MPH	25137	31311	37485
<b>35 KM/H</b>	<b>10545</b>	<b>13135</b>	<b>15725</b>
22 MPH	23252	28963	34674



**MICHELIN**

(7) More informations in the Michelin Databook 2019.



**MICHELIN**



**OUR WEBSITE**  
michelinearthmover.com



**TESTIMONIALS**  
YouTube channel



**PRESSURE ADVISOR**  
pressureadvisor.michelinearthmover.com

**AUTHORIZED DISTRIBUTOR:**

A large, empty white rounded rectangular box intended for the name of the authorized distributor.