



OFF ROAD APPLICATIONS

THE MICHELIN® XZL™ TIRE

All-terrain, all-position radial for special service such as Emergency Response and Tactical Wheeled vehicles.

Line Haul	Regional	Urban	On/Off Road
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Recommended Acceptable



THE MICHELIN® XZL™ TIRE

All-terrain, all-position radial for special service such as Emergency Response and Tactical Wheeled vehicles.

Self-cleaning, open shoulder tread design – features offset elements to help enhance traction and floatation capabilities on varied terrains including snow, sand, mud and highway.

Radial casing design optimized to operate at lower pressures to offer exceptional mobility and enhanced enveloping capabilities to resist impacts.

All-terrain, non-directional design – for added versatility.

Full-width steel belts and elastic protector ply – help provide added casing protection against most off-road hazards.

Tubeless construction – compatible with Central Tire Inflation systems and bead locks.



Size	Load Range	Catalog Number	Tread Depth		Max. Speed (*)		Loaded Radius		Overall Diameter		Overall Width (‡)		Approved Wheels (Measuring wheel listed first.)	Revs Per Mile	Max. Load and Pressure Single			
			32nds	mm	mph	kph	in.	mm	in.	mm	in.	mm			lbs.	psi	kg.	kPa
255/100R16	D	70864	21	533	68	109	16.8	427	36.3	923	10.0	255	6.50, 6.00	572	3750	65	1700	450
12.00R20	J	02383	24	610	68	109	20.7	527	44.5	1131	12.2	311	8.50, 8.00, 7.50	465	8270	120	3750	830
16.00R20	M	06306	34	864	55	88	23.9	609	52.9	1343	17.2	438	10.00W, 10.00, 10.00V	397	14540	110	6595	760
365/80R20 MPT	L	97627	25	635	68	109	19.7	501	43.1	1096	14.6	372	11.0	483	7830	90	3550	620
365/85R20	J	56389	28	711	55	88	20.4	519	45.0	1144	14.5	368	10.00W, 10.00V	465	11000	115	5000	790
395/85R20	J	54331	33	841	55	88	21.3	542	46.8	1189	15.3	388	10.00W, 10.00, 10.00V	447	12300	120	5600	830
24R21	H	76025	31	787	55	88	24.8	631	54.6	1388	23.9	608	18.00	383	15700	85	7100	590

Note: Wheel listed first is the measuring wheel.

(*) Exceeding the lawful speed limit is neither recommended nor endorsed.

(‡) Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

MICHELIN® tires and tubes are subject to a continuous development program. Michelin North America, Inc. reserves the right to change product specifications at any time without notice or obligations. MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect the current Load and Inflation information. Please visit www.michelintruck.com for the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions. Never exceed a wheel manufacturer's limits without permission from the component manufacturer.

TO FIND OUT MORE
 US: business.michelinman.com
 CA: michelintruck.com/en_CA

FIND US ON FACEBOOK
[michelintruck](https://www.facebook.com/michelintruck)

VISIT US ON THE WEB
 US: business.michelinman.com/contact-us
 CA: michelintruck.com/en_CA/contact-us

CONTACT US BY TELEPHONE
 US: 1-888-622-2306
 CA: 1-888-622-2306