


MICHELIN TRUCK AND BUS TYRE TECHNICAL DATABOOK




EDITION 2021 AUSTRALIA



MICHELIN
Total Performance



MICHELIN



SAFETY WARNINGS

BE SURE TO READ THE SAFETY INFORMATION PROVIDED HEREIN AS SERIOUS INJURY OR DEATH CAN RESULT FROM FAILURE TO FOLLOW SAFETY WARNINGS



WARNING: Tyre and rim servicing can be dangerous and must be done only by trained personnel using proper tools and procedures. Failure to read and comply with all procedures may result in serious injury or death to you or others.



WARNING: Re-inflation of any type of tyre and rim assembly that has been operated in a run-flat or underinflated condition (80% or less of recommended operating pressure) can result in serious injury or death. The tyre may be damaged on the inside and can explode while you are adding air. The rim parts may be worn, damaged or dislodged and can explosively separate.



WARNING: Use of gasoline, petrol or any other flammable material to lubricate, seal or seat the beads of a tyre can cause the tyre to explode or can cause the explosive separation of the tyre/rim assembly resulting in serious injury or death. The use of any flammable material during tyre servicing is absolutely prohibited.



WARNING: Any inflated tyre mounted on a rim contains explosive energy. The use of damaged, mismatched or improperly assembled tyre/rim parts can cause the assembly to burst apart with explosive force. If you are struck by an exploding tyre, rim part or the air blast, you can be seriously injured or killed.



WARNING: Re-assembly and inflation of mismatched rim parts can result in serious injury or death. Just because parts fit together does not mean they belong together. Check for proper matching of all rim parts before putting any parts together.



WARNING: Mismatching tyre and rim diameters is dangerous. A mismatched tyre and rim assembly may explode and can result in serious injury or death. This warning applies to any combination of mismatched components. Never assemble a tyre and rim unless you have positively identified and correctly matched the parts.

1

■ **TYRE KNOWLEDGE**

- **RADIAL TYRE COMPONENTS** 02
- **SIDEWALL DESIGN** 03
- **HOW TO READ TYRE MARKING** 04
- **INFLATION PRESSURE** 06

2

■ **TECHNICAL CHARACTERISTICS TABLE AND PRODUCT OFFER**

- **USER FOCUS, USAGE FOCUS** 08
- **TECHNICAL** 14 - 71
CHARACTERISTICS TABLE

3

■ **APPENDIX**

- **TUBE & FLAP ASSEMBLY** 74
- **TRUCK AND BUS WHEEL** 78
- **ACCESSORIES** 80
- **CONVERSION TABLE** 82
- **GENERAL INFORMATION** 85


CONTENTS

■ TYRE KNOWLEDGE 1

- **RADIAL TYRE COMPONENTS** 02
- **SIDEWALL DESIGN** 03
- **HOW TO READ TYRE MARKING** 04
- **INFLATION PRESSURE** 06




RADIAL TYRE COMPONENTS



MICHELIN X One

COMPONENTS



MICHELIN TRUCK & BUS TYRES NEW SIDEWALL DESIGN



385/55R22.5 F  = Front axle

295/80R22.5 D  = Drive axle

275/70R22.5 Z  = All position

455/55R22.5 T  = Trailer axle


F This marking indicates the tyre is designed for steer axles.

D This marking indicates the tyre is designed for drive axles.

Z This marking (<<Z>>) indicates the tyre is designed for all positions which includes steer, drive, free rolling, and trailer axles.

T This marking indicates the tyre is designed for trailer axles.
Tyre with marking (<<T>>) is specifically developed for trailer and semi-trailer fitments and is not suitable for front axle usage.


HOW TO READ TYRE MARKING



- 1** MICHELIN brand logo
- 2** Max load max press and max speed. US regulation
- 3** Tyre architecture
- 4** M+S Mud and Snow & 3PMSF picto
- 5** Traction new regulation (drive tyre) or FRT, free rolling tyre (trailer only tyre)
- 6** Specific code
- 7** Tyre position code (Letter F for Front axle, D for Drive, T for Trailer, Z for all axle ...) illustrated on a truck silhouette (arrow indicates axle position)
- 8** Tyre Size
- 9** Indicates added load and speed index (see chart)
- 10** Radial, tubeless, regroovable
- 11** Load and speed index
- 12** Made in...: indicates where the tyre has been manufactured
- 13** Place for logistic information: vignette, barcode & matricule number, ex: PRZ6596G
- 14** DOT: Department of transport. The last 4 numbers indicate tyre manufacturing.
- 15** Tyre evolution number: indicates production date
- 16** Brazil or China homologation
- 17** Option name: indicates tyre optional benefit.
- 18** Range Name: indicates tyre usage (see naming chart).
- 19** Usage Pictogram: illustrates tyre common usage
- 20** "Brand tire here": free space for hot branding
- 21** X® symbol of MICHELIN radial tyre, it's a registered brand
- 22** E2...: CEE homologation number
- 23** MICHELIN registered brand
- 24** Warning: gives user information

Tyre Marking Detailed Description

Overall dimensions



- S** Section width when measured on standard rim
- D** Free diameter (R $\times$ 2).
- $\emptyset$ Rim diameter.
- R** Free radius.
- E** Minimum dual spacing.
- R'** Laden radius.
- e** Static deflection (R-R').
- H** Section height.

Load Capacity Index: These numerical values are designed to correspond to a load value listed in a table similar to excerpt shown right. For a complete Load Capacity Index table, see page 85 in the appendix.

Speed Symbols: These alpha numeric symbols correspond to a maximum speed the tyre is designed for continuous operation. For a complete Speed Symbol table, see page 85 in the appendix.

Speed symbol and load index

Speed symbol	Speed		Index	Load kg	Index	Load kg	Index	Load kg	Index	Load kg
	mph	km/h								
A1	3	5	100	800	123	1550	146	3000	169	5800
A2	6	10	101	825	124	1600	147	3075	170	6000
A3	9	15	102	850	125	1650	148	3150	171	6150
A4	12	20	103	875	126	1700	149	3250	172	6300
A5	16	25	104	900	127	1750	150	3350	173	6500
A6	19	30	105	925	128	1800	151	3450	174	6700
A7	22	35	106	950	129	1850	152	3550	175	6900
A8	25	40	107	975	130	1900	153	3650	176	7100
B	31	50	108	1000	131	1950	154	3750	177	7300
C	37	60	109	1030	132	2000	155	3875	178	7500
D	40	65	110	1060	133	2060	156	4000	179	7750
E	43	70	111	1090	134	2120	157	4125	180	8000
F	50	80	112	1120	135	2180	158	4250	181	8250
G	56	90	113	1150	136	2240	159	4375	182	8500
J	62	100	114	1180	137	2300	160	4500	183	8750
K	68	110	115	1215	138	2360	161	4625	184	9000
L	74	120	116	1250	139	2430	162	4750	185	9250
M	81	130	117	1285	140	2500	163	4875	186	9500
N	87	140	118	1320	141	2575	164	5000	187	9750
			119	1360	142	2650	165	5150	188	10000
			120	1400	143	2725	166	5300	189	10300
			121	1450	144	2800	167	5450	190	10600
			122	1500	145	2900	168	5600	191	10900

IMPORTANT : At the time of fitting, it is vital that the various markings are checked, in order to be certain that the tyre is suitable for operation at the maximum allowed vehicle speed and loading.

Unique point

A number of truck tyre sizes carry a second load speed index marked on the sidewall. This is known as the «Unique Point» that is located after the main load index as shown below

135/133 G






For these sizes, the «Unique Point» provides additional load speed operating conditions in order to satisfy particular requirements.

IMPORTANT : Load variances based on speed do not apply to the additional couple load index / speed symbol of the unique point.

INFLATION PRESSURE

The most critical factor in tyre maintenance is proper inflation. No tyre or tube is completely impervious to loss of air pressure. To avoid the hazards of under inflation, lost-air must be replaced. Inflation pressure has a direct impact in tyre performance - both tread life and endurance - as shown in the following charts :



UNDERINFLATION
Causes abnormal tyre deflection, which builds up heat and causes irregular wear. Similar to the rim being too wide.

OVERINFLATION
Causes tyre to run hard and be more vulnerable to impacts. It also causes irregular wear. Similar to the rim being too narrow.

PROPER INFLATION
The correct profile for full contact with the road promotes traction, braking capability and safety.


■ TECHNICAL 2 CHARACTERISTICS TABLE AND PRODUCT OFFER

- USER FOCUS, USAGE FOCUS 08
- TECHNICAL 14 - 71
CHARACTERISTICS TABLE

TECHNICAL CHARACTERISTICS 2 TABLE AND PRODUCT OFFER

USER FOCUS, USAGE FOCUS

FIND THE RIGHT TYRES FOR YOUR APPLICATION



Reliable and cost effective tyre solution for long haulers, bringing fuel efficiency without compromising durability

Medium to heavy vehicle tyre ranges optimized for long distances

- Operating on improved road surfaces and high speeds
- Light aggression and scrub
- Slow wear rate applications



Outstanding durability and mobility on all kinds of roads and in all seasons for versatile activities

Small to heavy vehicle tyre ranges optimized for mixed regional and long distance service

- Primary and secondary road conditions
- Moderate to high scrub and frequent turns
- Medium to fast wear rate applications



Robustness, durability and off-road mobility for tippers, mixers, and construction service

Heavy duty vehicle tyre ranges optimized for mixed application on/off road service

- Construction, mining, forestry, agriculture activities
- Slow to moderate speeds, exposure to cuts and chipping
- Fast wear rate and high tyre aggression applications



Extreme robustness and off-road mobility for special vehicles

Heavy duty tyre ranges designed for off-road applications, on all type of soils



Reliable and cost effective tyre solutions especially designed for urban conditions, with optimized environmental impacts

Small to heavy vehicle tyre ranges optimized for urban/suburban service

- Variable loading with frequent stops, starts and turns
- City buses and municipal utilities
- Fast wear rate and high scrub applications



Robustness, durability and peace of mind for the light trucks user

Light truck tyre ranges designed for multipurpose service



Safe, comfortable and cost effective tyre solutions especially designed for coach, bring fuel efficiency without compromising durability

Medium to heavy vehicles tyre ranges optimized for motor coach on-road service

TECHNICAL CHARACTERISTICS

TABLE AND PRODUCT OFFER

2



Z



MICHELIN
X LINE ENERGY Z



MICHELIN
XZA 2+ ENERGY



MICHELIN
XZA 2 ENERGY



MICHELIN
XZA



MICHELIN
XJE 4 MIX ENERGY

F



MICHELIN
X LINE ENERGY F



MICHELIN
XFA 2 ENERGY

D



MICHELIN
XDA 2+ ENERGY



MICHELIN
XDA 2 ENERGY

T



MICHELIN
X ENERGY SAVERGREEN XT



MICHELIN
X LINE ENERGY T



MICHELIN
XTA 2+ ENERGY



MICHELIN
XTA 2 ENERGY



Z



MICHELIN
X MULTI Z



MICHELIN
X MULTI HD Z



MICHELIN
X MULTIWAY XZE R



MICHELIN
X MULTIWAY 3D XZE



MICHELIN
XZE 3 R



MICHELIN
XZE 2+



MICHELIN
XZE 2



MICHELIN
XZE



MICHELIN
XZN MIX ENERGY



MICHELIN
XJW 4+



MICHELIN
XJS WINTER GRIP+

F



MICHELIN
XFE

Z = ALL POSITION **F** = FRONT AXLE **D** = DRIVE AXLE **T** = TRAILER AXLE / MICHELIN Durable Technologies



X MULTI™

D



MICHELIN
X MULTI D



MICHELIN
X MULTI D+



MICHELIN
X MULTIWAY 3D XDE



MICHELIN
XDE 2



MICHELIN
XDE 2+



MICHELIN
XDN 2 GRIP



MICHELIN
XDW ICE GRIP

T



MICHELIN
X MULTI T



MICHELIN
XTE 3



MICHELIN
XTE 2 / XTE 2+



MICHELIN
XTA



MICHELIN
X ONE XTE

X WORKS™

Z



MICHELIN
X WORKS XZY



MICHELIN
X WORKS Z



MICHELIN
X WORKS XZ



MICHELIN
XZY 3



MICHELIN
XZY-2



MICHELIN
XZH 2 R

Z



MICHELIN
X ONE XZY 3

D



MICHELIN
X WORKS XDY



MICHELIN
X WORKS XD



MICHELIN
XDY 3

T



MICHELIN
XTY 2

X FORCE™

Z



MICHELIN
XZL 2



MICHELIN
XZL+



MICHELIN
XZL



MICHELIN
XML



MICHELIN
XS

D



MICHELIN
XDL

TECHNICAL CHARACTERISTICS

TABLE AND PRODUCT OFFER

2



MICHELIN
X INCITY Z



MICHELIN
XZU 3+



MICHELIN
XZU 3



MICHELIN
XZU ENERGY



MICHELIN
XZU 2T



MICHELIN
X ONE XZU S



MICHELIN
AGILIS



MICHELIN
AGILIS HD



MICHELIN
XZA



MICHELIN
XJE 4 MIX ENERGY



MICHELIN
XZY 3




MICHELIN
XDW Ice Grip



MICHELIN
X COACH ENERGY Z



MICHELIN
X COACH XD



Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
7.50R15	XTA	2	TT	16	135/133G	133/132J	8.50	10.5	4360	8.50	8240	8.50	220	787	2385	6.0 - 6.5 - 86.5	233	210	769	354	2340	238	6.00	15/16 J	15x6.00	
8.25R15	XTA	2	TT		143/141G	141/140J	8.50	11.2	5450	8.50	10300	8.50	246	853	2585	6.0 - 6.5 - 86.5 - 6.50	259	232	834	381	2547	262	6.50	15K	15x6.00	
10.00R15	XTA	2	TT	18	148/145G	146/144J	8.50	11.5	6300	8.50	11600	8.50	286	939	2845	7.0 - 7.5	298	269	914	419	2780	304	7.50	15P	15x7.50	
205/75R16	XDW ICE GRIP	7	TL		113/111L			11.9	2300	6.00	4360	6.00	213	726	2200	5.50 JI-6 JJ 5.50 K-6.5JJ	217	199	721	337	2207	225	5.50JJ			
195/85R16	XIE4 MIX ENERGY	7	TL		114/112L			8.5	2360	6.00	4480	6.00	206	751	2276	5J - 5.1/2J 6J - 6K	217	197	733	343.5	2241	223	5.50K			
195/85R16	XDW ICE GRIP	7	TL		114/112L			11.8	2360	6.00	4480	6.00	206	751	2276	5 J - 5.50 JI-6 JJ 5 K - 5.50 K-6 K	219	197	742	347	2270	223	5.50 JJ			
205/85R16	XIE4 MIX ENERGY	7	TL		117/115L			8.6	2570	6.00	4860	6.00	213	768	2327	5 - 5.5 - 6 - 6.5	233	211	752	352	2297	239	6.00			
	XDW ICE GRIP	7	TL		117/115L			11.9	2570	6.00	4860	6.00	213	768	2327	5J - 6J2K	231	211	761	356	2330	239	6.00K			
215/85R16	XIE4 MIX ENERGY	7	TL		120/118L			9.0	2800	6.00	5280	6.00	227	787	2385	5.5 - 6 - 6.5 - 7.0	241	219	769	358	2350	247	6.00K			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair Load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Tread pattern																				
		psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102
		bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
7.50R15	XTA	single													2950	3060	3180	3300	3420	3540	3650
		dual													5570	5790	6010	6240	6460	6680	6900
8.25R15	XTA	single													3680	3830	3980	4120	4270	4420	4570
		dual													6960	7240	7520	7790	8070	8350	8630
10.00R15	XTA	single													4260	4430	4600	4770	4940	5110	5280
		dual													7840	8150	8460	8780	9090	9410	9720
205/75R16	XDW ICE GRIP	single			1280	1360	1450	1530	1620	1700	1790	1870	1960	2040	2130	2210	2300				
		dual			2420	2580	2750	2910	3070	3230	3390	3550	3710	3880	4040	4200	4360				
195/85R16	X/E4MX ENERGY	single			1310	1400	1490	1570	1660	1750	1840	1920	2010	2100	2190	2270	2360				
		dual			2490	2650	2820	2990	3150	3320	3480	3650	3820	3980	4150	4310	4480				
195/85R16	XDW ICE GRIP	single			1310	1400	1490	1570	1660	1750	1840	1920	2010	2100	2190	2270	2360				
		dual			2490	2650	2820	2990	3150	3320	3480	3650	3820	3980	4150	4310	4480				
205/85R16	X/E4MX ENERGY	single			1430	1520	1620	1710	1810	1900	2000	2090	2190	2280	2380	2470	2570				
		dual			2700	2880	3060	3240	3420	3600	3780	3960	4140	4320	4500	4680	4860				
215/85R16	XDW ICE GRIP	single			1430	1520	1620	1710	1810	1900	2000	2090	2190	2280	2380	2470	2570				
		dual			2700	2880	3060	3240	3420	3600	3780	3960	4140	4320	4500	4680	4860				
215/85R16	X/E4MX ENERGY	single			1560	1660	1760	1870	1970	2070	2180	2280	2390	2490	2590	2700	2800				
		dual			2930	3130	3320	3520	3720	3910	4110	4300	4500	4690	4890	5080	5280				

2 TECHNICAL CHARACTERISTICS 15 - 16 INCHES

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
7.00 R16	AGILIS	7	TL	16	117/113L			9.2	2570	6.00	4600	6.00	208	794	2406	4.50E - 5.00E 5.50F - 6.00G	217	195	782	365.5	2388	221	5.50F	16J	16x6.00	
	AGILIS	7	TL	12	117/116L			9.2	2570	6.00	5000	6.00	208	794	2406	4.50E - 5.00E 5.50F - 6.00G	217	195	782	365	2388	221	5.50F	16J	16x6.00	
7.50R16	AGILIS	7	TL	14	122/121L			9.2	3000	7.00	5800	7.00	226	824	2497	5.50F - 6.00G 6.50H	231	209	800	375	2450	237	6.00G	16J	16x6.00	
	AGILIS HD	7	TL	14	122/121L			10.3	3000	7.00	5800	7.00	226	824	2497	5.50F - 6.00G 6.50H	227	207	804	377	2459	234	6.00G	16J	16x6.00	
8.25R16	AGILIS	7	TT	16	128/126K			10.5	3600	6.75	6800	6.75	239	878	2623	6.00G - 6.50H	256	232	858	400	2619	263	6.50H	16K	16x6.00	
	AGILIS HD	7	TT	16	128/126K			11.6	3600	6.75	6800	6.75	239	878	2623	6.00G - 6.50H	259	235	860	400.5	2627	265	6.50H	16K	16x6.00	

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed (pair load variations according to speed do not apply to the unique point).

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Tread pattern	psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131
		bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00
7.00 R16	AGLUS	single			1430	1520	1620	1710	1810	1900	2000	2090	2190	2280	2380	2470	2570												
		dual			2780	2960	3150	3330	3520	3700	3890	4070	4260	4440	4630	4810	5000												
	AGLUS	single			1430	1520	1620	1710	1810	1900	2000	2090	2190	2280	2380	2470	2570												
		dual			2780	2960	3150	3330	3520	3700	3890	4070	4260	4440	4630	4810	5000												
7.50R16	AGLUS	single						1840	1940	2000	2090	2190	2280	2380	2470	2570													
		dual							3550	3740	3890	4070	4260	4440	4630	4810	5000												
	AGLUS HD	single						1840	1940	2000	2090	2190	2280	2380	2470	2570													
		dual								3550	3740	3890	4070	4260	4440	4630	4810	5000											
8.25R16	AGLUS	single					2160	2280	2400	2030	2130	2230	2320	2420	2520	2610	2710	2810	2900	3000									
		dual					4080	4310	4550	3930	4120	4300	4490	4680	4860	5050	5240	5430	5610	5800									
	AGLUS HD	single					2160	2280	2400	2030	2130	2230	2320	2420	2520	2610	2710	2810	2900	3000									
		dual					4080	4310	4550	3930	4120	4300	4490	4680	4860	5050	5240	5430	5610	5800									

2 TECHNICAL

CHARACTERISTICS 17.5 INCHES

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal load per axle (dual) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
215/70R17.5	XZE2	6	TL		118/116L			12.8	2640	6.00	6.00	5000	6.00	222	759	2315	6.00 - 6.75	229	209	759	355	2306	237	6.00			
	X MULTI Z	6	TL		136/134M			12.5	4480	8.30	8.30	8480	8.30	258	803	2449	6.75 - 7.50	269	246	793	366	2417	209	6.75			
	XZE 2	6	TL		136/134M			13.5	4480	8.00	8.00	8480	8.00	258	803	2449	6.75 - 7.50	268	245	795	368	2424	277	6.75			
	X MULTI D	6	TL		136/134M			12.0	4480	8.30	8.30	8480	8.30	258	803	2449	6.75	268	246	795	368	2415	278	6.75			
205/75R17.5	XDE 2	6	TL		136/134M			14.0	4480	8.00	8.00	8480	8.00	258	811	2474	6.75 - 7.50	268	245	797	368	2419	277	6.75			
	X MULTI Z	6	TL	14	124/122M			11.5	3200	6.50	6.50	6000	6.50	212	765	2333	5.25 - 6.00 - 6.75	232	210	755	350	2304	238	6.00			
	XZE 2	6	TL		124/122M			12.5	3200	6.50	6.50	6000	6.50	212	765	2333	5.25 - 6.00 - 6.75	230	210	763	353	2310	238	6.00			
	XDE 2	6	TL		124/122M			14.0	3200	6.50	6.50	6000	6.50	212	773	2358	5.25 - 6.00 - 6.75	231	210	763	353	2312	238	6.00			
215/75R17.5	X MULTI Z	6	TL		126/124M			11.5	3400	6.90	6.90	6400	6.90	220	779	2376	6.00 - 6.75	237	217	770	357	2346	245	6.00			
	XZE 2	6	TL		126/124M			13.0	3400	6.50	6.50	6400	6.50	235	797	2431	6.00 - 6.75	238	217	774	357	2353	246	6.00			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed (air Load variations according to speed do not apply to the unique point).

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
215/75R17.5	XTE2+	2	TL		135/133J			12.2	4360	8.50	8240	8.50	220	779		6.00 - 6.75	236	215	777	359	2370	243	6.00			
	X MULTI T2	2	TL	18	136/134J			12.2	4480	9.00	8480	9.00	220	779		6.00 - 6.75	226	208	766	354	2353		6.00			
	X MULTI D	6	TL		126/124M			13.0	3400	6.90	6400	6.90	220	779	2376	6.00 - 6.75	236	216	775	359	2350	245	6.00			
	XDE 2	6	TL		126/124M			15.0	3400	6.50	6400	6.50	235	797	2431	6.00 - 6.75	238	216	778	360	2370	245	6.00			
	X MULTI Z	6	TL		129/127M			11.5	3700	7.20	7000	7.20	235	797	2431	6.00 - 6.75	255	233	787	366	2407	264	6.75			
225/75R17.5	XZE 2	6	TL		129/127M			13.0	3700	7.00	7000	7.00	235	797	2431	6.00 - 6.75	255	233	792	367	2414	264	6.75			
	X MULTI D	6	TL		129/127M			12.5	3700	7.20	7000	7.20	235	797	2431	6.00 - 6.75	256	234	790	367	2400	264	6.75			
	XDE 2	6	TL		129/127M			15.0	3700	7.00	7000	7.00	235	803	2449	6.00 - 6.75	255	232	798	369	2415	263	6.75			
	XTE2+	2	TL		143/141J			12.3	5450	8.50	10300	8.50	242	811		6.75 - 7.50	265	241	796	364	2410	273	6.75			
	X MULTI T2	2	TL	18	143/141J	145/145F	9.00	12.6	5450	9.00	10300	9.00	242	811		6.75 - 7.50	264	240	797	365	2445		6.75			
235/75R17.5	X MULTI Z	6	TL	16	132/130M			12.5	4000	7.60	7600	7.60	242	811	2474	6.75 - 7.50	243	241	799	371	2439	272	6.75			
	XZE 2	6	TL		132/130M			13.0	4000	7.25	7600	7.25	242	811	2474	6.75 - 7.50	261	239	805	373	2451	271	6.75			
	X MULTI D	6	TL	16	132/130M			12.5	4000	7.60	6800	7.60	242	811	2474	6.75 - 7.50	262	240	501	370	2433	272	6.75			
	XDE 2	6	TL		132/130M			15.0	4000	7.25	7600	7.25	242	811	2474	6.75 - 7.50	262	239	807	373	2447	271	6.75			

20

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair Load variations according to speed do not apply to the unique point.



Table of inflation pressure (bar) in relation to maximum load per axle (kg)

2 TECHNICAL CHARACTERISTICS 17.5 INCHES



Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
225/80R17.5	XZN+ MIX ENERGY	6	TL	14	123/122L			11.8	3100	6.00	6000	6.00	228	810	2471	6.00 - 6.75	248	225	811	378	2465	254	6.75			
	XZN MIX ENERGY	6	TL	14	123/122L			11.8	3100	6.00	6000	6.00	228	810	2471	6.00 - 6.75	248	225	811	378	2465	254	6.75			
	X/E4 MIX ENERGY	6	TL		123/122L			13.3	3100	6.00	6000	6.00	228	810	2471	6.00 - 6.75	248	225	810	378	2467	255	6.75			
	X/S WINTER GRIP+	6	TL	14	123/122L			14.5	3100	6.00	6000	6.00	228	810	2471	6.00 - 6.75	250	228	810	378	2480	258	6.75			
	XDW / ICE GRIP	6	TL	14	123/122L			14.5	3100	6.00	6000	6.00	228	810	2471	6.00 - 6.75	251	228	810	378	2480	258	6.75			
8.5R17.5	XZA	6	TL		121/120L			12.5	2900	6.25	5600	6.25	224	817	2492	5.25 - 6.00 - 6.75	221	200	802	372	2447	227	5.25			
	XZT	6	TL		121/120L			14.7	2900	6.25	5600	6.25	224	817	2492	5.25 - 6.00 - 6.75	222	200	806	374	2459	227	5.25			
	XZY	6	TL		121/120L			13.4	2900	6.25	5600	6.25	224	817	2492	5.25 - 6.00 - 6.75	220	200	806	374	2460	227	5.25			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point (load capacity/authorized additional speed) variations according to speed do not apply to the unique point.



Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Table of inflation pressure (bar) in relation to maximum load per axle (kg)																													
	Tread pattern																													
225/80R17.5	psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131		
	bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00		
	XZN+ MIX ENERGY	single			1720	1840	1950	2070	2180	2300	2410	2530	2640	2760	2870	2990	3100													
		dual			3330	3560	3780	4000	4220	4440	4670	4890	5110	5330	5560	5780	6000													
	XZN MIX ENERGY	single			1720	1840	1950	2070	2180	2300	2410	2530	2640	2760	2870	2990	3100													
		dual			3330	3560	3780	4000	4220	4440	4670	4890	5110	5330	5560	5780	6000													
	XJEA MIX ENERGY	single			1720	1840	1950	2070	2180	2300	2410	2530	2640	2760	2870	2990	3100													
		dual			3330	3560	3780	4000	4220	4440	4670	4890	5110	5330	5560	5780	6000													
	XIS WINTER GRIP+	single			1720	1840	1950	2070	2180	2300	2410	2530	2640	2760	2870	2990	3100													
		dual			3330	3560	3780	4000	4220	4440	4670	4890	5110	5330	5560	5780	6000													
	XDW ICE GRIP	single			1720	1840	1950	2070	2180	2300	2410	2530	2640	2760	2870	2990	3100													
		dual			3330	3560	3780	4000	4220	4440	4670	4890	5110	5330	5560	5780	6000													
	XZA	single			3330	3560	3780	4000	4220	4440	4670	4890	5110	5330	5560	5780	6000													
		dual			1660	1760	1860	1970	2070	2180	2280	2380	2490	2590	2690	2800	2900													
	XZT	single			3200	3400	3600	3800	4000	4200	4400	4600	4800	5000	5200	5400	5600													
		dual			1660	1760	1860	1970	2070	2180	2280	2380	2490	2590	2690	2800	2900													
XZY	single			3200	3400	3600	3800	4000	4200	4400	4600	4800	5000	5200	5400	5600														
	dual			1660	1760	1860	1970	2070	2180	2280	2380	2490	2590	2690	2800	2900														
8.5R17.5	single			3200	3400	3600	3800	4000	4200	4400	4600	4800	5000	5200	5400	5600														
	dual			1660	1760	1860	1970	2070	2180	2280	2380	2490	2590	2690	2800	2900														



Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
9.5R17.5	XTE2	2	TL		143/141J			13.0	5450	8.50	10300	8.50	250	857		6.00 - 6.75	257	230	846	386	2560	260	6.75			
	X MULTI Z	6	TL		129/127L	143J	8.50	11.6	3700	7.50	7000	7.50	250	857	2614	6.00 - 6.75	258	236	843	392	2580	267	6.00			
	XZA+	6	TL		129/127L	143J	8.50	12.1	3700	7.00	7000	7.00	250	857	2614	6.00 - 6.75	246	222	843	390	2568	252	6.00			
	XZA	6	TL	14	129/127L			11.6	3700	7.00	7000	7.00	250	857	2614	6.00 - 6.75	253	231	844	391	2572	262	6.00			
	XZT	6	TL		129/127L			16.0	3700	7.00	7000	7.00	250	857	2614	6.00 - 6.75	250	228	840	388	2559	258	6.00			
	XZY	6	TL		129/127L			14.0	3700	7.00	7000	7000	7.00	250	857	2614	6.00 - 6.75	266	241	861	397	2620	273	6.75		
10R17.5	XZA	6	TL		134/132L			12.5	4240	7.50	8000	7.50	264	875	2669	6.75 - 7.50	255	230	845	393	2573	260	6.75			
225/90R17.5	X/E4 MIX ENERGY	6	TL		140/138L			13.5	3500	6.50	6600	6.50	237	867	2644	6.00 - 6.75	257	232	849	395	2590	263	6.75			
	XDW / ICE GRIP	6	TL	14	127/125L			14.5	3500	6.50	6600	6.50	237	867	2644	6.75 - 6.00										

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair Load variations according to speed do not apply to the unique point.



Table of inflation pressure (bar) in relation to maximum load per axle (kg)

[illegible]

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Tread pattern																		
		psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94
225/70R19.5	bar																		
	single										2500	2620	2760	2830	2900	2950	3000	3140	3300
	dual										4720	4920	5200	5300	5400	5520	5640	5880	6200
	single												2980	3110	3240	3370	3500	3630	3750
	dual												5640	5880	6130	6370	6620	6860	7110
	single											2900	3030	3160	3290	3430	3560	3690	3820
	dual											5400	5740	5990	6240	6480	6730	6980	7230
	single											2900	3030	3160	3290	3430	3560	3690	3820
	dual											5400	5740	5990	6240	6480	6730	6980	7230
	single											2900	3030	3160	3290	3430	3560	3690	3820
245/70R19.5	ENERGY												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
245/70R19.5	ENERGY												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
245/70R19.5	ENERGY												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
245/70R19.5	ENERGY												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690
	dual												5490	5740	5990	6240	6480	6730	6980
	single												2900	3030	3160	3290	3430	3560	3690

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	245/70R19.5												Seal							
							Normal pressure for unique point (bar)	Original tread depth	Normal load per axle (single) (kg)	Normal pressure for load (single) (bar)	Normal load per axle (dual) (kg)	Normal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)		Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN		
245/70R19.5	XIS WINTER GRIP+	6	TL		136/134L			16.5	4480	7.75	8480	7.75	258	853	2602	6.75 - 7.50	269	247	855	397	2610	280	6.75			
	XDW ICE GRIP	6	TL		136/134L			16.5	4480	7.75	8480	7.75	258	853	2602	6.75 - 7.50	268	246	857	397	2610	278	6.75			
	X MULTI Z	6	TL	14	140/138M			12.5	5000	7.60	9440	7.60	272	881	2687	6.75-7.50-8.25	287	259	864	401	2642	293	7.50			
	XZN+ MIX ENERGY	6	TL		140/138L			13.0	5000	7.75	9440	7.75	272	881	2687	6.75-7.50-8.25	296	262	870	393	2615	300	7.50			
265/70R19.5	XZN MIX ENERGY	6	TL		140/138L			13.0	5000	7.75	9440	7.75	272	881	2687	6.75-7.50-8.25	296	262	870	393	2615	300	7.50			
	XZE2+	6	TL		140/138M			13.6	5000	7.75	9440	7.75	272	881	2687	6.75-7.50-8.25	287	263	870	402	2650	297	7.50			
	XIW4+	6	TL		140/138L			15.0	5000	7.75	9440	7.75	272	881	2687	6.75-7.50-8.25	283	263	872	405	2660	298	7.50			
	X MULTI D	6	TL		140/138M			12.5	5000	7.60	9440	7.60	272	881	2687	6.75-7.50-8.25	285	262	868	402	2638	296	7.50			
	XTE2	2	TL		143/141J			14.0	5450	8.50	10300	8.60	272	881		6.75-7.50-8.25	286	265	870	403	2650	300	7.50			
	XDE2+	6	TL		140/138M			16.0	5000	7.75	9440	7.75	272	881	2687	6.75-7.50-8.25	262	262	875	404	2660	297	7.50			
	XDW ICE GRIP	6	TL		140/138L			16.0	5000	7.75	9440	7.75	272	881	2687	6.75-7.50-8.25	288	264	875	405	2670	299	7.50			

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Tread pattern	Table of inflation pressure (bar) in relation to maximum load per axle (kg)																											
		psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131
245/70R19.5	bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	
	single										2900	3030	3160	3290	3430	3560	3690	3820	3950	4080	4220	4350	4480						
	dual										5490	5740	5990	6240	6480	6730	6980	7230	7480	7730	7980	8230	8480						
	single										2900	3030	3160	3290	3430	3560	3690	3820	3950	4080	4220	4350	4480						
	dual										5490	5740	5990	6240	6480	6730	6980	7230	7480	7730	7980	8230	8480						
	single											3440	3590	3740	3890	4040	4190	4340	4490	4640	4790	4940							
	dual										6500	6780	7070	7350	7630	7910	8200	8480	8760	9040	9320								
	single										3240	3380	3530	3680	3820	3970	4120	4260	4410	4560	4710	4860	5000						
	dual										6110	6390	6660	6940	7220	7500	7770	8050	8330	8610	8880	9160	9440						
	single										3240	3380	3530	3680	3820	3970	4120	4260	4410	4560	4710	4860	5000						
dual										6110	6390	6660	6940	7220	7500	7770	8050	8330	8610	8880	9160	9440							
single										3230	3380	3530	3670	3820	3970	4110	4260	4410	4550	4700	4850	5000							
dual										6110	6390	6660	6940	7220	7500	7770	8050	8330	8610	8880	9160	9440							
single										3230	3380	3530	3670	3820	3970	4110	4260	4410	4550	4700	4850	5000							
dual										6110	6390	6660	6940	7220	7500	7770	8050	8330	8610	8880	9160	9440							
single											3440	3590	3740	3890	4040	4190	4340	4490	4640	4790	4940								
dual										6500	6780	7070	7350	7630	7910	8200	8480	8760	9040	9320									
single														3680	3830	3980	4120	4270	4420	4570	4710	4860	5010	5160	5300				
dual														6960	7240	7520	7790	8070	8350	8630	8910	9190	9460	9740	10020				
single											3230	3380	3530	3670	3820	3970	4110	4260	4410	4550	4700	4850	5000						
dual										6110	6390	6660	6940	7220	7500	7770	8050	8330	8610	8880	9160	9440							
single										3230	3380	3530	3670	3820	3970	4110	4260	4410	4550	4700	4850	5000							
dual										6110	6390	6660	6940	7220	7500	7770	8050	8330	8610	8880	9160	9440							
single											3440	3590	3740	3890	4040	4190	4340	4490	4640	4790	4940								
dual											6500	6780	7070	7350	7630	7910	8200	8480	8760	9040	9320								
single																													
dual																													
single																													
dual																													
single																													
dual																													
single																													
dual																													
single																													
dual																													
single																													
dual																													
single																													
dual																													
single																													
dual																													
single																													
dual																													
single																													
dual																													
single																													
dual																													
single																													
dual																													

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
285/70R19.5	X MULTI Z	6	TL		146/144L	145/143M	8.30	12.5	6000	8.30	11200	8.30	294	911	2779	7.50-8.25-9.00	298	273	893	411	2721	309	7.50			
	XZE2+	6	TL		144/142M	145/143L	8.00	13.9	5600	8.00	10600	8.00	294	911	2779	7.50-8.25-9.00	301	275	895	412	2720	311	7.50			
	X MULTI D	6	TL		146/144L	145/143M	8.30	13.5	6000	8.30	11200	8.30	294	911	2779	7.50-8.25-9.00	276	273	897	412	2720	309	7.50			
	XDE2+	6	TL		144/142M	145/143L	8.00	16.5	5600	8.00	10600	8.00	294	911	2779	7.50-8.25-9.00	300	274	899	414	2740	310	7.50			
305/70R19.5	XZE2+	6	TL		147/145M	148/146L	8.00	14.9	6150	8.00	11600	8.00	309	941	2870	8.25-9.00	327	301	924	424	2800	341	8.25			
	XDE2+	6	TL		147/145M	148/146L	8.00	17.5	6150	8.00	11600	8.00	309	949	2894	8.25-9.00	327	301	931	428	2830	341	8.25			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Table of inflation pressure (bar) in relation to maximum load per axle (kg)																													
	psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131		
285/70R19.5	Tread pattern	bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	
	X MULTIZ	single										3810	3980	4140	4310	4480	4640	4810	4970	5140	5300	5470	5640	5800	5970					
		dual										7120	7430	7730	8040	8350	8660	8970	9280	9590	9900	10210	10520	10830	11140					
	XZE+	single										3680	3840	4000	4160	4320	4480	4640	4800	4960	5120	5280	5440	5600						
		dual										6970	7270	7570	7870	8180	8480	8780	9090	9390	9690	9990	10300	10600						
	X MULTID	single										3810	3980	4140	4310	4480	4640	4810	4970	5140	5300	5470	5640	5800	5970					
		dual										7120	7430	7730	8040	8350	8660	8970	9280	9590	9900	10210	10520	10830	11140					
	XDZ+	single										3680	3840	4000	4160	4320	4480	4640	4800	4960	5120	5280	5440	5600						
dual											6970	7270	7570	7870	8180	8480	8780	9090	9390	9690	9990	10300	10600							
305/70R19.5	XZE+	single										4040	4220	4390	4570	4740	4920	5100	5270	5450	5620	5800	5970	6150						
		dual										7620	7950	8290	8620	8950	9280	9610	9940	10270	10610	10940	11270	11600						
	XDZ+	single										4040	4220	4390	4570	4740	4920	5100	5270	5450	5620	5800	5970	6150						
		dual										7620	7950	8290	8620	8950	9280	9610	9940	10270	10610	10940	11270	11600						



Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Normal load per axle (single) (kg)	Normal pressure for load (single) (bar)	Normal load per axle (dual) (kg)	Normal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
8.25R20	XZE	6	TT		133/131K	133/131L	6.50	11.6	4120	6.50	7800	6.50	239	980	2989	5.5-85.5-6.0 6.001-86.0-6.5 86.5-7.0-87.0	256	232	962	451	2950	263	6.50	20 K	20x7.50	
9.00R20	XZE2	2	TT	16	144/142K			13.7	5600	9.00	10600	9.00				6.0-6.00T 6.5-7.0-7.5	283	256	1017	476.5	3115	290	7.00	20 M	20x7.50	
10.00R20	XZE3 R	2	TT	16	147/148K			12.5	6150	8.00	10900	8.00	286	1074	3276	6.50-7.00-7.50	307	277	1049	489	3212	314	7.50	20 N	20x7.50	
	XZE2	2	TT	16	147/143K	146/143L	7.75	13.8	6150	8.00	10900	8.00	286	1074	3276	6.50-7.00-7.50	307	277	1053	490	3211	314	7.50	20 N	20x7.50	
	XZY3 HD	3	TT	16	147/148K			15.6	6150	7.90	10900	7.90	286	1074	3276	6.50-7.00 7.50-8.00	309	277	1057	495		313	7.50	20 N	20x7.50	
	XZY3	3	TT	16	147/148K			16.6	6150	8.00	10900	8.00	286	1073	3273	7.0-7.33	311	280	1060	494	3226	317	7.50	20 N	20x7.50	
	XDY3 HD	3	TT	16	147/143K			19.8	6150	7.90	10900	7.90	286	1074	3276	6.50-7.00 7.50-8.00	309	279	1059	493	3240	316	7.50	20 N	20x7.50	
	XDY3	3	TT	16	147/143K			19.8	6150	8.00	10900	8.00	286	1073	3273	7.0-7.33-7.5-8.0	310	281	1064	497	3240	318	7.50	20 N	20x7.50	

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point, load capacity/authorized additional speed per Load variations according to speed do not apply to the unique point.





Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Tread pattern																				
		psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102
8.25R20	bar		2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
	single						2420	2560	2700	2840	2980	3130	3270	3410	3550	3690	3840	3980	4120		
9.00R20	dual						4570	4840	5110	5380	5650	5920	6190	6460	6720	6990	7260	7530	7800		
	single																3880	4020	4160	4310	4450
10.00R20	dual																7340	7610	7880	8150	8430
	single												4040	4220	4390	4570	4740	4920	5100	5270	5450
	dual												7160	7470	7790	8100	8410	8720	9030	9340	9650
	single												4040	4220	4390	4570	4740	4920	5100	5270	5450
	dual												7160	7470	7790	8100	8410	8720	9030	9340	9650
	single												4090	4270	4440	4620	4800	4980	5150	5330	5510
	dual												7250	7560	7880	8190	8510	8820	9140	9450	9770
	single												4040	4220	4390	4570	4740	4920	5100	5270	5450
	dual												7160	7470	7790	8100	8410	8720	9030	9340	9650
	single												4090	4270	4440	4620	4800	4980	5150	5330	5510

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Normal load per axle (single) (kg)	Normal pressure for load (single) (bar)	Normal load per axle (dual) (kg)	Normal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
11.00R20	XZE 3 R	2	TT	16	150/146K	150/1471	8,00	12,3	6700	8,00	12000	8,00	297	1104	3367	6.50 - 7.0 - 7.5 7.33 - 8.0	324	295	1081	503	3311	334	8.00	20 P	20x8.50	
	XZE 2	2	TT	16	147/143K			13,8	6150	8,00	10900	8,00	286	1074	3276	6.50 - 7.0 - 7.5 7.33 - 8.0	307	277	1053	490	3211	314	7.50	20 N	20x8.50	
	XZE 2	2	TT	16	150/146K			14,3	6700	8,00	12000	8,00	297	1104	3367	7.33V - 7.5 - 8.0 8.5 - 88.5 - 9.0	329	297	1082	503	3303	336	8.00	20 P	20x8.50	
	XZY 3	3	TT	16	150/146K			17,5	6700	8,00	12000	8,00	297	1104	3367	7.5 - 8.0 - 8.0V 8.5 - 8.50V	330	298	1090	506	3327	337	8.00	20 P	20x8.50	
	XDY 3	3	TT	16	150/146K			20,8	6700	8,00	12000	8,00	297	1104	3367	7.33 - 7.50 - 8.00 8.50 - 9.00	331	300	1096	509	3329	340	8.00	20 P	20x8.50	
	XZE 2	2	TT	18	154/150K			15,2	7500	8,50	13400	8,50	319	1146	3495	8.00V - 8.5 8.50V - 9.00V	345	313	1121	521	3420	354	8.50	20 Q	20x8.50	
12.00R20	XZY 3	3	TT	18	154/150K			18,1	7500	8,50	13400	8,50	319	1146	3495	7.33 - 8.00	348	315	1129	527	3451	357	8.50	20 Q	20x8.50	

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Tread pattern	psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131	134
		bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	9.25
11.00R20	XZE 3 R	single											4400	4590	4790	4980	5170	5360	5550	5740	5930	6130	6320	6510	6700					
		dual											7890	8220	8570	8910	9260	9600	9940	10290	10630	10970	11310	11660	12000					
	XZE 2	single											4040	4220	4390	4570	4740	4920	5100	5270	5450	5620	5800	5970	6150					
		dual											7160	7470	7790	8100	8410	8720	9030	9340	9650	9970	10280	10590	10900					
	XZE 2	single											4400	4590	4790	4980	5170	5360	5510	5740	5930	6130	6320	6510	6700					
		dual											7890	8230	8570	8910	9260	9600	9940	10290	10630	10970	11310	11660	12000					
	XZV 3	single											4400	4590	4790	4980	5170	5360	5510	5740	5930	6130	6320	6510	6700					
		dual											7890	8230	8570	8910	9260	9600	9940	10290	10630	10970	11310	11660	12000					
	XDV 3	single											4400	4590	4790	4980	5170	5360	5550	5740	5930	6130	6320	6510	6700					
		dual											7890	8230	8570	8910	9260	9600	9940	10290	10630	10970	11310	11660	12000					
12.00R20	XZE 2	single													5070	5270	5470	5680	5880	6080	6280	6490	6690	6890	7090	7300	7500			
		dual													9050	9420	9780	10140	10500	10860	11230	11590	11950	12310	12680	13040	13400			
	XZV 3	single													5070	5270	5470	5680	5880	6080	6280	6490	6690	6890	7090	7300	7500			
		dual													9050	9420	9780	10140	10500	10860	11230	11590	11950	12310	12680	13040	13400			



Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
12.00R20	XZH2 R	3	TL		154/149G	156F	9.00	22.0	7500	8.50	13000	8.50	319	1146	3495	7.33V - 8.0 - 8.0V 8.00 - 8.5 - 8.50V 8.85 - 9.0 - 9.00V	350	319	1140	531	3468	360	8.50	20x8.50		
	XDY 3	3	TT	18	154/150K			21.0	7500	8.50	13400	8.50	319	1158	3532	7.33 - 8.00	351	318	1135	529	3456	361	8.50	20x8.50		
325 95R24	X WORKS XZ	3	TL		162/160K			19.0	9500	8.50	18000	8.50	327	1252	3819	8.50	347	311	1223	566	3747	352	8.50	24/25x8.50		
	X WORKS XD	3	TL		162/160K			22.0	9500	8.50	18000	8.50	327	1265	3858	8.50	348	314	1230	570	3760	355	8.50	24/25x8.50		

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair load variations according to speed do not apply to the unique point.





Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Tread pattern	Table of inflation pressure (bar) in relation to maximum load per axle (kg)																													
		psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131	134	
12.00R20	bar		2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	9.25	
	single											4500	4630	4880	5070	5270	5470	5680	5880	6080	6280	6490	6690	6890	7090	7300	7500				
	dual											7800	8130	8450	8780	9140	9490	9840	10190	10540	10890	11240	11590	11950	12300	12650	13000				
	XDY 3														5070	5270	5470	5680	5880	6080	6280	6490	6690	6890	7090	7300	7500				
325/95R24	X WORKS XZ														9050	9420	9780	10140	10500	10860	11230	11590	11950	12310	12680	13040	13400				
	single																6930	7190	7450	7700	7960	8220	8470	8730	8990	9240	9500				
	dual																13140	13620	14110	14590	15080	15570	16050	16540	17030	17510	18000				
	X WORKS XD																	6930	7190	7450	7700	7960	8220	8470	8730	8990	9240	9500			
																		13140	13620	14110	14590	15080	15570	16050	16540	17030	17510	18000			

Dimension	Tread Pattern	Category	Type	PR (PLY Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
445/45R19.5	XTA2 ENERGY	1	TL		160J			13.0 9000	9.00							14.00	463	436	903	413	2761		14.00			
	X ONE LINE D	1	TL	20	LRL			19.2 9250	8.25				463	1036		14.00	464	434	1020	471			14.00			
	X ONE LINE GRIP D	2	TL	20	LRL			21.8 9250	8.25				463	1036		14.00	464	435	1026	473			14.00			
	X ONE LINE ENERGY T	1	TL	20	LRL			10.3 9250	8.25				463	1036		14.00	464	435	1004	465			14.00			
445/50R22.5	X ONE MULTI ENERGY T	2	TL	20	LRL			12.9 9250	8.25				463	1036		14.00	458	433	1008	467			14.00			
	XFA2 ENERGY	1	TL		158L	160J	9.00	13.0 8500	9.00				401	1012	3087	11.75	474	442	1071	495	3252		14.00			
	X MULTI T	2	TL		160K	158L	8.50	13.0 9000	9.00				401	1012	3087	11.75	406	378	998	460	3068		11.75			
	X MULTI T2	2	TL		160K	158L	9.00	14.9 4500	9.00				401	1012	3087	11.75-12.25	410	381	1001	461	3071		11.75			
385/55R22.5	X ONE MULTI ENERGY T	2	TL		160K	158L	9.00	11.3 4500	9.00				401	1012	3087	11.75-12.25	403	376	996	458	3060		11.75			
	X LINE ENERGY T	1	TL		160K	158L	9.00	11.3 4500	9.00				401	1012	3087	11.75-12.25	403	376	996	458	3060		11.75			
	X ONE XZ13	3	TL		LRM			10.3 10600	9.00							14.00	480	452	1065	492	3245		14.00			
	X ONE XZ15	5	TL		LRM			18.7 10600	9.00							14.00	480	452	1095	492	3245		14.00			
455/55R22.5	X ONE XD12	2	TL		LRL			21.6 10000	9.00							14.00	497	497	1076				14.00			
	X ONE LINE GRIP D	2	TL	20	164L			21.8 1000	8.30				470	1092		14.00	474	442	1071	495	3252		14.00			
	X ONE MULTI ENERGY T	2	TL		LRL			12.8 10000	9.00							14.00	490	490	1058				14.00			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair Load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)



Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth			Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
								Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)																		
385/65R22.5	X MULTI F	2	TL		158L	160K	9.00	12.5	8500	8.50					405	1092	3331	11.75	404	376	1073	497	3288		11.75			
	X LINE ENERGY F	1	TL		160K	158L	9.00	12.0	9000	9.00					405	1092	3331	11.75	405	376	1066	495	3270		11.75			
	XFE	2	TL		160K			16.3	9000	9.00					405	1092	3331	11.75	404	379	1072	499	3270		11.75			
	XFN 2	2	TL		158L	160J	9.00	15.4	8500	8.50					405	1103	3364	11.75 - 12.25	409	380	1074	498	3274		11.75			
	X MULTITWAY HD XZE	2	TL		164K			15.3	10000	9.00					405	1103	3364	11.75	414	384	1078	497	3309		11.75			
	XZY 3	3	TL		160K	158L	8.50	17.7	9000	9.00					405	1092	3331	11.75-12.25	409	379	1078	499	3280		11.75			
	X LINE ENERGY T	1	TL		160K	158L	8.50	12.4	9000	9.00					405	1103	3364	11.75	406	377	1066	494	3272		11.75			
	X MULTI T	2	TL		160K	158L	8.50	15.3	9000	9.00					405	1103	3364	11.75	403	377	1070	496	3286		11.75			
	X ENERGY SAVERGREEN XT	1	TL		160J	158L	8.50	16.0	9000	9.00					389	1072	3270	11.75	407	376	1072	498	3286		11.75			
	XFE 3	2	TL		160J	158L	8.50	17.3	9000	9.00					389	1092	3331	11.75	407	378	1074	497	3292		11.75			
	XZY 3	3	TL	20	165K			18.1	10300	8.50					430	1157	3529	13.00-14.00	453	421	1136	523	3460		13.00			
	XTF2	2	TL	20	165K			16.3	10300	8.50					447	1046	3190	13.00-14.00	449	421	1130	522	3440		13.00			
445/65R22.5	XZY 3	3	TL		169K			18.5	11600	9.00					472	1174	3581	14.00	486	451	1164	536	3540		14.00			
	XTF2	2	TL	20	169K			16.8	11600	9.00					472	1174	3581	14.00	481	451	1158	534	3520		14.00			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair (Load variations according to speed do not apply to the unique point).

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Tread pattern

Dimension

	psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131
	bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00
385/65R22.5	X MULTI F	single														6200	6430	6660	6890	7120	7350	7580	7810	8040	8270	8500		
	X LINE ENERGY F	single														6230	6460	6690	6920	7150	7380	7620	7850	8080	8310	8540	8770	9000
	XFE	single														6230	6460	6690	6920	7150	7380	7620	7850	8080	8310	8540	8770	9000
	XFN 2	single												5740	5970	6200	6430	6660	6890	7120	7350	7580	7810	8040	8270	8500		
	X MULTIWAY HD XZE	single														6920	7180	7440	7690	7950	8210	8460	8720	8970	9230	9490	9740	10000
	XZY 3	single														6230	6460	6690	6920	7150	7380	7620	7850	8080	8310	8540	8770	9000
	X LINE ENERGY T	single														6230	6460	6690	6920	7150	7380	7620	7850	8080	8310	8540	8770	9000
	X MULTI T	single														6230	6460	6690	6920	7150	7380	7620	7850	8080	8310	8540	8770	9000
	X ENERGY SAVER GREEN XT	single														6230	6460	6690	6920	7150	7380	7620	7850	8080	8310	8540	8770	9000
	XTE 3	single														7520	7790	8070	8350	8630	8910	9190	9460	9740	10020	10300		
425/65R22.5	XZY 3	single												6960	7240	7520	7790	8070	8350	8630	8910	9190	9460	9740	10020	10300		
445/65R22.5	XTE2	single														8030	8330	8630	8920	9220	9520	9820	10110	10410	10710	11010	11300	11600
	XZY 3	single														8030	8330	8630	8920	9220	9520	9820	10110	10410	10710	11010	11300	11600
	XTE2	single																										

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
9R22.5	XZA	6	TL		133/131L			13.0	4120	6.50	7800	6.50	239	986	3007	6.00 - 6.75	245	222	965	450	2950	251	6.00			
	XZY	3	TL		133/131K			13.8	4120	6.50	7800	6.50	239	986	3007	6.00 - 6.75	246	219	969	450	2960	248	6.00			
10R22.5	XZA	2	TL		144/142L			15.0	5600	8.00	10600	8.00	264	1038	3166	6.75 - 7.50	270	245	1014	473	3100	277	6.75			
	XZY	3	TL		144/142K			13.9	5600	8.00	10600	8.00	264	1038	3166	6.75 - 7.50	271	244	1017	473	3110	276	6.75			
11R22.5	X MULTI Z	2	TL	16	148/145L			13.8	6300	8.00	11600	8.00	290	1070	3264	7.50 - 8.25	302	281	1048	492	3267	314	8.25			
	X MULTI Z2	2	TL	16	148/145L			14.5	6300	8.50	11600	8.50	290	1070	3264	7.50 - 8.25	299	272	1044	488	3200		7.50			
	X INCTY Z	5	TL	16	148/145J	151/148E	8.30	16.0	6300	8.30	11600	8.30	290	1070	3264	7.50 - 8.25	308	282	1054	492	3221	320	8.25			
	X COACH ENERGY Z	8	TL		148/145M			13.8	6300	8.00	11600	8.00	290	1070	3264	7.50 - 8.25	302	281	1048	492	3267	314	8.25			
	XZA 2+ ENERGY	1	TL		148/145M			14.7	6300	8.00	11600	8.00	290	1070	3264	7.50 - 8.25	299	267	1056	489	3228	302	7.50			
	XIE4 MIX ENERGY	1	TL	16	148/145L			14.3	6300	8.00	11600	8.00	279	1037	3163	7.50 - 8.25	304	275	1048	486	3198	311	7.50			
	XJM4+	2	TL	16	148/145L			16.3	6300	8.00	11600	8.00	279	1037	3163	7.50 - 8.25	303	275	1054	490	3220	311	7.50			
	XZE2+	2	TL	16	148/145L			15.2	6300	8.00	11600	8.00	290	1070	3264	7.50 - 8.25	303	273	1055	490	3225	309	7.50			

42

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair Load variations according to speed do not apply to the unique point.

u

[illegible]



Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Normal load per axle (single) (kg)	Normal load per axle (dual) (kg)	Normal pressure for load (single) (bar)	Normal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
11R22.5	XZY 3	3	TL	16	148/145K			19.0	6300	8.00	11600	8.00	290	1070	3264	750	303	275	1060	493	3236	311	750			
	XZY 2	3	TL	16	148/145K			18.2	6300	8.00	11600	8.00	290	1070	3264	750 - 8.25	305	280	1059	492	3230	316	750			
	XZU3+	5	TL	16	148/145L	151/148E	8.00	19.7	6300	8.00	11600	8.00	290	1070	3264	750 - 8.25	303	275	1065	495	3227	311	750			
	XJS WINTER GRIP+	2	TL	16	148/145L			18.9	6300	8.00	11600	8.00	290	1070	3264	750 - 8.25	298	270	1060	493	3240	305	750			
	X MULTI D	2	TL	16	148/145L			21.5	6300	8.00	11600	8.00	290	1070	3264	750 - 8.25	297	268	1066	496	3234	303	750			
	X MULTI D+	2	TL	16	148/145L			23.5	6300	8.30	11600	8.30	290	1070	3264	750 - 8.25	314	284	1067	498	3233	321	8.25			
	XDE M/S*	2	TL	16	LRH			28.0	6000	8.25	10900	8.25	290	1070	3264	750 - 8.25	308	285		493	3238	318	8.25, 750			
	XDY 3	3	TL	16	148/145K			21.5	6300	8.00	11600	8.00	290	1070	3264	750 - 8.25	306	277	1065	496	3250	314	750			
	XDW ICE GRIP	2	TL	16				19.0	6300	8.00	11600	8.00	290	1070	3264	750 - 8.25	309	279	1055	491	3220	315	750			
	X MULTI T	2	TL	16	148/145L	152/148L	8.30	13.5	6300	8.30	11600	8.30	290	1070	3264	750 - 8.25	301	272	1048	487	3206	308	8.25			
	XTEZ	2	TL	14	142/142L			13.7	5300	8.00	10600	8.00	269	1064	3245	750 - 8.25	293	268	1050	492	3216	303	750			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed per load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)



Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Normal load per axle (single) (kg)	Normal pressure for load (single) (bar)	Normal load per axle (dual) (kg)	Normal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
12R22.5	X LINE ENERGY Z	1	TL	18	152/149L			15.6	7100	8.50	13000	8.50	312	1104	3367	8.25 - 9.00	317	287	1084	503	3312	329	8.25			
	X MULTI Z	2	TL	18	152/149L			14.5	7100	8.50	13000	8.50	312	1104	3367	8.25 - 9.00	323	296	1082	505	3314	338	8.25			
	X WORKS XZY	3	TL	16	152/149K			18.5	7100	8.50	13000	8.50	312	1104	3367	8.25 - 9.00	323	290	1092	507	3334	328	8.25			
	XZE2+	2	TL	18	152/149L			15.5	7100	8.50	13000	8.50	312	1104	3367	8.25 - 9.00	318	287	1085	504	3310	325	8.25			
	XZY 2	3	TL	16	152/148K			18.2	7100	8.50	12600	8.50	312	1104	3367	8.25 - 9.00	328	291	1092	507	3330	329	8.25			
	X WORKS XDY	3	TL	16	152/149K			23.2	7100	8.50	13000	8.50	312	1104	3367	8.25 - 9.00	322	292	1096	511	3350	330	8.25			
	XDE2+	2	TL	18	152/149L			23.2	7100	8.50	13000	8.50	312	1104	3367	8.25 - 9.00	319	288	1094	510	3340	326	8.25			
	XDE2+	2	TL	16	152/148L			23.2	7100	8.50	12600	8.50	312	1104	3367	8.25 - 9.00	320	288	1094	510	3340	326	8.25			
	XDY 3	3	TL	16	152/148K			22.3	7100	8.50	12600	8.50	312	1104	3367	8.25 - 9.00	320	290	1097	510	3350	328	8.25			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed per load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Tread pattern

Dimension

	psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131
	bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00
12R22.5	X LINE ENERGY Z	single												4800	4990	5180	5370	5560	5760	5950	6140	6330	6520	6720	6910	7100		
		dual												8780	9140	9490	9840	10190	10540	10890	11240	11590	11950	12300	12650	13000		
	X MULTI Z	single												4800	4990	5180	5370	5560	5760	5950	6140	6330	6520	6720	6910	7100		
		dual												8780	9140	9490	9840	10190	10540	10890	11240	11590	11950	12300	12650	13000		
	X WORKS XZY	single												4800	4990	5180	5370	5560	5760	5950	6140	6330	6520	6720	6910	7100		
		dual												8780	9140	9490	9840	10190	10540	10890	11240	11590	11950	12300	12650	13000		
	XZE2+	single												4800	4990	5180	5370	5560	5760	5950	6140	6330	6520	6720	6910	7100		
		dual												8780	9140	9490	9840	10190	10540	10890	11240	11590	11950	12300	12650	13000		
	XZY 2	single												4800	4990	5180	5370	5560	5760	5950	6140	6330	6520	6720	6910	7100		
		dual												8510	8850	9190	9540	9880	10220	10560	10900	11240	11580	11920	12260	12600		
	X WORKS XDY	single												4800	4990	5180	5370	5560	5760	5950	6140	6330	6520	6720	6910	7100		
		dual												8780	9140	9490	9840	10190	10540	10890	11240	11590	11950	12300	12650	13000		
	XOE2+	single												4800	4990	5180	5370	5560	5760	5950	6140	6330	6520	6720	6910	7100		
		dual												8780	9140	9490	9840	10190	10540	10890	11240	11590	11950	12300	12650	13000		
	XOE2+	single												4800	4990	5180	5370	5560	5760	5950	6140	6330	6520	6720	6910	7100		
		dual												8510	8850	9190	9540	9880	10220	10560	10900	11240	11580	11920	12260	12600		
	XDY 3	single												4800	4990	5180	5370	5560	5760	5950	6140	6330	6520	6720	6910	7100		
		dual												8510	8850	9190	9540	9880	10220	10560	10900	11240	11580	11920	12260	12600		

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Normal load per axle (single) (kg)	Normal load per axle (dual) (kg)	Normal pressure for load (single) (bar)	Normal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
13R22.5	X WORKS HD Z	3	TL 18	156/151K		158/152G	9,00	17,0	8000	8,75	13800	8,75	320	1158	3532	9,00 - 9,75	340	307	1122	523	3425	349	9,00			
	WORKS XZY	3	TL 18	156/150K				18,0	8000	8,75	13400	8,75	320	1158	3532	9,00 - 9,75	309	309	1122	520	3425	349	9,00			
	XZE 2	2	TL 18	156/150L				16,0	8000	8,50	13400	8,50	326	1146	3495	9,00 - 9,75	344	310	1122	519	3420	351	9,00			
	XZH2 R	3	TL 18	154/150G	156/150F		9,00	22,0	7500	8,00	13400	8,00	326	1146	3495	9,00 - 9,75	347	317	1135	528	3456	359	9,00			
	X WORKS HD D	3	TL 18	156/151K	158/152G		9,00	21,8	8000	8,75	13800	8,75	320	1158	3532	9,00 - 9,75	343	306	1129	524	3430	349	9,00			
	X WORKS XDY	3	TL 18	156/150K				22,5	8000	8,75	13400	8,75	320	1158	3532	9,00 - 9,75	341	308	1130	525	3430	349	9,00			
	XDY 3	3	TL 18	154/150K	156G		8,50	23,6	7500	8,00	13400	8,00	326	1146	3495	9,00 - 9,75	343	310	1136	527	3465	351	9,00			
	XZS2 ENERGY	1	TL	150/147K	149/146L		8,50	12,5	6700	9,00	12300	9,00	304	940	2867	9,00 - 9,75	311	290	918	424	2800	330	9,00			
	XDA 2+ ENERGY	1	TL	150/147K	149/146L		9,00	18,2	6700	9,00	12300	9,00	304	940	2867	9,00 - 9,75	312	289	928	429	2830	330	9,00			
	X MULTIWAY XD	2	TL	150/147K	149/146L		9,00	18,2	6700	9,00	12300	9,00	304	948	2891	9,00 - 9,75	312	289	927	430	2809	330	9,00			
295/60R22.5																										

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed per load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Tread pattern

Dimension

Dimer	Tread	psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131	
		bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	
13R22.5	X WORKS HD Z	single															5680	5890	6110	6320	6530	6740	6950	7160	7370	7580	7790	8000		
		dual															9810	10170	10530	10890	11260	11620	11980	12350	12710	13070	13440	13800		
	WORKS XZY	single															5680	5890	6110	6320	6530	6740	6950	7160	7370	7580	7790	8000		
		dual															9520	9870	10230	10580	10930	11280	11640	11990	12340	12690	13050	13400		
	XZE 2	single																6270	6485	6700	6920	7140	7350	7570	7780	8000				
		dual																10500	10865	11230	11590	11950	12310	12680	13040	13400				
	XZ42 R	single										4930	5140	5360	5570	5790	6000	6210	6430	6640	6860	7070	7290	7500						
		dual										8810	9190	9570	9950	10340	10720	11100	11490	11870	12250	12630	13020	13400						
	X WORKS HD D	single																5680	5890	6110	6320	6530	6740	6950	7160	7370	7580	7790	8000	
		dual																9810	10170	10530	10890	11260	11620	11980	12350	12710	13070	13440	13800	
295/60R22.5	X WORKS XDY	single															5680	5890	6110	6320	6530	6740	6950	7160	7370	7580	7790	8000		
		dual															9520	9870	10230	10580	10930	11280	11640	11990	12340	12690	13050	13400		
	XDY 3	single										4930	5140	5360	5570	5790	6000	6210	6430	6640	6860	7070	7290	7500						
		dual										8810	9190	9570	9950	10340	10720	11100	11490	11870	12250	12630	13020	13400						
295/60R22.5	XZA2 ENERGY	single															4640	4810	4980	5150	5330	5500	5670	5840	6010	6180	6360	6530	6700	
		dual															8520	8830	9150	9460	9780	10090	10410	10720	11040	11350	11670	11980	12300	
	XDA 2+ ENERGY	single															4640	4810	4980	5150	5330	5500	5670	5840	6010	6180	6360	6530	6700	
		dual															8520	8830	9150	9460	9780	10090	10410	10720	11040	11350	11670	11980	12300	
295/60R22.5	X MULTWAY XD	single															4640	4810	4980	5150	5330	5500	5670	5840	6010	6180	6360	6530	6700	
		dual															8520	8830	9150	9460	9780	10090	10410	10720	11040	11350	11670	11980	12300	

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
315/60R22.5	XZA2 ENERGY	1	TL		152/148L			12.5	7100	9.00	12600	8.50	326	966	2946	9.00 - 9.75	335	314	952	441	2900	350	9.00			
	XDA 2+ ENERGY	1	TL		152/148L			19.0	7100	9.00	12600	8.50	326	966	2946	9.00 - 9.75	337	313	964	447	2940	350	9.00			
255/70R22.5	XZA	1	TL		140/137M	140L	8.50	13.0	5000	8.00	9200	8.00	265	944	2879	6.75 - 7.50 - 8.25	271	248	930	433	2841	281	6.75			
	XZE*	2	TL		LRH			14.3	5000	8.25	9200	8.25	265	944	2879	6.75 - 7.50 - 8.25	280	260	932	437	2856	295	7.50			
275/70R22.5	X MULTI Z	2	TL	18	148/145L	149/146K	9.00	14.0	6300	9.00	11600	9.00	287	974	2971	7.50 - 8.25	302	278	959	448	2942	311	7.50			
	X INCITY Z	5	TL	18	148/145J	152/148E		16.0	6300	9.00	11600	9.00	287	974	2971	7.50 - 8.25	299	276	962	448	2933	303	7.50			
	XZE2+	2	TL	18	148/145M			15.0	6300	9.00	11600	9.00	287	974	2971	7.50 - 8.25	299	276	966	448	2950	312	7.50			
	XJW4+	2	TL		148/145L			16.3	6300	9.00	11600	8.50	287	974	2971	7.50 - 8.25 - 9.00	298	276	969	450	2960	312	7.50			
	X MULTI D	2	TL	18	148/145L	149/146K	9.00	15.0	6300	9.00	11600	9.00	287	974	2971	7.50 - 8.25	298	274	958	446	2929	310	7.50			
	XDE2+	2	TL	16	148/145M			18.5	6300	9.00	11600	9.00	287	974	2971	7.50 - 8.25	299	275	973	454	2970	311	7.50			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Tread pattern	Table of inflation pressure (bar) in relation to maximum load per axle (kg)																											
		psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131
315/60R22.5	bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	
	single dual															4920	5100	5280	5460	5640	5830	6010	6190	6370	6550	6740	6920	7100	
	single dual															4920	5100	5280	5460	5640	5830	6010	6190	6370	6550	6740	6920	7100	
	single dual											3290	3430	3570	3710	3860	4000	4140	4290	4430	4570	4710	4860	5000					
255/70R22.5	XZA											6050	6310	6570	6830	7100	7360	7620	7890	8150	8410	8670	8940	9200					
	XZE*													3800	3910	4020	4130	4240	4360	4480	4600	4700	4800	4900	5000				
														7200	7400	7600	7800	8000	8120	8240	8360	8570	8780	8990	9200				
	X MULTI Z																4360	4520	4680	4850	5010	5170	5330	5490	5650	5820	5980	6140	6300
275/70R22.5	X INCITY Z																8030	8330	8630	8920	9220	9520	9820	10110	10410	10710	11010	11300	11600
	XZE2+																4360	4520	4680	4850	5010	5170	5330	5490	5650	5820	5980	6140	6300
	XIW4+																8030	8330	8630	8920	9220	9520	9820	10110	10410	10710	11010	11300	11600
	X MULTI D																8030	8330	8630	8920	9220	9520	9820	10110	10410	10710	11010	11300	11600
	XDE2+																8030	8330	8630	8920	9220	9520	9820	10110	10410	10710	11010	11300	11600

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal	
275/70R22.5	XDW ICE GRIP	2	TL		148/145L			19.0	6300	9.00	11600	8.50	287	974	2971	7.50 - 8.25	299	276	970	452	2970	311	7.50				
	X MULTI T	2	TL	18	148/145L	152/148J		14.0	6300	9.00	11600	9.00	287	974	2971	7.50 - 8.25	303	280	960	447	2943	311	7.50				
	XTA2 ENERGY	1	TL		152/148J			12.4	7100	9.00	12600	9.00	287	974	2971	7.50 - 8.25	298	271	954	440	2924	307	7.50				
	XTY2	3	TL	16	148/145J			17.0	6300	9.00	11600	8.50	287	974	2971	7.50 - 8.25	298	276	970	450	2960	312	7.50				
	X MULTI HL Z	2	TL	20	154/150L	152/148M	9.00	14.3	7500	9.00	13400	9.00	317	1018	3105	8.25 - 9.00	328	308	998	462	3048	340	8.25				
305/70R22.5	X MULTI Z	2	TL	20	152/150L			13.5	7100	9.00	13400	9.00	317	1018	3105	8.25 - 9.00	333	308	1010	471	3093	340	8.25				
	X INCTY Z	5	TL		153/150J			19.2	7100	9.00	13400	9.00	317	1018	3105	8.25 - 9.00			1003	468		341	8.25				
	X INCTY EV Z	5	TL	20	153/150J	156/150E	9.00	17.5	7300	9.00	13400	9.00	317	1018	3105	8.25 - 9.00	323	296	1008	466	3070	340	8.25				
	XZA2 ENERGY	1	TL	16	152/148L	150/147M	8.50	12.5	7100	9.00	12600	9.00	317	1018	3105	8.25 - 9.00	324	300	995	460	3030	339	8.25				
	XZU2T	5	TL	16	150/147J	154/150E	8.75	17.5	6700	8.50	12300	8.00	317	1018	3105	8.25 - 9.00	327	302	1003	465	3060	342	8.25				
	XDA 2+ ENERGY	1	TL		152/148L	150/147M	8.50	16.0	7100	9.00	12600	9.00	309	1028	3135	8.25 - 9.00	325	299	1002	466	3064	340	8.25				
	XDE2+	2	TL		152/148L	150/147M	8.50	19.0	7100	9.00	12600	9.00	317	1018	3105	8.25 - 9.00	325	301	1006	467	3070	340	8.25				
	X MULTI D	2	TL		154/150L			18.5	7500	9.00	13400	9.00	317	1018	3105	8.25 - 9.00	326	299	1006	464	3061	340	8.25				

• (1) ETRTO rating standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN. • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point, load capacity/authorized additional speed pair Load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Tread pattern

Dimension

Dimer	Tread	psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131	
		bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	
275/70R22.5	XDOW ICE GRIP	single															4360	4520	4680	4850	5010	5170	5330	5490	5650	5820	5980	6140	6300	
		dual															8460	8780	9090	9410	9720	10030	10350	10660	10970	11290	11600			
	X MULTI	single															4360	4520	4680	4850	5010	5170	5330	5490	5650	5820	5980	6140	6300	
		dual															8030	8330	8630	8920	9220	9520	9820	10110	10410	10710	11010	11300	11600	
	XTA2 ENERGY	single																4920	5100	5280	5460	5640	5820	6010	6190	6370	6550	6740	6920	7100
		dual																8720	9050	9370	9690	10020	10340	10660	10980	11310	11630	11950	12280	12600
305/70R22.5	XTY2	single															4360	4520	4680	4850	5010	5170	5330	5490	5650	5820	5980	6140	6300	
		dual															8460	8780	9090	9410	9720	10030	10350	10660	10970	11290	11600			
	X MULTI HL Z	single															5160	5370	5570	5750	5920	6120	6330	6530	6710	6890	7070	7290	7500	
		dual															9280	9640	10000	10310	10620	10930	11280	11640	12000	12350	12700	13050	13400	
	X MULTI Z	single																4920	5100	5280	5460	5640	5820	6010	6190	6370	6550	6740	6920	7100
		dual																9280	9620	9960	10310	10650	10990	11340	11680	12030	12370	12710	13060	13400
305/70R22.5	X INCITY Z	single															4920	5100	5280	5460	5640	5820	6010	6190	6370	6550	6740	6920	7100	
		dual															9280	9620	9960	10310	10650	10990	11340	11680	12030	12370	12710	13060	13400	
	X INCITY EV Z	single											4300	4500	4700	4880	5060	5240	5420	5600	5780	5960	6160	6360	6560	6740	6920	7100	7300	
		dual											7840	8200	8560	8920	9280	9640	10000	10280	10600	10920	11280	11640	12000	12320	12680	13040	13400	
	XZA2 ENERGY	single																4920	5100	5280	5460	5640	5820	6010	6190	6370	6550	6740	6920	7100
		dual																8720	9050	9370	9690	10020	10340	10660	10980	11310	11630	11950	12280	12600
305/70R22.5	XZU2T	single													4530	4710	4890	5070	5250	5430	5610	5790	5980	6160	6340	6520	6700			
		dual														8790	9140	9490	9840	10190	10540	10890	11250	11600	11950	12300				
	XDA 2+ ENERGY	single																4920	5100	5280	5460	5640	5820	6010	6190	6370	6550	6740	6920	7100
		dual																8720	9050	9370	9690	10020	10340	10660	10980	11310	11630	11950	12280	12600
	XDEZ+	single																4920	5100	5280	5460	5640	5820	6010	6190	6370	6550	6740	6920	7100
		dual																8720	9050	9370	9690	10020	10340	10660	10980	11310	11630	11950	12280	12600
X MULTI D	single											4400	4610	4810	4970	5160	5370	5570	5750	5920	6120	6330	6530	6710	6890	7070	7290	7500	7700	
	dual											7870	8210	8570	8920	9280	9640	10000	10310	10620	10930	11280	11640	12000	12350	12700	13050	13400		

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Normal load per axle (single) (kg)	Normal load per axle (dual) (kg)	Normal pressure for load (single) (bar)	Normal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
315/70R22.5	X MULTWAY 3D XZE	2	TL		156/150L			14.2	8000	9,00	13400	9,00	318	1032	3148	9,00	345	317	1014	470	3099	350	9,00			
	X MULTWAY 3D XDE	2	TL		154/150L			18.3	7500	9,00	13400	9,00	318	1040	3172	9,00	342	316	1020	476	3109	350	9,00			
	XDA 2+ ENERGY	1	TL		154/150L	152/148M	8.50	17.0	7500	9,00	13400	9,00	318	1032	3148	9,00 - 9,75	344	316	1020	474	3113	350	9,00			
	XDW ICE GRIP	2	TL		154/150L			16.3	7500	9,00	13400	9,00	318	1032	3148	9,00 - 9,75	339	318	1018	473	3110	350	9,00			
	XZN+ MIX ENERGY	2	TL		151/148L	149/146L	9,00	14.6	6900	9,00	12600	9,00	276	1012	3087	7,50 - 8,25	306	278	1021	474	3117	315	7,50			
275/80R22.5	XZN MIX ENERGY	2	TL		151/148L	149/146L	9,00	14.6	6900	9,00	12600	9,00	276	1012	3087	7,50 - 8,25	306	278	1021	474	3117	315	7,50			
	X INCTY XZU3	5	TL		149/146L	152/148E	8,75	17.5	6500	8,50	12000	8,50	287	1030	3142	7,50 - 8,25	306	278	1027	478	3138	315	7,50			
	XZE2+	2	TL	16	149/146L			15.5	6500	8,50	12000	8,50	287	1030	3142	7,50 - 8,25	307	280	1023	475	3120	317	7,50			
	XUE4 MIX ENERGY	1	TL		151/148L	149/146L	8,50	14.4	6900	9,00	12600	9,00	287	1030	3142	7,50 - 8,25 - 9,00	306	277	1021	474	3120	315	7,50			
	XDE2+	2	TL	16	149/146L			22.0	6500	8,50	12000	8,50	287	1030	3142	7,50 - 8,25	307	280	1036	481	3160	317	7,50			
	XDW ICE GRIP	2	TL		151/148L	149/146L	8,50	18.2	6900	9,00	12600	9,00	287	1030	3142	7,50 - 8,25 - 9,00	309	281	1029	478	3140	317	7,50			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair Load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

[illegible]

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
295/80R22.5	X LINE ENERGY Z	1	TL	18	152/149M	153/150J	8.50	14.0	7100	9.00	13000	9.00	310	1072	3270	8.25 - 9.00	324	296	1053	490	3225	326	8.25			
	X MULTI Z	2	TL	18	152/149M	153/150J	9.00	15.3	7100	9.00	13000	9.00	310	1072	3270	8.25 - 9.00	326	298	1055	492	3231	337	8.25			
	X MULTI Z2	2	TL	18	154/150L	152/149M	8.50	15.0	7500	8.50	13400	8.50	310	1062	3270	8.25 - 9.00	325	295.5	1045	484	3198	334	8.25			
	X MULTIWAY 3D XZE	2	TL		152/148L			15.2	7100	8.30	12600	8.00	310	1072	3270	8.25 - 9.00	328	297	1054	488	3221	326	8.25			
	X WORKS Z	3	TL	18	152/148K	154/150J	8.50	17.0	7100	8.50	13000	8.50	310	1112	3392	8.25 - 9.00	327	298	1060	493	3239	326	8.25			
	X COACH ENERGY Z	8	TL	18	152/149M	153/150J	8.50	14.1	6100	9.00	13000	9.00	310	1072	3270	8.25 - 9.00	324	297	1048	489	3232	326	8.25			
	X COACH HL Z	8	TL		154/149M			14.0	7500	8.50	13000	8.00	302	1062	3239	8.25	329	299	1055	488	3229	326	8.25			
	XZA 2+ ENERGY	1	TL	16	152/148M	153/150J	8.75	14.8	7100	8.50	12600	8.50	310	1062	3239	8.25 - 9.00	325	296	1057	490	3220	335	8.25			
	XZE2+	2	TL		152/148M			15.3	7100	8.50	12600	8.50	310	1062	3239	8.25 - 9.00	327	296	1057	490	3220	334	8.25			
	XZY 2	3	TL		152/148K			17.8	7100	8.50	12600	8.50	310	1112	3392	8.25 - 9.00	328	299	1060	492	3240	330	8.25			
	X INCTY XZU 3+	5	TL	16	152/148J	154/150E	8.75	18.0	7100	8.50	12600	8.50	310	1072	3270	8.25 - 9.00	328	297	1056	491	3225	336	8.25			
	X INCTY Z	5	TL	16	154/149J			16.5	7500	8.50	13000	8.50	310	1062	3270	8.25 - 9.00	338	307	1048	484	3194		8.25			
	XW4+	2	TL		152/148L	153/150J	8.75	16.0	7100	8.50	13000	8.50	310	1112	3392	8.25 - 9.00	327	299	1054	489	3220	338	8.25			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair. Load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Normal load per axle (single) (kg)	Normal load per axle (dual) (kg)	Normal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
295/80R22.5	XJS WINTER GRIP +	2	TL	151/148L	151/148L	149/146L	8.50	19.4	6900	9,00	12600	9,00	290	1030	3142	7.50 - 8.25 - 9.00	306	279	1030	479	3128	316	7.50		
	XJS WINTER GRIP	2	TL	16	152/149L	153/150J		18.5	7100	8.50	13000	8.50	310	1112	3392	8.25 - 9.00	329	299	1064	495	3250	338	8.25		
	X MULTI D	2	TL	18	152/149M			18.7	7100	8.50	13000	8.50	310	1072	3270	8.25 - 9.00	327	297	1061	493	3225	326	8.25		
	X MULTID+	2	TL	18	152/149M			20.0	7100	8.30	13000	8.30	310	1072	3270	8.25 - 9.00	329	298	1064	493	3340	337	8.25		
	X MULTIWAY 3D XDE	2	TL	152/148L				19.0	7100	8.30	12600	8.00	310	1062	3239	8.25 - 9.00	328	297	1061	492	3228	326	8.25		
	X COACH XD	8	TL	152/148M	154L		8.50	19.4	7100	8.50	13320	8.50	302	1073	3273	8.25	329	300	1062	494	3223	330	8.25		
	XDA 2+ ENERGY	1	TL	152/148M				16.8	7100	8.50	12600	8.50	310	1073	3273	8.25 - 9.00	327	300	1055	491	3215	330	8.25		
	XDE2+	2	TL	152/148M				23.0	7100	8.50	12600	8.50	310	1112	3392	8.25 - 9.00	328	300	1070	497	3270	330	8.25		
315/80R22.5	XDW ICE GRIP	2	TL	152/149L	153/150J		8.75	19.7	7100	8.50	13000	8.50	310	1112	3392	8.25 - 9.00	329	300	1066	496	3260	330	8.25		
	X MULTI ENERGY Z	2	TL	156/151L				15.5	8000	8.50	13800	8.25	318	1096	3343	9.00 - 9.75							9.00		
	X MULTIWAY 3D XZE	2	TL	156/150L			8.00	16.5	8000	8.50	13400	8.00	318	1096	3343	9.00 - 9.75	347	316	1081	501	3302	350	9.00		

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair/ Load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Tread pattern	psi																	
		36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98
295/80R22.5	XIS WINTER GRIP+	bar	127	131	135	139	143	147	151	155	159	163	167	171	175	179	183	187	191
		single																	
	XIS WINTER GRIP	dual																	
		single																	
	X MULTI D	dual																	
		single																	
	X MULTI D+	single																	
		dual																	
	X MULTIWAY 3D XDE	single																	
		dual																	
	X COACH XD	single																	
		dual																	
315/80R22.5	XDA 2+ ENERGY	single																	
		dual																	
	XDE2+	single																	
		dual																	
	XDW ICE GRIP	single																	
		dual																	
	X MULTI ENERGY Z	single																	
		dual																	
	X MULTIWAY 3D XZE	single																	
		dual																	

Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Nominal load per axle (single) (kg)	Nominal pressure for load (single) (bar)	Nominal load per axle (dual) (kg)	Nominal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
315/80R22.5	X WORKS XZY	3	TL		156/150K			16.0	8000	8.50	13400	8.50	318	1096	3343	9.00 - 9.75	348	317	1080	502	3308	350	9.00			
	X MULTIWAY XZER	2	TL 18		156/151L	154/150M	8.50	13.9	8000	8.50	13800	8.30	318	1096	3343	9.00 - 9.75	347	316	1077	499	3300	358	9.00			
	XZA 2+ ENERGY	1	TL 18		156/151L	154/150M	8.50	15.9	8000	8.50	13800	8.30	318	1106	3373	9.00 - 9.75	345	314	1079	499	3306	355	9.00			
	X MULTIWAY 3D XDE	2	TL		156/150L	154/150M	8.00	19.2	8000	8.50	13400	8.00	318	1106	3373	9.00 - 9.75	349	318	1087	504	3303	350	9.00			
	X WORKS XDY	3	TL		156/150K			22.0	8000	8.50	13400	8.50	318	1096	3343	9.00 - 9.75	348	317	1091	507	3312	350	9.00			
	XDE2+	2	TL		156/150L	154/150M	8.00	23.5	8000	8.50	13400	8.50	318	1107	3376	9.00 - 9.75	347	318	1095	507	3320	350	9.00			
	XDW ICE GRIP	2	TL		156/150L			20.2	8000	8.50	13400	8.00	318	1096	3343	9.00 - 9.75	348	315	1090	504	3320	350	9.00			
	X WORKS HD Z	3	TL		156/150K			16.0	8000	8.50	13400	8.50	318	1096	3343	9.00 - 9.75	348	317	1080	502	3308	350	9.00			
	X WORKS HD D	3	TL		156/150K			22.0	8000	8.50	13400	8.50	318	1096	3343	9.00 - 9.75	348	317	1091	507	3312	350	9.00			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed per load variations according to speed do not apply to the unique point.

Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension	Tread pattern																		
		psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94
		bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
	X WORKS XZY	single															5840	6050	6270
		dual															5840	6050	6270
	X MULTIMAX ZE R	single															9780	10140	10500
		dual													5410	5620	5840	6050	6270
	XZA 2+ ENERGY	single													9580	9970	10350	10730	11120
		dual													5410	5620	5840	6050	6270
	X MULTIMAX 3D XDE	single													9860	10250	10650	11040	11430
		dual													5840	6050	6270	6490	6700
	X WORKS XDY	single													10340	10720	11100	11490	11870
		dual													5840	6050	6270	6490	6700
	XDE2+	single													9780	10140	10500	10860	11230
		dual													5840	6050	6270	6490	6700
	XDW ICE GRIP	single													10340	10720	11100	11490	11870
		dual													5410	5620	5840	6050	6270
	X WORKS HD Z	single													9570	9950	10340	10720	11100
		dual													5840	6050	6270	6490	6700
	X WORKS HD D	single													9780	10140	10500	10860	11230
		dual													5840	6050	6270	6490	6700

315/80R22.5



Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Norminal pressure for unique point (bar)	Original tread depth	Normal load per axle (single) (kg)	Normal pressure for load (single) (bar)	Normal load per axle (dual) (kg)	Normal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
325/85R16	XML	4	TL		137J	134K	4.50	16.5	4600	4.50		4.50	338	992		9.0	364	327	984	449	2980		9.0			Jt 1967
255/100R16	XZL	4	TL		126K	134J	5.75	16.5	3400	4.50			260	946		16-6.00 G	286	255	923	426	2810		16-6.50 H			Jt 1967
275/80R20	XZL	4	TL	8	128K			15.2	3600	4.20			289	974		9 - W9 - 9 SDC	305	280	939	431	2850		9	20 P	230-20LB / 20x8.50	
335/80R20	XZL	4	TL	16	141K			17.8	5150	4.30						9-W9-9 SDC-W10 DW10-11-11 SDC-W11 DW11-12-12 SDC	381	345	1037	473	3140		11	20 P	310-20LB / 20x10.00	Jt 1681
365/80R20	XZL	4	TL		152K			19.9	7100	6.00						11-11 SDC-12-12 SDC	410	372	1096	501	3330		11	20 Q	310-20LB / 20x10.00	Jt 1443
475/80R20	XML	4	TL		166G			23.5	10600	6.00						14.0V ⁵	526	480	1272	581	3859		14.0V			
365/85R20	XZL	4	TL		164G			22.5	10000	7.50						10.0-10.00V-10.00W	411	368	1144	520	3460		20-10.00 W	20 S	280-20 L	
395/85R20	XZL 2	4	TL		168K	164L	8.50	20.0	11200	8.50			401	1220			429	388	1176	534	3584		20-10.00 W			
	XZL	4	TL		168G	161J	8.50	25.8	11200	8.50						10.0-10.00V-10.00W	425	388	1189	542	3600		20-10.00 W	20 S	280-20L	Jt 1443
9.00R20	XL	4	TT		140/137K			17.0	5000	7.00	9200	7.00	268	1038		6.0-6.00T-6.5-86.5-7.0 B7.0-7.33V-7.5-B7.5	278	252	1032	479	3148	285	7.0	20 M	200-20L / 20x7.50	

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair Load variations according to speed do not apply to the unique point.



Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension		Tread pattern	For Pressure, Please Consult MICHELIN's Representatives																														
			psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131	134		
325/65R16	XML	bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	9.25			
		single dual			3290	3500	3720	3940	4160	4380	4600																						
255/100R16	XZL	single dual			2430	2590	2750	2910	3080	3240	3400																						
		single dual			2730	2910	3090	3270	3435	3600																							
275/80R20	XZL	single dual																															
		single dual																															
335/80R20	XZL	single dual																															
		single dual																															
365/60R20	XZL	single dual													6500	6700	6900	7100															
		single dual													9420	9810	10210	10600															
475/60R20	XML	single dual			5890	6280	6670	7070	7460	7850	8240	8640	9030	9420	9810	10210	10600																
		single dual													6970	7270	7580	7880	8180	8480	8790	9090	9390	9700	10000								
365/65R20	XZL	single dual																															
		single dual																															
395/65R20	XZL 2	single dual																															
		single dual																															
	XZL	single dual																															
		single dual																															
9.00R20	XL	single dual								3060	3230	3390	3550	3710	3870	4030	4190	4350	4520	4680	4840	5000											
		single dual								5640	5940	6230	6530	6830	7120	7420	7720	8010	8310	8610	8900	9200											



Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Normal load per axle (single) (kg)	Normal pressure for load (single) (bar)	Normal load per axle (dual) (kg)	Normal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
11.00R20	XZL	4	TL	16	150/146K			18.0	6700	8.00	12000	8.00	297	1104		733V-7.5-87.5-8.0 8.0V-88.0-8.5 8.50V-88.5-9.00V	330	299	1092	508	3340	338	8.0	20 P	20x8.50MI	
	XZL	4	TL	18	154/149K			18.7	7500	8.50	13000	8.50	319	1146		7.33V-8.0-8.0V-88.0 8.5-8.50V-88.5 9.0-9.00V	344	311	1131	527	3460	352	8.5	20 Q	230-201B / 20x8.50	
12.00R20	XML	4	TL	18	149/146J			19.5	6500	7.20	12000	7.20	319	1158		7.33V-8.0-8.0V 88.0-8.5-8.50V 88.5-9.0-9.00V	339	308	1131	526	3443	349	8.5	20 Q		
	XML	4	TL		153G	149K	6.20	24.4	7300	6.20			377	1268		9.0-10.0-10.00V 10.00W	421	383	1258	581	3830		10.00W			
14.00R20	XZL+	4	TL		164/161J	166G	7.90	22.3	10000	7.80	18500	7.80					428	386	1258	578	3832	436	20-10.00W			
	XZL+	4	TL	22	164/160J	166G	7.90	22.3	10000	7.60	18000	7.60					428	386	1258	578	3832	436	20-10.00W			
	XZL	4	TL	22	164/160G	156J	7.60	23.3	10000	7.60	16000	7.60	384	1258		9.0-9.00V-10.0 10.00V-10.00W	427	384	1258	579	3826	434	10.00			
	XS	4	TL		160/157F		16.5	9000	7.00	16500	7.00	377	1282			9.0-10.0-10.00V 10.00W	410	369	1238	566	3772	417	10.00W			
16.00R20	XZL	4	TL		173/170G		27.0	13000	7.50	24000	7.50	482	1413				488	438	1343	609	4090	495	10.00W	20 V	310-201B / 20x10.00	

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair Load variations according to speed do not apply to the unique point.



Table of inflation pressure (bar) in relation to maximum load per axle (kg)

Dimension		Tread pattern		Table of inflation pressure (bar) in relation to maximum load per axle (kg)																											
				psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131
11.00R20	bar	single	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	9.25	
	dual	single																													
	dual	single																													
12.00R20	bar	single	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	9.25	
	dual	single																													
	dual	single																													
14.00R20	bar	single	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	9.25	
	dual	single																													
	dual	single																													
16.00R20	bar	single	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	9.25	
	dual	single																													
	dual	single																													



Dimension	Tread Pattern	Category	Type	PR (Ply Rating)	Load / Speed Index	Unique point (3)	Normal pressure for unique point (bar)	Original tread depth	Normal load per axle (single) (kg)	Normal pressure for load (single) (bar)	Normal load per axle (dual) (kg)	Normal pressure for load (dual) (bar)	Maximum section width in service (mm)	Maximum diameter in service (mm) (1)	Rolling circumference (mm)	Approved rim(s) ETRTO	Laden section width (mm) (2)	Free section width (mm) (2)	Diameter (mm) (2)	Static laden radius (mm) (2)	Rolling circumference (mm) (2)	Minimum dual spacing (mm) (2)	Recommended rim(s) by MICHELIN	Tube	Flap	Seal
525/65R20.5	X5	4	TL	20	173F			16.8	13000	8.00			551	1231		16.00	558	521	1200	548	3639		16.00	19.5/20.5 UD		
24/70R20.5	X5	4	TL		176F			16.8	14200	6.00						18.00	661	602	1374	620	4150		18.00	20.5 WAMD		
24/70R21	X2L	4	TL	16	176G			25.0	14200	6.00			200	687			663	608	1388	631	4200		18.00			
445/65R22.5	X2L	4	TL		168G			21.0	11200	8.00						14.00	486	448	1168	537	3550		14.00			
13R22.5	X2L	4	TL	18	154/150K			20.2	7500	8.00	13400	8.00	326	1146		9.00 - 9.75	338	307	1130	525	3450	347	9.00			
12.00R24	XDL	4	TT		LRI			30.4	8000	7.50	14600	7.50				8.50, 8.00	356	323	1255	586	3944	358	8.50			

• (1) ETRTO rating (standard value, the ETRTO standard rim may be different to the rim recommended by MICHELIN). • (2) MICHELIN rating, value measured on rim recommended by MICHELIN. • (3) Unique point: load capacity/authorized additional speed pair load variations according to speed do not apply to the unique point.



Table of inflation pressure (bar) in relation to maximum load per axle (kg)

		Table of inflation pressure (bar) in relation to maximum load per axle (kg)																														
Dimension	Tread pattern	psi	36	40	44	47	51	54	58	62	65	69	73	76	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131	134		
		bar	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00	7.25	7.50	7.75	8.00	8.25	8.50	8.75	9.00	9.25		
		single												8500	8875	9250	9625	10000	10375	10750	11125	11500	11875	12250	12625	13000						
		dual												-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
		single						9000	9500	10000	10500	11000	11500	12000	12500	13000	13600	14200														
		dual						-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
24/70R21	XZL	single					9000	9500	10000	10500	11000	11500	12000	12500	13000	13600	14200															
		dual					-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
44S/6SR22.5	XZL	single											7360	7680	8000	8320	8640	8960	9280	9600	9920	10240	10560	10880	11200							
		dual											4930	5140	5360	5570	5790	6000	6210	6430	6640	6860	7070	7290	7500							
13R22.5	XZL	single											8810	9190	9570	9950	10340	10720	11100	11490	11870	12250	12630	13020	13400							
		dual											5090	5330	5580	5820	6060	6300	6550	6790	7030	7270	7520	7760	8000							
12.00R24	XDL	single										5090	5330	5580	5820	6060	6300	6550	6790	7030	7270	7520	7760	8000								
		dual									9290	9290	9730	10180	10620	11060	11500	11950	12390	12830	13270	13720	14160	14600								

TECHNICAL CHARACTERISTICS TABLE AND PRODUCT OFFER 2

MICHELIN AGILIS³ FOR LIGHT TRUCK



BENEFITS:

Safety made to last

- Shorter wet braking distance when new (5%) and when worn (11%) compared with leading competitor*

Your partner for longer

- Michelin's excellence in longevity proven by +25% more mileage vs. previous generation**
- Less downtime for you and your business

Every drop counts

- 12%*** superior rolling resistance resulting in reduced fuel consumption giving you the environmental advantage.

TECHNOLOGIES

Safety

- With the Evergrip technology
- Innovative compound with higher density of silica and carbon black to improve wet grip and reduce breaking distances (when new or worn).

Strength

- From the sidewall kerbing protectors.
- The position of kerbing protectors on the sidewall has been calculated to optimize tyre protection in all circumstances.



TECHNOLOGY
EVERGRIP
Optimized compound



TECHNOLOGY
EVERGRIP
U-SHAPE GROOVE



TECHNOLOGY
SHIELDS REINFORCED
SIDEWALL RUBBER

* Wet braking test 80 to 0 kph, conducted by TÜV Rheinland Thailand Ltd, on Michelin's request, in June 2020 on dimension 215/70R15C on Toyota Hiace Commuter, laden condition of 2,950 kg GVW. Comparing new and worn MICHELIN Agilis 3 RC versus three other competitor brands of tyres. Wet braking reference: TÜV Rheinland Thailand Ltd, Technical Report 242107901 001

** Test results from Michelin internal test, conducted on real roads in Thailand, with 215/70R15C tyres fitted in Ford Ranger (Ute car). Load: Front axle: 1446kg / Rear axle: 1443 kg. Wear life index was calculated by the "Harmonic average" of 4 tyres assuming the Customer regularly rotates tyres.

*** Rolling Resistance Test performed at Thailand Automotive Institute and certified by TÜV Rheinland Thailand Ltd, on Michelin's request, in December 2019, on dimension 215/70R15C. Comparing MICHELIN Agilis 3 RC versus other competitor brands. TÜV Reference Report No. 242105960 001.



Dimension	Tread Pattern	Type	Load / Speed Index	Original tread depth	Load Capacity (kgs) Single	Load Capacity (kgs) Dual	Section Width (mm)	Overall Diameter (mm)	Rolling Circumference (mm)	Min Rim Width (inches)	Measuring Rim Width (inches)	Maxi Rim Width (inches)
185R14C	AGILIS 3	TL	102T100R	8.0	850	800	188	650	1983	4.5	5.0	6.0
195/65R16C	AGILIS 3	TL	104T102R	8.5	900	850	201	660	2013	5.5	6.0	6.0
195/75R16C	AGILIS 3	TL	107T105T	8.0	975	925	196	698	2129	5.0	5.5	6.0
195/80R14C	AGILIS 3	TL	106T104R	8.0	950	900	196	688	2037	5.0	5.5	6.0
195/80R15C	AGILIS 3	TL	108T106S	8.0	1000	950	196	693	2114	5.0	5.5	6.0
205/65R16C	AGILIS 3	TL	107T105T	8.5	975	925	209	672	2050	5.5	6.0	6.5
205/70R15C	AGILIS 3	TL	106T104S	8.0	950	900	209	669	2040	5.5	6.0	6.5
205/75R14C	AGILIS 3	TL	109T107R	8.0	1030	975	203	664	2025	5.5	5.5	6.5
205/75R16C	AGILIS 3	TL	113T111R	8.5	1150	1090	203	714	2178	5.5	5.5	6.5
215/65R15C	AGILIS 3	TL	104T102T	7.5	900	850	221	661	2016	6.0	6.5	7.0
215/65R16C	AGILIS 3	TL	109T107T	8.0	1030	975	221	686	2092	6.0	6.5	7.0
215/70R15C	AGILIS 3	TL	109T107S	8.0	1030	975	221	683	2083	5.5	6.5	7.0
215/70R16C	AGILIS 3	TL	108T106T	8.0	1000	950	221	708	2159	5.5	6.5	7.0
215/75R16C	AGILIS 3	TL	113T111T	8.0	1150	1090	216	728	2220	5.5	6.0	7.0
225/65R16C	AGILIS 3	TL	112T110R	8.5	1120	1060	228	698	2129	6.0	6.5	7.0
225/70R15C	AGILIS 3	TL	112T110S	8.5	1120	1060	228	697	2126	6.0	6.5	7.0
225/75R16C	AGILIS 3	TL	121T120R	7.5	1450	1400	223	744	2269	6.0	6.0	7.0
235/60R17C	AGILIS 3	TL	117T115T	8.0	1285	1215	240	714	2178	6.5	7.0	7.5
235/65R16C	AGILIS 3	TL	121T119R	7.5	1415	1360	240	712	2172	6.5	7.0	7.5
235/65R16C	AGILIS 3	TL	115T113T	8.0	1215	1150	240	712	2172	6.5	7.0	7.5

TECHNICAL CHARACTERISTICS TABLE AND PRODUCT OFFER 2

MICHELIN XCD2 FOR LIGHT TRUCK

BENEFITS:

MICHELIN XCD2 tyres are the reference for usage in the most challenging conditions.

HEIGHT LOADING CAPACITY

- Perfect choice for commercial users.

ROBUST AND STRONG

- Built to endure and last with ability to carry heavy loads with maximum safety.



HARD OUTER LAYER

SOFT INNER LAYER

01

ENDURE MORE TRIPS

WITH A COMBINATION OF RUBBER COMPOUNDS

- Hard outer layer of 100% natural rubber protects casing ply
- Soft inner layer of synthetic rubber content lowers heat generation

02

INCREASED ROBUSTNESS

WITH MAXIMUM BEAD STRENGTH

- Five more wires in bead package
- 20% stronger bead
- Improved resistance to bead failure
- Improved damage resistance during fitting and removal

MICHELIN XCD2

MICHELIN XCD

03

BETTER HANDLING

WITH RUBBER INSERT ON LOWER SIDEWALL

- 27% increased height*
- 45% higher bead reinforcement*
- More rigid sidewall
- Improved handling stability



Incorrect tyre usage and driving can lead to accidents. To reduce any possible risk, Michelin recommends users to follow the tyre user manual, tyre sidewall information and vehicle user manual strictly. The tyre user manual is available at all Michelin dealers. For more information, please visit www.michelin.com.au

All claims are made in comparison to the previous generation of MICHELIN XCD tyres.
*Based on MICHELIN XCD2 size 205/70 R15C

2/ TECHNICAL CHARACTERISTICS MICHELIN XCD2 FOR LIGHT TRUCK



Dimension	Pattern	Type	Load Index	Load Index (Dual)	Speed Index	Load Capacity (Kgs) Single	Load Capacity (Kgs) Dual	Section Width Design Value (mm)	Overall Diameter (mm)	Rolling Circumference (mm)	Min Rim Width (inches)	Measuring Rim Width (inches)	Maxi Rim Width (inches)
195R14C	XCD	TL	106		P	950		198	666	2031	5.00	5.50	6.00
205R14C	XCD	TL	109		P	1030		208	686	2092	5.50	6.00	6.50
215R14C	XCD	TL	112		P	1120		218	714	2178	5.50	6.00	7.00
205/70R15C	XCD	TL	106		Q	950		209	669	2040	5.50	6.00	6.50
215R15C	XCD	TL	112		Q	1120		218	725	2211	5.50	6.00	7.00
205/75R14C	XCD2	TL	109	107	P	1030	975	203	664	2025	5.50	5.50	6.50
215/75R14C	XCD2	TL	112	110	P	1120	1060	216	678	2068	5.50	6.00	7.00
225/75R14C	XCD2	TL	115	113	P	1215	1150	223	693	2114	6.00	6.50	7.00
205/70R15C *	XCD2	TL	106	104	S	950	900	209	669	2040	5.50	6.00	6.50
225/75R15C *	XCD2	TL	116	114	Q	1250	1180	223	719	2193	6.00	7.00	7.50

APPENDIX 3

- **TUBE & FLAP ASSEMBLY** 74
- **TRUCK AND BUS WHEEL** 78
- **ACCESSORIES** 80
- **CONVERSION TABLE** 82
- **GENERAL INFORMATION** 85

TYRE/TUBE/FLAP ASSEMBLY

Tyre dimensions	Tube	Valve		Flap	Plates
	Reference	Reference	Bend type	Reference	
7.50R15	15/16J	570	Single	Flap 15X6.00	Plastic
8.25R15	15K	1221	Double	Flap 15X6.00	Plastic
10.00R15	15P	582	Triple	Flap 15X7.50	Plastic
	15P	1548	Straight		
7.00R16	16J 77-95	TR77A	Single, Fixed valve	Flap 16x6.00	Metal
7.50R16	16J 77-95	TR77A	Single, Fixed valve	Flap 16x6.00	Metal
8.25R16	16K 77-95	TR77A	Single, Fixed valve	Flap 16x6.00	Metal
8.25R20	20K	1021	Single	Flap 20x7.50	Metal
9.00R20	20M+ 175 95	TR175A	Single, Fixed valve	Flap 20x7.50	Metal
10.00R20	20N+ 78 95	TR78A	Single, Fixed valve	Flap 20x7.50	Metal
11.00R20	20P 78 95	TR78A	Single, Fixed valve	Flap 20X8.50	Metal
12.00R20 335/80R20	20Q	1158	Single	Flap 20X8.50	Metal
14.00R20 G20	20S	582	Triple	Flap 20X10.00	Plastic
365/85R20	20S	582	Triple	Flap 20X8.50	Metal
395/85R20	20S	582	Triple	Flap 20X10.00	Plastic
16.00R20	20V	1188	Single	Flap 20X10.00	Plastic
	20V	1548	Straight		
12.00R24	24Q	582	Triple	Flap 24/25X8.50 E	Plastic
325/95R24	24Q	582	Triple	Flap 24/25X8.50 E	Plastic

For other CAs not listed in this table, please contact your Michelin representative.

Flap Groups for use in MICHELIN tyres

Tyre size	Rim width	15X6.00	15X7.50	16X6.00+
7.00R15 7.50R15	5.00			
	5.50			
	6.00			
	6.50			
8.25R15	5.00			
	5.50			
	6.00			
	6.50			
10.00R15	6.50			
	7.00			
	7.50			
7.00R16	5.00			
	5.50			
	6.00			
7.50R16	5.50			
	6.00			
	6.50			
8.25R16	6.00			
	6.50			

Bold = Standard rim width



Preferred fitment on this rim



Fitment permitted but the flap may be wide



Fitment permitted but the flap may be narrow

TUBE AND FLAP ASSEMBLY

Flap Groups for use in MICHELIN tyres

Tyre size	Rim width	20X7.50	20X8.50	20X10.00	25/25X8.25	240-24/25L
8.25R20	6.00					
	6.50					
	7.00					
9.00R20	6.50					
	7.00					
	7.50					
10.00R20	7.00					
	7.50					
	8.00					
11.00R20	7.50					
	8.00					
	8.50					
12.00R20 335/80R20	8.00					
	8.50					
	9.00					
14.00R20 365/80R20	9.00					
	10.00					
16.00R20	10.00					
	11.25					
12.00R24	8.00					
	8.50					
	9.00					

Bold = Standard rim width




Preferred fitment on this rim



Fitment permitted but the flap may be wide




Fitment permitted but the flap may be narrow




TRUCK AND BUS WHEEL

Tube Type Wheel



Tubeless Wheel










Characteristics

A = Nominal Wheel Diameter
B = Inside width
C = Centre bore

D = Offset
E = Diameter of the fixing holes (PCD)
N = Number of fixing holes
Dual Spacing = 2 x offset

Types of Fixing


Single				 80°
	Cylindrical	Spherical nut or Spherical washer + Cylindrical	Spherical nut	Conical nut
Twinned				 80° 80°
	SPIGOT (P or M)	Spherical DIN	Budd/AMJ (American/Japanese)	Conical (AN)

TRUCK AND BUS WHEEL

Truck & Bus Rims


Characteristics

Flat base



size	F mm	H
3.75 P	95	25.4
4.33 R	110	28.6
5.00 S	127	33.3
6.00 T	152	38.1
7.33 V	186	44.4
8.50 V	216	44.4
9.00 V	229	44.4
10.00 V	254	44.4
10.00 W	254	51.0
11.25 {	286	51.0
	286	63.5

Advanced (3 pieces) Two 5° taper seats




size	F mm	H
5.0	127	27.9
5.5	140	30.5
6.0	152	33.0
6.5	165	35.6
7.0	178	38.1
7.5	190	40.6
8.0	203	43.2
8.5	216	45.7
9.0	229	48.3
10.0	254	50.8

Semi Drop Centre (SDC) Two 5° taper seats




size	F mm	H
4.50 E-SDC	114.3	19.8
5.00 E-SDC	127.0	19.8
5.50 F-SDC	139.7	22.2
6.00 G-SDC	152.4	27.9
6.50 H-SDC	165.1	33.7
7.00 N-SDC	177.8	34.5

Drop Centre 15° taper seats



size	F mm	H
5.25	133.4	12.7
6.00	152.4	12.7
6.75	171.5	12.7
7.50	190.5	12.7
8.25	209.6	12.7
9.00	228.6	12.7
9.75	247.6	12.7

Intermediate one 5° taper seats (on fixe side)



size	F mm	H
5.00 R	127	28.6
5.50 S	140	33.3
6.00 S	152	33.3
6.50 T	165	38.1
7.00 T	178	38.1
7.50 V	190	44.4
8.00 V	203	44.4

5° taper seats (English standard)

8.5.0	127	27.9
8.5.5	140	27.9
8.6.0	152	33.0
8.6.5	165	38.1
8.7.0	178	38.1
8.7.5	190	43.2
8.8.0	203	43.2
8.8.5	216	45.7

5° taper seats (Other standard)


5.0 R	127	28.6
5.5 S	140	33.3
6.0 S	152	33.3
6.5 T	165	38.1
7.0 T	178	38.1
7.5 V	190	44.4
8.0 V	203	44.4
8.5 V	216	44.4
9.0 V	229	44.4
10.0 Wi	254	51.0

Well base/Drop Centre 5° taper seats



size	F mm	H
4.50 E	114.3	19.8
5.00 F	127.0	22.2
5.50 F	139.7	22.2
5 1/2 K	139.7	19.6
6 L	152.4	21.6
6 1/2 L	165.1	21.6
20 x 5.0 BC	127.0	25.0
9 x 20	228.6	26.5
11 x 20	279.4	26.5

Wide base drop centre 15° taper seats




size	F mm	H
11.75	298.5	12.7
12.25	311.0	12.7
13.00	330.2	12.7
14.00	355.6	12.7
15.00	381.0	12.7
16.00	406.4	12.7
18.00	457.0	12.7



WARNING: Correct wheel components must be used. It is important to note that some hub centered and stud centered wheels may have the same bolt circle pattern. Therefore, they could mistakenly be interchanged. Each mounting system requires its correct mating parts. It is important that the proper components are used for each type of mounting, and that the wheels are fitted to the proper hubs. If hub centered wheel components (hubs, wheels, fasteners) are mixed with stud centered components, loss of torque, broken studs, cracked wheels and possible wheel loss can occur since these parts are not designed to work together.

ACCESSORIES


Rubber base valves for truck



Plastic ferrule for the fitment of valve 746 in 15.7 mm diameter hole


Reference		Ø hole of the valve
ETRTO	MICHELIN	
V2-01-1	746	11,3
V2-01-2	611	15,7
—	990	15,7

Base for truck valve stem




Reference		Ø
ETRTO	MICHELIN	
V3-08-4	1548	57

Single bend valve stem



Reference		L mm	H mm	α°
ETRTO	MICHELIN			
V3-02-2	570	43	22	120
V3-02-3	576	44	33	95
V3-02-4	577	44	39	110
V3-02-5	1003	47	20	90
V3-02-7	1188	71	22	100
V3-02-9	1156	99	20	94
V3-02-10	1021	115	20	94
V3-02-12	1157	132	20	94
V3-02-13	751	133	20	90
V3-02-14	1158	138	20	94
V3-02-20	750	53	22	95
V3-02-23	1012	66	29	90
V3-03-4	1010	84	15	94


Valve with straight stem



Reference		L mm
ETRTO	MICHELIN	
—	1964	49

Double bend valve stem


Reference		L mm	A mm	B mm	H mm	α°	β°
ETRTO	MICHELIN						
V3-04-1	578	60	32	37	20	90	138
V3-04-2	579	76	38	41	20	90	153
V3-04-6	734	128	86	47	20	90	153
V3-04-8	1198	80	38	43	20	90	167
V3-04-26	1877	140	99	42	20	99	189
V3-05-1	1221	96	32	66	16	90	165



ACCESSORIES

Triple bend valve stem

Reference		L mm	A mm	B mm	H mm	h mm	α°	γ°
ETRTO	MICHELIN							
V3-06-2	580	94	44	12	20	17	90	125
V3-06-3	581	114	46	20	20	17	90	140
V3-06-5	582	131	62	19	20	17	90	139
V3-06-7	1348	106	45	18	20	17	90	137



Mounting a universal valve stem




1. Check that air-tight rubber must be dry and clean when fitting.
2. Screw down the stem until contact is made with the washer.
3. Continue to screw in two complete turns for air-tightness.
4. Tighten the stem further until the final position is reached.




IMPORTANT : do not unscrew

NB : Do not tighten more than recommended above.
Do not forget to fit the valve cap which keeps it clean and helps keep the valve leakproof.


Essential accessories




Truck Tyre valve extension



In these assemblies, always fit the valves facing each other.



Fixing Clamps for Trucks Tyres valve extension



When tyres are twinned, in order to avoid abnormal wear and tyre overload problems, it is essential to ensure that twinned tyres are the same size, same manufacture, same type and tread pattern, and that the wear rates and pressures are the same.

Valve extensions fitted to inner twins, permit easy verification of tyre pressures. It is essential to ensure that they are correctly fitted, and supported with the appropriate brackets where necessary.

CONVERSION TABLE


Equivalent Sizes

100 Series	90 Series	Low Profile Series
7.50 R 15		215/75 R 17.5
8.25 R 15	9 R 17.5	235/75 R 17.5
10.00 R 15		285/70 R 19.5
7.00 R 16	8 R 17.5	205/75 R 17.5
7.50 R 16	8.5 R 17.5	215/75 R 17.5
		225/75 R 17.5
		225/80 R 17.5
8.25 R 16	9.5 R 17.5	235/75 R 17.5 245/70 R 19.5
	10 R 17.5	
	225/90 R 17.5	
7.50 R 20	8 R 22.5	
8.25 R 20	9 R 22.5	
9.00 R 20	10 R 22.5	255/70 R 22.5
		275/70 R 22.5
10.00 R 20	11 R 22.5	295/80 R 22.5
		275/80 R 22.5
		275/70 R 22.5
11.00 R 20	12 R 22.5	295/80 R 22.5
		315/80 R 22.5
		305/70 R 22.5
		315/70 R 22.5
12.00 R 20	13 R 22.5	315/80 R 22.5

Note : Before any change over please check :

- Load capacity
- Vehicle clearance
- Recommended rim/wheel
- Dual spacing

CONVERSION TABLE



Conversion Table

Quantity	Units	Other Units
Length	m (meter)	1 inch (*) = 0.0254 m (or 25.4 mm) 1 mile = 1,609 m (or 1.609 km)
Mass	kg (kilogram)	1 pound (lb) = 0.4536 kg
Pressure	kPa (kilo pascal)	1 bar = 14.5 PSI 1 bar = 100 kPa 1 kg/cm ² = 98.066 kPa
Speed	m/s (meter per second)	1 km per hour (km/hr)* = 0.27778 m/s 1 mile per hour (m.p.h.) = 0.4470 m/s 1 mile per hour (m.p.h.) = 1.60935 km/h

Load Range / Ply Rating

B - 4	F - 12	L - 20
C - 6	G - 14	M - 22
D - 8	H - 16	
E - 10	J - 18	

CONVERSION TABLE

Pressure Unit Conversion Table

kPa	bar	psi*	kg/cm ² *
100	1.0	15	1.0
150	1.5	22	1.5
200	2.0	29	2.0
250	2.5	36	2.5
300	3.0	44	3.1
350	3.5	51	3.6
400	4.0	58	4.1
450	4.5	65	4.6
500	5.0	73	5.1
550	5.5	80	5.6
600	6.0	87	6.1
650	6.5	94	6.6
700	7.0	102	7.1
750	7.5	109	7.7
800	8.0	116	8.2
850	8.5	123	8.7
900	9.0	131	9.2
950	9.5	138	9.7
1,000	10.0	145	10.2
1,050	10.5	152	10.7

* Values in psi and kg/cm² rounded to the nearest practical units.

Adjusted Inflation Pressure (psi) when inflating indoors at 18°C

Recommended Pressure (psi)	Outside Ambient Temperature (°C)										
	10°	4°	-1°	-7°	-12°	-18°	-23°	-29°	-34°	-40°	-46°
75	78	80	81	83	86	88	90	92	95	98	100
80	83	85	87	89	91	93	96	98	101	104	107
85	88	90	92	94	97	99	102	104	107	110	113
90	93	95	98	100	102	105	108	110	113	116	119
95	98	101	103	105	108	111	113	116	119	123	126
100	103	106	108	111	113	116	119	122	125	129	132
105	109	111	114	116	119	122	125	128	132	135	139
110	114	116	119	122	125	128	131	134	138	141	145
115	119	122	124	127	130	133	137	140	144	148	151
120	124	127	130	133	136	139	143	146	150	154	158
125	129	132	135	138	141	145	148	152	156	160	164
130	134	137	140	144	147	150	154	158	162	166	171

GENERAL INFORMATION

Load Capacity Index						Speed Category Symbols		
LI	kg	LI	kg	LI	kg	Speed symbol	Speed in km/hr	MPH approx
115	1,215	138	2,360	161	4,625	A1	5	3
116	1,250	139	2,430	162	4,750	A2	10	6
117	1,285	140	2,500	163	4,875	A3	15	9
118	1,320	141	2,575	164	5,000	A4	20	12
119	1,360	142	2,650	165	5,150	A5	25	16
120	1,400	143	2,725	166	5,300	A6	30	19
121	1,450	144	2,800	167	5,450	A7	35	22
122	1,500	145	2,900	168	5,600	A8	40	25
123	1,550	146	3,000	169	5,800	B	50	31
124	1,600	147	3,075	170	6,000	C	60	37
125	1,650	148	3,150	171	6,150	D	65	40
126	1,700	149	3,250	172	6,300	E	70	43
127	1,750	150	3,350	173	6,500	F	80	50
128	1,800	151	3,450	174	6,700	G	90	56
129	1,850	152	3,550	175	6,900	J	100	62
130	1,900	153	3,650			K	110	68
131	1,950	154	3,750			L	120	75
132	2,000	155	3,875			M	130	81
133	2,060	156	4,000			N	140	87
134	2,120	157	4,125					
135	2,180	158	4,250					
136	2,240	159	4,375					
137	2,300	160	4,500					

Important : At the time of fitting, it is vital that the various markings be checked, in order to be certain that the tyre is suitable for operation at the maximum allowed vehicle speed and loading.

Speed / Load / Pressure Combinations							
Speed symbol Speed in km/hr	Load capacity variation (%)						Pressure Adjustment (%)
	F (80 km/hr)	G (90 km/hr)	J (100 km/hr)	K (110 km/hr)	L (120 km/hr)	M (130 km/hr)	
0	+150	+150	+150	+150	+150	+150	+40
5	+110	+110	+110	+110	+110	+110	+40
10	+80	+80	+80	+80	+80	+80	+30
15	+65	+65	+65	+65	+65	+65	+25
20	+50	+50	+50	+50	+50	+50	+21
25	+35	+35	+35	+35	+35	+35	+17
30	+25	+25	+25	+25	+25	+25	+13
35	+19	+19	+19	+19	+19	+19	+11
40	+15	+15	+15	+15	+15	+15	+10
45	+13	+13	+13	+13	+13	+13	+9
50	+12	+12	+12	+12	+12	+12	+8
55	+11	+11	+11	+11	+11	+11	+7
60	+10	+10	+10	+10	+10	+10	+6
65	+7.5	+8.5	+8.5	+8.5	+8.5	+8.5	+4
70	+5.0	+7.0	+7.0	+7.0	+7.0	+7.0	+2
75	+2.5	+5.5	+5.5	+5.5	+5.5	+5.5	+1
80	[0]	+4.0	+4.0	+4.0	+4.0	+4.0	0
85		+2.0	+3.0	+3.0	+3.0	+3.0	0
90		[0]	+2.0	+2.0	+2.0	+2.0	0
95			+1.0	+1.0	+1.0	+1.0	0
100			[0]	0	0	0	0
110				[0]	0	0	0
120					[0]	0	0
130						[0]	0

"The coefficients indicated in this table correspond to the international standard e.g. European Standard (E.T.R.T.O.). They are given for information purpose only and may change. Please contact MICHELIN Technical Department for any modifications which are beyond the restrictions found either in this catalogue or on tyre sidewall markings. When the coefficients of this table require pressure adjustment more than 10 bars, essentially, reduce load to correspond with maximum 10 bars pressure and/or contact us. Also, use rims which are resistant to an increased pressure and respect the rules of rim mounting and usage."

[illegible]



www.michelin.com.au