

AGRIBIB 2

STANDARD SERIES



**From 60 to 170 HP tractors
and up to 500 HP with duals**
(Diameters : 42", 46", 50")



AGRIBIB 2 STANDARD SERIES

High level of performance throughout its life



Traction capacity



Service life



Robustness



Stubble protection

- Angled sculpture
- 5/32nd Extra-rubber along center rib

Load index

- Increased by over 15% ⁽⁴⁾

Traction

- 45 deg lug
- Retains AGRIBIB's outstanding traction ⁽³⁾

Tire life

- R1W lug ⁽¹⁾ for longer service life
- +8% deeper ⁽²⁾ than leading competitors R1W offer
- Up to +10% deeper than R1W standard

Self-cleaning capacity

Hinge in the center of the tread

(1) R1W lug depth as defined by the TRA standard.

(2) Michelin AGRIBIB2 480/80R50 vs leading competitors published depths

(3) Source: Analytical test performed on the test tracks at the MICHELIN test and research centre (Ladoux).

(4) Level of increase varies by size

Sizes

280/85 R28 123A8/120D
420/90 R30 147A8/147B (16,9R30)
380/85 R30 140A8/140B (14,9R30)
420/85 R34 147A8/147B (16,9R34)
380/85 R34 142A8/142B (14,9R34)
320/85 R34 133A8/133B (12,4R34)

520/85 R38 160A8/160B (20,8R38)
380/80 R38 142A8/139D (14,9R38)
520/85 R42 162A8/162B (20,8R42)
480/80 R42 156A8/156B (18,4R42)

480/80 R46 158A8/158B (18,4R46)
520/85 R46 164A8/164B (20,8R46)
420/80 R46 151A8/151B

480/80 R50 159A8/159B
380/90 R54 152A8/152B

MICHELIN ADVICE

MACHINE # 1

FRONT: PRESSURE: (bars / psi)
REAR: PRESSURE: (bars / psi)

MACHINE # 2

FRONT: PRESSURE: (bars / psi)
REAR: PRESSURE: (bars / psi)



MICHELIN



agro.michelin.com



www.youtube.com/user/AgMichelin