

The ultimate front axle tyre for optimal performance in severe usage conditions

Operating Cost Optimization



Best Mileage*
Highest Retreadability*
*When compared to Michelin's previous generation of products (315/80 R22.5)












Directional Tread Design



Ozone Resistant Sidewall Compound



Patented FAZ Technology

BEST MILEAGE*

- More uniform footprint due to FAZ stabilizing effect
- Truly directional sculpture optimizes exit from contact patch area and reduces onset of irregular wear
- New slow wearing compound extends the kilometers per millimeter

HIGHEST RETREADABILITY*

- New Sidewall Compound protects against Ozone
- New Crown Design and optimized tread depth reduces operating temperature
- New FAZ technology reinforces and stablizes the entire belt package

						Dimensional characteristics				Advised	Regrooving			
Load per axle kg		Inflation		Load index	Unique	Dimensions E.T.R.T.O			MICHELIN dimensions					
Single	Twin			speed symbol	point	S	D	CdR/RC	R'	E	E rims			
Kg	Kg	Bar	PSI			mm	mm	mm	mm	mm		Blade	Depth	
315/80 R22.5 X Line Tropic F														
8000	13400	8.30	120	156 / 150 L	154 / 150 M	318	1096	3282	496	350	9.00 9.75	R3	3 mm	

*When compared to Michelin's previous generation of products (315/80 R22.5)

