

# MICHELIN MEGAXBIB 2



## IMPROVED TYRE DESIGN

especially in the shoulder area, compared to the previous range

- Highly robust
- Protection against stubble damage
- Long tyre life
- Excellent plant protection




## REINFORCED CARCASS


- MICHELIN MEGAXBIB 2 offers one of the highest load indexes for a similar tyre in the market with equivalent tyre construction

## HIGH COVERAGE TREAD

- Outstanding driver comfort
- Excellent road handling



ROBUSTNESS



LOAD CAPACITY



ROAD HANDLING

## SIZES

1000/50R25 172A8/166D TL

800/65R32 178A8/178B TL

**NEW** 800/70R32 181A8/181B TL

750/50R26 160A8/154D TL

1050/50R32 178A8/172D TL

**NEW** 710/75R34 178A8/178B TL

650/75R32 172A8/172B TL

900/60R32 181A8/181B TL

**NEW** 620/70R38 170A8/170B TL

## RECOMMENDATIONS

### VEHICLE N° 1

FRONT ..... PRESSURE ..... (bar / psi)

REAR ..... PRESSURE ..... (bar / psi)

REAR ..... PRESSURE ..... (bar / psi)

### VEHICLE N° 2

FRONT ..... PRESSURE ..... (bar / psi)

REAR ..... PRESSURE ..... (bar / psi)

REAR ..... PRESSURE ..... (bar / psi)

# MICHELIN MEGAXBIB 2



**THE GREAT VALUE TYRE  
FOR HARVESTING AND  
SPREADING**



**MICHELIN**



**MICHELIN**





Tyre specifications and pressure table. Load per tyre in kg.

Ø INCHES	DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube code	75% internal volume (litres)	Tread depth (mm)					
<b>25</b>	<b>MEGAXBIB 2</b> 1000/50 R25 172A8/166D TL	852423	1033	1654	732	4907	36.0TH		Joint R1438	892	46					
<b>Bar (Psi)</b>		1.00 (13)	1.30 (19)	1.60 (23)	1.90 (28)	2.20 (32)	2.30 (33)	2.40 (35)	2.50 (36)	2.60 (38)	2.70 (39)	2.80 (41)	2.90 (42)	3.20 (46)	3.50 (51)	3.80 (55)
10 km/h Cyc		8290	9005	9725	9960	10200	10330	10455	10585	10710						
30 km/h Cyc		6565	7480	8390	8695	9000	9115	9225	9340	9450						
10 km/h		5815	6940	7740	8385	9025	9235	9450								
30 km/h		4145	4950	5670	6070	6475	6605	6740								
40 km/h		3875	4625	5300	5675	6050	6175	6300								
65 km/h		3255	3885	4450	4765	5080	5185	5290								
<b>26</b>	<b>MEGAXBIB 2</b> 750/50R26 160A8/154D TL	236906	742	1406	629	4171	DW25B (A)			466	39					
<b>Bar (Psi)</b>		1.00 (13)	1.30 (19)	1.60 (23)	1.90 (28)	2.20 (32)	2.30 (33)	2.40 (35)	2.50 (36)	2.60 (38)	2.70 (39)	2.80 (41)	2.90 (42)	3.20 (46)	3.50 (51)	3.80 (55)
10 km/h Cyc		5230	5660	6090	6230	6375	6535	6695	6855	7015	7170	7650				
30 km/h Cyc		4200	4735	5270	5445	5625	5765	5910	6050	6190	6330	6750				
10 km/h		3750	4400	5175	5555	5935	6065	6190	6330	6470	6610	6750				
30 km/h		2675	3135	3690	3960	4235	4325	4415	4515	4615	4715	4815				
40 km/h		2500	2930	3450	3705	3955	4040	4125	4220	4310	4405	4500				
65 km/h		2100	2465	2900	3110	3325	3395	3465	3545	3620	3700	3780				
<b>32</b>	<b>MEGAXBIB 2</b> 650/75R32 172A8/172B TL	642277	637.7	1817	817	5400	DW21B (A)	DW20B (A) DW23B (A)		647	56					
<b>Bar (Psi)</b>		1.00 (13)	1.30 (19)	1.60 (23)	1.90 (28)	2.20 (32)	2.30 (33)	2.40 (35)	2.50 (36)	2.60 (38)	2.70 (39)	2.80 (41)	2.90 (42)	3.20 (46)	3.50 (51)	3.80 (55)
10 km/h Cyc		4900	5710	6520	7090	7665	7855	8045	8235	8425	8615	8805	8995	9565	10140	10710
10 km/h		4500	5220	5940	6420	6895	7055	7215	7375	7535	7695	7855	8015	8495	8970	9450
25 km/h		3630	4235	4840	5245	5645	5780	5915	6050	6185	6320	6455	6590	6990		
30 km/h		3500	4085	4670	5060	5445	5575	5705	5835	5965	6095	6225	6355	6740		
50 km/h		3280	3820	4360	4725	5090	5210	5330	5450	5575	5695	5815	5935	6300		
<b>32</b>	<b>MEGAXBIB 2</b> 800/65R32 178A8/178B TL	135425	786	1839	832	5471	DW27B (A)	DW25B (A) DH27(B)	831	871	56.2					
<b>Bar (Psi)</b>		1.00 (13)	1.30 (19)	1.60 (23)	1.90 (28)	2.20 (32)	2.30 (33)	2.40 (35)	2.50 (36)	2.60 (38)	2.70 (39)	2.80 (41)	2.90 (42)	3.20 (46)	3.50 (51)	3.80 (55)
10 km/h Cyc		5865	7080	8290	8880	9470	9665	9860	10075	10285	10500	10710	10915	11525	12140	12750
10 km/h		5175	6060	6940	7600	8260	8480	8700	8890	9075	9265	9450	9630	10170	10710	11250
25 km/h		4440	5165	5885	6300	6720	6855	6995	7160	7330	7495	7660	7825	8325		
30 km/h		4280	4975	5670	6070	6475	6605	6740	6900	7065	7225	7385	7545	8025		
50 km/h		4000	4650	5300	5675	6050	6175	6300	6450	6600	6750	6900	7050	7500		
<b>32</b>	<b>MEGAXBIB 2</b> 1050/50R32 178A8/172D TL	424273	1037	1866	828	5537	36.00VA		Joint R2052	1233	42					
<b>Bar (Psi)</b>		1.00 (13)	1.30 (19)	1.60 (23)	1.90 (28)	2.20 (32)	2.30 (33)	2.40 (35)	2.50 (36)	2.60 (38)	2.70 (39)	2.80 (41)	2.90 (42)	3.20 (46)	3.50 (51)	3.80 (55)
10 km/h Cyc		9860	10690	11520	11795	12070	12240	12410	12580	12750						
30 km/h Cyc		7725	8820	9920	10285	10650	10800	10950	11100	11250						
10 km/h		6940	8260	9450	10125	10800	11025	11250								
30 km/h		4950	5890	6740	7220	7705	7865	8025								
40 km/h		4625	5505	6300	6750	7200	7350	7500								
65 km/h		3885	4625	5290	5670	6050	6175	6300								

Tyre specifications and pressure table. Load per tyre in kg.

Ø INCHES	DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube code	75% internal volume (litres)	Tread depth (mm)					
<b>32</b>	<b>MEGAXBIB 2</b> 900/60R32 181A8/181B TL	166896	861.6	1899	848	5635	DW27B (A)	DW30B (A)	831	1033	56.6					
<b>Bar (Psi)</b>		1.00 (13)	1.30 (19)	1.60 (23)	1.90 (28)	2.20 (32)	2.30 (33)	2.40 (35)	2.50 (36)	2.60 (38)	2.70 (39)	2.80 (41)	2.90 (42)	3.20 (46)	3.50 (51)	3.80 (55)
10 km/h Cyc		6375	7695	9010	9775	10540	10795	11050	11305	11560	11815	12070	12265	12850	13440	14025
10 km/h		5625	6675	7725	8485	9245	9495	9750	9975	10200	10425	10650	10825	11340	11860	12375
25 km/h		4720	5580	6440	6980	7520	7700	7880	8060	8245	8425	8605	8745	9160		
30 km/h		4550	5380	6205	6725	7250	7420	7595	7770	7945	8120	8295	8430	8830		
50 km/h		4250	5025	5800	6290	6775	6940	7100	7265	7425	7590	7750	7875	8250		
<b>32</b>	<b>MEGAXBIB 2</b> 800/70R32 181A8/181B TL	366785	803	1927	893	5737	DW27B (A)	DW25B (A)	831	966	56.5					
<b>Bar (Psi)</b>		1.00 (13)	1.30 (19)	1.60 (23)	1.90 (28)	2.20 (32)	2.30 (33)	2.40 (35)	2.50 (36)	2.60 (38)	2.70 (39)	2.80 (41)	2.90 (42)	3.20 (46)	3.50 (51)	3.80 (55)
10 km/h Cyc		6375	7820	9265	9965	10625	10840	11050	11220	11390	11560	11730	11960	12650	13335	14025
10 km/h		5625	6675	7725	8830	9475	9615	9750	9900	10050	10200	10350	10555	11160	11770	12375
20 km/h		5335	6360	7380	7795	8210	8345	8485	8695	8900	9110	9320	9525	10150		
25 km/h		4815	5740	6660	7035	7410	7535	7660	7850	8035	8225	8410	8600	9160		
30 km/h		4680	5550	6420	6780	7140	7260	7380	7560	7745	7925	8105	8285	8830		
50 km/h		4375	5190	6000	6340	6675	6790	6900	7070	7240	7405	7575	7745	8250		
<b>34</b>	<b>MEGAXBIB 2</b> 710/75R34 178A8/178B TL	312036	697	1909	857	5671	DW23B (A)	DW21B (A) MW23B (A)	765	863	56					
<b>Bar (Psi)</b>		1.00 (13)	1.30 (19)	1.60 (23)	1.90 (28)	2.20 (32)	2.30 (33)	2.40 (35)	2.50 (36)	2.60 (38)	2.70 (39)	2.80 (41)	2.90 (42)	3.20 (46)	3.50 (51)	3.80 (55)
10 km/h Cyc		6260	6955	7650	8345	9040	9275	9505	9735	9970	10200	10430	10665	11360	12055	12750
10 km/h		5700	6295	6890	7485	8080	8275	8475	8675	8870	9070	9270	9465	10060	10655	11250
25 km/h		4650	5150	5655	6155	6655	6825	6990	7160	7325	7495	7660	7830	8330		
30 km/h		4480	4965	5450	5930	6415	6580	6740	6900	7060	7225	7385	7545	8030		
50 km/h		4190	4640	5095	5545	5995	6145	6295	6445	6595	6750	6900	7050	7500		
<b>38</b>	<b>MEGAXBIB 2</b> 620/70R38 170A8/170B TL	126128	614	1857	853	5548	DW20B (A)	DW18L	825	592	56.5					
<b>Bar (Psi)</b>		1.00 (13)	1.30 (19)	1.60 (23)	1.90 (28)	2.20 (32)	2.30 (33)	2.40 (35)	2.50 (36)	2.60 (38)	2.70 (39)	2.80 (41)	2.90 (42)	3.20 (46)	3.50 (51)	3.80 (55)
10 km/h Cyc		5010	5565	6120	6680	7235	7420	7605	7790	7975	8160	8345	8530	9090	9645	10200
10 km/h		4560	5035	5510	5985	6465	6620	6780	6940	7095	7255	7415	7575	8050	8525	9000
25 km/h		3710	4110	4515	4915	5320	5455	5585	5720	5855	5990	6125	6260	6660		
30 km/h		3580	3965	4355	4740	5130	5260	5385	5515	5645	5775	5905	6035	6420		
50 km/h		3350	3710	4075	4435	4795	4915	5035	5155	5275	5400	5520	5640	6000		

**IMPORTANT:**  
The inflation pressure is always determined according to the load per tyre, speed and work to be carried out and according to the legislation in force in the country.  
10 and 30 km/h Cyc: Work with cyclic load, field use only.  
25, 30 and 50 km/h: use on the road up to 25, 30 and 50 km/h.

