



Short journeys and long distances
on all types of roads

MICHELIN X[®] MULTI[™] Z & D

WORK WITH MORE PEACE OF
MIND

MULTI POSITIONS



- 215/75 R 17.5 126/124 M
- 225/75 R 17.5 129/127 M*
- 235/75 R 17.5 132/130 M*
- 245/70 R 17.5 136/134 M*
- 245/70 R 19.5 136/134 M*
- 265/70 R 19.5 140/138 M*
- 285/70 R 19.5 146/144 L

DRIVE AXLE



- 215/75 R 17.5 126/124 M
- 225/75 R 17.5 129/127 M
- 235/75 R 17.5 132/130 M
- 245/70 R 17.5 136/134 M
- 245/70 R 19.5 136/134 M
- 265/70 R 19.5 140/138 M
- 285/70 R 19.5 146/144 L

MICHELIN X[®] MULTI[™] Z
215/75 R 17.5

MICHELIN X[®] MULTI[™] D
215/75 R 17.5



MOBILITY MAXIMISED, PROFITABILITY IMPROVED

DRIVE FOR LONGER WITH THE SAME TYRES ALL YEAR**

* In preparation. ** Customer trials 2011/2012 - Results show + 18% lifespan compared with the MICHELIN XDE 2 tyre.



MICHELIN X[®] MULTI[™] Z & D

WORK WITH MORE PEACE OF MIND,
YOU WILL BE ABLE TO GIVE YOUR CUSTOMERS MORE SATISFACTION



«YOU GET THERE ON TIME, IN ALL WEATHER CONDITIONS...»

YOUR MOBILITY MAXIMISED

You waste less time, and you cut your costs

Dedicated drive axle pattern to ensure maximum grip in all weather conditions.



«YOU ARE A STRONG COMPANY»

YOUR PROFITABILITY IMPROVED

You minimise your vehicle's downtime

You cut your costs as much as possible by driving for longer ⁽¹⁾ with the same tyres.
 A lifespan increased by 2 to 6 months ⁽²⁾ compared with its predecessor, the MICHELIN XDE 2.



«YOU SATISFY ENVIRONMENTAL REQUIREMENTS»

YOUR BUSINESS OPTIMISED

Your company can better meet delivery requests that demand environmentally responsible standards

Your vehicles generate less road noise.

A tyre at least twice as quiet as its competitors ⁽³⁾.

(1)** Customer trials 2011/2012 - Results show + 18% lifespan compared with the MICHELIN XDE 2 tyre


(2) Assumption: if the MICHELIN XDE 2 tyre lasts 12 months, the MICHELIN X[®] MULTI D tyre lasts 18% longer, i.e. 14 months.

(3) according to competitors' labelling data .


REGROOVING TABLES

Dimensions	Theoretical regrooving depth	Regrooving width	Blade
17.5 Z	H = 2 mm	7 to 8 mm	R3
17.5 D	H = 2 mm	7 to 8 mm	R3
19.5 Z	H = 3 mm	8 to 10 mm	R4
19.5 D	H = 3 mm	8 to 10 mm	R4

Regroovable and retreadable



MICHELIN X[®] MULTI[™] Z



MICHELIN X[®] MULTI[™] D

Tread Pattern	Load index/ Speed symbol	Section width (mm)	Free diameter (mm)	Laden radius (mm)	Minimum dual spacing (mm)	Advised Rims (Inch)	S = Single T = Twin	Pressure (Bars) / Load per axle (Kg)				
								4,50	5,00	5,50	6,00	6,50
215/ 75 R 17.5 MICHELIN X [®] MULTI [™] Z & D	126/124 M	235	1076	357	245	6.00 6.75	S	2475	2700	2935	3165	3400
							T	4655	5085	5525	5960	6400

