MICHELIN X® MULTI™ HL T®

IMPROVED LONGEVITY⁽²⁾ AND MOBILITY IN ALL **CLIMATIC CONDITIONS**





LOAD CARRYING CAPACITY INCREASED TO 10T PER AXLE(5)





LOWER OPERATING COSTS:

UP TO 25% INCREASED MILEAGE POTENTIAL⁽²⁾

TRAILER AXLE





in 1030 In 1030 September 22.5 MICHELIN X® MULTITM HL T : Internal calculations based on new tyre design methods between 385/65 R 22.5 MICHELIN X® MULTITM HL T vs.





MICHELIN X® MULTI™ HL T



LOWER YOUR OPERATING COSTS

- Up to 25% increased mileage potential⁽²⁾
 - New generation of tread rubber mix that enables a reduction in original tread depth without affecting mileage performance
- Powercoil, InfiniCoil, Regenion and Duracoil technologies
- Maximise your journey with a load carrying capacity increased⁽³⁾ to 10t per axle
- Suitable for all road surfaces



SAFE TRANSPORTATION

- High level of grip throughout the tyres lifetime
 - 3PMSF and M+S marking
 - Innovative rubber compound
 - Regenion technology
 maintaining a high level of grip
 in wet and winter conditions
 throughout the entire lifetime
 of the tyre



A GREENER WAY TO TRANSPORT GOODS

- Retreading and regrooving save materials and fuel
- Tyres manufactured in compliance with ISO 14001 environmental standards



- Continuous steel wire wrapped around the tyre
- Greater stability throughout the tyre's lifetime
- Enhanced tyre endurance
- Increased load carrying capacity



POWERCOIL TECHNOLOGY

- A new generation of robust steel casing cables
- Improved resistance to oxidation
- Enhanced casing endurance



DURACOIL

- An improved tyre/ wheel interface to improve casing endurance
- High quality nylon protects the bead
- Improved stability, casing endurance and retreadability.



REGENION TECHNOLOGY

- Self-regenerating tread blocks, supported by our mold 3D metal printing techniques
- New grooves emerge over the tyres
 lifetime


TECHNICAL INFORMATION

							LONO! LAN LABELLING		
TREAD PATTERN AND DIMENSION	TYPE	LOAD/SPEED INDEX	SPECIAL MARKINGS	RADIO FREQUENCY IDENTIFICATION CHIP INTEGRATED	(C)	A.	((c1))		
385/65 R 22.5 MICHELIN X [®] MULTI™ HL T	TL	164K	M+S	RFID	С	С	([-o n) 70 dB		



REGROOVING INFORMATION

TREAD PATTERN AND DIMENSION	REGROOVING DEPTH	APPROXIMATE REGROOVE WIDTH	SUGGESTED BLADE	
385/65 R 22.5 MICHELIN X [®] MULTI™ HL T	3 mm	8 to 10mm	R3 OR R4	



ELIPODEAN LA PELLING

Retreadable with MICHELIN O REMIX

MICHELIN products are manufactured from high quality materials to high tolerances, ensuring a uniform and consistent performance. Correct application, fitting, inflation and regular inspection of the product are essential to its safe and efficient operation. Remix and the tyre designations mentioned are trademarks of Michelin. For further information about any of the products in this document, contact your local Michelin representative.



WEBSITE business.michelin.co.uk

myportal.michelingroup.com

MY PORTAL



LINKEDINMichelin For Professional Businesses



YOUTUBEMichelin Trucks & Buses Tyres Europe



BY TELEPHONE 0845 366 1535



BY EMAIL b2benquiriesuk@michelin.com

