

MICHELIN® AGRIBIB® TIRE



ALL AROUND PERFORMING RADIAL TIRE WITH A LONG SERVICE LIFE

LONG SERVICE LIFE

- Deep lugs, low slip and optimized rubber compounds help reduce wear for exceptionally long tire life
- Proven radial casing endurance
- Damage-resistant rubber fights stubble damage

OPTIMIZED TREAD DESIGN

- Super flat tread and large footprint helps reduce soil compaction
- Strong but flexible casing delivers exceptional ride and comfort

EXCEPTIONAL YEAR-ROUND TRACTION

- Strong flexible sidewalls deliver long footprint with more lugs on the soil
- 45 degree lug angle for better transfer of tractive force to the ground
- “Self cleaning hinge” between lugs keeps tread mud free for optimized pulling power
- Sharp vertical lug design provides traction even when worn; +22% more traction when 60% worn¹

(1) Analytic test on MICHELIN test tracks Ladoux Centre – Size 18.4 R38



Tractors (4x4)



Tractors (FWA)



Tractors (2WD)




Combines



Sprayers



Tow-Behind Sprayers



MICHELIN

MICHELIN® AGRIBIB® TIRE

ALL AROUND PERFORMING RADIAL WITH A LONG SERVICE LIFE

Optimized tread pattern

- Lug angle 45° for better transfer of tractive force to the ground
- Hinge in the center of the tread aids self-cleaning



Deep tread lugs

- R1W lug
- Lug design: straight profile

Damage-resistant rubber

Size	I.S.O. Index	Product Code	Equivalent Size	Max Inflation Pressure (psi)	Max Load	Section Width (in)	Overall Dia. (in)	Rolling Circum. (in)	RCI	Tread Depth (32nds)
9.5R24	112A8/109B	07126	-	35	3605	10	41.1	122.7	35	40
11.2R24	119A8/116B	92311	-	35	4365	11.3	43.1	128.7	36	47
12.4R24	119A8/116B	78449	-	26	4355	12.8	45.2	134.6	37	52
13.6R24	124A8/121B	06947	-	35	5125	14.6	47.2	141.1	38	54
14.9R24	130A8/127B	92158	-	35	6120	15.6	49.8	148.4	39	61
16.9R24	134A8/131B	97341	-	26	6790	18.1	52.4	154.9	-	69
12.4R28	126A8/123B	20895	-	35	5455	12.7	49.8	148.7	-	51
13.6R28	123A8/120B	87976	-	26	4970	14.6	51.5	153.3	39	58
14.9R28	134A8/131B	25543	-	41	7010	15.5	53.7	160.3	40	59
16.9R28	141A8/138B	13991	-	41	8520	17.9	56.5	168.4	41	64
16.9R30	137A8/134B	41545	-	26	7365	17.6	58.3	173	42	62
18.4R30	142A8/139B	42060	-	26	8500	19.8	61	181.2	-	68
18.4R34	149A8/146B	71754	-	35	10415	19.3	65.4	194.5	44	68
12.4R36	124A8/121B	03338	-	26	5125	12.5	57.5	171.8	41	42
12.4R38	131A8/128B	15336	-	35	6120	12.8	59.1	176.5	42	44
13.6R38	128A8/125B	666666	-	26	5765	14.1	61.6	185.2	43	57
380/95R38	147A8/147B	65207	-	41	10165	15.4	66.5	198.2	-	59
18.4R38	151A8/148B	63603	-	35	11080	19.4	69.7	207.4	45	68
20.8R38	159A8/156B	17548	-	41	14475	21.3	72.8	216.8	46	72
480/95R50	164A8/164B	54736	-	41	16535	20.3	85.6	255.3	-	67



TO FIND OUT MORE
 US: business.michelinman.com/agriculture
 CA: business.michelin.ca

FIND US ON FACEBOOK
 @MichelinTruck

CONTACT US BY EMAIL
 US: business.michelinman.com/contact-us
 CA: business.michelin.ca/contact

CONTACT US BY TELEPHONE
 US: 1-888-622-2306
 CA: 1-888-622-2306

Michelin North America Inc., One Parkway South, Greenville, SC 29615
 Michelin North America (Canada) Inc., 2500 Daniel Johnson Blvd., Suite 500, Laval (QC) H7T 2P6
 Copyright © 2022 Michelin North America, Inc. All rights reserved. | © 2022 MNA(C). All rights reserved.
 Specifications subject to change without notice. | An Equal Opportunity Employer | PDF Only (BWA 06/22)

