

MICHELIN® X® AGV^{EV}

RELIABILITY YOU CAN DEPEND ON



MICHELIN



OUR WEBSITE
michelinearthmover.com



TESTIMONIALS
YouTube channel



PRESSURE ADVISOR
pressureadvisor.michelinearthmover.com

AUTHORIZED DISTRIBUTOR:



18.00 R 25 X AGV EV TL 207 A5



AGV






RELIABILITY YOU CAN DEPEND ON



AGV

Michelin
TPMS
Ready



■ **ROBUSTNESS**

New casing ply developed to ensure maximal reliability on automated machines



■ **SMOOTH RUNNING**

Specifically designed smooth pattern allowing for smooth running while optimizing tire life



■ **REDUCED ROLLING RESISTANCE**

Specifically designed IND3 structure to ensure minimal rolling resistance, helping customers limiting emissions



■ **TPMS READY**

Built-in patch to ensure easy mounting of Michelin Tire Care TPMS temperature / pressure sensors

MICHELIN TECHNICAL DATA

| COMMERCIAL DESCRIPTION | CAI MSPN | Max. dist. / hour km mile | e mm inch | D mm inch | R' mm inch | RC mm inch | Tread depth mm 32rd | Dual Spacing mm inch | Cap liter gallon | Measuring Recommended Rim (2) | Other Approved Rims (2) |
|----------------------------------|---|------------------------------|--------------|--------------|---------------|---------------|------------------------|-------------------------|---------------------|-------------------------------|-------------------------|
| 18.00 R 25 X AGV EV TL 207 A5 | 677019 26910 | 14 8.7 | 506 19.9 | 1656 65.2 | 741 29 | 4984 196 | 40 50 | 612 24.1 | 534 18.9 | 13.00/2.5 | 15.00/2.5 |
| Bar | | 6 | | | | 8 | | | | 10 | |
| Psi | | 87 | | | | 116 | | | | 145 | |
| Machine - Use (kg - lb) | MECHANICAL HANDLING, CYCLIC SERVICE: All axles | | | | | | | | | | |
| STATIC | | 18380 | | | | 22280 | | | | 26250 | |
| | | 40528 | | | | 49127 | | | | 57881 | |
| <= 10 KM/H | | 15930 | | | | 19180 | | | | 22750 | |
| <= 6 MP/H | | 35126 | | | | 42292 | | | | 50164 | |
| 25 KM/H | | 12250 | | | | 14750 | | | | 17500 | |
| 15 MPH | | 27011 | | | | 32524 | | | | 38588 | |
| Machine - Use (kg - lb) | COUNTERBALANCED LIFT TRUCK: Load wheel | | | | | | | | | | |
| <= 10 KM/H | | 15930 | | | | 19180 | | | | 22750 | |
| <= 6 MP/H | | 35126 | | | | 42292 | | | | 50164 | |
| 25 KM/H | | 15930 | | | | 19180 | | | | 22750 | |
| 15 MPH | | 35126 | | | | 42292 | | | | 50164 | |

(2) More informations in the Michelin Databook 2019.