

# MICHELIN OMNIBIB



## WIDE & FLAT TREAD

Greater stability

## WIDE LUGS

Long Service Life



## BORROWING SURFACE

- Up to 16%\* of surface additional impression
- Optimized ground pressure

## FLEXIBLE, ROBUST CASING

### Available sizes

747196	280/70 R16 112D TL	375821	480/70 R24 138D TL	939411	520/70 R34 148D TL
263806	280/70 R20 116D TL	118587	380/70 R28 127D TL	936570	480/70 R38 145D TL
415039	320/70 R24 116D TL	532215	420/70 R28 133D TL	833744	520/70 R38 150D TL
198698	360/70 R24 122D TL	570026	480/70 R28 140D TL	001240	580/70 R38 155D TL
085816	380/70 R24 125D TL	599351	480/70 R30 141D TL	989457	620/70 R42 160D TL
829095	420/70 R24 130D TL	280033	480/70 R34 143D TL		

### Michelin recommendations

#### Machine n° 1

FRONT ..... PRESSURE ..... (bars / psi)  
 REAR ..... PRESSURE ..... (bars / psi)

#### Machine n° 2

FRONT ..... PRESSURE ..... (bars / psi)  
 REAR ..... PRESSURE ..... (bars / psi)

**GREAT VERSATILITY  
TO OPTIMISE  
YOUR OPERATIONS**



**MICHELIN**



**MICHELIN**

[agro.michelin.com](http://agro.michelin.com)

[www.youtube.com/user/AgMichelin](https://www.youtube.com/user/AgMichelin)

[agro.michelin.com](http://agro.michelin.com)

[www.youtube.com/user/AgMichelin](https://www.youtube.com/user/AgMichelin)







Tire specifications and pressure table (bar & psi). Load per tire in kg

Ø INCHES	DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)					
34	OMNIBIB 480/70 R34 143D TL	280033	497	1593	713	4728	DW15L	DW14L, DW16L, W14L, W15L, W16L	704	345	50					
<b>Bar (Psi)</b>		<b>0.40 (6)</b>	<b>0.50 (7)</b>	<b>0.60 (9)</b>	<b>0.80 (12)</b>	<b>1.00 (15)</b>	<b>1.20 (17)</b>	<b>1.40 (20)</b>	<b>1.60 (23)</b>	<b>1.80 (26)</b>	<b>1.90 (28)</b>	<b>2.00 (29)</b>	<b>2.20 (32)</b>	<b>2.40 (35)</b>	<b>2.70 (39)</b>	<b>2.80 (41)</b>
10 km/h		1880	2020	2155	2435	2710	2985	3260	3540	3815	3950	4090				
30 km/h		1440	1580	1720	2005	2285	2565	2850	3130							
40 km/h				1640	1910	2175	2445	2710	2980							
40 km/h Dual		1205	1325	1445	1680	1915	2155	2390	2625							
50 km/h				1580	1835	2090	2350	2605	2860							
65 km/h				1500	1745	1990	2235	2480	2725							
34	OMNIBIB 520/70 R34 148D TL	939411	535	1651	730	4887	DW16L	DW15L, DW18L, W15L, W16L, W18L	823	421.5	53					
<b>Bar (Psi)</b>		<b>0.40 (6)</b>	<b>0.50 (7)</b>	<b>0.60 (9)</b>	<b>0.80 (12)</b>	<b>1.00 (15)</b>	<b>1.20 (17)</b>	<b>1.40 (20)</b>	<b>1.60 (23)</b>	<b>1.80 (26)</b>	<b>1.90 (28)</b>	<b>2.00 (29)</b>	<b>2.20 (32)</b>	<b>2.40 (35)</b>	<b>2.70 (39)</b>	<b>2.80 (41)</b>
10 km/h		2100	2265	2430	2760	3085	3415	3745	4075	4400	4565	4730				
30 km/h		1610	1780	1945	2280	2615	2950	3285	3620							
40 km/h				1860	2180	2495	2815	3130	3450							
40 km/h Dual		1350	1495	1640	1920	2200	2475	2755	3035							
50 km/h				1790	2095	2400	2700	3005	3310							
65 km/h				1700	1990	2280	2570	2860	3150							
38	OMNIBIB 480/70 R38 145D TL	936570	498	1694	759	5030	DW15L	DW14L, DW16L, W14L, W15L, W16L	786	377.25	52					
<b>Bar (Psi)</b>		<b>0.40 (6)</b>	<b>0.50 (7)</b>	<b>0.60 (9)</b>	<b>0.80 (12)</b>	<b>1.00 (15)</b>	<b>1.20 (17)</b>	<b>1.40 (20)</b>	<b>1.60 (23)</b>	<b>1.80 (26)</b>	<b>1.90 (28)</b>	<b>2.00 (29)</b>	<b>2.20 (32)</b>	<b>2.40 (35)</b>	<b>2.70 (39)</b>	<b>2.80 (41)</b>
10 km/h		1980	2130	2275	2575	2870	3165	3460	3760	4055	4200	4350				
30 km/h		1520	1670	1825	2125	2430	2735	3035	3340							
40 km/h				1750	2035	2320	2610	2895	3180							
40 km/h Dual		1270	1405	1540	1790	2040	2295	2545	2795							
50 km/h				1680	1955	2230	2500	2775	3050							
65 km/h				1600	1860	2120	2380	2640	2900							
38	OMNIBIB 520/70 R38 150D TL	833744	539	1766	782	5229	DW16L	DW15L, DW18L, W15L, W16L, W18L	824	463.5	53					
<b>Bar (Psi)</b>		<b>0.40 (6)</b>	<b>0.50 (7)</b>	<b>0.60 (9)</b>	<b>0.80 (12)</b>	<b>1.00 (15)</b>	<b>1.20 (17)</b>	<b>1.40 (20)</b>	<b>1.60 (23)</b>	<b>1.80 (26)</b>	<b>1.90 (28)</b>	<b>2.00 (29)</b>	<b>2.20 (32)</b>	<b>2.40 (35)</b>	<b>2.70 (39)</b>	<b>2.80 (41)</b>
10 km/h		2250	2425	2600	2945	3295	3640	3990	4335	4685	4855	5030				
30 km/h		1730	1905	2085	2435	2790	3145	3495	3850							
40 km/h				1970	2310	2650	2990	3330	3670							
40 km/h Dual		1445	1590	1735	2035	2335	2630	2930	3230							
50 km/h				1890	2215	2540	2870	3195	3520							
65 km/h				1800	2110	2420	2730	3040	3350							
38	OMNIBIB 580/70 R38 155D TL	001240	601	1836	815	5440	DW18L	W18L	825	589.5	56					
<b>Bar (Psi)</b>		<b>0.40 (6)</b>	<b>0.50 (7)</b>	<b>0.60 (9)</b>	<b>0.80 (12)</b>	<b>1.00 (15)</b>	<b>1.20 (17)</b>	<b>1.40 (20)</b>	<b>1.60 (23)</b>	<b>1.80 (26)</b>	<b>1.90 (28)</b>	<b>2.00 (29)</b>	<b>2.20 (32)</b>	<b>2.40 (35)</b>	<b>2.70 (39)</b>	<b>2.80 (41)</b>
10 km/h		2630	2830	3030	3425	3825	4220	4620	5015	5415	5610	5810				
30 km/h		2010	2215	2420	2825	3235	3645	4050	4460							
40 km/h				2320	2705	3090	3470	3855	4240							
40 km/h Dual		1685	1865	2045	2385	2720	3060	3395	3735							
50 km/h				2230	2600	2965	3335	3700	4070							
65 km/h				2120	2470	2820	3175	3525	3875							
42	OMNIBIB 620/70 R42 160D TL	989457	639	1953	863	5781	DW20B (A)	DW18L	802	657.75	58					
<b>Bar (Psi)</b>		<b>0.40 (6)</b>	<b>0.50 (7)</b>	<b>0.60 (9)</b>	<b>0.80 (12)</b>	<b>1.00 (15)</b>	<b>1.20 (17)</b>	<b>1.40 (20)</b>	<b>1.60 (23)</b>	<b>1.80 (26)</b>	<b>1.90 (28)</b>	<b>2.00 (29)</b>	<b>2.20 (32)</b>	<b>2.40 (35)</b>	<b>2.70 (39)</b>	<b>2.80 (41)</b>
10 km/h		1390	1495	1605	1815	2030	2240	2455	2665	2880	2985	3090				
30 km/h		1060	1170	1280	1495	1715	1935	2150	2370							
40 km/h				1230	1435	1640	1850	2055	2260							
40 km/h Dual		890	985	1080	1260	1440	1625	1805	1985							
50 km/h				1180	1375	1570	1770	1965	2160							
65 km/h				1120	1310	1495	1685	1870	2060							

## MICHELIN OMNIBIB, SAVINGS IN TIME AND FUEL



**UP TO 14%**  
MORE LOAD THAN A STANDARD TIRE\*

### • SAVINGS IN TIME AND FUEL

- Excellent self-cleaning capacity
- Better grip

### • MORE LONGEVITY

### • COMFORT ON THE ROAD AND IN THE FIELD

- Pressure generally 0.2 bar lower than the other 70 series tyres on the market
- Flexible casing
- Performance guaranteed up to 65 km/h. - D rating, where authorised by the country legislation

### • HIGH LOAD CAPACITY FOR WORKING WITH FRONT LOADERS

- Up to 14%\* more load than a standard tyre
- Robust tread lugs

### PRODUCTIVITY



up to 65 km / h

### SOIL PROTECTION



Performing in fields  
and on the road

### COMFORT ON ROADS



Excellent performance

**MICHELIN OMNIBIB, STRONG TRACTION CAPACITY  
FOR SAVING TIME AND MONEY**

\* According to tire sizes, 28 psi compared with the equivalent size in the MICHELIN AGRIBIB range