

MICHELIN SPRAYBIB



The **very low-pressure**
solution for **self-propelled**
sprayers



agro.michelin.com



[youtube.com/user/AgMichelin](https://www.youtube.com/user/AgMichelin)





Tire specifications and pressure table. Load per tire in kg.

DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)					
34 VF 420/90 R34 CFO 174D/170E TL	343695	427	1603	720	4762	DW15L	DW14L - W14L	-	309.75	40					
Bar	0.80	1.10	1.40	1.70	2.00	2.30	2.60	2.90	3.20	3.50	3.80	4.10	4.40		
Psi	12	16	20	25	29	33	38	42	46	51	55	59	64		
15 km/h Cyc	2285	2885	3485	4085	4685	5130	5470	5810	6115	6425	6730	7055	7505		
30 km/h Cyc	2285	2885	3485	4085	4685	5130	5470	5810	6115	6425	6730	7055	7505		
10 km/h	2215	2800	3380	3965	4545	4970	5300	5630	5930	6225	6525	6840	7275		
20 km/h	2095	2645	3195	3745	4295	4700	5015	5325	5605	5890	6170	6465	6875		
50 km/h	2015	2545	3075	3600	4130	4520	4820	5120	5390	5660	5930	6215	6700		
65 km/h	2015	2545	3075	3600	4130	4520	4820	5120	5390	5660	5930	6215	6700		
70 km/h	1830	2315	2795	3280	3760	4110	4385	4660	4905	5150	5395	5655	6000		
38 VF 380/80 R38 167D TL	352109	382	1577	726	4712	DW13	DW12	795	231	38					
Bar	0.80	1.10	1.40	1.70	2.00	2.30	2.60	2.90	3.20	3.50	3.80	4.10	4.40		
Psi	26	29	32	35	38	41	44	46	49	52	55	58	61		
65 km/h	3100	3375	3650	3750	3940	4125	4315	4500	4625	4750	4875	5000	5225		
38 VF 380/80R38 CFO 167D/163E TL	523910	380	1586	722	4727	DW13	DW12	795	230	38					
Bar	0.8	0.9	1	1.1	1.4	1.7	2	2.3	2.6	2.9	3.2	3.5	3.8	4.1	4.4
Psi	12	13	15	16	20	25	29	33	38	42	46	51	55	59	64
15 km/h Cyc	2095	2240	2390	2535	2975	3415	3850	4205	4440	4705	4965	5230	5490		
30 km/h Cyc	2095	2240	2390	2535	2975	3415	3850	4205	4440	4705	4965	5230	5490		
50 km/h	1845	1975	2105	2235	2620	3010	3395	3705	3910	4145	4375	4610	4840		
65 km/h	1845	1975	2105	2235	2620	3010	3395	3705	3910	4145	4375	4610	4840		
70 km/h	1680	1800	1915	2035	2385	2740	3090	3375	3560	3770	3985	4195	4405		
42 VF 320/90 R42 163D TL	920383	332	1635	758	4890	DW11	DW10	-	195	36					
Bar	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80	4.00	4.20		
Psi	26	29	32	35	38	41	44	46	49	52	55	58	61		
65 km/h	2815	3025	3250	3350	3500	3650	3825	4000	4125	4250	4405	4565	4720		
42 VF 320/90R42 CFO 163D/159E TL	028790	325	1640	761	4908	DW10	DW11	-	196	36					
Bar	0.8	0.9	1	1.1	1.4	1.7	2	2.3	2.6	2.9	3.2	3.5	3.8	4.1	4.4
Psi	12	13	15	16	20	25	29	33	38	42	46	51	55	59	64
15 km/h Cyc	1810	1945	2085	2220	2630	3040	3450	3780	3990	4225	4460	4695	4935		
30 km/h Cyc	1810	1945	2085	2220	2630	3040	3450	3780	3990	4225	4460	4695	4935		
50 km/h	1595	1715	1835	1955	2315	2680	3040	3330	3515	3720	3930	4140	4345		
65 km/h	1595	1715	1835	1955	2315	2680	3040	3330	3515	3720	3930	4140	4345		
70 km/h	1450	1560	1670	1780	2110	2435	2765	3030	3195	3385	3580	3770	3960		
42 VF 480/80 R42 176D TL	929553	489	1838	833	5471	DW16A	DD16 - W16A	801	420	38					
Bar	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80	4.00	4.20		
Psi	26	29	32	35	38	41	44	46	49	52	55	58	61		
65 km/h	5000	5200	5400	5600	5875	6150	6425	6700	6900	7100	-	-	-		

Important:
The inflation pressure must always be appropriate for the load per tire, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (January 2022). Technical data is subject to change without prior notice.
Add 0.4 bar for use on slopes of more than 20% | Add 0.4 bar for intense road use exceeding 50% if time on road
15 km/h Cyc: work with cyclic loads at 15 km/h | 30 km/h Cyc: work with cyclic loads at 30 km/h

Tire specifications and pressure table. Load per tire in kg.

DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)					
42 VF 480/80R42 CFO 176D/172E TL	579330	482	1843	834	5484	DW16A	DD16 W16	801	420	38					
Bar	0.8	1	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6
Psi	12	15	17	20	23	26	29	32	35	38	41	44	46	49	52
15 km/h Cyc	3005	3580	4120	4660	5195	5730	5940	6155	6365	6665	6960	7260	7515		
30 km/h Cyc	3005	3580	4120	4660	5195	5730	5940	6155	6365	6665	6960	7260	7515		
50 km/h	2650	3155	3630	4105	4580	5050	5235	5425	5610	5870	6135	6395	6630		
65 km/h	2650	3155	3630	4105	4580	5050	5235	5425	5610	5870	6135	6395	6630		
70 km/h	2410	2870	3305	3735	4165	4595	4765	4935	5105	5345	5580	5820	5980		
46 VF 320/90 R46 165D TL	684579	318	1736	810	5350	DW10	-	835	210.75	37					
Bar	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80	4.00	4.20		
Psi	26	29	32	35	38	41	44	46	49	52	55	58	61		
65 km/h	3000	3230	3450	3550	3715	3875	4000	4125	4315	4500	4665	4825	4990		
46 VF 320/90R46 CFO 165D/161E TL	443039	311	1741	807	5209	DW10	-	835	211	37					
Bar	0.8	0.9	1	1.1	1.4	1.7	2	2.3	2.6	2.9	3.2	3.5	3.8	4.1	4.4
Psi	12	13	15	16	20	25	29	33	38	42	46	51	55	59	64
15 km/h Cyc	1945	2085	2225	2365	2785	3210	3630	3965	4195	4455	4715	4980	5250		
30 km/h Cyc	1945	2085	2225	2365	2785	3210	3630	3965	4195	4455	4715	4980	5250		
50 km/h	1715	1840	1960	2085	2455	2825	3200	3495	3695	3925	4155	4390	4635		
65 km/h	1715	1840	1960	2085	2455	2825	3200	3495	3695	3925	4155	4390	4635		
70 km/h	1560	1675	1785	1900	2235	2575	2910	3180	3365	3575	3780	3990	4200		
46 VF 380/90 R46 CFO 173D/169E TL	007760	385	1843	847	5504	DW13A	DW12A, W12, W12A, W13, W13A	835	308.25	38					
Bar	0.80	1.10	1.40	1.70	2.00	2.30	2.60	2.90	3.20	3.50	3.80	4.10	4.40		
Psi	12	16	20	25	29	33	38	42	46	51	55	59	64		
15 km/h Cyc	2250	2885	3475	4060	4610	5125	5425	5765	6100	6440	6725	7025	7400		
30 km/h Cyc	2250	2885	3475	4060	4610	5125	5425	5765	6100	6440	6725	7025	7400		
10 km/h	2175	2795	3375	3935	4465	4950	5250	5615	5950	6250	6500	6775	7150		
20 km/h	2050	2640	3200	3720	4220	4675	4975	5300	5600	5900	6150	6410	6750		
50 km/h	1975	2540	3075	3575	4060	4500	4815	5115	5450	5715	5900	6125	6500		
65 km/h	1975	2540	3075	3575	4060	4500	4815	5115	5450	5715	5900	6125	6500		
70 km/h	1800	2310	2800	3255	3695	4100	4350	4640	4900	5165	5375	5575	5800		
46 VF 480/80 R46 177D TL	159186	485	1943	884	5788	DW16A (L)	DW15L, DW16B, W16A	834	449.25	38					
Bar	0.8	0.9	1	1.1	1.4	1.7	2	2.3	2.6	2.9	3.2	3.5	3.8	4.1	4.4
Psi	12	13	15	16	20	25	29	33	38	42	46	51	55	59	64
65 km/h					5465	5715	6075	6490	6900	7200					

Important:
The inflation pressure must always be appropriate for the load per tire, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (January 2022). Technical data is subject to change without prior notice.
Add 0.4 bar for use on slopes of more than 20% | Add 0.4 bar for intense road use exceeding 50% if time on road
15 km/h Cyc: work with cyclic loads at 15 km/h | 30 km/h Cyc: work with cyclic loads at 30 km/h



Tire specifications and pressure table. Load per tire in kg.

DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)					
46 VF 480/80R46 CFO 177D/173E TL	325824	485	1943	884	5788	DW16A(L)	DW15LD W16B W16A	834	449	38					
Bar	0.8	1	1.4	1.8	1.9	2	2.1	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6
PSI	12	15	20	26	28	29	30	32	35	38	41	44	46	49	52
15 km/h Cyc	3225	3830	4960	5995	6105	6215	6330	6440	6660	6970	7280	7590	7820	8055	8285
30 km/h Cyc	3225	3830	4960	5995	6105	6215	6330	6440	6660	6970	7280	7590	7820	8055	8285
50 km/h	2845	3375	4370	5280	5380	5475	5575	5670	5865	6140	6415	6690	6895	7095	7300
65 km/h	2845	3375	4370	5280	5380	5475	5575	5670	5865	6140	6415	6690	6895	7095	7300
70 km/h	2585	3070	3975	4805	4895	4985	5075	5160	5340	5590	5835	6085	6225	6360	6500
46 VF 710/60 R46 CFO 186D/182E TL	574801	722	2002	900	5948	DW25B (A)	-	-	757.5	41					
Bar	0.80	1.10	1.40	1.70	2.00	2.30	2.60	2.90	3.20	3.50	3.80	4.10	4.40		
Psi	12	16	20	25	29	33	38	42	46	51	55	59	64		
15 km/h Cyc	4840	5875	6915	7795	8360	8925	9535	10160	10785						
30 km/h Cyc	4840	5875	6915	7795	8360	8925	9535	10160	10785						
10 km/h	4690	5695	6705	7560	8105	8655	9240	9845	10450						
20 km/h	4435	5385	6335	7145	7665	8180	8735	9310	9880						
50 km/h	4265	5180	6095	6870	7370	7865	8400	8950	9500						
65 km/h	4265	5180	6095	6870	7370	7865	8400	8950	9500						
70 km/h	3880	4715	5545	6250	6705	7160	7610	8055	8500						
50 VF 320/90 R50 166D TL	946508	320	1850	866	5682	DW11	DW10 - W10 - W11	816	208	36					
Bar	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80	4.00	4.20	4.40	
Psi	26	29	32	35	38	41	44	46	49	52	55	58	61	64	
65 km/h	3040	3300	3650	3750	3875	4000	4190	4375	4500	4625	4795	4965	5130	5300	
50 VF 320/90R50 CFO 166D/162E TL	840040	323	1849	865	5545	DW11	DW10 W10 W11	816	226	37					
Bar	0.8	0.9	1	1.1	1.4	1.7	2	2.3	2.6	2.9	3.2	3.5	3.8	4.1	4.4
PSI	12	13	15	16	20	25	29	33	38	42	46	51	55	59	64
15 km/h Cyc	2095	2240	2380	2525	2950	3375	3805	4175	4435	4700	4970	5220	5495	5785	6075
30 km/h Cyc	2095	2240	2380	2525	2950	3375	3805	4175	4435	4700	4970	5220	5495	5785	6075
50 km/h	1845	1970	2095	2220	2600	2975	3355	3680	3910	4140	4380	4600	4830	5065	5300
65 km/h	1845	1970	2095	2220	2600	2975	3355	3680	3910	4140	4380	4600	4830	5065	5300
70 km/h	1680	1795	1910	2025	2365	2710	3050	3350	3555	3770	3985	4185	4375	4565	4750
50 VF 380/90 R50 175D TL	722276	384	1951	903	5836	DW13B	DW12A - W12A - W12B	-	329	38					
Bar	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80	4.00	4.20	4.40	
Psi	26	29	32	35	38	41	44	46	49	52	55	58	61	64	
65 km/h	3950	4300	4625	4750	4950	5150	5375	5600	5800	6000	6150	6300	6600	6900	
50 VF 380/90R50 CFO 175D/171E TL	340728	384	1951	901	5834	DW13B	DW12A - W12A W12B - W13A - W13B	-	329	38					
Bar	0.8	1	1.4	1.8	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.4
PSI	12	15	20	26	32	35	38	41	44	46	49	52	55	58	64
15 km/h Cyc	2405	2860	3710	4505	5260	5410	5655	5905	6150	6395	6635	6875	7110	7350	7830
30 km/h Cyc	2405	2860	3710	4505	5260	5410	5655	5905	6150	6395	6635	6875	7110	7350	7830
50 km/h	2120	2520	3265	3970	4635	4765	4985	5200	5420	5635	5845	6055	6270	6480	6900
65 km/h	2120	2520	3265	3970	4635	4765	4985	5200	5420	5635	5845	6055	6270	6480	6900
70 km/h	1925	2290	2975	3610	4215	4340	4540	4735	4935	5130	5300	5470	5640	5810	6150

Tire specifications and pressure table. Load per tire in kg.

DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)					
50 VF 420/95 R50 177D TL	085405	423	2052	937	6118	DW14B (A)	DW13B (A) - W13B(A)	-	440	38					
Bar	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80	4.00	4.20	4.40	
Psi	26	29	32	35	38	41	44	46	49	52	55	58	61	64	
65 km/h	5150	5365	5585	5800	6075	6350	6625	6900	7100	7300	-	-	-	-	
50 VF 420/95R50 CFO 179D/175E TL	358639	418	2059	941	6140	DW14B(A)	DW13B(A) W13B(A) W14B(A)	-	439	38					
Bar	0.8	1	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.6	4
PSI	12	15	17	20	23	26	29	32	35	38	41	44	46	52	58
15 km/h Cyc	3065	3660	4225	4785	5345	5905	6125	6340	6560	6865	7175	7480	7750	8285	8715
30 km/h Cyc	3065	3660	4225	4785	5345	5905	6125	6340	6560	6865	7175	7480	7750	8285	8715
50 km/h	2700	3225	3720	4215	4710	5200	5395	5585	5780	6050	6320	6590	6825	7300	7750
65 km/h	2700	3225	3720	4215	4710	5200	5395	5585	5780	6050	6320	6590	6820	7280	7750
70 km/h	2460	2935	3385	3835	4285	4735	4910	5085	5260	5505	5750	5995	6205	6625	6900
50 VF 480/80 R50 179D TL	431251	485	2045	935	6101	DW16A(L)	DW15B(A) - DW15L - DW16B	-	480	38					
Bar	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80	4.00	4.20	4.40	
Psi	26	29	32	35	38	41	44	46	49	52	55	58	61	64	
65 km/h	5450	5685	5915	6150	6440	6725	7015	7300	7525	7750	-	-	-	-	
50 VF 480/80R50 CFO 179D/175E TL	162735	485	2045	934	6098	DW16A(L)	DW15B(A) W15B(A) DW15L DW16B - W16B	-	479	38					
Bar	0.8	1	1.4	1.8	1.9	2	2.1	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6
PSI	12	15	20	26	28	29	30	32	35	38	41	44	46	49	52
15 km/h Cyc	3325	3955	5140	6255	6370	6485	6605	6720	6950	7275	7595	7920	8210	8505	8795
30 km/h Cyc	3325	3955	5140	6255	6370	6485	6605	6720	6950	7275	7595	7920	8210	8505	8795
50 km/h	2930	3485	4530	5510	5610	5715	5815	5915	6120	6405	6695	6980	7235	7495	7750
65 km/h	2930	3485	4530	5510	5610	5715	5815	5915	6120	6405	6695	6980	7235	7495	7750
70 km/h	2665	3170	4120	5015	5110	5200	5295	5385	5570	5830	6090	6350	6535	6715	6900
54 VF 320/105R54 172D TL	624140	339	2028	938	6066	DW11	DW11	816	289	38					
Bar	0.8	0.9	1	1.1	1.4	1.7	2	2.3	2.6	2.9	3.2	3.5	3.8	4.1	4.4
PSI	12	13	15	16	20	25	29	33	38	42	46	51	55	59	64
65 km/h	2025	2200	2375	2550	3050	3525	3975	4315	4565	4850	5150	5375	5625	5925	6300
54 VF 320/90 R54 168D TL	044008	323	1950	914	5851	DW11	DW10 - W10 - W11	816	240	36					
Bar	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80	4.00	4.20	4.40	
Psi	26	29	32	35	38	41	44	46	49	52	55	58	61	64	
65 km/h	3225	3500	3750	3875	4065	4250	4440	4625	4750	4875	5055	5240	5420	5600	

Important:

The inflation pressure must always be appropriate for the load per tire, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (January 2022). Technical data is subject to change without prior notice.

Add 0.4 bar for use on slopes of more than 20% | Add 0.4 bar for intense road use exceeding 50% if time on road
15 km/h Cyc: work with cyclic loads at 15 km/h | 30 km/h Cyc: work with cyclic loads at 30 km/h



agro.michelin.com



youtube.com/user/AgMichelin



Tire specifications and pressure table. Load per tire in kg.

DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Recommended rim	Acceptable rims	Tube (code)	75% internal volume (litres)	Tread depth (mm)					
54 VF 320/90R54 CFO 168D/164E TL	666915	322	1955	910	5855	DW11	DW10 W10 W11	816	240	36					
Bar	0.8	0.9	1	1.1	1.4	1.7	2	2.3	2.6	2.9	3.2	3.5	3.8	4.1	4.4
PSI	12	13	15	16	20	25	29	33	38	42	46	51	55	59	64
15 km/h Cyc	2075	2230	2390	2545	3015	3485	3950	4325	4575	4860	5150	5435	5730	6035	6335
30 km/h Cyc	2075	2230	2390	2545	3015	3485	3950	4325	4575	4860	5150	5435	5730	6035	6335
50 km/h	1830	1970	2105	2245	2655	3070	3485	3815	4035	4285	4535	4785	5055	5325	5600
65 km/h	1830	1970	2105	2245	2655	3070	3485	3815	4035	4285	4535	4785	5055	5325	5600
70 km/h	1665	1790	1915	2040	2415	2795	3170	3470	3670	3900	4125	4355	4575	4785	5000
54 VF 380/90 R54 176D TL	816598	384	2049	950	6131	DW13A	W12A	-	350	37					
Bar	1.80	2.00	2.20	2.40	2.60	2.80	3.00	3.20	3.40	3.60	3.80	4.00	4.20	4.40	
Psi	26	29	32	35	38	41	44	46	49	52	55	58	61	64	
65 km/h	4175	4525	4875	5000	5190	5375	5565	5750	5940	6125	6315	6500	6800	7100	
54 VF 380/90R54 CFO 176D/172E TL	019737	384	2049	948	6129	DW13A	W12A	-	349	37					
Bar	0.8	1	1.4	1.8	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.4
PSI	12	15	20	26	32	35	38	41	44	46	49	52	55	58	64
15 km/h Cyc	2570	3045	3930	4750	5480	5635	5895	6150	6410	6665	6900	7130	7360	7595	8060
30 km/h Cyc	2570	3045	3930	4750	5480	5635	5895	6150	6410	6665	6900	7130	7360	7595	8060
50 km/h	2265	2680	3460	4185	4830	4965	5190	5420	5645	5870	6075	6280	6485	6690	7100
65 km/h	2265	2680	3460	4185	4830	4965	5190	5420	5645	5870	6075	6280	6485	6690	7100
70 km/h	2060	2440	3150	3810	4395	4520	4725	4930	5135	5340	5500	5660	5820	5980	6300



Productivity

- ✓ Robustness of tread lugs to reduce stubble
- ✓ **Up to +20%* more traction**
*Comparison carried out in Pagnant - France - in November 2021, between MICHELIN SPRAYBIB range and the new generation range of MICHELIN SPRAYBIB CFO, with equipment fitted in VF 380/90 R46.
- ✓ **E speed index rating (70 km/h)**
- ✓ **Up to +14%** load capacity in the field due to the reinforced casing**
**Comparison with a non-CFO tire.



Soil protection

- ✓ Wide and shallow tread lugs
- ✓ **+20%* footprint compared to a standard tire**
*Comparison carried out in Artonne - France in January 2022 between MICHELIN SPRAYBIB CFO range and a competitor standard equipment fitted with 380/90 R 46.
- ✓ **Reduced pressure up to -0.7 bar****
**Comparison with a non-CFO tire.



Comfort

- ✓ Low pressure with Very high Flexion (VF)
- ✓ **MICHELIN ULTRAFLEX Technology*** tire casing
*MUT allows contact patch enlargement and sidewall deflation.

NEW SPRAYBIB CFO: Allows the pressure range to start now at 0.8 bar instead of 1.8 bar.

Available sizes

343695 VF 420/90 R34 CFO 174D/170E TL	684579 VF 320/90 R46 165D TL	840040 VF 320/90 R50 CFO 166D/162E TL	044008 VF 320/90 R54 168D TL
352109 VF 380/80 R38 167D TL	443039 VF 320/90 R46 CFO 165D/161E TL	722276 VF 380/90 R50 175D TL	666915 VF 320/90 R54 CFO 168D/164E TL
523910 VF 380/80 R38 CFO 167D/163E TL	007760 VF 380/90 R46 CFO 173D/169E TL	340728 VF 380/90 R50 CFO 175D/171E TL	624140 VF 320/105 R54 172D TL
920383 VF 320/90 R42 163D TL	159186 VF 480/80 R46 177D TL	085405 VF 420/95 R50 177D TL	816598 VF 380/90 R54 176D TL
028790 VF 320/90 R42 CFO 163D/159E TL	325824 VF 480/80 R46 CFO 177D/173E TL	358639 VF 420/95 R50 CFO 179D/175E TL	019737 VF 380/90R54 CFO 176D/172E TL
929553 VF 480/80 R42 176D TL	578401 VF 710/60 R46 CFO 186D/182E TL	431251 VF 480/80 R50 179D TL	
579330 VF 480/80 R42 CFO 176D/172E TL	946508 VF 320/90 R50 166D TL	162735 VF 480/80 R50 CFO 179D/175E TL	

MICHELIN recommendations

Machine n° 1

FRONT PRESSURE (bars / psi)
REAR PRESSURE (bars / psi)

Machine n° 2

FRONT PRESSURE (bars / psi)
REAR PRESSURE (bars / psi)



agro.michelin.com



youtube.com/user/AgMichelin

