

MICHELIN®

XADN +®

**TAILORED FOR YOUR BOTTOM LINE
IN ANYWORKING CONDITIONS**



20.5 R 25 XADN E3T TL 177B

23.5 R 25 XADN + E3 TL ** 185B

26.5 R 25 XADN + E3 TL ** 193B

29.5 R 25 XADN + E3 TL ** 200B



ARTICULATED
DUMP TRUCKS



SCRAPER



MICHELIN

TAILORED FOR YOUR BOTTOM LINE

IN ANY WORKING CONDITIONS



ARTICULATED DUMP TRUCKS

SCRAPER



EXCELLENT PRODUCTIVITY POTENTIAL

Michelin's E3 (including wide base) TKPH is up to 34% higher¹ than the average TKPH of the premium competitors



Multi-block tread pattern with shoulder made of alternating and multi-edged blocks



GOOD LONG-TERM INVESTMENT

Up to 90% of Michelin tires are retreadable due to the casing quality offered by MICHELIN C² Technology³

Summit designed to resist stresses when cornering



EXCELLENT TRACTION

Maneuverability on soft or muddy soil with proven flotation and traction

EXCELLENT TREAD WEAR RESISTANCE THANKS TO NEW RUBBER COMPOUND²



Excellent lateral grip on soft terrain due to self-cleaning tread pattern

¹ Compared to the average TKPH of Michelin premium competitors, published in the following databook: Goodyear OTR tire engineering data (02/07/2014) and Goodyear OTR website (<http://www.goodyearotr.com>, 11/2015) and Bridgestone OTR tires databook (2015).

² Compared to the MICHELIN® X-Super Terrain tire.

³ Measurements taken at retreader facilities in Europe between 2012 and 2014.

AUTHORIZED DISTRIBUTOR :





MICHELIN TECHNICAL DATA

COMMERCIAL DESCRIPTION	CAI MPSTN	Max. dist / hour km mile	TKPH (1) TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm inch	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (1)	Other Approved Rims (1)
XADN E3T ** 177B 20.5 R 25 Tubeless	123407	28	164	528	1490	667	4485	36		474	17.00/2.0	
	23290	17.4	112	20.8	58.7	26.3	176.6	45.4		125.2		

Bar	2	2.5	3	3.5	4	4.25	4.5
Psi	29	36	44	51	58	62	65

Machine - Use (kg - lbs) ARTICULATED DUMP TRUCKS

STANDARD	4750	5250	5750	6250	6800	7050	7300
	10474	11576	12679	13781	14994	15545	16097

COMMERCIAL DESCRIPTION	CAI MPSTN	Max. dist / hour km mile	TKPH (1) TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm inch	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (1)	Other Approved Rims (1)
XADN+ E3 ** 185B 23.5 R 25 Tubeless	295773	28	207	602	1598	721	4824	38		702	19.50/2.5	
	31373	17.4	142	23.7	62.9	28.4	189.9	47.9		185.5		

Bar	2	2.5	3	3.5	3.75	4	4.5	5
Psi	29	36	44	51	54	58	65	73

Machine - Use (kg - lbs) ARTICULATED DUMP TRUCKS

STANDARD	4930	5650	6380	7100	7450	7800	8550	9250
	10871	12458	14068	15656	16427	17199	18853	20396

COMMERCIAL DESCRIPTION	CAI MPSTN	Max. dist / hour km mile	TKPH (1) TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm inch	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (1)	Other Approved Rims (1)
XADN+ E3 ** 193B 26.5 R 25 Tubeless	154324	28	258	687	1726	773	5196	41		908	22.00/3.0	22.00/3.0 IF
	72625	17.4	177	27	68	30.4	204.6	51.7		239.9		

Bar	2	2.5	3	3.25	3.5	4	4.5	5
Psi	29	36	44	47	51	58	65	73

Machine - Use (kg - lbs) ARTICULATED DUMP TRUCKS

STANDARD	6500	7500	8000	8500	9500	10500	11500
	14333	16538	17640	18743	20948	23153	25358

COMMERCIAL DESCRIPTION	CAI MPSTN	Max. dist / hour km mile	TKPH (1) TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm inch	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (1)	Other Approved Rims (1)
XADN+ E3 ** 200B 29.5 R 25 Tubeless	597428	28	314	767	1858	826	5578	44		1221	25.00/3.5	
	40883	17.4	215	30.2	73.1	32.5	219.6	55.4		322.6		

Bar	2	2.5	3	3.25	3.5	4	4.5	5
Psi	29	36	44	47	51	58	65	73

Machine - Use (kg - lbs) ARTICULATED DUMP TRUCKS

STANDARD	7800	9050	9675	10300	11500	12750	14000
	17199	19955	21333	22712	25358	28114	30870



MICHELIN

(1) More informations in the Michelin Databook 2019.



MICHELIN



OUR WEBSITE
michelinearthmover.com



TESTIMONIALS
YouTube channel



PRESSURE ADVISOR
pressureadvisor.michelinearthmover.com