

# MICHELIN®

## XLD 65

LOW PROFILE TECHNOLOGY  
FOR MORE PRODUCTIVITY  
IN MODERATE CONDITIONS



XLD 65 L3T \* 550/65 R 25 Tubeless

XLD 65 L3T \* 600/65 R 25 Tubeless

XLD 65 L3T \* 650/65 R 25 Tubeless

XLD 65 L3T \* 750/65 R 25 Tubeless

XLD 65 L3 \* 800/65 R 29 Tubeless



LOADERS



GRADERS



MICHELIN


# MICHELIN® XLD 65

LOW PROFILE TECHNOLOGY  
**FOR MORE PRODUCTIVITY**  
IN MODERATE CONDITIONS



LOADERS

GRADERS



## ■ **PRODUCTIVITY**

Load capacity increased by 12 to 15%<sup>2</sup> while maintaining the same inflation pressure

Risk of shocks reduced and damage resistance increased at constant load

Significant increase in life of 25 to 30%<sup>2</sup>



## ■ **SAFETY & HANDLING IMPROVEMENT**

Improved traction and adhesion

Better stability

Reduced vibration



## ■ **MOBILITY**


Superior flotation capacity and exceptional mobility on yielding underfoot conditions

Appreciable gain in traction



## **FITS ON A WIDER RIM**

Same diameter as an 80 series tire



**MICHELIN**

<sup>(2)</sup> Comparison of the Michelin® XLD 65 and the Michelin® XHA® with the equivalent overall diameter, in real life conditions made by Michelin.



## MICHELIN TECHNICAL DATA

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	TKPH <sup>(1)</sup> TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim <sup>(1)</sup>	Other Approved Rims <sup>(1)</sup>
XLD 65 L3T * 550/65 R 25 Tubeless	123570	16		549	1400	600	4147	32		450	17.00/1.7	17.00/2.0
	86785	9.9		21.6	55.1	23.6	163.3	40.3		118.9		
Bar	2	2.25		2.5	3	3.25	3.5	4		4.25	4.5	5
Psi	29	33		36	44	47	51	58		62	65	73
Machine - Use (kg - lbs)	<b>LOADERS</b>											
FRONT LADEN	4900	5350		5800	6700	7150	7600	8500		8950	9400	10300
	10805	11797		12789	14774	15766	16758	18743		19735	20727	22712
REAR UNLADEN	3925	4290		4650	5350	5720	6075	6800		7165	7525	8250
	8655	9459		10253	11797	12613	13395	14994		15799	16593	18191
Machine - Use (kg - lbs)	<b>GRADERS</b>											
ALL AXLES	2940	3210		3480	4020	4290	4560	5100				
	6483	7078		7673	8864	9459	10055	11246				
XLD 65 L3T * 600/65 R 25 Tubeless	063799	16		622	1429	617	4246	34		484	19.50/2.5	17.00/1.7
	82704	9.9		24.5	56.3	24.3	167.2	42.8		127.9	17.00/2.0	
Bar	2	2.5		3	3.5	4	4.5	5				
Psi	29	36		44	51	58	65	73				
Machine - Use (kg - lbs)	<b>LOADERS</b>											
FRONT LADEN	5650	6675		7700	8725	9750	10725	11700				
	12458	14718		16979	19239	21499	23649	25799				
REAR UNLADEN	4520	5340		6160	6980	7800	8580	9360				
	9967	11775		13583	15391	17199	18919	20639				
Machine - Use (kg - lbs)	<b>GRADERS</b>											
ALL AXLES	3390	4005		4600								
	7475	8831		10143								
XLD 65 L3T * 650/65 R 25 Tubeless	123820	16		634	1498	637	4425	37		596	19.50/2.5	
	90278	9.9		25	59	25.1	174.2	46.6		157.5		
Bar	2	2.5		3	3.5	4	4.5	5				
Psi	29	36		44	51	58	65	73				
Machine - Use (kg - lbs)	<b>LOADERS</b>											
FRONT LADEN	6700	7900		9100	10300	11500	12700	13900				
	14774	17420		20066	22712	25358	28004	30650				
REAR UNLADEN	5400	6350		7300	8250	9200	10150	11100				
	11907	14002		16097	18191	20286	22381	24476				
Machine - Use (kg - lbs)	<b>GRADERS</b>											
ALL AXLES	4100	4800		5500	6200	6900	7600	8300				
	9041	10584		12128	13671	15215	16758	18302				
XLD 65 L3T * 750/65 R 25 Tubeless	123940	16		747	1591	683	4714	41		788	24.00/3.0	22.00/3.0
	50629	9.9		29.4	62.6	26.9	185.6	51.7		208.2		
Bar	2	2.5		3	3.25	3.5	4	4.5		5	5.5	
Psi	29	36		44	47	51	58	65		73	80	
Machine - Use (kg - lbs)	<b>LOADERS</b>											
FRONT LADEN	8400	9720		11040	11700	12360	13680	15000		16320	17640	
	18522	21433		24343	25799	27254	30164	33075		35986	38896	
REAR UNLADEN	6725	7775		8825	9365	9900	10950	12000		13050	14100	
	14829	17144		19459	20650	21830	24145	26460		28775	31091	
Machine - Use (kg - lbs)	<b>GRADERS</b>											
ALL AXLES	5040	5830		6620	7020	7420	8210					
	11113	12855		14597	15479	16361	18103					

## MICHELIN TECHNICAL DATA

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	TKPH <sup>(1)</sup> TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim <sup>(1)</sup>	Other Approved Rims <sup>(1)</sup>
XLD 65 L3 * 800/65 R 29 Tubeless	123059 45325	16 9.9		793 31.2	1818 71.6	790 31.1	5412 213.1	48 60.5		1093 288.8	27.00/3.0	24.00/3.5
Bar	2	2.5	3	3.5	4	4.25	4.5	5	5.5			
Psi	29	36	44	51	58	62	65	73	80			
Machine - Use (kg - lbs)	<b>LOADERS</b>											
<b>FRONT LADEN</b>	10100 22271	11800 26019	13500 29768	15200 33516	16900 37265	17500 38588	18600 41013	20300 44762	22000 48510			
<b>REAR UNLADEN</b>	8100 17861	9450 20837	10800 23814	12150 26791	13500 29768	14000 30870	14900 32855	16250 35831	17600 38808			

<sup>(1)</sup> More informations in the Michelin Databook 2019.



**AUTHORIZED DISTRIBUTOR:**