

# MICHELIN®

## XAD 65

**TAILORED FOR YOUR BOTTOM LINE  
IN ANY WORKING CONDITIONS**



XAD 65-1 SUPER E3T \*\* 180B  
650/65 R 25 Tubeless

XAD 65-1 SUPER E3T \*\* 190B  
750/65 R 25 Tubeless

XAD 65-1 SUPER E3T \*\* 195B  
775/65 R 29 Tubeless

XAD 65-1 SUPER E3T \*\* 203B  
875/65 R 29 Tubeless



ARTICULATED DUMP TRUCKS



**MICHELIN**

## **TAILORED FOR YOUR BOTTOM LINE**

IN ANY WORKING CONDITIONS



ARTICULATED DUMP TRUCKS

Larger footprint with lower ground contact pressure, better stability, excellent mobility



Multi-block tread pattern



Excellent lateral grip on soft terrain due to self-cleaning tread pattern



### ■ **MORE PRODUCTIVITY POTENTIAL**

Michelin's E3 (including wide base) TKPH is up to 38% higher<sup>2</sup> than the average TKPH of the premium competitors



### ■ **EXCELLENT TRACTION**


Maneuverability on soft or muddy soil with proven flotation and traction thanks to a high-performance tread pattern



### ■ **GOOD LONG-TERM INVESTMENT**

Long-lasting, even-wearing tread pattern

Up to 90% of Michelin tires are retreadable due to the casing quality offered by MICHELIN C<sup>2</sup> Technology<sup>3</sup>



**MICHELIN**

<sup>(2)</sup> Compared to the average TKPH of Michelin premium competitors, published in the 2019 databook: Goodyear OTR tire engineering data (02/07/2014) and Goodyear OTR website (<http://www.goodyearotr.com>, 11/2015) and Bridgestone OTR tires databook (2015).

<sup>(3)</sup> Measurements taken at retreader facilities in Europe between 2012 and 2014.



## MICHELIN TECHNICAL DATA

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	TKPH <sup>(1)</sup> TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim <sup>(1)</sup>	Other Approved Rims <sup>(1)</sup>
XAD 65-1 SUPER E3T ** 180B 650/65 R 25 Tubeless	840573 89647	28 17.4	179 123	630 24.8	1494 58.8	669 26.3	4498 177.1	40 50.4		595 157.2	19.50/2.5	22.00/3.0

Bar	2.5	3	3.5	4
Psi	36	44	51	58

### Machine - Use (kg - lbs)

#### ARTICULATED DUMP TRUCKS

<b>STANDARD</b>	5450 12017	6300 13892	7150 15766	8000 17640
-----------------	---------------	---------------	---------------	---------------

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	TKPH <sup>(1)</sup> TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim <sup>(1)</sup>	Other Approved Rims <sup>(1)</sup>
XAD 65-1 SUPER E3T ** 190B 750/65 R 25 Tubeless	123895 79374	28 17.4	237 162	738 29.1	1599 63	701 27.6	4777 188.1	43 54.2		810 214	24.00/3.0	22.00/3.0 25.00/3.0

Bar	2.5	3	3.25	3.5	4
Psi	36	44	47	51	58

### Machine - Use (kg - lbs)

#### ARTICULATED DUMP TRUCKS

<b>STANDARD</b>	7350 16207	8400 18522	8950 19735	9500 20948	10600 23373
-----------------	---------------	---------------	---------------	---------------	----------------

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	TKPH <sup>(1)</sup> TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim <sup>(1)</sup>	Other Approved Rims <sup>(1)</sup>
XAD 65-1 SUPER E3T ** 195B 775/65 R 29 Tubeless	510085 74895	28 17.4	272 186	785 30.9	1759 69.3	778 30.6	5272 207.6	45 56.7		1050 277.4	24.00/3.0	24.00/3.5 25.00/3.5

Bar	2	2.5	3	3.5	4
Psi	29	36	44	51	58

### Machine - Use (kg - lbs)

#### ARTICULATED DUMP TRUCKS

<b>STANDARD</b>	6900 15215	8100 17861	9350 20617	10700 23594	12150 26791
-----------------	---------------	---------------	---------------	----------------	----------------

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	TKPH <sup>(1)</sup> TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim <sup>(1)</sup>	Other Approved Rims <sup>(1)</sup>
XAD 65-1 SUPER E3T ** 203B 875/65 R 29 Tubeless	086953 40269	28 17.4	347 238	883 34.8	1881 74.1	822 32.4	5613 221	51 64.3		1376 363.5	27.00/3.0	27.00/3.5 28.00/3.5

Bar	2	2.5	3	3.5	4
Psi	29	36	44	51	58

### Machine - Use (kg - lbs)

#### ARTICULATED DUMP TRUCKS

<b>STANDARD</b>	9100 20066	10800 23814	12500 27563	14100 31091	15500 34178
-----------------	---------------	----------------	----------------	----------------	----------------

<sup>(1)</sup> More informations in the Michelin Databook 2019.





**OUR WEBSITE**  
business.michelin.uk



**TESTIMONIALS**  
YouTube channel



**PRESSURE ADVISOR**  
pressureadvisor.michelinearthmover.com

**AUTHORIZED DISTRIBUTOR:**

A large, empty white rounded rectangular box intended for the name of the authorized distributor.