

# MICHELIN® X® GLA2™

**MAXIMIZE YOUR GRADER TRACTION!**



13.00R24 XGL A2 TL TG\*

14.00R24 XGL A2 TL TG\*

16.00R24 XGL A2 TL TG\*



GRADERS



**MICHELIN**

## MAXIMIZE YOUR GRADER TRACTION!



FOR GRADERS



### EXCELLENT PRODUCTIVITY

Resistance to impacts and cuts resulting in less downtime with steel casing



### EXCELLENT TRACTION AND SIDE HILL GRIP

An aggressive tread pattern, formed from many nondirectional blocks, provides a high traction capability on unstable and muddy soils. An important contribution of the tread pattern to avoid lateral slip.



### LOW OPERATING COST

Easy to repair. Long-lasting, even-wearing tread pattern and durable with low rolling resistance for efficient fuel economy.



AUTHORIZED DISTRIBUTOR :





## MICHELIN TECHNICAL DATA

COMMERCIAL DESCRIPTION	CAI MPSN	Max. dist / hour km mile	TKPH (1) TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm inch	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (1)	Other Approved Rims (1)
XGL A2 L2 * TG 13.00 R 24 Tubeless (6 - 10)	123386	16		335	1296	570	3875	25		215	8.00 TG SDC	10.00 VA SDC 9.00/1.5 DC
	24704	9.9		13.2	51	22.4	152.6	31.5		56.8		

Bar	2	2.5	3	3.5	4	4.5	5
Psi	29	36	44	51	58	65	73

Machine - Use (kg - lbs)	LOADERS						
<b>FRONT LADEN</b>	2650	3100	3600	4050	4500	4950	5400
	5843	6836	7938	8930	9923	10915	11907
<b>REAR UNLADEN</b>	2100	2500	2900	3250	3600	3950	4300
	4631	5513	6395	7166	7938	8710	9482

Machine - Use (kg - lbs)	GRADERS			
<b>ALL AXLES</b>	1900	2225	2550	2900
	4190	4906	5623	6395

COMMERCIAL DESCRIPTION	CAI MPSN	Max. dist / hour km mile	TKPH (1) TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm inch	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (1)	Other Approved Rims (1)
XGL A2 L2 * TG 14.00 R 24 TG Tubeless (6)	123395	16		371	1360	592	4051	25		310	8.00 TG SDC	10.00VA SDC 9.00/1.5 DC
	15924	9.9		14.6	53.5	23.3	159.5	31.5		81.9		

Bar	2	2.5	3	3.5	4	4.5	5	5.5
Psi	29	36	44	51	58	65	73	80

Machine - Use (kg - lbs)	LOADERS							
<b>FRONT LADEN</b>	3250	3750	4300	4800	5350	5900	6400	6900
	7166	8269	9482	10584	11797	13010	14112	15215
<b>REAR UNLADEN</b>	2600	3000	3450	3850	4300	4700	5100	5500
	5733	6615	7607	8489	9482	10364	11246	12128

Machine - Use (kg - lbs)	GRADERS			
<b>ALL AXLES</b>	2300	2725	3125	3550
	5072	6009	6891	7828

COMMERCIAL DESCRIPTION	CAI MPSN	Max. dist / hour km mile	TKPH (1) TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm inch	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (1)	Other Approved Rims (1)
XGL A2 L2 * TG 16.00 R 24 Tubeless (6)	123903	16		435	1500	646	4451	27		412	10.00 VA SDC	
	45611	9.9		17.1	59.1	25.4	175.2	34		108.9		

Bar	2	2.5	3	3.5	4	4.5	5
Psi	29	36	44	51	58	65	73

Machine - Use (kg - lbs)	LOADERS						
<b>FRONT LADEN</b>	4500	5150	5800	6400	7050	7700	8350
	9923	11356	12789	14112	15545	16979	18412
<b>REAR UNLADEN</b>	3600	4100	4650	5100	5650	6150	6700
	7938	9041	10253	11246	12458	13561	14774

Machine - Use (kg - lbs)	GRADERS			
<b>ALL AXLES</b>	3150	3625	4125	4625
	6946	7993	9096	10198



**MICHELIN**

(1) More informations in the Michelin Databook 2019.



**MICHELIN**



**OUR WEBSITE**  
[michelinearthmover.com](http://michelinearthmover.com)



**TESTIMONIALS**  
YouTube channel



**PRESSURE ADVISOR**  
[pressureadvisor.michelinearthmover.com](http://pressureadvisor.michelinearthmover.com)