

MICHELIN® XMS

**E3 RADIAL TIRE FOR *LARGE SCRAPERS*
DELIVERS *EXCELLENT TRACTION, SUPERIOR
DAMAGE RESISTANCE* AND A *SMOOTH RIDE***



XMS B E3R ** 40.5/75 R 39 TUBELESS



SCRAPERS



E3 RADIAL TIRE FOR **LARGE SCRAPERS** DELIVERS **EXCELLENT TRACTION, SUPERIOR DAMAGE RESISTANCE AND A SMOOTH RIDE**



SCRAPERS



■ **MAXIMUM RESISTANCE**

The square tread contour protects shoulders and sidewalls from damage



■ **EXCELLENT LATERAL GRIP**

The edges of the circumferential tread pattern offer exceptional lateral grip




■ **EXTENDED TIRE LIFE**

The innovative tread design has a high lug-to-void ratio



■ **OPTIMAL COMFORT**


Staggered tread blocks provide excellent operator comfort





MICHELIN TECHNICAL DATA

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	TKPH (1) TMPH	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim (1)	Other Approved Rims (1)
XMS B E3R ** 40.5/75 R 39 Tubeless	379296	33	766	998	2588	1151	7770	51		2940	32.00/4.5	
	93211	20.5	525	39.3	101.9	45.3	305.9	64.3		776.7		
Bar	3		3.5	4		4.25		4.5		5	5.5	6
Psi	44		51	58		62		65		73	80	87
Machine - Use (kg - lb)	TRANSPORT											
STANDARD	20200		22400	24600		25700		26800		29000	30100	31200
	44541		49392	54243		56669		59094		63945	66371	68796



MICHELIN

(1) More informations in the Michelin Databook 2019.



OUR WEBSITE
business.michelin.uk



TESTIMONIALS
YouTube channel



PRESSURE ADVISOR
pressureadvisor.michelinearthmover.com

AUTHORIZED DISTRIBUTOR: