

MICHELIN X[®] MULTI[™] ENERGY[™] TYRES

**MAXIMISED ENERGY
EFFICIENCY
WITH HIGH LEVEL
OF MILEAGE POTENTIAL**



DESIGNED FOR NATIONAL
AND REGIONAL OPERATIONS
ON ALL TYPES OF ROADS



**MAINLY FOR
STEER AXLE**

295/80 R 22.5
315/70 R 22.5
315/80 R 22.5



DRIVE AXLE

295/80 R 22.5
315/70 R 22.5
315/80 R 22.5

295/80 R 22.5

MICHELIN
X[®] MULTI[™] ENERGY[™] Z & D

315/70 R 22.5

MICHELIN
X[®] MULTI[™] ENERGY[™] Z & D

315/80 R 22.5

MICHELIN
X[®] MULTI[™] ENERGY[™] Z & D



(1) 3PMSF: Tyre for use in severe snow conditions.
(2) Retreadable with MICHELIN REMIX



MICHELIN X[®] MULTI[™] ENERGY[™] TYRES



FUEL SAVING:

• **UP TO -1.1 L/100 KM⁽¹⁾**



CO₂ REDUCTION:

• **UP TO -2.84 KG OF CO₂ EMISSIONS/100 KM⁽²⁾**



- HIGH MILEAGE POTENTIAL THANKS TO MICHELIN TECHNOLOGIES:

• **TO OFFER THE RIGHT TOTAL COST OF OWNERSHIP**



315/80 R 22.5 MICHELIN X[®] MULTI[™] ENERGY[™] Z & D:

a well known tread pattern (MICHELIN X[®] MULTI[™]) for long-lasting grip (still 3PMSF at 2 mm⁽²⁾), with specific technologies and compounds allowing low rolling resistance.

TREAD PATTERN

REGENION: grip throughout the tyre's service life

- Self-regenerating tread blocks, supported by our mold 3D metal printing techniques
- New grooves emerge over the tyre's lifetime

CASING

INFINICOIL: reinforced casing for greater stability and safety

- A continuous steel wire – which can be as long as 400 metres wrapped around the tyre to provide it with greater stability throughout its lifetime
- In addition to endurance, tyres designed with INFINICOIL give you better mileage potential and enhanced fuel savings

CASING

POWERCOIL: improved casing endurance

- A new generation of robust steel casing cables
- Improved resistance to oxidation
- Enhanced casing endurance

CASING

DURACOIL: reinforced heel for better endurance

- An improved tyre/wheel interface to improve casing endurance
- High quality nylon protects the bead area
- Improved stability, casing endurance and retreadability

TECHNICAL INFORMATION

REGROOVING INFORMATION

TREAD PATTERN AND DIMENSION	TYPE	LOAD/SPEED INDEX	MICHELIN PREFERRED RIM	ORIGINAL TREAD DEPTH	SPECIAL MARKINGS	RADIO FREQUENCY IDENTIFICATION CHIP INTEGRATED	EUROPEAN LABELLING				REGROOVE DEPTH	SUGGESTED BLADE
NEW 295/80 R 22.5 MICHELIN X [®] MULTI [™] ENERGY [™] Z	TL	154/150L (152/149 M)	9.00	14.5 mm	^(d) [M+S] Traction		B	C	A	72 dB	3 mm	R3
NEW 295/80 R 22.5 MICHELIN X [®] MULTI [™] ENERGY [™] D	TL	154/150L (152/149 M)	9.00	16 mm	^(d) [M+S] Traction		C	C	B	76 dB	3 mm	R3
315/70 R 22.5 MICHELIN X [®] MULTI [™] ENERGY [™] Z	TL	156/150L	9.00	13.5 mm	^(d) [M+S] Traction		B	B	A	72 dB	3 mm	R3
315/70 R 22.5 MICHELIN X [®] MULTI [™] ENERGY [™] D	TL	154/150L	9.00	14.5 mm	^(d) [M+S] Traction		C	C	A	72 dB	3 mm	R3
315/80 R 22.5 MICHELIN X [®] MULTI [™] ENERGY [™] Z	TL	156/150L (154/150 M)	9.00	15.8 mm	^(d) [M+S] Traction		B	C	B	74 dB	3 mm	R3
315/80 R 22.5 MICHELIN X [®] MULTI [™] ENERGY [™] D	TL	156 /150L (154/150 M)	9.00	16.3 mm	^(d) [M+S] Traction		C	C	B	75 dB	3 mm	R3

Retreadable with **MICHELIN** **REMIX**

(a) Fuel efficiency class (from A to E). (b) Wet grip class (from A to E). (c) External rolling noise class (from A to C) and measured value in decibels (dB). (d) 3PMSF: Tyre for use in severe snow conditions.

(1) -1.1 L/100 km and -2.84 kg CO₂/100 km for 315/70 R 22.5 MICHELIN X[®] MULTI[™] ENERGY[™] Z & D vs 315/70 R 22.5 MICHELIN X[®] MULTI[™] Z & D; -0.7 L/100 km and -1.8 kg CO₂/100 km for 315/80 R 22.5 MICHELIN X[®] MULTI[™] ENERGY[™] Z & D vs 315/80 R 22.5 MICHELIN X[®] MULTI[™] Z & D; -0.8 L/100 km and -2.2 kg CO₂/100 km for 295/80 R 22.5 MICHELIN X[®] MULTI[™] ENERGY[™] Z & D vs 295/80 R 22.5 MICHELIN X[®] MULTI[™] Z & D; -0.4 L/100 km and -1.1 kg CO₂/100 km for 295/80 R 22.5 MICHELIN X[®] MULTI[™] ENERGY[™] Z & D vs MICHELIN XZ2[®]/XDA2[®] ENERGY. Certified value using VECTO calculation tool comparing fuel consumption and CO₂ emissions of standard tractor unit 4x2 + semi-trailer 3 axles (with neutralization of Semi-Trailer effect) in regional usage (50%) and long haul usage (50%), with standard reference load.

(2) Internal study, Ivalo (Finland), February 2018. Snow motricity test (3PMSF) on 4x2 rigid truck with the 315/70 R 22.5 MICHELIN X[®] MULTI[™] D (same tread pattern features than MICHELIN X[®] MULTI[™] ENERGY[™] D dimensions): stable 3PMSF result at three tread wear levels (new, 8 mm and 2 mm of remaining tread depth).

MICHELIN products are manufactured from high quality materials to high tolerances, ensuring a uniform and consistent performance. Correct application, fitting, inflation and regular inspection of the product are essential to its safe and efficient operation. Remix[®] and the tyre designations mentioned are trademarks of Michelin. For further information about any of the products in this document, contact your local Michelin representative.



WEBSITE
business.michelin.co.uk



MY PORTAL
myportal.michelingroup.com



LINKEDIN
Michelin For Professional Businesses



YOUTUBE
Michelin Truck & Bus Tyres Europe



MICHELIN