

MICHELIN® X®TRA POWER™ L5

TAKES ON FACEWORK AT FULL POWER



35/65R33 XTRA POWER L5 ***



MICHELIN



OUR WEBSITE
michelinearthmover.com



TESTIMONIALS
YouTube channel



PRESSURE ADVISOR
pressureadvisor.michelinearthmover.com

AUTHORIZED DISTRIBUTOR:



LOADER / WHEELDOZER





TAKES ON FACEWORK AT FULL POWER



LOADER / WHEELDOZER



■ MAXIMIZE POWER, MINIMIZE RIM SLIP

Redesigned bead optimizes transfer of torque



■ INCREASE LOAD-CARRYING CAPACITY¹

Carry 16%² more load due to increased *** rating




■ MORE TIRE CROWN PROTECTION²

Designed with reinforced steel crown belt package



■ MAKES LUG CRACKING A THING OF THE PAST

Designed with new bridges and curved sculpture



MICHELIN


⁽¹⁾ Increase in Load Carrying Capacity Requires Speed Reduction.

⁽²⁾ Reference Michelin® Technical Earthmover Data Book 2019. Internal comparison between Michelin® XLD® D2 35/65R33 and Michelin® X^{TRA} POWER™ L5 35/65R33.

MICHELIN TECHNICAL DATA

COMMERCIAL DESCRIPTION	CAI MSPN	Max. dist. / hour km mile	e mm inch	D mm inch	R' mm inch	RC mm inch	Tread depth mm 32rd	Dual Spacing mm inch	Cap liter gallon	Measuring Recommended Rim ⁽³⁾	Other Approved Rims ⁽³⁾
XTRA POWER L5 35/65 R 33	169990 51910	10 6.2 if load per tire < = 28 t	930 36.6	2058 81	905 36	6154 242	95 119.7		1403 49.5	28.00/3.5	
		8 5 if load per tire > 28 t									
Bar	3	4	4.5	5	5.5	6	6.5	7	7.5	8	
Psi	44	58	65	73	80	87	94	102	109	116	
Machine - Use (kg - lb)	LOADER LOAD PER TIRE < = 28 t										
FRONT LADEN	16100 35501	19000 41895	21200 46746	23000 50715	24300 53582	25750 56779	28000 61740				
REAR UNLADEN	12900 28445	15200 33516	16950 37375	18400 40572	19450 42887	20600 45423	22400 46392				
Machine - Use (kg - lb)	LOADER LOAD PER TIRE > 28 t										
FRONT LADEN									30000 66150	31500 69458	32500 71663
REAR UNLADEN									24000 52920	25200 55566	26000 57330

⁽³⁾ More informations in the Michelin Databook 2019.



MICHELIN