

MICHELIN X STACKER 3 HD



TECHNICAL CHARACTERISTICS

DESCRIPTION	CAI [MSPN]	Max. dist./ hour km [mile]	e mm [in]	D mm [in]	R' mm [in]	RC mm [in]	Tread depth mm [32rd]	Dual spacing mm [in]	Cap liter [gal]	Measuring recommended rim	Other approved rims
18.00 R 25 X STACKER 3 HD TL 207 A5	397347 -	12 7,5	503 19,8	1659 65,3	740 29,1	4986 196,3	53 67	600 23,6	489 129	13.00/2.5	15.00/2.5

LOAD CAPACITY BASED ON INFLATION PRESSURE AND SPEED

Bar Psi	6 87	8 116	10 145		
Machine - use kg - lbs	MECHANICAL HANDLING, CYCLIC SERVICE				
STATIC	18380 40528	22280 49127	26250 57881		
<= 10 km/h <= 6 mp/h	15930 35126	19180 42292	22750 50164		
25 km/h 12 mp/h	12250 27011	14750 35524	17500 38588		
Machine - use kg - lbs	COUNTERBALANCED LIFT TRUCK, LOAD WHEEL				
<= 10 km/h <= 6 mp/h	15930 35126	19180 42292	22750 50164		
25 km/h 15 mp/h	15930 35126	19180 42292	22750 50164		
MOUNTING ACCESSORIES AVAILABLE	Recommended rim 13.00/2.5	Tubeless bead seal [CAI] N/A	Rubber ring [Michelin Ref./CAI] OR 3-25 SULLA/553200	Tube [Michelin Ref./CAI] 25 WAM/101871	Flap [CAI] 16-24/25 (551608)

LEARN MORE

ON THE WEB
business.michelin.co.uk

TESTIMONIALS
youtube.com

UPDATED APR 2022

CONTACT

Please contact your local sales representative for more information.

