

# **MICHELIN®** **CEREXBIB® 2**

*HIGH PRODUCTIVITY  
AND GOOD SOIL PROTECTION*



*A **HIGH LOAD CAPACITY** TIRE  
AT **LOW PRESSURE**  
IN THE FIELD, FOR LARGE  
**HARVESTING MACHINERY***



**MICHELIN**

Tire specifications and pressure table. Load per tire in kg.

DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC. (mm)	Tube (Code)	Tread depth (mm)	75% internal volume (litres)	Recommended rim	Acceptable rims					
<b>CEREXBIB 2</b> VF 520/80 R26 CFO+ 168A8 TL	850494	503	1491	649	4400	716	44	366	DW16L	DW18L   W16L					
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	5230	5805	6375	6510	6645	6775	6910	7045	7175	7310	7440	7600	7760	7915	8075
15 km/h Cyc	4765	5290	5815	5935	6060	6180	6300	6420	6540	6660	6780	6925	7075	7220	7365
40 km/h	3550	3965	4375	4470	4570	4665	4760	4860	4955	5055	5150	5265	5375	5490	5600
<b>CEREXBIB 2</b> VF 620/70 R26 CFO+ 173A8 TL	228272	606	1513	655	4461	716	45	462.75	DW20B (A)						
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	6035	6740	7440	7605	7770	7935	8100	8265	8430	8590	8755	8945	9140	9330	9520
15 km/h Cyc	5505	6145	6780	6930	7080	7230	7380	7530	7685	7835	7985	8160	8335	8505	8680
40 km/h	4125	4640	5150	5255	5365	5470	5575	5680	5790	5895	6000	6125	6250	6375	6500
<b>CEREXBIB 2</b> VF 750/65 R26 CFO+ 180A8 TL	132266	748	1623	701	4786	833	48	659.25	DW25B (A)						
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	7440	8225	9010	9225	9435	9650	9860	10075	10285	10500	10710	10965	11220	11475	11730
15 km/h Cyc	6780	7500	8215	8410	8605	8795	8990	9185	9380	9570	9765	10000	10230	10465	10695
40 km/h	5150	5650	6150	6295	6440	6580	6725	6870	7015	7155	7300	7475	7650	7825	8000
<b>CEREXBIB 2</b> VF 520/85 R30 CFO+ 172A8 TL	188276	522	1624	709	4797	737	46	435	W16L						
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	5865	6545	7225	7360	7495	7625	7760	7895	8025	8160	8290	8535	8780	9020	9265
15 km/h Cyc	5350	5970	6590	6710	6830	6950	7070	7190	7315	7435	7555	7780	8005	8225	8450
40 km/h	4000	4440	4875	4990	5110	5225	5340	5455	5570	5685	5800	5925	6050	6175	6300
<b>CEREXBIB 2</b> VF 620/70 R30 CFO+ 175A8 TL	049288	608	1615	700	4765	737	43	505.5	DW20B (A)						
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	6375	7120	7865	8040	8215	8390	8565	8740	8915	9090	9265	9500	9735	9965	10200
15 km/h Cyc	5815	6495	7170	7330	7490	7650	7810	7970	8130	8290	8450	8665	8875	9090	9300
40 km/h	4500	4975	5450	5555	5665	5770	5875	5980	6090	6195	6300	6450	6600	6750	6900
<b>CEREXBIB 2</b> VF 710/60R30 CFO+ 179A8 TL	<b>NEW</b> 907583	693	1591	689	4687		41	564.75	DW23B(A)	DW25B(A)					
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	6685	7390	8095	8355	8615	8875	9135	9340	9545	9745	9950	10175	10395	10620	10840
15 km/h Cyc	6100	6745	7385	7625	7860	8100	8335	8520	8710	8895	9080	9285	9485	9690	9890
30 km/h Cyc	5110	5650	6185	6385	6585	6780	6980	7135	7295	7450	7605	7775	7945	8115	8285
40 km/h	4500	4975	5450	5625	5800	5975	6150	6290	6425	6565	6700	6850	7000	7150	7300
<b>CEREXBIB 2</b> VF 710/65 R30 CFO+ 179A8 TL	608814	693.9	1676	735	4952		46	630	DW25B (A)	DW23B (A)					
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	7225	7990	8755	8970	9180	9395	9605	9820	10030	10245	10455	10690	10925	11155	11390
15 km/h Cyc	6590	7290	7985	8180	8375	8565	8760	8955	9150	9340	9535	9750	9960	10175	10385
40 km/h	5000	5500	6000	6140	6275	6415	6550	6690	6825	6965	7100	7265	7425	7590	7750
<b>CEREXBIB 2</b> IF 800/65 R32 CFO+ 181A8 TL	987406	772	1855	826	5501	831	57	903	DW27B (A)						
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	9010	9860	10710	10965	11220	11475	11730	11985	12240	12495	12750	13070	13390	13705	14025
15 km/h Cyc	8215	8990	9765	10000	10230	10465	10695	10930	11160	11395	11625	11915	12210	12500	12790
40 km/h	5300	5800	6300	6450	6600	6750	6900	7050	7200	7350	7500	7690	7875	8065	8250
<b>CEREXBIB 2</b> IF 800/70 R32 CFO+ 185A8 TL	789156	796	1950	864	5800	831	55	966	DW27B (A)						
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	9860	10965	12070	12370	12665	12965	13260	13560	13855	14155	14450	14770	15090	15405	15725
15 km/h Cyc	8990	10000	11005	11275	11550	11820	12090	12360	12635	12905	13175	13465	13760	14050	14340
40 km/h	5800	6450	7100	7275	7450	7625	7800	7975	8150	8325	8500	8690	8875	9065	9250
<b>CEREXBIB 2</b> VF 900/60 R32 CFO+ 191A8 TL	430737	893	1903	827	5618		58	1,032.75	DW30B (A)	DW27B (A) (NRO)					
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	9860	10965	12070	12370	12665	12965	13260	13560	13855	14155	14450	14770	15090	15405	15725
15 km/h Cyc	8990	10000	11005	11275	11550	11820	12090	12360	12635	12905	13175	13465	13760	14050	14340
40 km/h	6700	7475	8250	8470	8690	8905	9125	9345	9565	9780	10000	10225	10450	10675	10900





Tire specifications and pressure table. Load per tire in kg.

DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Tube (Code)	Tread depth (mm)	75% internal volume (litres)	Recommended rim	Acceptable rims					
<b>CEREXBIB 2</b> VF 500/85 R34 CFO+ 172A8 TL	038009	497	1676	741	4961		46	430.5	DW16L	DW18L					
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	5870	6445	7020	7180	7340	7495	7655	7815	7975	8130	8290	8470	8650	8830	9010
15 km/h Cyc	5350	5875	6400	6545	6690	6835	6980	7125	7270	7415	7560	7725	7890	8055	8220
40 km/h	4000	4440	4875	4965	5060	5150	5240	5330	5420	5510	5600	5775	5950	6125	6300
<b>CEREXBIB 2</b> IF 800/70 R38 CFO+ 187A8 TL	610997	790	2051	912	6079	804	57	1,087.5	DW27B (A)						
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	10710	11945	13175	13440	13705	13970	14240	14505	14770	15035	15300	15620	15940	16255	16575
15 km/h Cyc	9765	10885	12000	12245	12490	12730	12975	13220	13465	13705	13950	14240	14530	14820	15110
40 km/h	6300	7025	7750	7905	8065	8220	8375	8530	8690	8845	9000	9190	9375	9565	9750
<b>CEREXBIB 2</b> VF 900/60 R38 CFO+ 193A8 TL	853285	880	2027	888	5987		58	1,147.5	DW30B (A)	DW27B (A) (NRO)					
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	10455	11605	12750	13070	13390	13705	14025	14345	14665	14980	15300	15725	16150	16575	17000
15 km/h Cyc	9765	10885	12000	12245	12490	12730	12975	13220	13465	13705	13950	14350	14750	15150	15550
40 km/h	7300	8025	8750	8980	9215	9445	9675	9905	10140	10370	10600	10825	11050	11275	11500
<b>CEREXBIB 2</b> VF 520/85 R42 CFO+ 177A8 TL	270459	541	1953	881	5807	802	55	544.5	DW18B(A)	DD18   W18L					
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	6800	7545	8285	8465	8650	8830	9010	9225	9435	9650	9860	10075	10285	10500	10710
15 km/h Cyc	6200	6880	7555	7720	7885	8050	8215	8410	8605	8795	8990	9185	9380	9570	9765
10 km/h Cyc Dual	5985	6640	7295	7470	7640	7815	7985	8160	8330	8505	8675	8865	9050	9240	9425
15 km/h Cyc Dual	5455	6055	6650	6810	6965	7125	7280	7440	7595	7755	7910	8080	8255	8425	8595
40 km/h	4625	5215	5800	5915	6025	6140	6250	6365	6475	6590	6700	6850	7000	7150	7300
<b>CEREXBIB 2</b> VF 580/85 R42 CFO+ 183A8 TL	844076	580	2040	903	6040	802	58	700.5	DW18B(A)						
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	8075	8970	9860	10050	10245	10435	10625	10815	11010	11200	11390	11730	12070	12410	12750
15 km/h Cyc	7365	8180	8990	9165	9340	9515	9690	9860	10035	10210	10385	10695	11005	11315	11625
10 km/h Cyc Dual	7110	7895	8680	8850	9015	9185	9350	9520	9685	9855	10020	10320	10620	10920	11220
15 km/h Cyc Dual	6480	7195	7910	8065	8220	8370	8525	8680	8835	8985	9140	9415	9685	9960	10230
40 km/h	5450	6075	6700	6865	7025	7190	7350	7515	7675	7840	8000	8190	8375	8565	8750
<b>CEREXBIB 2</b> VF 710/70 R42 CFO+ 188A8 TL	499992	705	2097	927	6207	802	64	867	DW23B (A)	DW25B (A)					
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	9265	10330	11390	11615	11835	12060	12280	12505	12730	12950	13175	13495	13815	14130	14450
15 km/h Cyc	8450	9420	10385	10590	10795	10995	11200	11405	11610	11810	12015	12305	12595	12885	13175
40 km/h		7750	7905	8065	8220	8375	8530	8690	8845	9000	9250	9500	9750	10000	
<b>CEREXBIB 2</b> VF 900/60 R42 CFO+ 195A8 TL	856296	843	2118	930	6281		59	1227	DW30B (A)	TW30B					
<b>Bar</b>	<b>1,20</b>	<b>1,40</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>
10 km/h Cyc	11050	12325	13600	13920	14240	14555	14875	15195	15515	15830	16150	16490	16830	17170	17510
15 km/h Cyc	10075	11240	12400	12690	12985	13275	13565	13855	14145	14435	14725	15035	15345	15655	15965
30 km/h Cyc	8450	9425	10400	10645	10890	11130	11375	11620	11865	12105	12350	12610	12870	13130	13390
40 km/h	7500	8375	9250	9515	9775	10040	10300	10525	10750	10975	11200	11440	11675	11915	12150
<b>CEREXBIB 2</b> VF 800/70 R46 CFO+ 199A8 TL	<b>NEW</b> 645288	805	2301	1015	6808			1216.5	TW27B						
<b>Bar</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>		
10 km/h Cyc	14025	14450	14875	15300	15725	15940	16150	16365	16575	17045	17510	17765	18020		
15 km/h Cyc	13210	13585	13955	14160	14365	14770	15175	15380	15585	15790	15990	16465	16940		
40 km/h	9750	10025	10030	10450	10600	10900	11200	11350	11500	11650	11800	12150	12500		
<b>CEREXBIB 2</b> VF 900/65R46 CFO+ 199A8	<b>NEW</b> 649062	900	2322	1022	6866		60		DW30B						
<b>Bar</b>	<b>1,60</b>	<b>1,70</b>	<b>1,80</b>	<b>1,90</b>	<b>2,00</b>	<b>2,10</b>	<b>2,20</b>	<b>2,30</b>	<b>2,40</b>	<b>2,50</b>	<b>2,60</b>	<b>2,70</b>	<b>2,80</b>		
10 km/h Cyc	14875	15300	15725	16150	16575	17045	17510	17765	18020	18530	19040	19295	19550		
15 km/h Cyc	13955	14365	14770	15180	15585	154790	15990	16465	16940	17175	17410	17920	18430		
40 km/h	10300	10600	10900	11200	11500	11650	11800	12150	12500	12675	12850	13225	13600		



# MICHELIN® CEREXBIB® 2

## High productivity

Steel belted casing providing a greater load capacity  
(Except for dual sizes)

⇒ At a pressure of 2.8 bar and a **cyclic speed of 10 km/h**, MICHELIN CEREXBIB 2 (VF 710/70 R42) can carry **over 4 tons more** than at 40 km/h. ✱

## MICHELIN ULTRAFLEX Technology

High sidewall resistance for **greater tire deflection**

## Good soil protection

The **new 10 km/h cyclic speed** allows you to reduce the inflation pressure by **up to 20%** for the same load in the field, compared to the 15km/h cyclic table.

⇒ For a given load of 13175 kilos, MICHELIN CEREXBIB 2 (VF 710/70 R42) allows you to **reduce the pressure in field by 0.4 bar**, at a speed of 10 km/h for cyclic loads. ✱

**AIR SYSTEMS<sup>®</sup> READY**  
CTIS compatible



**EXCELLENT TRACTION**  
Better traction on slopes  
Ability to work on wet soil



**Productivity**



**Soil Protection**



**Traction & Flotation**

* MICHELIN CEREXBIB 2 VF 710/70 R42 CFO+ 188A8TL	1,20 (17)	1,60 (23)	2,00 (29)	2,40 (35)	2,80 (41)
Bar					
10 km/h Cyclic	9265	11390	12280	13175	14450
15 km/h Cyclic	8450	10385	11200	12015	13175
40 km/h		7750	8375	9000	10000



## AVAILABLE SIZES

### FRONT

IF 800/65 R32 CFO+ 181A8  
VF 900/60 R32 CFO+ 191A8  
IF 800/70 R32 CFO+ 185A8  
VF 900/60 R38 CFO+ 193A8  
IF 800/70 R38 CFO+ 187A8  
VF 520/85 R42 CFO+ 177A8

VF 580/85 R42 CFO+ 183A8  
VF 710/70 R42 CFO+ 188A8  
VF 900/60 R42 CFO+ 195A8  
VF 800/70 R46 CFO+ 199A8  
VF 900/65 R46 CFO+ 199A8

### REAR

VF 520/80 R26 CFO+ 168A8  
VF 620/70 R26 CFO+ 173A8  
VF 750/65 R26 CFO+ 180A8  
VF 710/60 R30 CFO+ 179A8

VF 620/70 R30 CFO+ 175A8  
VF 520/85 R30 CFO+ 172A8  
VF 710/65 R30 CFO+ 179A8  
VF 500/85 R34 CFO+ 172A8

## MICHELIN RECOMMENDATIONS

### VEHICLE N° 1

FRONT ..... PRESSURE ..... (bar / psi)  
REAR ..... PRESSURE ..... (bar / psi)

### VEHICLE N° 2

FRONT ..... PRESSURE ..... (bar / psi)  
REAR ..... PRESSURE ..... (bar / psi)