


MICHELIN® **CEREXBIB® 2**

*HIGH PRODUCTIVITY
AND GOOD SOIL PROTECTION*



*A **HIGH LOAD CAPACITY** TIRE
AT **LOW PRESSURE**
IN THE FIELD, FOR LARGE
HARVESTING MACHINERY*



MICHELIN

Tire specifications and pressure table. Load per tire in kg.

DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC. (mm)	Tube (Code)	Tread depth (mm)	75% internal volume (litres)	Recommended rim	Acceptable rims					
CEREXBIB 2 VF 520/80 R26 CFO+ 168A8 TL	850494	503	1491	649	4400	716	44	366	DW16L	DW18L W16L					
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	5230	5805	6375	6510	6645	6775	6910	7045	7175	7310	7440	7600	7760	7915	8075
15 km/h Cyc	4765	5290	5815	5935	6060	6180	6300	6420	6540	6660	6780	6925	7075	7220	7365
40 km/h	3550	3965	4375	4470	4570	4665	4760	4860	4955	5055	5150	5265	5375	5490	5600
CEREXBIB 2 VF 620/70 R26 CFO+ 173A8 TL	228272	606	1513	655	4461	716	45	462.75	DW20B (A)						
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	6035	6740	7440	7605	7770	7935	8100	8265	8430	8590	8755	8945	9140	9330	9520
15 km/h Cyc	5505	6145	6780	6930	7080	7230	7380	7530	7685	7835	7985	8160	8335	8505	8680
40 km/h	4125	4640	5150	5255	5365	5470	5575	5680	5790	5895	6000	6125	6250	6375	6500
CEREXBIB 2 VF 750/65 R26 CFO+ 180A8 TL	132266	748	1623	701	4786	833	48	659.25	DW25B (A)						
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	7440	8225	9010	9225	9435	9650	9860	10075	10285	10500	10710	10965	11220	11475	11730
15 km/h Cyc	6780	7500	8215	8410	8605	8795	8990	9185	9380	9570	9765	10000	10230	10465	10695
40 km/h	5150	5650	6150	6295	6440	6580	6725	6870	7015	7155	7300	7475	7650	7825	8000
CEREXBIB 2 VF 520/85 R30 CFO+ 172A8 TL	188276	522	1624	709	4797	737	46	435	W16L						
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	5865	6545	7225	7360	7495	7625	7760	7895	8025	8160	8290	8535	8780	9020	9265
15 km/h Cyc	5350	5970	6590	6710	6830	6950	7070	7190	7315	7435	7555	7780	8005	8225	8450
40 km/h	4000	4440	4875	4990	5110	5225	5340	5455	5570	5685	5800	5925	6050	6175	6300
CEREXBIB 2 VF 620/70 R30 CFO+ 175A8 TL	049288	608	1615	700	4765	737	43	505.5	DW20B (A)						
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	6375	7120	7865	8040	8215	8390	8565	8740	8915	9090	9265	9500	9735	9965	10200
15 km/h Cyc	5815	6495	7170	7330	7490	7650	7810	7970	8130	8290	8450	8665	8875	9090	9300
40 km/h	4500	4975	5450	5555	5665	5770	5875	5980	6090	6195	6300	6450	6600	6750	6900
CEREXBIB 2 VF 710/60R30 CFO+ 179A8 TL	NEW 907583	693	1591	689	4687		41	564.75	DW23B(A)	DW25B(A)					
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	6685	7390	8095	8355	8615	8875	9135	9340	9545	9745	9950	10175	10395	10620	10840
15 km/h Cyc	6100	6745	7385	7625	7860	8100	8335	8520	8710	8895	9080	9285	9485	9690	9890
30 km/h Cyc	5110	5650	6185	6385	6585	6780	6980	7135	7295	7450	7605	7775	7945	8115	8285
40 km/h	4500	4975	5450	5625	5800	5975	6150	6290	6425	6565	6700	6850	7000	7150	7300
CEREXBIB 2 VF 710/65 R30 CFO+ 179A8 TL	608814	693.9	1676	735	4952		46	630	DW25B (A)	DW23B (A)					
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	7225	7990	8755	8970	9180	9395	9605	9820	10030	10245	10455	10690	10925	11155	11390
15 km/h Cyc	6590	7290	7985	8180	8375	8565	8760	8955	9150	9340	9535	9750	9960	10175	10385
40 km/h	5000	5500	6000	6140	6275	6415	6550	6690	6825	6965	7100	7265	7425	7590	7750
CEREXBIB 2 IF 800/65 R32 CFO+ 181A8 TL	987406	772	1855	826	5501	831	57	903	DW27B (A)						
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	9010	9860	10710	10965	11220	11475	11730	11985	12240	12495	12750	13070	13390	13705	14025
15 km/h Cyc	8215	8990	9765	10000	10230	10465	10695	10930	11160	11395	11625	11915	12210	12500	12790
40 km/h	5300	5800	6300	6450	6600	6750	6900	7050	7200	7350	7500	7690	7875	8065	8250
CEREXBIB 2 IF 800/70 R32 CFO+ 185A8 TL	789156	796	1950	864	5800	831	55	966	DW27B (A)						
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	9860	10965	12070	12370	12665	12965	13260	13560	13855	14155	14450	14770	15090	15405	15725
15 km/h Cyc	8990	10000	11005	11275	11550	11820	12090	12360	12635	12905	13175	13465	13760	14050	14340
40 km/h	5800	6450	7100	7275	7450	7625	7800	7975	8150	8325	8500	8690	8875	9065	9250
CEREXBIB 2 VF 900/60 R32 CFO+ 191A8 TL	430737	893	1903	827	5618		58	1,032.75	DW30B (A)	DW27B (A) (NRO)					
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	9860	10965	12070	12370	12665	12965	13260	13560	13855	14155	14450	14770	15090	15405	15725
15 km/h Cyc	8990	10000	11005	11275	11550	11820	12090	12360	12635	12905	13175	13465	13760	14050	14340
40 km/h	6700	7475	8250	8470	8690	8905	9125	9345	9565	9780	10000	10225	10450	10675	10900



Tire specifications and pressure table. Load per tire in kg.

DESCRIPTION	CAI	e (mm)	D (mm)	R' (mm)	RC (mm)	Tube (Code)	Tread depth (mm)	75% internal volume (litres)	Recommended rim	Acceptable rims					
CEREXBIB 2 VF 500/85 R34 CFO+ 172A8 TL	038009	497	1676	741	4961		46	430.5	DW16L	DW18L					
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	5870	6445	7020	7180	7340	7495	7655	7815	7975	8130	8290	8470	8650	8830	9010
15 km/h Cyc	5350	5875	6400	6545	6690	6835	6980	7125	7270	7415	7560	7725	7890	8055	8220
40 km/h	4000	4440	4875	4965	5060	5150	5240	5330	5420	5510	5600	5775	5950	6125	6300
CEREXBIB 2 IF 800/70 R38 CFO+ 187A8 TL	610997	790	2051	912	6079	804	57	1,087.5	DW27B (A)						
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	10710	11945	13175	13440	13705	13970	14240	14505	14770	15035	15300	15620	15940	16255	16575
15 km/h Cyc	9765	10885	12000	12245	12490	12730	12975	13220	13465	13705	13950	14240	14530	14820	15110
40 km/h	6300	7025	7750	7905	8065	8220	8375	8530	8690	8845	9000	9190	9375	9565	9750
CEREXBIB 2 VF 900/60 R38 CFO+ 193A8 TL	853285	880	2027	888	5987		58	1,147.5	DW30B (A)	DW27B (A) (NRO)					
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	10455	11605	12750	13070	13390	13705	14025	14345	14665	14980	15300	15725	16150	16575	17000
15 km/h Cyc	9765	10885	12000	12245	12490	12730	12975	13220	13465	13705	13950	14350	14750	15150	15550
40 km/h	7300	8025	8750	8980	9215	9445	9675	9905	10140	10370	10600	10825	11050	11275	11500
CEREXBIB 2 VF 520/85 R42 CFO+ 177A8 TL	270459	541	1953	881	5807	802	55	544.5	DW18B(A)	DD18 W18L					
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	6800	7545	8285	8465	8650	8830	9010	9225	9435	9650	9860	10075	10285	10500	10710
15 km/h Cyc	6200	6880	7555	7720	7885	8050	8215	8410	8605	8795	8990	9185	9380	9570	9765
10 km/h Cyc Dual	5985	6640	7295	7470	7640	7815	7985	8160	8330	8505	8675	8865	9050	9240	9425
15 km/h Cyc Dual	5455	6055	6650	6810	6965	7125	7280	7440	7595	7755	7910	8080	8255	8425	8595
40 km/h	4625	5215	5800	5915	6025	6140	6250	6365	6475	6590	6700	6850	7000	7150	7300
CEREXBIB 2 VF 580/85 R42 CFO+ 183A8 TL	844076	580	2040	903	6040	802	58	700.5	DW18B(A)						
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	8075	8970	9860	10050	10245	10435	10625	10815	11010	11200	11390	11730	12070	12410	12750
15 km/h Cyc	7365	8180	8990	9165	9340	9515	9690	9860	10035	10210	10385	10695	11005	11315	11625
10 km/h Cyc Dual	7110	7895	8680	8850	9015	9185	9350	9520	9685	9855	10020	10320	10620	10920	11220
15 km/h Cyc Dual	6480	7195	7910	8065	8220	8370	8525	8680	8835	8985	9140	9415	9685	9960	10230
40 km/h	5450	6075	6700	6865	7025	7190	7350	7515	7675	7840	8000	8190	8375	8565	8750
CEREXBIB 2 VF 710/70 R42 CFO+ 188A8 TL	499992	705	2097	927	6207	802	64	867	DW23B (A)	DW25B (A)					
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	9265	10330	11390	11615	11835	12060	12280	12505	12730	12950	13175	13495	13815	14130	14450
15 km/h Cyc	8450	9420	10385	10590	10795	10995	11200	11405	11610	11810	12015	12305	12595	12885	13175
40 km/h		7750	7905	8065	8220	8375	8530	8690	8845	9000	9250	9500	9750	10000	
CEREXBIB 2 VF 900/60 R42 CFO+ 195A8 TL	856296	843	2118	930	6281		59	1227	DW30B (A)	TW30B					
Bar	1,20	1,40	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80
10 km/h Cyc	11050	12325	13600	13920	14240	14555	14875	15195	15515	15830	16150	16490	16830	17170	17510
15 km/h Cyc	10075	11240	12400	12690	12985	13275	13565	13855	14145	14435	14725	15035	15345	15655	15965
30 km/h Cyc	8450	9425	10400	10645	10890	11130	11375	11620	11865	12105	12350	12610	12870	13130	13390
40 km/h	7500	8375	9250	9515	9775	10040	10300	10525	10750	10975	11200	11440	11675	11915	12150
CEREXBIB 2 VF 800/70 R46 CFO+ 199A8 TL	NEW 645288	805	2301	1015	6808						1216.5		TW27B		
Bar	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80		
10 km/h Cyc	14025	14450	14875	15300	15725	15940	16150	16365	16575	17045	17510	17765	18020		
15 km/h Cyc	13210	13585	13955	14160	14365	14770	15175	15380	15585	15790	15990	16465	16940		
40 km/h	9750	10025	10030	10450	10600	10900	11200	11350	11500	11650	11800	12150	12500		
CEREXBIB 2 VF 900/65R46 CFO+ 199A8	NEW 649062	900	2322	1022	6866		60						DW30B		
Bar	1,60	1,70	1,80	1,90	2,00	2,10	2,20	2,30	2,40	2,50	2,60	2,70	2,80		
10 km/h Cyc	14875	15300	15725	16150	16575	17045	17510	17765	18020	18530	19040	19295	19550		
15 km/h Cyc	13955	14365	14770	15180	15585	154790	15990	16465	16940	17175	17410	17920	18430		
40 km/h	10300	10600	10900	11200	11500	11650	11800	12150	12500	12675	12850	13225	13600		



MICHELIN® CEREXBIB® 2

High productivity

Steel belted casing providing a greater load capacity
(Except for dual sizes)

⇒ At a pressure of 2.8 bar and a **cyclic speed of 10 km/h**, MICHELIN CEREXBIB 2 (VF 710/70 R42) can carry **over 4 tons more** than at 40 km/h. ✱

MICHELIN ULTRAFLEX Technology

High sidewall resistance for **greater tire deflection**

Good soil protection

The **new 10 km/h cyclic speed** allows you to reduce the inflation pressure by **up to 20%** for the same load in the field, compared to the 15km/h cyclic table.

⇒ For a given load of 13175 kilos, MICHELIN CEREXBIB 2 (VF 710/70 R42) allows you to **reduce the pressure in field by 0.4 bar**, at a speed of 10 km/h for cyclic loads. ✱

* MICHELIN CEREXBIB 2 VF 710/70 R42 CFO+ 188A8TL	1,20 (17)	1,60 (23)	2,00 (29)	2,40 (35)	2,80 (41)
Bar					
10 km/h Cyclic	9265	11390	12280	13175	14450
15 km/h Cyclic	8450	10385	11200	12015	13175
40 km/h		7750	8375	9000	10000



AIR SYSTEMS READY
CTIS compatible



EXCELLENT TRACTION
Better traction on slopes
Ability to work on wet soil



Productivity



Soil Protection



Traction & Flotation

AVAILABLE SIZES

FRONT		REAR	
IF 800/65 R32 CFO+ 181A8	VF 580/85 R42 CFO+ 183A8	VF 520/80 R26 CFO+ 168A8	VF 620/70 R30 CFO+ 175A8
VF 900/60 R32 CFO+ 191A8	VF 710/70 R42 CFO+ 188A8	VF 620/70 R26 CFO+ 173A8	VF 520/85 R30 CFO+ 172A8
IF 800/70 R32 CFO+ 185A8	VF 900/60 R42 CFO+ 195A8	VF 750/65 R26 CFO+ 180A8	VF 710/65 R30 CFO+ 179A8
VF 900/60 R38 CFO+ 193A8	VF 800/70 R46 CFO+ 199A8	VF 710/60 R30 CFO+ 179A8	VF 500/85 R34 CFO+ 172A8
IF 800/70 R38 CFO+ 187A8	VF 900/65 R46 CFO+ 199A8		
VF 520/85 R42 CFO+ 177A8			

MICHELIN RECOMMENDATIONS

VEHICLE N° 1

FRONT PRESSURE (bar / psi)
REAR PRESSURE (bar / psi)

VEHICLE N° 2


FRONT PRESSURE (bar / psi)
REAR PRESSURE (bar / psi)



agro.michelin.com



youtube.com/user/AgMichelin



MICHELIN