

THE MICHELIN X® LINE ENERGY™ Z+ TIRE

A long haul steer tire with a casing so durable it's designed to reach up to 1 million miles with up to 4 retreads.





The Michelin X® Line Energy™ Z+ tire delivers 17% more miles than its predecessor.⁽²⁾



.....

The Michelin X® Line Energy™ Z+ tire is 12% lower in rolling resistance than its predecessor.(3)

(3) Calculated based on internal ISO28580 rolling resistance testing; 295/75R22.5 LRH X[®] Line Energy™ Z+ vs. 275/80R22.5 LRH X[®] Line Energy™ Z (equivalent sizes).



THE MICHELIN® X® LINE ENERGY™ Z+ TIRE

Dual tread compound for long, even wear and maximum fuel efficiency.

Mileage Layer

- Advanced tread compound delivers exceptional wear (Top Layer).

Fuel and Durability Layer

- Cool running tread compound minimizes internal casing temperatures for extended casing life and fuel efficiency (Bottom Layer).



Infini-Coil Technology

1/8 mile steel cable wound circumferentially around the belt package to provide casing protection, consistent footprint and long, even wear.



Infini-Coil **Technology**


PowerCoil Technology

Casing ply made with high tensile steel cables infused with rubber to resist damage due to oxidation and friction for excellent casing durability and maximum retreading.



Regenion Technology

Evolving grooves open as tread wears for long lasting traction and control in all-weather conditions.



Line Haul	Regional	Urban	On/Off Road			
Recommen						

	Load Range		Tread Depth			Loaded Radius		Overall Diameter		Overall Width (‡)		Approved Wheels (Measuring wheel	Min. Dual Spacing (‡)		Revs Per	Max. Load and Pressure Single			Max. Load and Pressure Dual				
			32nds	mph	kph	in.	mm	in.	mm	in.	mm	listed first.)	in	mm	Mile Ibs.	lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
295/75R22.5	Н	45779	18	75	120	18.7	475	40.1	1019	11.1	282	8.25, 9.00	13.1	332	517	7160	123	3250	850	6610	123	3000	850

Note: Wheel listed first is the measuring wheel.

(*) Exceeding the lawful speed limit is neither recommended nor endorsed.

(‡) Overall width will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

Michelin tires and tubes are subject to a continuous development program. Michelin North America, Inc. reserves the right to change product specifications at any time without notice or obligations. MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect the current Load and Inflation information.

Please visit business michelinman com for the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions.

Never exceed a wheel manufacturer's limits without permission from the component manufacturer.



US: business.michelinman.com CA: business.michelin.ca





US: business.michelinman.com/contact-us CA: business.michelin.ca/contact-us

