MICHELIN X® WORKS Z2 TIRE

ON/OFF ROAD APPLICATIONS



The Michelin X® Works Z2 tire helps haul heavy and difficult loads wherever the next job takes you. It is designed to achieve the perfect balance of toughness, durability and wear for On/Off Road fleets.



MICHELIN ROAD HAZARD GUARANTEE

Line Haul	Regional	Urban	On/Off Road

Recommended Acceptable

business.michelinman.ca

MICHELIN

MICHELIN X® WORKS Z2 TIRE


Optimized Uptime in Aggressive On-Road and Off-Road Environments



- New tread compound for aggressive applications and chip and tear resistance
- Increased sidewall protection performance for rugged conditions and tough environments
- Proven tread pattern stands up to aggression while providing traction in demanding conditions



- Dual-layered defense against stone drilling
  - V-Channels – helps resist stone retention
  - Groove Bottom Protectors – helps prevent stone drilling



- Hard-packed cables to combat road hazards and protect the casing

MICHELIN ROAD HAZARD GUARANTEE

Michelin stands behind its on/off-road products—providing unsurpassed durability against road hazards and the uptime fl eets demand. With the Michelin Road Hazard Guarantee, Michelin will credit you 50% of your acquisition price per tire if the tire is taken out of service (not repairable or retreadable) in the first six months or before 50% of its useable tread life—whichever comes first.(1) It's just our way of helping you experience breakthrough performance and durability without the risk.

Size	Load Range	Catalog Number	Tread Depth	Max Speed*		Loaded Radius		Overall Diameter		Overall Width**		Approved Wheels (Measuring wheel listed first)	Min. Dual Spacing**		Revs Per Mile	Max. Load & Pressure Single				Max. Load & Pressure Dual			
			32nds	mph	km/h	in.	mm	in.	mm	in.	mm		in.	mm		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
11R22.5	H	03309	24	68	110	19.6	498	41.8	1061	11.3	287	8.25, 7.50	12.5	318	495	6610	120	3000	830	6005	120	2725	830
11R24.5	H	35699	24	68	110	20.6	522	43.8	1113	11.3	287	8.25, 7.50	12.5	318	472	7160	120	3250	830	6610	120	3000	830
315/80R22.5(2)	L	07481	23	68	110	19.7	501	42.8	1086	12.5	318	9.00, 9.75	13.8	351	486	10200	130	4625	900	9370	130	4250	900

Note: Wheel listed first is the measuring wheel.

(1) Contact your local Michelin representative for details. Michelin reserves the right to modify or discontinue this program at any time for any reason without prior notice.

(2) Not approved for use with an 8.25 wheel

* Exceeding the lawful speed limit is neither recommended nor endorsed.

** Overall width will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

Michelin tires and tubes are subject to a continuous development program. Michelin North America, Inc. reserves the right to change product specifications at any time without notice or obligations.

MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect the current Load and Inflation information. Please visit www.michelintruck.com for the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions. Never exceed a wheel manufacturer's limits without permission from the component manufacturer.

business.michelinman.ca

Michelin North America Inc., One Parkway South, Greenville, SC 29615
Michelin North America (Canada) Inc., 2500 Daniel Johnson Blvd., Suite 500, Laval (QC) H7T 2P6

Copyright © 2026 Michelin North America, Inc. All rights reserved. | © 2026 MNA(C)I. All rights reserved.
The Michelin Man is a registered trademark owned by Michelin. | Specifications subject to change without notice.
An Equal Opportunity Employer | PDF Only (BWA 9/26)

MICHELIN