



KLEBER Traker

**FOR YOUR TRACTORS
FROM 80 to 200 HP**



KLEBER Traker



LONGEVITY

- Flat crown guaranteeing an even distribution of pressure in the contact area.
- High tread lugs.
- Profile ensuring rapid self-cleaning



EFFICIENT PLOUGHING

- Flat crown and slightly rounded shoulders.



RELIABILITY

- A durable carcass and a rubber quality resistant to aggression



Sizes available

210/95 R16 106A8/106B TL	380/85 R24 131A8/128B TL	420/85 R30 140A8/137B TL	400/75 R38 138A8/135B TL
210/95 R18 108A8/108B TL	NEW 420/85 R24 142A8/139B TL	460/85 R30 145A8/142B TL	420/85 R38 144A8/141B TL
280/85 R20 122A8/122B TL	NEW 280/85 R28 118A8/115B TL	320/85 R32 126A8/123B TL	460/85 R38 149A8/146B TL
320/85 R20 119A8/116B TL	320/85 R28 124A8/121B TL	420/85 R34 142A8/139B TL	520/85 R38 155A8/152B TL
250/85 R24 109A8/106B TL	340/85 R28 127A8/124B TL	460/85 R34 147A8/144B TL	520/85 R42 157A8/157B TL
280/85 R24 115A8/112B TL	380/85 R28 133A8/130B TL	320/85 R36 128A8/125B TL	
320/85 R24 122A8/119B TL	420/85 R28 144A8/141B TL	340/85 R36 132A8/129B TL	
340/85 R24 130A8/127B TL	380/85 R30 135A8/132B TL	340/85 R38 133A8/130B TL	

Technical characteristics

DESCRIPTION		CAI [MSPN]	e mm	D mm	R' mm	RC mm	Measuring recommended rim	Other approved rims	Tube [code]	75% Internal volume liter	Tread depth mm				
210/95 R16 106A8/106B TL		758228	219	803	367	2394	W7	5.50F W6	317 431	39.75	27				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	485	585	630	680	715	755	790	830	865	900	975	1100	1225	1305	1420
30 km/h	415	485	520	555	590	625	660	695	730	765	835	935	1015		
40 km/h		455	490	520	555	585	620	650	685	715	780	870	950		
50 km/h			520	555	585	620	650	685	715	780	870	950			
210/95 R18 108A8/108B TL NEW		818854	217	854	389	2545	W7	5.50F W6	440 441	43.5	27				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	515	620	670	720	755	790	825	855	890	925	1015	1155	1290	1375	1500
30 km/h	440	515	550	585	625	660	695	730	770	805	870	970	1070		
40 km/h		480	515	550	585	620	650	685	720	755	815	910	1000		
50 km/h			550	585	620	655	685	720	755	815	910	1000			
280/85 R20 122A8/122B TL NEW		227122	286	980	440	2910	W9	W10 W8	542	78	35				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	760	915	990	1065	1125	1180	1240	1295	1355	1410	1525	1720	1915	2040	2220
30 km/h	650	760	815	870	925	975	1030	1085	1140	1195	1305	1455	1585		
40 km/h		710	760	810	860	910	965	1015	1065	1115	1220	1365	1500		
50 km/h			810	860	910	965	1015	1065	1115	1220	1365	1500			
320/85 R20 119A8/116B TL		161882 56173	332	1047	466	3104	W11	W10 W8	444	105	38				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1160	1275	1335	1395	1455	1510	1570	1630	1690	1745	1865	2040			
30 km/h	950	1050	1105	1155	1205	1255	1305	1360	1410	1460					
40 km/h		980	1030	1075	1125	1170	1220	1265	1315	1360					
50 km/h			980	1025	1070	1115	1160	1205	1250						
250/85 R24 109A8/106B TL		162160	248	1042	472	3101	W8	W7	686	68.25	37				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	880	970	1015	1060	1105	1150	1195	1235	1280	1325	1415	1550			
30 km/h	720	795	835	870	910	950	985	1025	1060	1100					
40 km/h		740	775	815	850	885	920	960	995	1030					
50 km/h			740	775	810	845	880	915	950						

To measure the loads per tire, it is imperative to weigh the tractor with the implement attached and raised.

• Field use without high and sustained torque: refer to the 10 km/h line.

• Field use with high and sustained torque: refer to the 30 km/h line.

• Use on slopes: add 0.4 bar.

• Intensive road use: add 0.4 bar.

• Front loader use: refer to the 10 km/h line.

Technical characteristics

DESCRIPTION		CAI [MSPN]	e mm	D mm	R' mm	RC mm	Measuring recommended rim	Other approved rims	Tube [code]	75% Internal volume liter	Tread depth mm				
280/85 R24 115A8/112B TL		161767	288	1100	493	3267	W10	W9	692	87.75	37				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1040	1145	1195	1250	1300	1350	1405	1455	1510	1560	1665	1820			
30 km/h	850	940	985	1030	1075	1120	1165	1210	1255	1300					
40 km/h		870	915	960	1000	1045	1090	1135	1175	1220					
50 km/h			870	910	955	995	1035	1080	1120						
320/85 R24 122A8/119B TL		161768	324	1149	516	3413	W11	W10	692	120.75	42				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1280	1410	1475	1540	1605	1670	1735	1795	1860	1925	2055	2250			
30 km/h	1040	1155	1210	1270	1325	1380	1440	1495	1555	1610					
40 km/h		1080	1135	1185	1240	1290	1345	1395	1450	1500					
50 km/h			1060	1110	1160	1210	1260	1310	1360						
340/85 R24 130A8/127B TL		760563 83063	363	1202	547	3580	W12	W11	700	138.75	43				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1410	1555	1625	1695	1765	1840	1910	1980	2050	2125	2265	2480	2620	2710	2850
30 km/h	1150	1275	1335	1400	1460	1520	1585	1645	1710	1770	1835	1935	2035		
40 km/h		1190	1250	1305	1365	1420	1480	1535	1595	1650	1715	1805	1900		
50 km/h			1170	1225	1280	1335	1390	1445	1500	1560	1645	1730			
380/85 R24 131A8/128B TL		161770	390	1252	551	3703	W13	W11 W12	703	180	40				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1670	1840	1920	2005	2090	2175	2260	2340	2425	2510	2680	2930			
30 km/h	1360	1505	1580	1650	1725	1800	1870	1945	2015	2090					
40 km/h		1400	1470	1540	1605	1675	1745	1815	1880	1950					
50 km/h			1400	1465	1535	1600	1665	1735	1800						
420/85 R24 142A8/139B TL		875390 74884	460	1329	598	3949	DW15L	DW14L W14L W15L	710	228	42				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1970	2165	2265	2365	2465	2560	2660	2760	2860	2955	3155	3450	3645	3780	3975
30 km/h	1600	1770	1860	1945	2030	2115	2200	2290	2375	2460	2555	2695	2835		
40 km/h		1660	1740	1820	1900	1980	2060	2140	2220	2300	2390	2520	2650		
50 km/h			1650	1730	1805	1885	1965	2040	2120	2195	2300	2410			

To measure the loads per tire, it is imperative to weigh the tractor with the implement attached and raised.

• Field use without high and sustained torque: refer to the 10 km/h line.

• Field use with high and sustained torque: refer to the 30 km/h line.

• Use on slopes: add 0.4 bar.

• Intensive road use: add 0.4 bar.

• Front loader use: refer to the 10 km/h line.

Technical characteristics

DESCRIPTION		CAI [MSPN]	e mm	D mm	R' mm	RC mm	Measuring recommended rim	Other approved rims	Tube [code]	75% Internal volume liter	Tread depth mm				
250/85 R28 112A8/109B TL		162161	247	1142	520	3403	W8	W7	725	75	37				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	960	1055	1105	1150	1200	1250	1295	1345	1390	1440	1535	1680			
30 km/h	780	865	905	950	990	1030	1075	1115	1160	1200					
40 km/h		810	850	890	925	965	1005	1045	1080	1120					
50 km/h			800	840	875	915	955	990	1030						
280/85 R28 118A8/115B TL		161885	297	1200	543	3571	W10	W9	725	99.75	39				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1130	1245	1300	1355	1415	1470	1525	1585	1640	1695	1810	1980			
30 km/h	920	1020	1065	1115	1165	1215	1265	1310	1360	1410					
40 km/h		950	995	1045	1090	1135	1180	1230	1275	1320					
50 km/h			950	995	1040	1085	1130	1175	1220						
320/85 R28 124A8/121B TL		161772	322	1253	562	3721	W11	W10	726	134.25	42				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1370	1505	1575	1645	1715	1780	1850	1920	1990	2055	2195	2400			
30 km/h	1110	1230	1290	1350	1410	1470	1530	1590	1650	1710					
40 km/h		1150	1205	1265	1320	1375	1430	1490	1545	1600					
50 km/h			1130	1185	1235	1290	1345	1395	1450						
340/85 R28 127A8/124B TL		161773	363	1307	586	3882	W12	W11 W12L	732	154.5	40				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1500	1650	1725	1800	1875	1950	2025	2105	2180	2255	2405	2630			
30 km/h	1220	1350	1415	1480	1545	1610	1675	1740	1805	1870					
40 km/h		1260	1320	1385	1445	1505	1565	1630	1690	1750					
50 km/h			1250	1310	1365	1425	1485	1540	1600						
380/85 R28 133A8/130B TL		161774 53490	391	1360	607	4034	W13	W11 W12	821	204	40				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1760	1935	2025	2115	2205	2290	2380	2470	2560	2645	2825	3090			
30 km/h	1430	1585	1660	1740	1815	1890	1970	2045	2125	2200					
40 km/h		1480	1555	1625	1700	1770	1845	1915	1990	2060					
50 km/h			1480	1550	1620	1690	1760	1830	1900						

To measure the loads per tire, it is imperative to weigh the tractor with the implement attached and raised.

• Field use without high and sustained torque: refer to the 10 km/h line.

• Field use with high and sustained torque: refer to the 30 km/h line.

• Use on slopes: add 0.4 bar.

• Intensive road use: add 0.4 bar.

• Front loader use: refer to the 10 km/h line.

Technical characteristics

DESCRIPTION		CAI [MSPN]	e mm	D mm	R' mm	RC mm	Measuring recommended rim	Other approved rims	Tube [code]	75% Internal volume liter	Tread depth mm				
420/85 R28 144A8/141B TL		955665 80647	458	1435	647	4267	DW15L	DW14L W14L W15L	822	251.25	47				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	2080	2290	2395	2500	2605	2710	2815	2915	3020	3125	3335	3650	3855	3995	4200
30 km/h	1690	1870	1965	2055	2145	2235	2325	2420	2510	2600	2700	2850	3000		
40 km/h		1750	1835	1920	2005	2090	2175	2260	2345	2430	2525	2660	2800		
50 km/h			1750	1830	1915	1995	2075	2160	2240	2320	2435	2550			
380/85 R30 135A8/132B TL		161886	396	1413	628	4188	W13	W12	734	214.5	43				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1860	2050	2140	2235	2330	2425	2520	2610	2705	2800	2990	3270			
30 km/h	1520	1680	1765	1845	1925	2005	2085	2170	2250	2330					
40 km/h		1570	1645	1725	1800	1875	1950	2030	2105	2180					
50 km/h			1560	1635	1705	1780	1855	1925	2000						
420/85 R30 140A8/137B TL		161776 92979	447	1474	657	4371	DW15L	DW14L W14L W15L	754	263.25	48				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	2140	2355	2460	2570	2675	2785	2890	3000	3105	3215	3430	3750			
30 km/h	1740	1930	2020	2115	2210	2305	2400	2490	2585	2680					
40 km/h		1800	1890	1975	2065	2150	2240	2325	2415	2500					
50 km/h			1790	1875	1960	2045	2130	2215	2300						
460/85 R30 145A8/142B TL		161887	478	1547	681	4574	DW16L	DW15L W15L W16L	757	325.5	50				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	2480	2730	2855	2980	3105	3230	3355	3475	3600	3725	3975	4350			
30 km/h	2020	2235	2345	2450	2560	2670	2775	2885	2990	3100					
40 km/h		2090	2190	2295	2395	2495	2595	2700	2800	2900					
50 km/h			2070	2165	2265	2360	2455	2555	2650						
320/85 R32 126A8/123B TL		161888 49112	330	1356	615	4037	W11	W10	760	153	40				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1450	1595	1670	1745	1815	1890	1965	2035	2110	2185	2330	2550			
30 km/h	1180	1310	1370	1435	1500	1565	1630	1690	1755	1820					
40 km/h		1220	1280	1340	1400	1460	1520	1580	1640	1700					
50 km/h			1210	1265	1325	1380	1435	1495	1550						

To measure the loads per tire, it is imperative to weigh the tractor with the implement attached and raised.

• Field use without high and sustained torque: refer to the 10 km/h line.

• Field use with high and sustained torque: refer to the 30 km/h line.

• Use on slopes: add 0.4 bar.

• Intensive road use: add 0.4 bar.

• Front loader use: refer to the 10 km/h line.

Technical characteristics

DESCRIPTION		CAI [MSPN]	e mm	D mm	R' mm	RC mm	Measuring recommended rim	Other approved rims	Tube [code]	75% Internal volume liter	Tread depth mm				
420/85 R34 142A8/139B TL		161777	442	1581	708	4693	DW15L	DW14L W14L W15L	704	293.25	46				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	2270	2500	2610	2725	2840	2955	3070	3180	3295	3410	3640	3980			
30 km/h	1840	2040	2140	2240	2340	2440	2540	2640	2740	2840					
40 km/h		1910	2005	2095	2190	2280	2375	2465	2560	2650					
50 km/h			1900	1990	2075	2165	2255	2340	2430						
460/85 R34 147A8/144B TL		161778	488	1659	737	4916	DW16L	DW15L W15L W16L	823	354.75	50				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	2630	2895	3025	3160	3290	3420	3555	3685	3820	3950	4215	4610			
30 km/h	2140	2370	2485	2600	2715	2830	2945	3060	3175	3290					
40 km/h		2210	2320	2430	2535	2645	2755	2865	2970	3080					
50 km/h			2180	2285	2385	2490	2595	2695	2800						
320/85 R36 128A8/125B TL		161779	323	1461	667	4357	W11	W10	779	165	43				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1540	1695	1770	1850	1925	2005	2080	2160	2235	2315	2470	2700			
30 km/h	1250	1385	1455	1520	1590	1660	1725	1795	1860	1930					
40 km/h		1300	1365	1425	1490	1550	1615	1675	1740	1800					
50 km/h			1290	1350	1410	1470	1530	1590	1650						
340/85 R36 132A8/129B TL		161780	354	1503	684	4478	W12	W11	780	192	43				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1710	1880	1970	2055	2140	2225	2310	2400	2485	2570	2740	3000			
30 km/h	1390	1540	1615	1690	1765	1840	1915	1990	2065	2140					
40 km/h		1440	1510	1580	1650	1720	1790	1860	1930	2000					
50 km/h			1440	1510	1575	1645	1715	1780	1850						
340/85 R38 133A8/130B TL		161781	361	1563	714	4661	W12	W11	795	193.5	46				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
Psi	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1760	1935	2025	2115	2205	2290	2380	2470	2560	2645	2825	3090			
30 km/h	1430	1585	1660	1740	1815	1890	1970	2045	2125	2200					
40 km/h		1480	1555	1625	1700	1770	1845	1915	1990	2060					
50 km/h			1480	1550	1620	1690	1760	1830	1900						

To measure the loads per tire, it is imperative to weigh the tractor with the implement attached and raised.

• Field use without high and sustained torque: refer to the 10 km/h line.

• Field use with high and sustained torque: refer to the 30 km/h line.

• Use on slopes: add 0.4 bar.

• Intensive road use: add 0.4 bar.

• Front loader use: refer to the 10 km/h line.

Technical characteristics

DESCRIPTION		CAI [MSPN]	e mm	D mm	R' mm	RC mm	Measuring recommended rim	Other approved rims	Tube [code]	75% Internal volume liter	Tread depth mm				
400/75 R38 138A8/135B TL		447557	404	1563	704	4647	DW14L	W12 W13 W14L	796	238.5	42				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	1925	2140	2245	2350	2460	2565	2670	2780	2885	2990	3205	3525			
30 km/h	1370	1600	1715	1830	1945	2055	2170	2285	2400	2515					
40 km/h		1495	1605	1710	1820	1925	2035	2145	2250	2360					
50 km/h				1555	1655	1750	1850	1945	2065	2180					
420/85 R38 144A8/141B TL		161782	445	1665	748	4947	DW15L	DW14L W14L W15L	786	322.5	48				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	2390	2630	2750	2875	2995	3115	3235	3355	3475	3595	3840	4200			
30 km/h	1950	2160	2265	2370	2475	2580	2685	2790	2895	3000					
40 km/h		2020	2120	2215	2315	2410	2510	2605	2705	2800					
50 km/h				2010	2105	2200	2295	2390	2485	2580					
40 km/h FRT				2425	2540	2660	2775	2895	3010	3125	3360				
460/85 R38 149A8/146B TL		161783 67062	488	1754	786	5208	DW16L	DW15L W15L W16L	824	383.25	50				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	2780	3060	3200	3340	3480	3620	3760	3900	4040	4180	4460	4880			
30 km/h	2260	2505	2625	2750	2870	2990	3115	3235	3360	3480					
40 km/h		2340	2455	2570	2680	2795	2910	3025	3135	3250					
50 km/h				2340	2450	2560	2670	2780	2890	3000					
40 km/h FRT				2810	2945	3085	3220	3355	3490	3630	3900				
520/85 R38 155A8/152B TL		161784 49040	541	1838	820	5452	DW18L	DW16L W16L W18L	825	517.5	56				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	3310	3645	3810	3975	4145	4310	4475	4645	4810	4975	5310	5810			
30 km/h	2700	2990	3135	3280	3425	3570	3715	3860	4005	4150					
40 km/h		2790	2925	3065	3200	3335	3470	3610	3745	3880					
50 km/h				2770	2900	3030	3160	3290	3420	3550					
40 km/h FRT				3350	3515	3680	3840	4005	4170	4335	4660				
520/85 R42 157A8/157B TL		656000	557	1948	867	5776	DW18L	DW16L W16L W18L	802	544.5	52				
Bar	0.60	0.80	0.90	1.00	1.10	1.20	1.30	1.40	1.50	1.60	1.80	2.10	2.40	2.60	2.90
<i>Psi</i>	9	12	13	15	16	17	19	20	22	23	26	30	35	38	42
10 km/h	3310	3645	3810	3975	4145	4310	4475	4645	4810	4975	5310	5810			
30 km/h	2700	2990	3135	3280	3425	3570	3715	3860	4005	4150					
40 km/h		2790	2925	3065	3200	3335	3470	3610	3745	3880					
50 km/h				2770	2900	3030	3160	3290	3420	3550					
40 km/h FRT				3350	3515	3680	3840	4005	4170	4335	4660				

To measure the loads per tire, it is imperative to weigh the tractor with the implement attached and raised.

• Field use without high and sustained torque: refer to the 10 km/h line.

• Field use with high and sustained torque: refer to the 30 km/h line.

• Use on slopes: add 0.4 bar.

• Intensive road use: add 0.4 bar.

• Front loader use: refer to the 10 km/h line.