MICHELIN TYRES APPROVED FOR ROAD USE DNT CAI Dimensions 833295 110/70 ZR 17 (54W) 120/70 ZR 17 (58W) 149126 Dimensions CAI 389695 140/70 ZR 17 (66W) N Л 981679 150/60 ZR 17 (66W) Л 050185 160/60 ZR 17 (69W) 180/55 ZR 17 (73W) 857557 190/55 ZR 17 (75W) 534402 140448 200/55 ZR 17 (78W) N = NEW Minimum cold 1.5 2.1 pressure on track (1) A For road use, comply with the constructor's pressure recommendations. THE TREADED VERSION OF THE SLICK TYRE 2 An exceptional level of grip for a multipurpose road-approved tyre WHAT TYRES SHOULD • Quick control, without specific adjustments **BE USED IN COMPETITION** to the bike FOR A 300CC BIKE? • Straight line stability and optimum hold while MICHELIN Power Cup Evo is now available in four new cornering with the Michelin "Adaptive Casing dimensions: Technology" (ACT) • For the front: 110/70 ZR 17 (54W) • For the rear: 140/70 ZR 17 (66W), 150/60 ZR 17 (66W) & 160/60 ZR 17 (69W) The solution for 300cc bikes!

ROAD-APPROVED TRACK USE

 Pressure taken with tyre and rim at ambient temperature, just before the first ride or just before installing the tyre warmers.