

**NEW****PILOT SPORT H S5C**

- Quick warm up, like its predecessor
- Consistency throughout the climb
- New mixture that has greatly reduced pickup



## REFERENCES AND TECHNICAL CHARACTERISTICS

CAI	DESIGNATION	TYPE	RECOMMENDED RIM (")	TREAD WIDTH (MM)	TYRE SECTION (MM)	INFLATED DIAMETER (MM)	ROLLING CIRCUMFERENCE (MM)	
	417166	<b>20/54 - 13</b>	S5C	9J13	199	245	541	1661
<b>N</b>	166944	<b>22/54 - 13</b>	S5C	10J13	220	270	541	1661
<b>N</b>	799284	<b>24/57 - 13</b>	S5C	10J13	241	289	585	1765
	308815	<b>26/64 - 13</b>	S5C	12J13	288	328	634	1958
	024687	<b>19/57 - 15</b>	S5B	7J17	185	212	568	1759
<b>N</b>	546802	<b>19/57 - 15</b>	S5C	7J17	185	206	573	1774
	816036	<b>20/61 - 17</b>	S5B	8J17	190	221	604	1861
<b>N</b>	384649	<b>20/61 - 17</b>	S5C	8J17	187	219	606	1870
	628978	<b>24/61 - 17</b>	S5B	9J17	235	249	605	1872
<b>N</b>	562022	<b>24/61 - 17</b>	S5C	9J17	235	250	605	1857
	833429	<b>24/65 - 18</b>	S5A	9J18	229	251	647	1988
<b>N</b>	658524	<b>24/65 - 18</b>	S5C	9J18	229	251	647	1988
	869437	<b>27/65 - 18</b>	S5A	11J18	262	298	647	1988
<b>N</b>	547868	<b>27/65 - 18</b>	S5C	11J18	262	298	647	1988
<b>N</b>	667424	<b>30/65 - 18</b>	S5C	12.5J18	288	329	650	1996
<b>N</b>	472130	<b>31/71 - 18</b>	S5C	13J18	316	343	709	2192

⚠ The technical data contained in this document is given for information purposes only. Checks must be made under real conditions.

**N** = NEW