

REFERENCES AND TECHNICAL CHARACTERISTICS

CAI	DESIGNATION	TYPE	PROFILE	RECOMMENDED RIM (")	TREAD WIDTH (MM)	TYRE SECTION (MM)	INFLATED DIAMETER (MM)	ROLLING CIRCUMFERENCE (MM)
174056	20/54 - 13	S412 RFID	Medium	9	199	245	541	1661
280983	20/54 - 13	P412	Rain	9	199	246	540	1658
566639	22/54 - 13	S412 RFID	Medium	10	220	270	541	1661
013656	22/54 - 13	P412	Rain	10	222	269	540	1658
668917	24/57 - 13	S412 RFID	Medium	10	241	289	575	1765
327040	24/57 - 13	P412	Rain	10	244	288	600	1842
451019	32/66 - 13	S412	Medium	13,7	308	379	656	2023
554920	32/66 - 13	P412	Rain	13,7	310	380	654	2013
N 188873	33/65 - 18	S819 RFID	Medium/Hard	13,5	312	357	651	2019
N 012133	33/65 - 18	P219	Rain	13,5	312	357	651	2008
N 840076	33/68 - 18	S819 RFID	Hard	13,5	312	360	681	2110
N 627171	33/68 - 18	P219	Rain	13,5	312	360	681	2095
N 466857	36/71 - 18	S819 RFID	Medium/Hard	14,5	350	391	710	2200
N 476628	36/71 - 18	P219	Rain	14,5	350	391	710	2189
N 993138	37/71 - 18	S819 RFID	Medium/Hard	14,5	356	400	715	2220

⚠ The technical data contained in this document is given for information purposes only. Checks must be made under real conditions.

N = NEW

