

## REFERENCES AND TECHNICAL CHARACTERISTICS

CAI	DESIGNATION	TYPE	PROFILE	RECOMMENDED RIM (")	TREAD WIDTH (MM)	TYRE SECTION (MM)	INFLATED DIAMETER (MM)	ROLLING CIRCUMFERENCE (MM)
386513	<b>25/64 - 18</b>	N2	Hard	9,5	249	271	642	1990
448993	<b>25/64 - 18</b>	P2L	Rain	10	231	269	647	2031
907466	<b>27/65 - 18</b>	N2#	Hard	11	263	295	646	2025
463077	<b>27/65 - 18</b>	P2L	Rain	11	260	299	652	2048
587114	<b>27/68 - 18</b>	N2	Hard	11	265	306	679	2111
765707	<b>27/68 - 18</b>	P2L	Rain	11	255	295	684	2147
628143	<b>30/68 - 18</b>	N2	Hard	12	298	327	680	2108
447350	<b>30/68 - 18</b>	P2L	Rain	12,5	311	329	684	2150
297596	<b>31/71 - 18</b>	N2	Hard	13	314	348	707	2131
797297	<b>31/71 - 18</b>	P2L	Rain	13	313	347	711	2232

⚠ The technical data contained in this document is given for information purposes only. Checks must be made under real conditions.

