



TAURUS POINT 8

- ✓ Standard 85-series
- ✓ Modern tread pattern design
- ✓ Tubeless
- ✓ Proven durability

SIZES

11.2 R20 111A8/108B TL

11.2 R24 114A8/111B TL

12.4 R24 119A8/116B TL

13.6 R24 121A8/118B TL

14.9 R24 126A8/123B TL

16.9 R24 134A8/131B TL

11.2 R28 116A8/113B TL

12.4 R28 121A8/118B TL

13.6 R28 123A8/120B TL

14.9 R28 128A8/125B TL

16.9 R28 136A8/133B TL

14.9 R30 129A8/126B TL

16.9 R30 137A8/134B TL

18.4 R30 142A8/139B TL

12.4 R32 122A8/119B TL

16.9 R34 139A8/136B TL

18.4 R34 144A8/141B TL

12.4 R36 124A8/121B TL

13.6 R36 127A8/124B TL

13.6 R38 128A8/125B TL

16.9 R38 141A8/138B TL

18.4 R38 146A8/143B TL

20.8 R38 153A8/150B TL

20.8 R42 155A8/152B TL

TAURUS POINT 8

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
20	11.2 R20 111A8/108B TL	085018	295	995	446	2954	W10	W7 W8 W9	542	75	37		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	780	880	980	1025	1070	1155	1240	1275	1310	1385	1460		
25 km/h	640	725	810	850	890	960	1030	1055	1080	1145	1210		
30 km/h	620	700	780	820	860	925	990	1015	1040	1105	1170		
40 km/h	580	655	730	765	800	865	925	950	975	1035	1090		
50 km/h							840	865	890	940	990		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	11.2 R24 114A8/111B TL	523567	283	1084	497	3253	W10	W9	692	80	42		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	820	930	1040	1090	1140	1240	1340	1380	1420	1500	1580		
25 km/h	680	770	860	900	940	1025	1110	1145	1180	1245	1310		
30 km/h	660	745	830	870	910	990	1070	1100	1130	1195	1260		
40 km/h	615	695	775	815	850	925	1000	1030	1060	1120	1180		
50 km/h							910	935	960	1015	1070		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	12.4 R24 119A8/116B TL	039023	325	1141	517	3396	W11	W10 W9	692	116	42		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	950	1080	1210	1275	1340	1440	1540	1585	1630	1725	1820		
25 km/h	790	895	1000	1055	1110	1195	1280	1315	1350	1430	1510		
30 km/h	760	860	960	1015	1070	1150	1230	1265	1300	1380	1460		
40 km/h	710	805	900	950	1000	1075	1150	1185	1215	1290	1360		
50 km/h							1050	1080	1110	1175	1240		

* Refer to the notes at the end of the tables of this range

TAURUS POINT 8

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	13.6 R24 121A8/118B TL	039029	359	1196	536	3578	W12	W11	W11	W11	700	137	46
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1010	1140	1270	1325	1380	1480	1580	1630	1680	1810	1940		
25 km/h	830	940	1050	1095	1140	1225	1310	1350	1390	1500	1610		
30 km/h	800	910	1020	1060	1100	1180	1260	1300	1340	1445	1550		
40 km/h	750	850	950	990	1030	1105	1180	1215	1250	1350	1450		
50 km/h							1070	1105	1140	1230	1320		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	14.9 R24 126A8/123B TL	733804	390	1250	561	3710	W13	W11	W12	W11	703	176	46
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1170	1335	1500	1565	1630	1755	1880	1945	2010	2145	2280		
25 km/h	970	1105	1240	1295	1350	1450	1550	1610	1670	1780	1890		
30 km/h	940	1070	1200	1250	1300	1400	1500	1555	1610	1715	1820		
40 km/h	875	995	1120	1170	1215	1310	1400	1450	1500	1600	1700		
50 km/h							1270	1320	1370	1460	1550		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	16.9 R24 134A8/131B TL	615665	454	1324	594	3933	DW15L	DW14L	W14L	W15L	710	228	44
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1270	1450	1630	1810	1990	2170	2350	2475	2595	2720	2840		
25 km/h	1050	1200	1345	1495	1645	1790	1940	2045	2145	2250	2350		
30 km/h	1020	1160	1305	1445	1585	1730	1870	1970	2070	2170	2270		
40 km/h	950	1085	1215	1350	1485	1615	1750	1845	1935	2030	2120		
50 km/h							1500	1600	1700	1800	1900		

* Refer to the notes at the end of the tables of this range

TAURUS POINT 8

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
28	11.2 R28 116A8/113B TL	093269	291	1201	554	3622	W10	W9	725	99	43		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	870	990	1110	1175	1240	1330	1420	1460	1500	1590	1680		
25 km/h	720	820	920	975	1030	1105	1180	1210	1240	1315	1390		
30 km/h	700	790	880	935	990	1060	1130	1165	1200	1270	1340		
40 km/h	650	740	825	875	925	995	1060	1090	1120	1185	1250		
50 km/h							960	990	1020	1080	1140		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
28	12.4 R28 121A8/118B TL	093032	323	1254	573	3770	W11	W10 W9	726	128	43		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1040	1175	1310	1365	1420	1525	1630	1700	1770	1855	1940		
25 km/h	860	970	1080	1130	1180	1265	1350	1410	1470	1540	1610		
30 km/h	830	935	1040	1085	1130	1215	1300	1355	1410	1480	1550		
40 km/h	775	875	975	1020	1060	1140	1215	1270	1320	1385	1450		
50 km/h							1110	1155	1200	1260	1320		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
28	13.6 R28 123A8/120B TL	093283	370	1284	579	3817	W12	W11	732	150	45		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1070	1205	1340	1400	1460	1590	1720	1770	1820	1950	2080		
25 km/h	890	1000	1110	1160	1210	1320	1430	1470	1510	1615	1720		
30 km/h	860	965	1070	1120	1170	1270	1370	1415	1460	1560	1660		
40 km/h	800	900	1000	1045	1090	1190	1285	1325	1360	1455	1550		
50 km/h							1170	1205	1240	1325	1410		

* Refer to the notes at the end of the tables of this range

TAURUS POINT 8

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	14.9 R28 128A8/125B TL	869675	406	1347	604	3999	W13		W12		821	193	43
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1270	1425	1580	1675	1770	1890	2010	2075	2140	2275	2410		
25 km/h	1050	1180	1310	1390	1470	1570	1670	1725	1780	1890	2000		
30 km/h	1020	1140	1260	1335	1410	1510	1610	1660	1710	1820	1930		
40 km/h	950	1065	1180	1250	1320	1410	1500	1550	1600	1700	1800		
50 km/h							1370	1415	1460	1550	1640		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	16.9 R28 136A8/133B TL	039043	446	1418	628	4240	DW15L		DW14L W14L W15L		822	248	48
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1540	1740	1940	2040	2140	2310	2480	2545	2610	2805	3000		
25 km/h	1280	1445	1610	1695	1780	1915	2050	2105	2160	2325	2490		
30 km/h	1230	1390	1550	1630	1710	1845	1980	2035	2090	2245	2400		
40 km/h	1150	1300	1450	1525	1600	1725	1850	1900	1950	2095	2240		
50 km/h							1680	1725	1770	1905	2040		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	14.9 R30 129A8/126B TL	527022	384	1408	633	4185	W13		W12		734	211	46
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1310	1470	1630	1725	1820	1950	2080	2145	2210	2345	2480		
25 km/h	1080	1215	1350	1430	1510	1615	1720	1775	1830	1940	2050		
30 km/h	1040	1170	1300	1380	1460	1560	1660	1715	1770	1875	1980		
40 km/h	975	1095	1215	1290	1360	1455	1550	1600	1650	1750	1850		
50 km/h							1410	1455	1500	1590	1680		

* Refer to the notes at the end of the tables of this range

TAURUS POINT 8

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	16.9 R30 137A8/1348 TL	093248	452	1463	655	4343	DW15L		DW14L W14L W15L		754	268	48
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1580	1795	2010	2110	2210	2380	2550	2615	2680	2880	3080		
25 km/h	1310	1490	1670	1750	1830	1970	2110	2165	2220	2385	2550		
30 km/h	1260	1435	1610	1690	1770	1900	2030	2085	2140	2300	2460		
40 km/h	1180	1340	1500	1575	1650	1775	1900	1950	2000	2150	2300		
50 km/h							1730	1775	1820	1955	2090		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	18.4 R30 142A8/1398 TL	039066	467	1545	675	4613	DW16L		DW15L W15L W16L		757	350	49
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1880	2115	2350	2480	2610	2805	3000	3080	3160	3355	3550		
25 km/h	1550	1745	1940	2050	2160	2325	2490	2555	2620	2780	2940		
30 km/h	1500	1685	1870	1980	2090	2245	2400	2465	2530	2685	2840		
40 km/h	1400	1575	1750	1850	1950	2095	2240	2300	2360	2505	2650		
50 km/h							2040	2095	2150	2280	2410		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
32	12.4 R32 122A8/1198 TL	093280	327	1350	611	4016	W11		W10		760	137	45
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1040	1190	1340	1400	1460	1570	1680	1750	1820	1915	2010		
25 km/h	860	985	1110	1160	1210	1300	1390	1450	1510	1590	1670		
30 km/h	830	950	1070	1120	1170	1255	1340	1400	1460	1535	1610		
40 km/h	775	890	1000	1045	1090	1170	1250	1305	1360	1430	1500		
50 km/h							1140	1190	1240	1305	1370		

* Refer to the notes at the end of the tables of this range

TAURUS POINT 8

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
34	16.9 R34 139A8/136B TL	039010	448	1573	706	4672	DW15L	DW14L W14L W15L	704	288	48		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1675	1845	2010	2180	2345	2515	2680	2770	2860	2950	3040		
25 km/h	1390	1530	1670	1805	1945	2085	2220	2340	2460	2575	2695		
30 km/h	1340	1475	1605	1740	1875	2005	2140	2255	2370	2485	2600		
40 km/h	1250	1375	1500	1625	1750	1875	2000	2110	2215	2325	2430		
50 km/h							1820	1920	2015	2115	2210		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
34	18.4 R34 144A8/141B TL	625296	480	1646	740	4890	DW16L	DW15L W15L W16L	823	362	49		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	2010	2280	2550	2655	2760	3010	3260	3355	3450	3600	3750		
25 km/h	1670	1890	2110	2200	2290	2495	2700	2780	2860	2985	3110		
30 km/h	1610	1820	2030	2115	2200	2400	2600	2680	2760	2880	3000		
40 km/h	1500	1700	1900	1980	2060	2245	2430	2505	2575	2690	2800		
50 km/h							2210	2275	2340	2445	2550		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
36	12.4 R36 124A8/121B TL	039036	318	1455	668	4375	W11	W10	779	152	43		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1140	1280	1420	1480	1540	1680	1820	1880	1940	2040	2140		
25 km/h	940	1060	1180	1230	1280	1395	1510	1560	1610	1695	1780		
30 km/h	910	1020	1130	1180	1230	1345	1460	1505	1550	1630	1710		
40 km/h	850	955	1060	1105	1150	1255	1360	1405	1450	1525	1600		
50 km/h							1240	1280	1320	1390	1460		

* Refer to the notes at the end of the tables of this range

TAURUS POINT 8

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
36	13.6 R36 127A8/124B TL	039039	364	1500	685	4473	W12	W11	780	189	45		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1240	1410	1580	1650	1720	1865	2010	2045	2080	2215	2350		
25 km/h	1030	1170	1310	1370	1430	1550	1670	1695	1720	1830	1940		
30 km/h	990	1125	1260	1315	1370	1490	1610	1635	1660	1765	1870		
40 km/h	925	1055	1180	1235	1285	1395	1500	1525	1550	1650	1750		
50 km/h							1370	1390	1410	1500	1590		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
38	13.6 R38 128A8/125B TL	039041	369	1559	710	4646	DW12	W11 W12	795	206	46		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
15 km/h	1270	1425	1580	1675	1770	1890	2010	2075	2140	2275	2410		
25 km/h	1050	1180	1310	1390	1470	1570	1670	1725	1780	1890	2000		
30 km/h	1020	1140	1260	1335	1410	1510	1610	1660	1710	1820	1930		
40 km/h	950	1065	1180	1250	1320	1410	1500	1550	1600	1700	1800		
50 km/h							1370	1415	1460	1550	1640		

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
38	16.9 R38 141A8/138B TL	093446	439	1677	757	5030	DW15L	DW14L W14L W15L	786	313	49		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
10 km/h **		2100	2250	2400	2550	2700	2850	3105	3360	3615	3870		
30 km/h		1660	1785	1905	2030	2150	2275	2395	2515	2640	2760		
40 km/h					1850	1985	2120	2235	2350	2460	2575		
50 km/h							1930	1985	2040	2190	2340		
max 40 km/h FRT							2220	2365	2510	2655	2800	2945	3090

* Refer to the notes at the end of the tables of this range

TAURUS POINT 8

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	18.4 R38 146A8/143B TL	521555	498	1755	783	5205	DW16L	DW15L W15L W16L	824	418	47		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
10 km/h **	2475	2635	2795	2950	3110	3270	3580	3885	4195	4500			
30 km/h	1930	2030	2130	2230	2330	2475	2625	2770	2915	3065	3210		
40 km/h				2180	2380	2575	2680	2790	2895	3000			
50 km/h						2340	2410	2480	2605	2730			
max 40 km/h FRT						2615	2780	2945	3110	3270	3435	3600	

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	20.8 R38 153A8/150B TL	413224	525	1846	822	5473	DW18L	DW16L W16L W18L	825	510	50		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
10 km/h **	3000	3195	3390	3585	3780	3975	4350	4725	5100	5475			
30 km/h	2330	2500	2670	2840	3020	3195	3375	3555	3730	3910			
40 km/h				2650	2865	3075	3220	3365	3505	3650			
50 km/h						2800	2880	2960	3140	3320			
max 40 km/h FRT						3180	3380	3580	3780	3980	4180	4380	

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
42	20.8 R42 155A8/152B TL	659276	523	1940	870	5761	DW18L	DW16L W16L W18L	802	548	50		
Bar	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8
Psi	9	10	12	13	15	16	17	19	20	22	23	25	26
10 km/h **	3180	3385	3590	3790	3995	4200	4405	4605	4810	5010	5215	5415	
30 km/h	2400	2600	2800	3000	3215	3435	3650	3865	4085	4300			
40 km/h				2855	3055	3250	3405	3565	3720	3875			
50 km/h						2960	3110	3255	3405	3550			
max 40 km/h FRT						3425	3630	3835	4040	4240	4445	4650	

*IMPORTANT:

The inflation pressure must always be appropriate for the load per TYRE, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (July 2019). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h line.
- When using single TYRE configuration:
 - add 0.4 bar for use on slopes of more than 20%
 - add 0.4 bar for intensive road use exceeding 50%
- **10 km/h LT (Low Torque) (max speed 10 km/h).