



# TAURUS POINT 65

- ✓ Tread pattern providing greater soil protection
- ✓ Lower tyre pressure
- ✓ Improved yield

## SIZES

440/65 R24 128A8/128B TL

480/65 R24 133A8/133B TL

480/65 R28 136A8/136B TL

540/65 R28 142A8/142B TL

540/65 R30 143A8/143B TL

540/65 R34 145A8/145B TL

600/65 R34 151A8/151B TL

600/65 R38 153A8/153B TL

650/65 R38 157A8/157B TL

650/65 R42 158A8/158B TL

# TAURUS POINT 65

Tyre specifications and pressure table (bar & psi). Load per tyre in kg\*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>24</b>	<b>440/65 R24 128A8/128B TL</b>	529617	430	1194	528	3542	DW14L		DW13 DW15L W13 W14L W15L	703	154	39		
<b>Bar</b>	<b>0.6</b>	<b>0.8</b>	<b>1.0</b>	<b>1.1</b>	<b>1.2</b>	<b>1.3</b>	<b>1.4</b>	<b>1.5</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>	<b>1.9</b>	<b>2.0</b>	<b>2.1</b>
<b>Psi</b>	9	12	15	16	17	19	20	22	23	25	26	28	29	30
10 km/h **		1645	1840	1940	2040	2110	2185	2255	2325	2420	2515	2605	2700	
30 km/h		1260	1455	1560	1660	1725	1795	1860	1925					
40 km/h			1360	1455	1550	1615	1675	1740	1800					
50 km/h			1360	1455	1550	1615	1675	1740	1800					
40 km/h Dual		1045	1200	1285	1365	1420	1475	1530	1585					

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>24</b>	<b>480/65 R24 133A8/133B TL</b>	224881	471	1234	548	3657	DW15L		DW14L W14L W15L	710	218	40		
<b>Bar</b>	<b>0.6</b>	<b>0.8</b>	<b>1.0</b>	<b>1.1</b>	<b>1.2</b>	<b>1.3</b>	<b>1.4</b>	<b>1.5</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>	<b>1.9</b>	<b>2.0</b>	<b>2.1</b>
<b>Psi</b>	9	12	15	16	17	19	20	22	23	25	26	28	29	30
10 km/h **		1860	2040	2140	2235	2335	2430	2530	2625	2740	2860	2975	3090	
30 km/h		1420	1660	1770	1875	1960	2040	2125	2205					
40 km/h			1550	1650	1750	1830	1905	1985	2060					
50 km/h			1550	1650	1750	1830	1905	1985	2060					
40 km/h Dual		1200	1365	1455	1540	1610	1680	1745	1815					

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>28</b>	<b>480/65 R28 136A8/136B TL</b>	632102	479	1337	591	3959	DW15L		DW14L W14L W15L	822	242	42		
<b>Bar</b>	<b>0.6</b>	<b>0.8</b>	<b>1.0</b>	<b>1.1</b>	<b>1.2</b>	<b>1.3</b>	<b>1.4</b>	<b>1.5</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>	<b>1.9</b>	<b>2.0</b>	<b>2.1</b>
<b>Psi</b>	9	12	15	16	17	19	20	22	23	25	26	28	29	30
10 km/h **		1995	2235	2355	2475	2630	2785	2935	3090	3155	3220	3285	3350	
30 km/h		1560	1795	1915	2035	2125	2220	2310	2400					
40 km/h			1650	1775	1900	1985	2070	2155	2240					
50 km/h			1650	1775	1900	1985	2070	2155	2240					

\* Refer to the notes at the end of the tables of this range

# TAURUS POINT 65

Tyre specifications and pressure table (bar & psi). Load per tyre in kg\*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>28</b>	<b>540/65 R28 142A8/142B TL</b>	987252	529	1414	622	4187	DW16L		DW18L W16L		822	317	45	
<b>Bar</b>	<b>0.6</b>	<b>0.8</b>	<b>1.0</b>	<b>1.1</b>	<b>1.2</b>	<b>1.3</b>	<b>1.4</b>	<b>1.5</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>	<b>1.9</b>	<b>2.0</b>	<b>2.1</b>
<b>Psi</b>	9	12	15	16	17	19	20	22	23	25	26	28	29	30
10 km/h **	2000	2335	2665	2835	3000	3125	3250	3375	3500	3625	3750	3875	4000	
30 km/h	1605	1870	2135	2270	2400	2510	2620	2730	2840					
40 km/h		1750	2000	2120	2240	2345	2445	2550	2650					
50 km/h			2000	2120	2240	2345	2445	2550	2650					

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>30</b>	<b>540/65 R30 143A8/143B TL</b>	391329	522	1470	648	4347	DW16L		DW18L W16L W18L		754	333	45	
<b>Bar</b>	<b>0.6</b>	<b>0.8</b>	<b>1.0</b>	<b>1.1</b>	<b>1.2</b>	<b>1.3</b>	<b>1.4</b>	<b>1.5</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>	<b>1.9</b>	<b>2.0</b>	<b>2.1</b>
<b>Psi</b>	9	12	15	16	17	19	20	22	23	25	26	28	29	30
10 km/h **		2480	2785	2935	3090	3285	3475	3670	3860	3920	3975	4035	4090	
30 km/h		1925	2190	2325	2460	2575	2690	2800	2915					
40 km/h			2060	2180	2300	2405	2515	2620	2725					
50 km/h			2060	2180	2300	2405	2515	2620	2725					

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>34</b>	<b>540/65 R34 145A8/145B TL</b>	688712	540	1560	692	4621	DW16L		DW18L W16L W18L		704	364	44	
<b>Bar</b>	<b>0.6</b>	<b>0.8</b>	<b>1.0</b>	<b>1.1</b>	<b>1.2</b>	<b>1.3</b>	<b>1.4</b>	<b>1.5</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>	<b>1.9</b>	<b>2.0</b>	<b>2.1</b>
<b>Psi</b>	9	12	15	16	17	19	20	22	23	25	26	28	29	30
10 km/h **	2325	2610	2895	3040	3180	3325	3465	3610	3750	3870	3990	4110	4230	4350
30 km/h	1765	2070	2370	2525	2675	2785	2890	3000	3105					
40 km/h	1650	1935	2215	2360	2500	2600	2700	2800	2900					
50 km/h	1650	1935	2215	2360	2500	2600	2700	2800	2900					
40 km/h Dual	1450	1700	1950	2075	2200	2290	2375	2465	2550					

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>34</b>	<b>600/65 R34 151A8/151B TL</b>	681849	591	1644	736	4880	DW20B (A)		DW18L W18L		823	461	47	
<b>Bar</b>	<b>0.6</b>	<b>0.8</b>	<b>1.0</b>	<b>1.1</b>	<b>1.2</b>	<b>1.3</b>	<b>1.4</b>	<b>1.5</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>	<b>1.9</b>	<b>2.0</b>	<b>2.1</b>
<b>Psi</b>	9	12	15	16	17	19	20	22	23	25	26	28	29	30
10 km/h **		3110	3485	3675	3860	4025	4190	4355	4520	4680	4845	5010	5175	
30 km/h		2420	2755	2930	3105	3250	3400	3545	3690					
40 km/h			2575	2740	2900	3040	3175	3315	3450					
50 km/h			2575	2740	2900	3040	3175	3315	3450					
40 km/h Dual		1950	2265	2410	2550	2670	2795	2915	3035					

\* Refer to the notes at the end of the tables of this range

# TAURUS POINT 65

Tyre specifications and pressure table (bar & psi). Load per tyre in kg\*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)			
<b>38</b>	<b>600/65 R38 153A8/153B TL</b>	579551	591	1745	787	5188	DW20B (A)	DW18LW18L	825	498	51			
<b>Bar</b>	<b>0.6</b>	<b>0.8</b>	<b>1.0</b>	<b>1.1</b>	<b>1.2</b>	<b>1.3</b>	<b>1.4</b>	<b>1.5</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>	<b>1.9</b>	<b>2.0</b>	<b>2.1</b>
<b>Psi</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>16</b>	<b>17</b>	<b>19</b>	<b>20</b>	<b>22</b>	<b>23</b>	<b>25</b>	<b>26</b>	<b>28</b>	<b>29</b>	<b>30</b>
10 km/h **	3290	3690	3890	4090	4265	4435	4610	4785	4955	5130	5300	5475		
30 km/h	2530	2925	3090	3250	3415	3580	3740	3905						
40 km/h		2735	2905	3075	3220	3365	3505	3650						
50 km/h		2735	2905	3075	3220	3365	3505	3650						

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)			
<b>38</b>	<b>650/65 R38 157A8/157B TL</b>	764412	645	1811	812	5378	DW20B (A)		825	599	52			
<b>Bar</b>	<b>0.6</b>	<b>0.8</b>	<b>1.0</b>	<b>1.1</b>	<b>1.2</b>	<b>1.3</b>	<b>1.4</b>	<b>1.5</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>	<b>1.9</b>	<b>2.0</b>	<b>2.1</b>
<b>Psi</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>16</b>	<b>17</b>	<b>19</b>	<b>20</b>	<b>22</b>	<b>23</b>	<b>25</b>	<b>26</b>	<b>28</b>	<b>29</b>	<b>30</b>
10 km/h **	3680	4145	4380	4610	4805	4995	5190	5380	5575	5765	5960	6150		
30 km/h	2880	3290	3480	3665	3855	4040	4230	4415						
40 km/h		3265	3510	3750	3845	3940	4030	4125						
50 km/h		3265	3510	3750	3845	3940	4030	4125						

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)			
<b>42</b>	<b>650/65 R42 158A8/158B TL</b>	271958	633	1924	858	5708	DW20B (A)		802	643	52			
<b>Bar</b>	<b>0.6</b>	<b>0.8</b>	<b>1.0</b>	<b>1.1</b>	<b>1.2</b>	<b>1.3</b>	<b>1.4</b>	<b>1.5</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>	<b>1.9</b>	<b>2.0</b>	<b>2.1</b>
<b>Psi</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>16</b>	<b>17</b>	<b>19</b>	<b>20</b>	<b>22</b>	<b>23</b>	<b>25</b>	<b>26</b>	<b>28</b>	<b>29</b>	<b>30</b>
10 km/h **	2925	3505	4080	4370	4655	4945	5235	5520	5810	5935	6055	6180	6300	
30 km/h	2525	3070	3610	3765	3925	4080	4235	4395	4550					
40 km/h	2360	2865	3370	3515	3665	3810	3955	4105	4250					
50 km/h	2360	2865	3370	3515	3665	3810	3955	4105	4250					

#### \*IMPORTANT:

The inflation pressure must always be appropriate for the load per TYRE, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (July 2019). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h line.
- When using single TYRE configuration:
  - add 0.4 bar for use on slopes of more than 20%
  - add 0.4 bar for intensive road use exceeding 50%
- \*\*10 km/h LT (Low Torque) (max speed 10 km/h).