



# TAURUS RC 95 SOILSAVER

- ✓ Tread pattern designed for plant protection
- ✓ Good self-cleaning ability

## SIZES

230/95 R32 128A8/128B TL

270/95 R32 136A8/136B TL

230/95 R36 130A8/130B TL

270/95 R36 139A8/139B TL

270/95 R38 140A8/140B TL

270/95 R42 141A8/141B TL

230/95 R44 134A8/134B TL

270/95 R44 142A8/142B TL

300/95 R46 148A8/148B TL

230/95 R48 136A8/136B TL

270/95 R48 144A8/144B TL

340/85 R48 152A8/152B TL

380/90 R50 160A8/160B TL

# TAURUS RC 95 SOILSAVER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg\*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)				
<b>32</b>	<b>230/95 R32 128A8/128B TL</b> <i>9.5 R32</i>	965452	228	1250	579	3740	W8	W7	758	75	31				
<b>Bar</b>	<b>1.6</b>	<b>1.8</b>	<b>2.0</b>	<b>2.2</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>	<b>3.0</b>	<b>3.2</b>	<b>3.4</b>	<b>3.6</b>	<b>3.8</b>	<b>4.0</b>	<b>4.4</b>	<b>4.8</b>
<b>Psi</b>	23	26	29	32	35	38	41	44	46	49	52	55	58	64	70
10 km/h Cyc	1405	1520	1630	1745	1855	1960	2065	2145	2230	2310	2395	2475	2555	2720	
30 km/h Cyc	1315	1375	1430	1490	1545	1590	1635	1715	1790	1870	1945	2025	2100		
25 km/h	1280	1340	1395	1455	1510	1560	1610	1675	1740	1805	1870	1935	2000		
30 km/h	1230	1285	1345	1400	1455	1505	1550	1615	1675	1740	1800	1865	1925		
40 km/h	1150	1205	1255	1310	1360	1405	1450	1510	1565	1625	1685	1740	1800		
50 km/h					1360	1405	1450	1510	1565	1625	1685	1740	1800		
max 40 km/h FRT													1920	2040	2160

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)				
<b>32</b>	<b>270/95 R32 136A8/136B TL</b> <i>11.2 R32</i>	085528	263	1310	600	3902	W8	W10	763	105	35				
<b>Bar</b>	<b>1.6</b>	<b>1.8</b>	<b>2.0</b>	<b>2.2</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>	<b>3.0</b>	<b>3.2</b>	<b>3.4</b>	<b>3.6</b>	<b>3.8</b>	<b>4.0</b>	<b>4.4</b>	<b>4.8</b>
<b>Psi</b>	23	26	29	32	35	38	41	44	46	49	52	55	58	64	70
10 km/h Cyc	1800	1945	2090	2235	2380	2510	2635	2745	2850	2960	3070	3175	3285	3500	
30 km/h Cyc	1635	1710	1785	1855	1930	2015	2100	2190	2275	2365	2450	2540	2625		
25 km/h	1610	1680	1750	1820	1890	1970	2050	2125	2195	2270	2340	2415	2485		
30 km/h	1550	1620	1685	1755	1820	1900	1980	2050	2120	2190	2255	2325	2395		
40 km/h	1450	1515	1575	1640	1700	1775	1850	1915	1980	2045	2110	2175	2240		
50 km/h					1700	1775	1850	1915	1980	2045	2110	2175	2240		
max 40 km/h FRT													2470	2580	2690

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)				
<b>36</b>	<b>230/95 R36 130A8/130B TL</b> <i>9.5 R36</i>	245116	234	1354	632	4063	W8	W7	779	84	31				
<b>Bar</b>	<b>1.6</b>	<b>1.8</b>	<b>2.0</b>	<b>2.2</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>	<b>3.0</b>	<b>3.2</b>	<b>3.4</b>	<b>3.6</b>	<b>3.8</b>	<b>4.0</b>	<b>4.4</b>	<b>4.8</b>
<b>Psi</b>	23	26	29	32	35	38	41	44	46	49	52	55	58	64	70
10 km/h Cyc	1500	1635	1770	1905	2040	2115	2195	2270	2365	2455	2550	2625	2700		
30 km/h Cyc	1390	1455	1520	1585	1650	1715	1775	1840	1910	1980	2050	2150	2250		
25 km/h	1350	1415	1480	1545	1610	1670	1730	1790	1860	1930	2000	2055	2110		
30 km/h	1300	1365	1425	1490	1550	1610	1670	1730	1795	1865	1930	1985	2035		
40 km/h	1215	1275	1335	1390	1450	1505	1555	1610	1675	1735	1800	1850	1900		
50 km/h					1450	1505	1555	1610	1675	1735	1800	1850	1900		
max 40 km/h FRT														2185	2280

\* Refer to the notes at the end of the tables of this range

# TAURUS RC 95 SOILSAVER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg\*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)							
<b>36</b>	<b>270/95 R36 139A8/139B TL</b> <i>11.2 R36</i>	425455	287	1413	653	4228	W8		W10		779	120	34							
<b>Bar</b>	<b>1.6</b>	<b>1.8</b>	<b>2.0</b>	<b>2.2</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>	<b>3.0</b>	<b>3.2</b>	<b>3.4</b>	<b>3.6</b>	<b>3.8</b>	<b>4.0</b>	<b>4.4</b>	<b>4.8</b>					
<b>Psi</b>	23	26	29	32	35	38	41	44	46	49	52	55	58	64	70					
10 km/h Cyc	1905	2065	2230	2390	2550	2680	2805	2920	3030	3145	3255	3370	3480	3705						
30 km/h Cyc	1725	1805	1885	1960	2040	2145	2250	2350	2450	2550	2650	2750								
25 km/h	1720	1790	1860	1930	2000	2110	2220	2300	2380	2460	2540	2620								
30 km/h	1660	1725	1795	1860	1925	2035	2140	2215	2295	2370	2445	2525								
40 km/h	1550	1615	1675	1740	1800	1900	2000	2070	2145	2215	2285	2360		2430						
50 km/h												1800	1900	2000	2070	2145	2215	2285	2360	2430
max 40 km/h FRT														2615	2765	2915				

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)							
<b>38</b>	<b>270/95 R38 140A8/140B TL</b> <i>11.2 R38</i>	709100	267	1467	683	4408	W8		DW10 W10		779	121	34							
<b>Bar</b>	<b>1.6</b>	<b>1.8</b>	<b>2.0</b>	<b>2.2</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>	<b>3.0</b>	<b>3.2</b>	<b>3.4</b>	<b>3.6</b>	<b>3.8</b>	<b>4.0</b>	<b>4.4</b>	<b>4.8</b>					
<b>Psi</b>	23	26	29	32	35	38	41	44	46	49	52	55	58	64	70					
10 km/h Cyc	1955	2105	2255	2400	2550	2720	2890	3005	3120	3235	3350	3465	3580	3810						
30 km/h Cyc	1770	1855	1935	2020	2100	2175	2250	2365	2475	2590	2700	2815		2925						
25 km/h	1780	1850	1915	1985	2050	2170	2290	2370	2450	2535	2615	2695								
30 km/h	1710	1780	1845	1915	1980	2095	2205	2285	2360	2440	2520	2595								
40 km/h	1600	1665	1725	1790	1850	1955	2060	2135	2205	2280	2355	2425		2500						
50 km/h												1850	1955	2060	2135	2205	2280	2355	2425	2500
max 40 km/h FRT														2690	2845	3000				

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)							
<b>42</b>	<b>270/95 R42 141A8/141B TL</b> <i>11.2 R42</i>	962607	266	1570	729	4691	W8		W10			129	34							
<b>Bar</b>	<b>1.6</b>	<b>1.8</b>	<b>2.0</b>	<b>2.2</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>	<b>3.0</b>	<b>3.2</b>	<b>3.4</b>	<b>3.6</b>	<b>3.8</b>	<b>4.0</b>	<b>4.4</b>	<b>4.8</b>					
<b>Psi</b>	23	26	29	32	35	38	41	44	46	49	52	55	58	64	70					
10 km/h Cyc	2065	2230	2395	2555	2720	2890	3060	3180	3300	3415	3535	3655	3775	4010						
30 km/h Cyc	1875	1970	2065	2155	2250	2325	2400	2515	2630	2745	2860	2975		3090						
25 km/h	1890	1960	2025	2095	2160	2255	2350	2435	2520	2605	2690	2775								
30 km/h	1820	1930	2035	2145	2250	2295	2335	2405	2475	2545	2615	2685		2755						
40 km/h	1700	1765	1825	1890	1950	2065	2180	2245	2310	2380	2445	2510		2575						
50 km/h												1950	2065	2180	2245	2310	2380	2445	2510	2575
max 40 km/h FRT														2830	2960	3090				

\* Refer to the notes at the end of the tables of this range

# TAURUS RC 95 SOILSAVER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg\*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)				
<b>44</b>	<b>230/95 R44 134A8/134B TL</b> <i>9.5 R44</i>	589041	228	1560	732	4669	W8	W7		99	31				
<b>Bar</b>	<b>1.6</b>	<b>1.8</b>	<b>2.0</b>	<b>2.2</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>	<b>3.0</b>	<b>3.2</b>	<b>3.4</b>	<b>3.6</b>	<b>3.8</b>	<b>4.0</b>	<b>4.4</b>	<b>4.8</b>
<b>Psi</b>	23	26	29	32	35	38	41	44	46	49	52	55	58	64	70
10 km/h Cyc	1700	1835	1975	2110	2245	2355	2465	2560	2655	2750	2850	2945	3040	3230	
30 km/h Cyc	1545	1615	1685	1755	1825	1905	1980	2065	2145	2230	2310	2395	2475		
25 km/h	1510	1580	1645	1715	1780	1860	1940	2010	2080	2150	2215	2285	2355		
30 km/h	1455	1520	1585	1645	1710	1795	1875	1940	2005	2075	2140	2205	2270		
40 km/h	1360	1420	1480	1540	1600	1675	1750	1810	1875	1935	1995	2060	2120		
50 km/h					1600	1675	1750	1810	1875	1935	1995	2060	2120		
max 40 km/h FRT													2280	2415	2545

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)				
<b>44</b>	<b>270/95 R44 142A8/142B TL</b> <i>11.2 R44</i>	171447	263	1632	762	4892	W8	W10	813	135	34				
<b>Bar</b>	<b>1.6</b>	<b>1.8</b>	<b>2.0</b>	<b>2.2</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>	<b>3.0</b>	<b>3.2</b>	<b>3.4</b>	<b>3.6</b>	<b>3.8</b>	<b>4.0</b>	<b>4.4</b>	<b>4.8</b>
<b>Psi</b>	23	26	29	32	35	38	41	44	46	49	52	55	58	64	70
10 km/h Cyc	2125	2295	2465	2635	2805	2975	3145	3270	3390	3515	3640	3760	3885	4130	
30 km/h Cyc	1930	1985	2035	2090	2140	2240	2335	2460	2585	2715	2840	2965	3090		
25 km/h	1890	1975	2055	2140	2220	2320	2420	2505	2595	2680	2765	2855	2940		
30 km/h	1820	1900	1980	2060	2140	2240	2335	2420	2500	2585	2670	2750	2835		
40 km/h	1700	1775	1850	1925	2000	2090	2180	2260	2335	2415	2495	2570	2650		
50 km/h					2000	2090	2180	2260	2335	2415	2495	2570	2650		
max 40 km/h FRT													2915	3050	3180

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)				
<b>46</b>	<b>300/95 R46 148A8/148B TL</b> <i>12.4 R46</i>	065793	306	1733	809	5206	W10	DW10	835	183	40				
<b>Bar</b>	<b>1.6</b>	<b>1.8</b>	<b>2.0</b>	<b>2.2</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>	<b>3.0</b>	<b>3.2</b>	<b>3.4</b>	<b>3.6</b>	<b>3.8</b>	<b>4.0</b>	<b>4.4</b>	<b>4.8</b>
<b>Psi</b>	23	26	29	32	35	38	41	44	46	49	52	55	58	64	70
10 km/h Cyc	2550	2740	2935	3125	3315	3510	3705	3860	4010	4165	4320	4470	4625	4930	
30 km/h Cyc	2325	2420	2515	2605	2700	2815	2925	3065	3200	3340	3475	3615	3750		
25 km/h	2290	2395	2495	2600	2700	2820	2940	3035	3125	3220	3310	3405	3495		
30 km/h	2205	2305	2405	2500	2600	2720	2835	2925	3015	3105	3190	3280	3370		
40 km/h	2060	2155	2245	2340	2430	2540	2650	2735	2815	2900	2985	3065	3150		
50 km/h					2430	2540	2650	2735	2815	2900	2985	3065	3150		
max 40 km/h FRT													3480	3630	3780

\* Refer to the notes at the end of the tables of this range

# TAURUS RC 95 SOILSAVER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg\*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
<b>48</b>	<b>230/95 R48 136A8/136B TL</b> <i>9.5 R48</i>	812409	241	1672	790	5023	W8				835	107	31		
<b>Bar</b>	<b>1.6</b>	<b>1.8</b>	<b>2.0</b>	<b>2.2</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>	<b>3.0</b>	<b>3.2</b>	<b>3.4</b>	<b>3.6</b>	<b>3.8</b>	<b>4.0</b>	<b>4.4</b>	<b>4.8</b>
<b>Psi</b>	23	26	29	32	35	38	41	44	46	49	52	55	58	64	70
10 km/h Cyc	1750	1890	2030	2170	2310	2430	2550	2655	2765	2870	2975	3080	3190	3400	
30 km/h Cyc	1635	1710	1785	1855	1930	1985	2040	2140	2235	2335	2430	2530	2625		
25 km/h	1610	1665	1720	1775	1830	1940	2050	2125	2195	2270	2340	2415	2485		
30 km/h	1550	1620	1685	1755	1820	1900	1980	2050	2120	2190	2255	2325	2395		
40 km/h	1450	1515	1575	1640	1700	1775	1850	1915	1980	2045	2110	2175	2240		
50 km/h					1700	1775	1850	1915	1980	2045	2110	2175	2240		
max 40 km/h FRT												2400	2545	2690	

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
<b>48</b>	<b>270/95 R48 144A8/144B TL</b> <i>11.2 R48</i>	424954	272	1729	812	5197	W8		W10		835	146	38		
<b>Bar</b>	<b>1.6</b>	<b>1.8</b>	<b>2.0</b>	<b>2.2</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>	<b>3.0</b>	<b>3.2</b>	<b>3.4</b>	<b>3.6</b>	<b>3.8</b>	<b>4.0</b>	<b>4.4</b>	<b>4.8</b>
<b>Psi</b>	23	26	29	32	35	38	41	44	46	49	52	55	58	64	70
10 km/h Cyc	2245	2430	2610	2795	2975	3105	3230	3375	3520	3660	3805	3950	4095	4380	
30 km/h Cyc	2040	2130	2220	2310	2400	2515	2625	2735	2840	2950	3055	3165	3270		
25 km/h	2000	2090	2175	2265	2350	2450	2550	2645	2735	2830	2925	3015	3110		
30 km/h	1925	2010	2100	2185	2270	2365	2460	2550	2640	2730	2815	2905	2995		
40 km/h	1800	1880	1960	2040	2120	2210	2300	2385	2465	2550	2635	2715	2800		
50 km/h					2120	2210	2300	2385	2465	2550	2635	2715	2800		
max 40 km/h FRT												3090	3225	3360	

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
<b>48</b>	<b>340/85 R48 152A8/152B TL</b> <i>13.6 R48</i>	409717	369	1774	826	5314	W12		W11			214	38		
<b>Bar</b>	<b>1.6</b>	<b>1.8</b>	<b>2.0</b>	<b>2.2</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>	<b>3.0</b>	<b>3.2</b>	<b>3.4</b>	<b>3.6</b>	<b>3.8</b>	<b>4.0</b>	<b>4.4</b>	<b>4.8</b>
<b>Psi</b>	23	26	29	32	35	38	41	44	46	49	52	55	58	64	70
10 km/h Cyc	2890	3095	3300	3500	3705	3920	4130	4305	4480	4655	4830	5000	5175	5525	
30 km/h Cyc	2625	2740	2860	2975	3090	3180	3270	3425	3580	3735	3890	4045	4200		
25 km/h	2550	2670	2785	2905	3020	3175	3330	3430	3535	3635	3735	3840	3940		
30 km/h	2460	2575	2690	2800	2915	3065	3210	3310	3405	3505	3605	3700	3800		
40 km/h	2300	2405	2515	2620	2725	2865	3000	3090	3185	3275	3365	3460	3550		
50 km/h					2725	2865	3000	3090	3185	3275	3365	3460	3550		
max 40 km/h FRT												3900	4080	4260	

\* Refer to the notes at the end of the tables of this range

# TAURUS RC 95 SOILSAVER

Tyre specifications and pressure table (bar & psi). Load per tyre in kg\*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
<b>50</b>	<b>380/90 R50 160A8/160B TL</b>	332270	380	1954	913	5882	DW13A		DW12 W12 W13A			329	43		
<b>Bar</b>	<b>1.6 1.8 2.0 2.2 2.4 2.6 2.8 3.0 3.2 3.4 3.6 3.8 4.0 4.4 4.8</b>														
<b>Psi</b>	<b>23 26 29 32 35 38 41 44 46 49 52 55 58 64 70</b>														
10 km/h Cyc	3540	3945	4350	4555	4765	4970	5175	5380	5590	5795	6000	6125	6250	6500	6750
25 km/h Cyc	3540	3710	3875	4045	4210	4380	4545	4715	4880	5035	5185	5340	5490		
30 km/h Cyc	3305	3465	3620	3780	3935	4090	4250	4405	4560	4705	4845	4990	5130		
25 km/h	3220	3375	3525	3680	3830	3985	4135	4290	4440	4580	4720	4860	5000		
30 km/h	3100	3250	3395	3545	3690	3840	3985	4135	4280	4415	4550	4680	4815		
50 km/h	2900	3040	3175	3315	3450	3590	3725	3865	4000	4125	4250	4375	4500		

#### \*IMPORTANT:

The inflation pressure must always be appropriate for the load per TYRE, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (July 2019). Technical data is subject to change without prior notice.

- For use on side slopes >20%: add 0.4 bar without exceeding the max. TYRE pressure.
- For heavy road use >50%, add 0.4 bar.
- Use 10, 25 or 30 km/h cyclic loading tables for field use only, travel with full load not to exceed 1,5 km