



TAURUS POINT 70

- ✓ Low profile tyres result in more benefits when working the land
- ✓ Heavy-duty design for agricultural work

SIZES

320/70 R24 116A8/116B TL
360/70 R24 122A8/122B TL
380/70 R24 125A8/125B TL
420/70 R24 130A8/130B TL
480/70 R24 138A8/138B TL
360/70 R28 125A8/125B TL

380/70 R28 127A8/127B TL
420/70 R28 133A8/133B TL
480/70 R28 140A8/140B TL
480/70 R30 141A8/141B TL
480/70 R34 143A8/143B TL
520/70 R34 148A8/148B TL

480/70 R38 145A8/145B TL
520/70 R38 150A8/150B TL
580/70 R38 155A8/155B TL
620/70 R42 160A8/160B TL

TAURUS POINT 70

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	320/70 R24 116A8/116B TL	723294	311	1092	495	3252	W10	W11	692	104	39		
Bar	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0
Psi	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h **	1130	1195	1255	1320	1385	1450	1515	1580	1645	1705	1770	1835	1900
30 km/h	850	915	980	1040	1105	1170	1235	1295	1360				
40 km/h	800	855	915	970	1025	1080	1140	1195	1250				
50 km/h								1250					

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	360/70 R24 122A8/122B TL	007646	357	1152	514	3416	W11	W10 W12	692	124	40		
Bar	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0
Psi	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h **	1330	1405	1485	1560	1635	1710	1785	1860	1935	2015	2090	2165	2240
30 km/h	1030	1100	1175	1245	1315	1385	1460	1530	1600				
40 km/h	950	1020	1090	1155	1225	1295	1365	1430	1500				
50 km/h								1500					

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	380/70 R24 125A8/125B TL	604562	380	1190	525	3521	W12	W11 W13	700	140	41		
Bar	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0
Psi	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h **	1450	1530	1610	1695	1775	1860	1940	2020	2105	2185	2265	2350	2430
30 km/h	1120	1200	1280	1355	1435	1515	1595	1670	1750				
40 km/h	1060	1135	1210	1280	1355	1430	1505	1575	1650				
50 km/h								1650					

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	420/70 R24 130A8/130B TL	677050	415	1245	553	3690	W13	DW14L W12 W14L	703	194	42		
Bar	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0
Psi	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h **	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900
30 km/h	1320	1415	1505	1600	1690	1785	1875	1970	2060				
40 km/h	1215	1300	1385	1470	1560	1645	1730	1815	1900				
50 km/h								1900					

* Refer to the notes at the end of the tables of this range

TAURUS POINT 70

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
24	480/70 R24 138A8/138B TL	928586	479	1316	577	3888	DW15L		DW14L DW16L W14L W15L W16L		710	241	45
Bar	0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6									1.7 1.8 1.9 2.0			
Psi	12 13 15 16 17 19 20 22 23									25 26 28 29			
10 km/h **	2095	2215	2335	2455	2580	2700	2820	2945	3065	3185	3305	3430	3550
30 km/h	1600	1715	1825	1940	2050	2165	2275	2390	2500				
40 km/h	1500	1610	1715	1825	1930	2040	2145	2255	2360				
50 km/h									2360				

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	360/70 R28 125A8/125B TL	423583	357	1251	563	3717	W11		W10 W12		726	138	40
Bar	0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6									1.7 1.8 1.9 2.0			
Psi	12 13 15 16 17 19 20 22 23									25 26 28 29			
10 km/h **	1450	1530	1610	1695	1775	1860	1940	2020	2105	2185	2265	2350	2430
30 km/h	1120	1200	1280	1355	1435	1515	1595	1670	1750				
40 km/h	1030	1110	1185	1265	1340	1420	1495	1575	1650				
50 km/h									1650				

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	380/70 R28 127A8/127B TL	405953	380	1293	583	3842	W12		W11 W13		732	156	41
Bar	0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6									1.7 1.8 1.9 2.0			
Psi	12 13 15 16 17 19 20 22 23									25 26 28 29			
10 km/h **	1580	1670	1755	1845	1935	2025	2115	2205	2295	2380	2470	2560	2650
30 km/h	1215	1300	1385	1470	1560	1645	1730	1815	1900				
40 km/h	1120	1200	1280	1355	1435	1515	1595	1670	1750				
50 km/h									1750				

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	420/70 R28 133A8/133B TL	212493	419	1350	605	4008	W13		DW14L W12 W14L		821	219	42
Bar	0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6									1.7 1.8 1.9 2.0			
Psi	12 13 15 16 17 19 20 22 23									25 26 28 29			
10 km/h **	1810	1915	2020	2125	2230	2340	2445	2550	2655	2760	2865	2970	3075
30 km/h	1400	1500	1595	1695	1790	1890	1985	2085	2180				
40 km/h	1320	1415	1505	1600	1690	1785	1875	1970	2060				
50 km/h									2060				

* Refer to the notes at the end of the tables of this range

TAURUS POINT 70

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
28	480/70 R28 140A8/140B TL	976420	476	1422	633	4214	DW15L		DW14L DW16L W14L W15L W16L		822	293	46
Bar	0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6	1.7 1.8 1.9 2.0											
Psi	12 13 15 16 17 19 20 22 23	25 26 28 29											
10 km/h **	2250	2375	2500	2625	2750	2875	3000	3125	3250	3375	3500	3625	3750
30 km/h	1700	1830	1955	2085	2215	2340	2470	2595	2725				
40 km/h	1600	1715	1825	1940	2050	2165	2275	2390	2500				
50 km/h									2500				

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
30	480/70 R30 141A8/141B TL	683605	479	1480	661	4392	DW15L		DW14L DW16L W14L W15L W16L		754	307	45
Bar	0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6	1.7 1.8 1.9 2.0											
Psi	12 13 15 16 17 19 20 22 23	25 26 28 29											
10 km/h **	2320	2450	2580	2710	2840	2970	3095	3225	3355	3485	3615	3745	3875
30 km/h	1750	1880	2015	2145	2275	2405	2540	2670	2800				
40 km/h	1650	1765	1880	1995	2115	2230	2345	2460	2575				
50 km/h									2575				

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
34	480/70 R34 143A8/143B TL	369476	468	1583	709	4701	DW15L		DW14L DW16L W14L W15L W16L		704	334	48
Bar	0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6	1.7 1.8 1.9 2.0											
Psi	12 13 15 16 17 19 20 22 23	25 26 28 29											
10 km/h **	2390	2525	2655	2790	2925	3060	3195	3330	3465	3595	3730	3865	4000
30 km/h	1850	1980	2115	2245	2375	2505	2640	2770	2900				
40 km/h	1700	1830	1955	2085	2215	2340	2470	2595	2725				
50 km/h									2725				

* Refer to the notes at the end of the tables of this range

TAURUS POINT 70

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
34	520/70 R34 148A8/148B TL	061874	509	1641	735	4874	DW16L		DW15L DW18L W15L W16L W18L		823	398	48
Bar	0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6	1.7 1.8 1.9 2.0											
Psi	12 13 15 16 17 19 20 22 23	25 26 28 29											
10 km/h **	2745	2900	3055	3215	3370	3530	3685	3840	4000	4155	4310	4470	4625
30 km/h	2120	2275	2430	2580	2735	2890	3045	3195	3350				
40 km/h	2000	2145	2290	2430	2575	2720	2865	3005	3150				
50 km/h										3150			

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	480/70 R38 145A8/145B TL	794424	474	1684	759	5010	DW15L		DW14L DW16L W14L W15L W16L		786	362	48
Bar	0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6	1.7 1.8 1.9 2.0											
Psi	12 13 15 16 17 19 20 22 23	25 26 28 29											
10 km/h **	2595	2745	2895	3040	3190	3340	3485	3635	3780	3930	4080	4225	4375
30 km/h	2000	2145	2290	2430	2575	2720	2865	3005	3150				
40 km/h	1850	1980	2115	2245	2375	2505	2640	2770	2900				
50 km/h										2900			

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
38	520/70 R38 150A8/150B TL	250048	515	1762	789	5229	DW16L		DW15L DW18L W15L W16L W18L		824	434	48
Bar	0.8 0.9 1.0 1.1 1.2 1.3 1.4 1.5 1.6	1.7 1.8 1.9 2.0											
Psi	12 13 15 16 17 19 20 22 23	25 26 28 29											
10 km/h **	3005	3185	3365	3545	3720	3900	4080	4255	4435	4615	4795	4970	5150
30 km/h	2300	2470	2640	2805	2975	3145	3310	3480	3650				
40 km/h	2180	2325	2475	2620	2765	2910	3060	3205	3350				
50 km/h										3350			

* Refer to the notes at the end of the tables of this range

TAURUS POINT 70

Tyre specifications and pressure table (bar & psi). Load per tyre in kg*

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
38	580/70 R38 155A8/155B TL	642040	560	1831	820	5436	DW18L	W18L	825	557	51		
Bar	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0
Psi	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h **	3465	3660	3855	4050	4245	4440	4630	4825	5020	5215	5410	5605	5800
30 km/h	2650	2835	3020	3205	3390	3570	3755	3940	4125				
40 km/h	2500	2670	2845	3015	3190	3360	3530	3705	3875				
50 km/h									3875				

Ø inches	Description	CAI	S mm	OD mm	LR mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
42	620/70 R42 160A8/160B TL	680909	625	1935	861	5736	DW20B (A)	DW18L	802	658	53		
Bar	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0
Psi	12	13	15	16	17	19	20	22	23	25	26	28	29
10 km/h **	3535	3645	3905	4170	4430	4690	4950	5215	5475	5795	6115	6430	6750
30 km/h	3035	3255	3470	3690	3905	4135	4360	4590	4815				
40 km/h	2835	3040	3245	3445	3650	3865	4075	4290	4500				
50 km/h	2835	3040	3245	3445	3650	3865	4075	4290	4500				
40 km/h Dual	2495	2675	2855	3030	3210	3400	3585	3775	3960				

*IMPORTANT:

The inflation pressure must always be appropriate for the load per TYRE, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (July 2019). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h line.
 - When using single TYRE configuration:
 - add 0.4 bar for use on slopes of more than 20%
 - add 0.4 bar for intensive road use exceeding 50%
- **10 km/h LT (Low Torque) (max speed 10 km/h).